Accurate Multi-Sensor Localization on Android Devices

Christos Laoudias KIOS Research Center University of Cyprus laoudias@ucy.ac.cy

Yu-Kuen Tsai Cywee Corporation Ltd Taipei, Taiwan YKTsai@cywee.com George Larkou
Dept. of Computer Science
University of Cyprus
glarko01@cs.ucy.ac.cy

Demetrios Zeinalipour-Yazti Dept. of Computer Science University of Cyprus dzeina@cs.ucy.ac.cy Chin-Lung Li Cywee Corporation Ltd Taipei, Taiwan chinlung@cywee.com

Christos G. Panayiotou KIOS Research Center University of Cyprus christosp@ucy.ac.cy

ABSTRACT

In our indoor localization approach we employ a multitude of location-dependent data that are readily available on modern sensor-rich Android smartphones¹. In particular, we exploit WiFi Received Signal Strength (RSS) observations and combine them with Inertial Measurement Unit (IMU) readings, i.e. accelerometer, gyroscope and magnetometer, to deliver accurate location information on top of digital floorplan maps within the user-carried device. The system follows a modular architecture, where the key components include the WiFi Fingerprinting, the IMU Positioning and the Location Fusion modules [1].

The WiFi Fingerprinting module relies on RSS values from the surrounding Access Points (AP) and is based on a machine learning algorithm, developed in-house, to determine location. Moreover, by leveraging orientation data we mitigate the effect of the user body, in case some AP signals are blocked.

The *IMU Positioning* module computes the user orientation in real-time and implements a custom Pedestrian Dead Reckoning (PDR) algorithm for accurate trajectory tracking. The orientation readings are refined by incorporating raw magnetic data to account for magnetic disturbances inside buildings, due to power cables, electrical appliances or metal surfaces.

Finally, the *Location Fusion* module processes the WiFi

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

Copyright 200X ACM X-XXXXX-XX-X/XX/XX ...\$5.00.







Figure 1: Indoor localization using solely WiFi (left), solely IMU (middle) and location fusion (right) while a user walks several times along a rectangular path in a typical office environment.

and IMU locations, as well as their associated uncertainties, by means of a particle filter. Moreover, a mapmatching submodule handles and corrects any inaccurate locations after filtering, e.g., a user crossing a wall or moving into a non accessible area. Thus, our system delivers a fine grain final location that accurately reflects the travelled path; see Fig. 1 taken from [1].

The system is a software-based solution that may run on any commercial Android smartphone for the provision of indoor geolocation information in real-time. It is efficient and reliable, while it attains meter level localization accuracy through the integration and optimization of diverse technologies. For the deployment only the floorplan digital map of the venue is required, while additional APs can be quickly deployed by our team to provide adequate WiFi coverage, if necessary.

1. REFERENCES

[1] C.-L. Li, et al. Indoor geolocation on multi-sensor smartphones. In *MobiSys*, pages 503–504, 2013.

¹A demo video of the prototype system inside a conference hall is available at: http://youtu.be/DyvQLSuI00I