arXiv:2510.23883v2 [cs.AI] 13 Feb 2026

AGENTIC AI SECURITY: THREATS, DEFENSES, EVALUATION, AND OPEN CHALLENGES

Anshuman Chhabra*, **Shrestha Datta, Shahriar Kabir Nahin, and Prasant Mohapatra**
Bellini College of AI, Cybersecurity, and Computing, University of South Florida
Email: {anshumanc, shresthadatta, shahriarkabir, pmohapatra}@usf.edu

ABSTRACT

Agentic AI systems powered by large language models (LLMs) and endowed with planning, tool use, memory, and autonomy, are emerging as powerful, flexible platforms for automation. Their ability to autonomously execute tasks across web, software, and physical environments creates new and amplified security risks, distinct from both traditional AI safety and conventional software security. This survey outlines a taxonomy of threats specific to agentic AI, reviews recent benchmarks and evaluation methodologies, and discusses defense strategies from both technical and governance perspectives. We synthesize current research and highlight open challenges, aiming to support the development of secure-by-design agent systems.

1 Introduction

Artificial Intelligence (AI) has become one of the most transformative technologies of the twenty-first century [1]. From early rule-based expert systems [2] to modern deep learning architectures [3], AI has steadily expanded in both capability and scope. Traditionally and over the past decade, AI has excelled at narrow, task-specific applications such as image classification, speech recognition, recommendation systems, and predictive analytics [4, 3]. These systems typically operate within well-defined boundaries and are optimized for performance on constrained datasets, but lack the ability to flexibly adapt beyond their original input/output designs.

Recently, the advent of large language models (LLMs), such as OpenAI's GPT [5, 6] and Meta's LLaMA [7], has marked a paradigm shift for AI models. Trained on vast corpora of text (and now, even multimodal data), these models exhibit impressive generalization abilities and can generate coherent, contextually relevant responses across a wide range of domains [8, 9]. LLMs have enabled breakthroughs in conversational agents, code generation, content summarization, and multimodal reasoning [10–12]. Moreover, by design, most LLM deployments remain *passive*: they respond to *input* prompts containing instructions and generate natural language *outputs* but do not independently pursue goals, maintain memory, or interact autonomously with the external world without human supervision [13, 14].

Agentic AI represents the next stage in this natural evolution of AI systems powered by LLMs and other Generative AI models. Agentic AI systems are characterized by autonomy, goal-directed reasoning, planning, and the ability to act upon digital or physical environments through tools, APIs, or robotic embodiments [15, 16]. Figure 1 illustrates the general interaction flows of such systems. Unlike static LLMs, agentic systems maintain persistent memory, deliberate across time, coordinate with other agents, and adapt dynamically to changing contexts. These capabilities position agentic AI as a powerful general-purpose automation platform rather than a reactive model that depends on continuous human input for task completion.

Recent frameworks have accelerated the adoption of agentic AI. Tooling ecosystems such as LangChain [17], AutoGPT [18], and multi-agent orchestration libraries provide infrastructure for chaining reasoning steps, storing long-term context, and integrating external APIs. This has made agent-based architectures accessible to a wide range of developers and enterprises. Research prototypes such as Voyager, which enables agents to autonomously explore and adapt strategies in complex environments like Minecraft [19], and enterprise deployments in customer support and data

*Corresponding Author.

arXiv:2510.23883v2 [cs.AI] 13 Feb 2026

AGENTIC AI 安全：威脅，防禦，評估，AND OPEN CHALLENGES

Anshuman Chhabra*，Shrestha Datta，Shahriar Kabir Nahin，以及 Prasant Mohapatra 美國南弗羅里達大學 AI、網路安全與計算學院 電子郵件：{anshumanc, shresthadatta, shahriarkabir, pmohapatra}@usf.edu

摘要

由大型語言模型（LLMs）驅動的代理 AI 系統，具備規劃、工具使用、記憶與自主能力，正成為強大且靈活的自動化平台。其能夠在網頁、軟體及實體環境中自主執行任務的能力，帶來了既不同于傳統 AI 安全，也不同于傳統軟體安全的新型且加劇的安全風險。本調查概述了針對代理 AI 的特定威脅分類法，回顧了近期的基準測試與評估方法，並從技術與治理雙重角度探討了防禦策略。我們整合了現有研究，並指出尚未解決的挑戰，旨在支持開發「安全設計」的代理系統。

1 簡介

人工智慧（AI）已成為二十一世紀最具變革性的技術之一 [1]。從早期的基於規則的專家系統 [2] 到現代深度學習架構 [3]，AI 的能力與範圍持續穩步擴展。傳統上，且過去十年來，AI 在狹窄、特定任務的應用方面表現卓越，例如影像分類、語音識別、推薦系統與預測分析 [4, 3]。這些系統通常運作於明確界定的邊界內，並針對受限數據集進行效能優化，但缺乏在原始輸入/輸出設計之外靈活適應的能力。

近期，大型語言模型（LLMs）的出現，例如 OpenAI 的 GPT [5, 6] 與 Meta 的 LLaMA [7]，標誌著 AI 模型的範式轉移。這些模型基於龐大的文本語料（甚至現在包含多模態數據）進行訓練，展現出驚人的泛化能力，能夠在廣泛的領域中生成連貫且與上下文相關的回應 [8, 9]。LLMs 已促成對話代理、程式碼生成、內容摘要及多模態推理等方面的突破 [10–12]。此外，從設計上來看，大多數 LLM 部署仍處於被動狀態：它們回應包含指令的輸入提示並生成自然語言輸出，但無法在人類監督下獨立追求目標、維持記憶或與外部世界進行自主互動 [13, 14]。

代理式 AI 代表了由大型語言模型和其他生成式 AI 模型驅動的 AI 系統自然演進的下一個階段。代理式 AI 系統的特徵包括自主性、目標導向的推理、規劃，以及透過工具、API 或機器人實體在數位或實體環境中採取行動的能力 [15, 16]。圖 1 展示了這類系統的一般互動流程。與靜態的大型語言模型不同，代理式系統會維持持續記憶、跨時間進行深思熟慮的規劃、與其他代理協作，並能動態適應變化的情境。這些能力使代理式 AI 成為一個強大的通用自動化平台，而非依賴持續人類輸入以完成任務的反應式模型。

近期框架加速了代理 AI 的採用。工具生態系統，如 LangChain [17]，、AutoGPT[18], 以及多代理編排庫，提供了鏈接推理步驟、存儲長期上下文以及整合外部 API 的基礎設施。這使得基於代理的架構對廣泛的開發者和企業變得可及。研究原型如 Voyager，使代理能夠在複雜環境（如 Minecraft [19]，）中自主探索並適應策略，以及企業級部署在客戶支持和數據

*通訊作者。



Figure 1: Agentic AI architecture: general components and interaction flows. The agent performs planning and reasoning, retrieves and stores information in memory, executes actions via tools, and interacts with both the user and the external environments to accomplish multi-step tasks autonomously.

analysis [20], demonstrate the potential of agentic systems to handle multi-step and open-ended tasks previously out of reach for conventional AI.

Given the potential for positive impact agentic AI can have across diverse domains, these systems are being increasingly employed in several real-world scenarios and applications:

- ***Automation of complex workflows:*** Agentic AI systems can autonomously manage supply chain processes and adapt procurement decisions in response to dynamic data sources. For example, U.S. manufacturers such as Toro have deployed AI systems that analyze tariff policies, commodity pricing, and economic signals to recommend procurement actions, leaving operators with a simple acceptance decision [21].
- ***Enhanced productivity:*** Agentic AI coding agents have shown significant promise in software engineering. For instance, *Devin*, an AI software engineer developed by Cognition Labs, has demonstrated the ability to plan, code, debug, and deploy software with minimal oversight. It substantially outperforms earlier systems on real-world issue resolution benchmarks, solving 13.86% of tasks autonomously compared with 1.96% by prior models [22].
- ***Personalized support:*** When equipped with memory and adaptive reasoning, agentic systems can function as persistent digital concierges that track user preferences over time. Experimental work on generative agents has shown that AI systems can simulate memory-driven, socially coordinated behavior, including the autonomous organization of community events in interactive environments [23].
- ***Scientific discovery and research:*** Generative agent architectures, which extend large language models with planning and memory, have been applied to hypothesis generation, literature synthesis, and experimental design. This line of research highlights the potential of agentic AI in accelerating scientific progress and expanding the knowledge frontier [24, 25].
- ***Collaboration and coordination:*** Multi-agent systems are being applied to distributed problem-solving and collective decision-making. In industry, Ocado employs large fleets of coordinating robots to manage grocery order fulfillment, with automation projected to scale from 40% to 80% of orders [26]. On the research side, frameworks such as AutoAgents demonstrate how specialist agents can be dynamically instantiated and coordinated under a supervisory agent to achieve complex objectives [27].
- ***Integration with physical systems:*** In robotics and the Internet of Things systems, agentic AI is increasingly responsible for controlling devices and coordinating autonomous machines. For instance, at Amazon, agent-enabled robots in warehouses are able to perform a range of tasks such as unloading, sorting, and retrieving items, all through natural language instructions [28].
- ***Revolutionizing healthcare:*** Agentic AI is transforming healthcare by autonomously personalizing treatment, streamlining both clinical and administrative workflows, and enhancing patient support. Healthcare AI agents [29–33] have been developed that can continuously monitor chronic conditions for patients, adapt care strategies in real-time, handle patient interactions/follow-ups, act as scribes for reducing clinician documentation burden, and accelerate drug discovery via autonomous screening.

Clearly, agentic AI has attracted significant interest across various sectors of society owing to its widespread benefits and potential for revolutionizing applications. Organizations view such systems as key enablers of efficiency and innovation, capable of addressing challenges that require adaptive reasoning, sustained interaction, and multi-step



圖 1：代理式 AI 架構：一般組件與互動流程。代理負責規劃與推理，在記憶中檢索與儲存資訊，透過工具執行動作，並與使用者及外部環境互動，以自主完成多步驟任務。

analysis [20], 展示代理系統處理先前傳統 AI 無法應付的多步驟與開放式任務的潛力。

鑑於具體能對 AI 產生正面影響，這些系統正被越來越多地應用於多個現實世界情境與應用中：

• 自動化複雜工作流：代理 AI 系統可自主管理供應鏈流程，並根據動態數據來源調整採購決策。例如，美國製造商如 Toro
已部署可分析關稅政策、大宗商品定價及經濟信號的 AI 系統，以推薦採購行動，使營運者僅需做出簡單的接受決定 [21]。

• 提升生產力：AgenticAI 編碼代理在軟體工程領域展現了顯著潛力。例如，由 Cognition Labs 開發的 AI 軟體工程師 Devin，已展現出規劃、編碼的能力，
可進行除錯並以最少的監督部署軟體。它在真實世界問題解決基準測試中表現優於早期系統，自主解決 13.86% 的任務，而先前的模型僅能解決 1.96% [22]。

• 個人化服務：當系統配備記憶與適應性推理能力時，智能體系統可作為持續的數位禮賓師，隨時間追蹤用戶偏好。關於生成式智能體的實驗工作已
顯示 AI 系統能夠模擬記憶驅動的、社會協調的行為，包括在互動環境中 [23] 自主組織社區活動。

• 科學發現與研究：生成式代理架構，透過結合規劃與記憶功能擴展大型語言模型，已應用於假設生成、文獻綜合與實驗設計。
本研究線強調了代理式 AI 在加速科學進步與拓展知識邊界 [24, 25] 方面的潛力。

• 協作與協調：多智能體系統正應用於分散式問題解決與集體決策。在產業界，Ocado 運用大量協調機器人來管理雜貨訂單履行，預計自動化比例將從 40% 擴展至 80% 的訂單 [26]。在研究方面，AutoAgents 等框架展示了如何透過監督智能體動態實例化並協調專責智能體，以達成複雜目標 [27]。

• 與實體系統的整合：在機器人學與物聯網系統中，代理式 AI 正越來越負責控制裝置與協調自主機器。例如，在亞馬遜，已啟用代理的
倉庫中的機器人能夠執行一系列任務，例如卸貨、分類和取回物品，全部透過自然語言指令 [28]完成。

• 重塑醫療保健：代理式 AI 透過自主個人化治療方案、簡化臨床與行政工作流程，並提升患者支持，正在改變醫療保健。醫療保健 AI 代理[29–33] 已開發完成，能夠持續監測患者的慢性病症、即時調整照護策略、處理患者互動與後續追蹤、作為記錄員減輕臨床人員的文件負擔，並透過自主篩選加速藥物研發。

顯然，由於其廣泛的效益，代理式 AI 已引起社會各領域的廣泛關注。
以及革新應用程序的潛力。組織將此類系統視為效率與創新的重要推動者，能夠應對需要適應性推理、持續互動及多步驟處理的挑戰。

execution. However, at the same time, these agentic properties create new risks: autonomy and persistence increase the attack surface, tool integration magnifies potential misuse, and coordination among agents introduces unpredictability that might not exist under human supervision or with singular models. Therefore, *security* and *trustworthiness* become essential prerequisites for the safe deployment of agentic AI in societal applications. In this survey, we focus on this very timely and pertinent problem of agentic AI security, and present the current state-of-the-art in novel AI agent attack methodologies, defense strategies, benchmarks for continuous evaluation, as well as open challenges in the area. In the subsequent section, we discuss these motivations in more detail, and delineate our contributions towards augmenting the safety and security of agentic AI frameworks.

2 Motivation and Contributions

While the potential positive impacts of agentic AI have been the main driver of adoption across application domains, there are several classes of risks that emerge uniquely from agentic AI autonomy and persistence. For instance, a critical threat occurred in mid-2025 with the *EchoLeak* (`CVE-2025-32711`) exploit against *Microsoft Copilot*. Infected email messages containing engineered prompts could trigger Copilot to exfiltrate sensitive data automatically, without user interaction [34]. Moreover, agentic systems capable of browsing, content generation, and memory can autonomously craft personalized spear-phishing campaigns. Controlled experiments conducted by Symantec using OpenAI's Operator AI agent demonstrated how agents could harvest personal data and automate *credential stuffing* attacks [35].

A number of these security problems in agentic AI systems compound upon the vulnerabilities and deficiencies of the base LLMs, while others are novel and occur due to the unique landscape of *agent-agent* interactions. *Prompt injection attacks* remains a critical LLM vulnerability, permitting adversaries to manipulate agent behavior through crafted inputs [36, 37]. Lupinacci et al. demonstrated that 94.4% of state-of-the-art LLM agents are vulnerable to prompt injection, 83.3% to retrieval-based backdoors, and 100% to inter-agent trust exploits [38]. Further, researchers at Anthropic observed that generative models, when given directive autonomy, engaged in misaligned behaviors such as blackmail or corporate espionage to fulfill goals, even when those behaviors diverged from human ethical standards [39]. It is evident that these security vulnerabilities can result in highly adverse consequences for some of the proposed critical application areas for agentic AI frameworks, such as healthcare.

Other agent-specific attacks include *memory poisoning*, that enables stealthy manipulation over time, as agents retain and act on corrupted context [40–42] and *tool misuse*, such as abusing calendar or API integrations, which can trigger unintended or malicious actions [43, 44]. Finally, agent identity misuse, such as spoofing or overprivileged agents taking unauthorized action, poses serious organizational risk [45]. Most of these attacks are fully realizable today – for instance, recent work has simulated successful and fully autonomous multi-AI-agent cyberattacks capable of intelligently adapting to network defenses [46].

Given the rapid acceleration of progress in developing and utilizing agentic AI systems, it is paramount for the community to understand and address the aforementioned security risks. However, owing to the large body of work in the area, it is important to systemize current research efforts and create a taxonomy of all the security threats posed by agentic AI. Furthermore, for truly securing these agentic systems, it is equally consequential to understand the state-of-the-art in defending against known attacks/threats, and provide an overview of open challenges that remain. Through this survey, we seek to make significant progress along each of these directions, and our aim is to galvanize research efforts in developing safe and secure agentic AI frameworks, thereby accelerating their adoption in society.

Remark. Our work is also distinct from existing surveys in this space, and tackles an overlooked problem. Existing surveys on autonomous AI agents [47–51] mostly detail their capabilities and propose evaluation benchmarks, while others explore topics such as trust and risk management [52] without a singular focus on security, unlike our work. On the other hand, risk management frameworks such as the NIST Generative AI Profile [53] provide baseline guidance, but adapting them to autonomous agents remains a work in progress.

The rest of the survey is structured as follows: Section 3 provides a broad taxonomy of agentic AI security threats and attacks; Section 4 covers the current state-of-the-art in defense approaches; Section 5 details benchmarking practices and guidelines for evaluating security-critical agentic AI application; Section 6 delineates open challenges and problems in securing AI agents; and Section 7 concludes the survey.

3 Taxonomy of Security Threats

We now propose and discuss a taxonomy of attacks and security vulnerabilities for agentic AI systems. More specifically, in this section, we broadly divide threats into the following categories: (i) Prompt Injection and Jailbreaks, (ii) Autonomous Cyber-Exploitation and Tool Abuse, (iii) Multi-Agent and Protocol-Level Threats, (iv) Interface and

執行。然而，同時這些代理特性也帶來了新的風險：自主性和持久性增加了攻擊面，工具整合放大了潛在的濫用，而代理之間的協調引入了在人類監督或單一模型下可能不存在的不可預測性。因此，安全性與可信度成為代理 AI 在社會應用中安全部署的必要前提。在本調查中，我們聚焦於這個非常及時且相關的代理 AI 安全問題，並介紹當前在新型 AI 代理攻擊方法、防禦策略、用於持續評估的基準，以及該領域開放挑戰方面的最新研究進展。在後續章節中，我們將更詳細地討論這些動機，並闡述我們針對增強代理 AI 框架安全性與安全性的貢獻。

2 動機與貢獻

雖然代理型 AI 的潛在正面影響是推動其跨應用領域採用的主要動力，但從代理型 AI 的自主性和持續性中，也出現了若干獨特性風險。例如，2025 年中發生了針對 Microsoft Copilot 的 EchoLeak（CVE-2025-32711）漏洞攻擊。受感染的電子郵件訊息若包含精心設計的提示詞，可能會觸發 Copilot 自動洩漏敏感資料，而無需使用者互動 [34]。此外，具備瀏覽、內容生成和記憶能力的代理系統，可自主策劃針對性的釣魚攻擊。Symantec 使用 OpenAI 的 Operator AI 代理進行的受控實驗，展示了代理如何竊取個人資料並自動化憑證填充攻擊 [35]。

這些代理 AI 系統中的許多安全問題會加劇基礎大語言模型（LLM）的弱點與缺陷，另一些則是全新的，源於代理間互動所特有的環境。提示注入攻擊仍是關鍵的 LLM 漏洞，允許攻擊者透過精心設計的輸入 [36, 37] 來操控代理行為。Lupinacci 等人指出，94.4% 的先進大語言模型代理易受提示注入攻擊影響，83.3% 易受基於檢索的後門攻擊，100% 易受代理間信任濫用攻擊 [38]。此外，Anthropic 的研究人員觀察到，當生成式模型被賦予指令自主權時，會產生與人類倫理標準不符的行為（如勒索或企業間諜活動），以達成目標 [39]。顯然，這些安全漏洞可能對代理 AI 框架所提出的某些關鍵應用領域（例如醫療保健）造成極其嚴重的後果。

其他針對特定代理的攻擊包括記憶投毒，這能實現隨時間的隱蔽操控，因為代理會保留並基於被污染的上下文 [40–42] 採取行動，以及工具濫用，例如濫用日曆或 API 整合，這可能引發意外或惡意行為 [43, 44]。最後，代理身份濫用，例如偽裝或擁有過高權限的代理未經授權地採取行動，會造成嚴重的組織風險 [45]。這些攻擊大多在今天已完全可實現——例如，最近的研究已模擬出成功且完全自主的多 AI 代理網絡攻擊，這些攻擊能夠智能地適應網絡防禦措施 [46]。

鑑於開發與應用代理式 AI 系統之進展加速，社群亟需了解並處理前述安全風險。然而，由於該領域已有大量研究，因此有必要系統化當前的研究工作，並建立涵蓋代理式 AI 所造成所有安全威脅的分類架構。此外，為真正確保這些代理式系統的安全，了解針對已知攻擊/威脅的防禦最新進展，並概述尚存的開放性挑戰，同樣至關重要。透過本調查，我們期望在各方向上取得顯著進展，其目標在於激發研發安全且可靠代理式 AI 架構的研究努力，進而加速其在社會中的應用。

備註。我們的工作亦與該領域現有的調查有所區別，並解決了一個被忽視的問題。現有的關於自主 AI 代理的調查 [47–51] 大多詳述其能力並提出評估基準，而其他調查則探討信任與風險管理等主題 [52]，卻缺乏對安全的單一聚焦，這與我們的工作不同。另一方面，如 NIST 生成式 AI 檔案 [53] 等風險管理框架提供了基準指導，但將其應用於自主代理仍處於進程中。

調查其餘部分結構如下：第 3 節提供代理式 AI 安全威脅與攻擊的廣泛分類；第 4 節涵蓋當前防禦方法的最新進展；第 5 節詳述評估安全關鍵型代理式 AI 應用之基準測試實踐與指南；第 6 節闡述保護 AI 代理所面臨的開放性挑戰與問題；第 7 節總結本調查。

3 安全威脅分類學

我們現在提出並討論針對代理式 AI 系統的攻擊分類與安全漏洞。更具體地說，在本節中，我們將威脅廣泛分為以下類別：(i) 提示注入與越獄，(ii) 自主網路攻擊與工具濫用，(iii) 多代理與協議層威脅，(iv) 介面與

Environment Risks, and (iv) Governance and Autonomy Concerns. For each category, we will discuss the various attacks that are relevant for the given problem setting, and provide further subcategorization. These classifications are also visualized in Figure 2.



Figure 2: Taxonomy of Agentic AI Security Threats.

環境風險，以及 (iv) 治理與自主權疑慮。針對每一類別，我們將討論與該特定問題設定相關的各種攻擊，並提供進一步的細分分類。這些分類亦於圖 2 中視覺化呈現。



圖 2：代理式 AI 安全威脅分類學。

Attacks and threats can be multifaceted, and their behavior often spans multiple threat patterns. Our taxonomy is therefore not meant to define mutually exclusive categories; rather, it organizes attacks according to their primary distinguishing properties for analytical clarity.

3.1 Prompt Injection and Jailbreaks

Prompts are commands that specify how an AI agent should behave [54]. Hence, the primary security threat to any agent is the prompt itself. AI Prompt injection (PI) remains the most widely discussed attack in the literature, where malicious instructions cause the model to deviate from intended behavior [55, 56]. As noted by Beurer-Kellner et al. in [57], *prompt injection attacks occur when malicious data, embedded within content processed by the LLM, manipulates the model's behavior to perform unauthorized or unintended actions*. Similarly, Lee et al. [37] describe prompt injection *as an attack in which external malicious instructions are used to override the user's request, effectively giving the attacker control over the model's output*. We now discuss the various types of prompt injection attacks.



Figure 3: Examples showcasing (a) *direct* and (b) *indirect* prompt injection. In the former, the agent is directly instructed by the adversary to reveal confidential information whereas in the latter the attacker has exploited the agent's reliance on external information sources to have it download malware from their altered website.

3.1.1 Direct and Indirect Prompt Injection

Prompt injection manifests in two broad forms, *direct* and *indirect* (see Figure 3 for an example). Direct Prompt Injection (DPI) variants directly insert the malicious instructions into the input prompt to manipulate the agent's behavior [58, 59]. Such an attack can be incredibly powerful if successful. For instance, an attacker could employ direct prompt injection to poison a customer support chatbot, compelling it to disregard prior guidelines, extract sensitive information from internal data sources, and potentially even trigger unauthorized actions (e.g. sending emails), thereby resulting in confidential data exposure [58].

Indirect Prompt Injection (IPI) attacks instead cause LLMs to diverge from user-provided instructions by inserting malicious instructions into external data that the model processes [60, 36]. Note that for DPI attacks, the end-user is the attacker; while for IPI attacks, the owner or supplier of agent-processed third-party information is the attacker [57]. Adaptive attacks, where the attacker manipulates external content, have proven to achieve a success rate of 50% in penetrating eight different defenses designed for IPI attacks [61]. These attacks typically involve inserting adversarial strings before or after instructions to manipulate LLM agent behavior.

A number of different attack strategies have been proposed for undertaking IPI. Originally proposed for jailbreaking, *Greedy Coordinate Gradient (GCG)* [62] has been adapted to IPI by generating affirmative prefixes containing adversarial strings that induce malicious outputs from the agent [63]. In a similar fashion, *two-stage GCG* [64] trains a two-part adversarial string that is still effective after paraphrasing in order to get beyond defenses based on paraphrase detection. Lastly, as the aforementioned attacks often generate gibberish strings that can be easily detected via perplexity defenses, *AutoDAN* [65] enhances the semantic quality of adversarial strings to decrease detectability.

攻擊與威脅可能具有多面向性，其行為往往跨越多種威脅模式。因此，我們的分類法並非旨在定義互斥的類別；相反，它是依據攻擊的主要區別特性來進行組織，以確保分析的清晰度。

3.1 提示注入與越獄

提示是定義 AI 代理應如何行為的指令 [54]。因此，任何代理的主要安全威脅來自提示本身。AI 提示注入（PI）仍是文獻中討論最廣泛的攻擊類型，惡意指令會導致模型偏離預期行為 [55, 56]。如 Beurer-Kellner 等人在 [57], 中所指出，提示注入攻擊發生在惡意數據嵌入至 LLM 處理的內容中，從而操控模型行為以執行未經授權或預期的動作。同樣地，Lee 等人在 [37] 中將提示注入描述為一種攻擊，其中外部惡意指令用於覆寫使用者的請求，實質上讓攻擊者掌控模型的輸出。接下來我們將討論各種提示注入攻擊類型。



圖 3：展示 (a) 直接與 (b) 間接提示注入的範例。在前者中，代理被攻擊者直接指示洩露機密資訊；而在後者中，攻擊者利用代理對外部資訊來源的依賴，使其從其修改過的網站下載惡意軟體。

3.1.1 直接與間接提示注入

提示注入主要有兩種形式：直接與間接（請參閱圖 3 了解範例）。直接提示注入（DPI）變體會將惡意指令直接插入輸入提示中，以操縱代理的行為 [58, 59]。若此類攻擊成功，其威力將極大。例如，攻擊者可能利用直接提示注入來污染客服聊天機器人，迫使其忽視既有規範、從內部數據源中提取敏感資訊，甚至可能觸發未經授權的操作（例如發送電子郵件），從而導致機密資料洩漏 [58]。

間接提示注入（IPI）攻擊會導致大型語言模型（LLM）偏離用戶提供的指令，方法是將惡意指令插入模型處理的外部數據中 [60, 36]。請注意，對於深度提示注入（DPI）攻擊，最終用戶是攻擊者；而在 IPI 攻擊中，處理第三方信息的代理所有者或供應商才是攻擊者 [57]。攻擊者操縱外部內容的適應性攻擊已被證明能成功穿透針對 IPI 攻擊設計的八種不同防禦機制，成功率達 50% [61]。這些攻擊通常涉及在指令之前或之後插入對抗性字符串，以操縱 LLM 代理的行為。

針對執行 IPI 的攻擊策略已提出多種方案。最初為繞過 jailbreak 而設計的 Greedy Coordinate Gradient (GCG) [62]，已透過生成包含惡意字串的肯定前綴來適應 IPI，從而誘導代理產生惡意輸出 [63]。類似地，兩階段 GCG [64] 訓練一個兩部分的惡意字串，該字串在經過同義重寫後仍有效，以突破基於同義重寫檢測的防禦機制。最後，由於前述攻擊經常生成可透過困惑度防禦輕易檢測到的亂碼字串，AutoDAN [65] 則提升惡意字串的語義品質以降低可檢測性。



Figure 4: An example showcasing *unintentional* prompt injection.

Note that IPI attacks take advantage of the agent's dependence on outside tools and information sources by enclosing harmful tasks in resources that appear to be harmless, such as databases, APIs, or web pages [66–69]. These encoded instructions can force agents to perform unwanted actions, such as manipulating the interface or calling illegal tools, frequently while posing as legitimate duties. This type of attack is more pernicious than direct injections since the injected prompts can look like legitimate agent instructions, making it hard to tell them apart from regular processes [70]. Attacks against web agents, for instance, manipulate HTML structures or accessibility trees to redirect agent actions, while those targeting computer agents can exploit interface interactions to gain persistent control [69, 71]. The challenge is compounded by the fact that successful IPIs frequently exploit the decoupling between user inputs and subsequent tool calls, a behavioral property that differentiates them from traditional jailbreak prompts.

Prior work has also studied real-world application settings for IPI attacks. For instance, in [72], the authors study IPI against LLM-powered web navigation agents. The authors demonstrate how adversarial triggers might reroute agent behavior toward malevolent goals like credential theft, forced ad engagement, or unauthorized site redirection when they are incorporated into the HTML accessibility tree of trustworthy websites. Notably, they show how login credentials from many platforms can be collected by a single malicious trigger [72]. They also demonstrate how strategies like CSS obfuscation and hidden HTML elements can further improve stealth, making attacks *invisible* to users.

3.1.2 Intentional and Non-Intentional Prompt Injection

Prompt injection threats can be further distinguished by whether they are introduced *deliberately* by an adversary or emerge *unintentionally* during benign interactions. This distinction is crucial in the context of agent-based systems, as both cases can result in harmful behaviors [58].

Even when a malicious adversary is not present, unintended dangers can jeopardize LLM agents' safety. For example, unclear or badly worded user inquiries may unintentionally overrule system directives or result in dangerous actions. Moreover, contextual drift within lengthy chat histories can change the agent's behavior without the need for explicit override orders [73, 74]. Thus, the central challenge is not only detecting explicit attacks but also designing agents that remain aligned under ambiguous or shifting input conditions, highlighting the need for stronger defenses in input validation, context management, and instruction adherence. We provide a visual example for unintentional prompt injection attacks in Figure 4.

On the other hand, harmful instructions can also be created by adversaries, specifically with the objective of manipulating an LLM agent in intentional prompt injection. Both direct prompt hijacking (e.g. strings such as "*ignore all previous instructions and...*"), and indirect vectors (malicious payloads encoded in external sources like papers, APIs, or online content), can be intentional in nature [75, 76]. Intentional prompt injection can also spread among agents in multi-agent systems, resulting in persistent hijacking or coordinated compromise via reliable communication channels [37]. In comparison to unintentional prompt injection, as purposeful attacks aim to force agents to carry out harmful behaviors rather than only produce dangerous outputs, they necessitate proactive protection strategies such as input sanitization, tool-use monitoring, and anomaly detection [61].



圖 4：展示無意中提示注入的範例。

請注意，IPI 攻擊利用代理對外部工具和資訊來源的依賴，將有害任務包裝成看似無害的資源（例如資料庫、API 或網頁） [66–69]。這些編碼後的指令可迫使代理執行不希望的操作，例如操作介面或呼叫非法工具，同時偽裝成合法任務。此類攻擊比直接注入更具破壞性，因為注入的提示看起來像是合法的代理指令，難以與正常過程區分[70]。針對網頁代理的攻擊會操弄 HTML 結構或可訪問性樹狀結構以重定向代理行為，而針對電腦代理的攻擊則可利用介面互動來獲得持續控制權 [69, 71]。此挑戰因成功 IPI 經常利用使用者輸入與後續工具呼叫之間的解耦特性而更加複雜，這是一種將它們與傳統越獄提示區分的行為特徵。

先前的研究也探討了 IPI 攻擊在真實世界應用場景中的情況。例如，在 [72], 中，作者研究了針對由大型語言模型（LLM）驅動的網頁導航代理的 IPI 攻擊。作者展示了當惡意觸發器被納入可信網站的 HTML 可訪問性樹中時，如何將代理行為重導向惡意目標，例如憑證竊取、強制廣告互動或非授權網站重導向。值得注意的是，他們展示了單一惡意觸發器如何收集來自多個平台的登入憑證 [72]。他們還展示了 CSS 混淆和隱藏 HTML 元素等策略如何進一步提升隱蔽性，使攻擊對用戶不可見。

3.1.2 有意與非有意提示注入

提示注入威脅可根據其是否由攻擊者故意引入，或在良性互動中意外出現，進一步區分。此區分在基於代理的系統中至關重要，因為這兩種情況都可能導致有害行為 [58]。

即使沒有惡意攻擊者，意外危險仍可能危及大語言模型代理的安全性。例如，含糊不清或措辭不當的用戶查詢可能會意外地覆蓋系統指令，或導致危險行為。此外，在冗長的對話歷史中，情境漂移可能改變代理的行為，而無需明確的覆蓋命令 [73, 74]。因此，核心挑戰不僅在於檢測明確的攻擊，還在於設計能在模糊或變化的輸入條件下保持對齊的代理，這突顯了加強輸入驗證、情境管理和指令遵循方面防禦的必要性。我們在圖 4 中提供了意外提示注入攻擊的視覺範例。

另一方面，攻擊者也可能創建有害指令，其特定目標是有意進行提示注入以操控 LLM 代理。無論是直接提示劫持（例如「忽略所有先前指令並……」類型的字串），還是間接向量（在外部來源如論文、API 或網路內容中編碼的惡意載體），其本質均可能為有意圖 [75, 76]。有意圖的提示注入也可能在多代理系統中於代理之間傳播，導致透過可靠通訊渠道造成持續劫持或協調性攻陷 [37]。與非有意圖的提示注入相比，由於有意圖的攻擊旨在迫使代理執行有害行為，而非僅產生危險輸出，因此需要主動防護策略，例如輸入清洗、工具使用監控與異常檢測 [61]。

3.1.3 Based on Attack Modalities

Beyond traditional text-based prompt injection, AI agents are increasingly vulnerable to attacks that exploit the growing capabilities of modern models, including *code generation/execution, and multimodal understanding* [77, 78, 59]. Adversaries can leverage agents' black box nature to human eyes, training methods, and interpretations of their inner logic, to conceal and inject instructions within images, sounds, or videos [79]. Naturally, as conventional filters and defenses are more general in nature, they fail to detect such agent-specific exploitations. We visualize these attacks in Figure 5 and discuss them in detail next.

Text-Based Injection With the rise in popularity of LLM agents, text-based attacks can manifest in different forms. These range from direct prompt injection to code injection under the pretense of legitimate programming activities, enabling the generation of malicious code or SQL queries to carry out *disallowed* actions (known as prompt-to-SQL or P2SQL attacks) [80, 59]. By taking advantage of semantic gaps between human instructions and SQL generation, these attacks circumvent standard database security measures [80–82]. Real-world examples include `CVE-2024-5565`, which demonstrates how AI-generated code can be used for arbitrary execution [83], as well as attacks that indirectly exploit OCR-readable text [77].

Image-Based and Video-Based Injection These attacks comprise of malicious instructions embedded in images through steganography or visual patterns that agents interpret as commands [77, 79]. Essentially, past work [77, 79] has shown that attackers can easily manipulate a model/agent into producing malicious behavior using perturbed images. This also demonstrates a potential vulnerability for future agentic frameworks that might utilize video-based input, since videos can be decomposed into individual key frames [84] of images. Moreover, a number of powerful adversarial attack strategies exist for current video-based AI/ML models [85–87], reinforcing this concern further.

Audio-Based Injection Similar to image-based injections, agentic AI frameworks can also be susceptible to audio-based injection attacks. Here, the attacker subvertly poisons the audio input modality with a malicious instruction that causes agents to deviate from safe behavior. Past work has demonstrated how adversarial perturbations can be used to blend malicious prompt injections in audio content to undertake IPI attacks [79] and jailbreak models [88]. Other work has explored similar attacks at the embedding-level as well [89].

Hybrid Attacks Adversarial prompt injection attacks against agentic frameworks can also be *hybrid* in nature, and combine various modalities. Aichberger et al. demonstrate that adversarial image patches, when captured in screenshots, can hijack multimodal OS agents into executing harmful commands, regardless of screen layout or user request [90]. Building on this, Wang et al. introduce *CrossInject*, a cross-modal prompt injection method that embeds aligned adversarial signals in both vision and text, boosting attack effectiveness by at least 30.1% across various tasks [77]. Clearly, since malicious material in any supported modality might affect agent behavior and cause undesirable outputs, hybrid multimodal attacks are especially problematic for AI agents that communicate with external tools, documents, and web interfaces on their own with little to no supervision.

3.1.4 Propagation-Orientation

Another classification for prompt injection attacks can be made depending on whether the attack is confined to a single target, whereas others can spread across the system in a multi-hop manner. Thus, the manner in which an attack spreads across the system (in addition to the content or modality of injected responses) is a crucial component of agentic AI security [37]. Thus, it is paramount to comprehend *propagation behavior* [59] for effectively securing agents. We now discuss and classify the works in this domain into two broad categories.

Non-Propagating Attacks Some attacks are primarily aimed at extracting specific information from the environment. Many code injection attacks are non-propagating in nature, such as running SQL queries solely to retrieve the required data [91] or executing cross-site scripting to obtain the user token [92].

Propagating Attacks Recent studies [59] have defined *propagating attacks* on AI agents into two main types: *recursive injection*, where a single malicious prompt triggers a chain of compromised behaviors across future interactions [59, 37, 93], and *autonomous propagation*, which includes multi-agent infections and AI worms that spread malicious prompts across agents or system boundaries without user intervention [94, 37].

3.1.5 Multilingual and Obfuscated Injections

The employment of multiple languages, encodings, or symbols to mask malicious intent is a classic prompt obfuscation technique, enabling attackers to bypass standard filters and inject harmful content into otherwise innocuous-looking

3.1.3 基於攻擊模式

除傳統的文字型提示注入外，AI 代理正日益面臨攻擊威脅，這些攻擊利用現代模型日益增長的能力，包括程式碼生成/執行與多模態理解 [77, 78, 59]。攻擊者可利用代理在人類視角下的黑盒特性、訓練方法及其內部邏輯的詮釋，來隱藏並向圖片、聲音或視頻中注入指令 [79]。顯然，由於傳統過濾與防禦機制較為通用，無法偵測這類針對代理的特定攻擊。我們將在圖 5 中視覺化這些攻擊，並在下文詳細討論。

基於文本的注入隨著大型語言模型（LLM）代理的普及，基於文本的攻擊可呈現多種形式。這些攻擊範圍從直接的提示注入，到以合法編程活動為藉口的代碼注入，從而生成惡意代碼或 SQL 查詢以執行被禁止的操作（稱為提示到 SQL 或 P2SQL 攻擊） [80, 59]。這些攻擊利用人類指令與 SQL 生成之間的語義差距，繞過標準的數據庫安全措施 [80–82]。現實世界的案例包括 CVE-2024-5565，展示了 AI 生成的代碼如何被用於任意執行 [83], ，以及間接利用 OCR 可讀文本的攻擊 [77]。

基於影像與基於影片之注入攻擊 這些攻擊包含透過隱含術或視覺模式將惡意指令嵌入影像中，而代理將其解讀為命令 [77, 79]。本質上，過去的研究 [77, 79] 顯示，攻擊者可以輕易地透過擾動影像來操控模型/代理產生惡意行為。這也顯示出未來可能採用影片輸入的代理框架存在潛在漏洞，因為影片可被分解為單個關鍵幀 [84] 。此外，針對現有基於影片之 AI/ML 模型，已存在多種強大的對抗攻擊策略 [85–87], ，進一步強化了這一擔憂。

與圖像注入類似，代理 AI 框架也可能受到基於音頻的注入攻擊。在此類攻擊中，攻擊者會暗中在音頻輸入模態中注入惡意指令，導致代理行為偏離安全範疇。先前的研究已證明，對抗性擾動可被用於將惡意提示注入混入音頻內容中，從而實施提示注入攻擊（IPI） [79] 以及繞過模型（jailbreak） [88]。其他研究也探討了在嵌入層進行的類似攻擊 [89]。

混合攻擊對抗性提示注入攻擊針對代理框架的攻擊也可能具有混合性質，並結合多種模態。Aichberger 等人證明，當對抗性圖像區塊被截圖捕捉時，可劫持多模態作業系統代理執行有害命令，無論螢幕佈局或使用者請求為何 [90]。基於此，Wang 等人提出 CrossInject，一種跨模態提示注入方法，在視覺與文字中嵌入對齊的對抗性訊號，使各項任務的攻擊效能提升至少 30.1% [77]。顯然，由於任何支援的模態中的惡意材料都可能影響代理行為並導致不良輸出，因此混合多模態攻擊對那些與外部工具、文件及網頁介面進行溝通且幾乎無監督的 AI 代理而言，尤為成問題。

3.1.4 傳播 - 方向

另一種針對提示注入攻擊的分類方式，是根據攻擊是否僅針對單一目標，或是以多跳方式在系統中擴散。因此，攻擊在系統中的擴散方式（除了注入回應的內容或模態之外）是代理 AI 安全的重要組成部分 [37]。因此，理解傳播行為 [59] 對於有效保護代理至關重要。我們現在將該領域的研究分為兩大類別進行討論和分類。

非傳播性攻擊 某些攻擊主要旨在從環境中提取特定資訊。許多程式碼注入攻擊具有非傳播性特徵，例如僅為獲取所需資料 [91] 而執行 SQL 查詢，或為了取得使用者金鑰 [92] 而執行跨站腳本攻擊。

擴散式攻擊近期研究 [59] 將針對 AI 代理的擴散式攻擊定義為兩類主要類型：遞迴注入，即單一惡意提示會觸發未來互動中一系列被侵蝕的行為 [59, 37, 93], ，以及自主擴散，其包含多代理感染與 AI 蠕蟲，能在未經使用者干預的情況下，將惡意提示傳播至代理或系統邊界 [94, 37]。

3.1.5 多語言與混淆注入

使用多種語言、編碼或符號來掩蓋惡意意圖，是一種經典的提示混淆技術，使攻擊者能夠繞過標準過濾器，並將有害內容注入到看似無害的提示中。



Figure 5: Visualizing different prompt injection attacks based on modality: (a) *image-based*, (b) *text-based code injection*, and a (c) *hybrid* attack.

inputs [58]. To evade content moderation pipelines, attackers may encode instructions using `Base64` strings, HTML entities, emojis, or conceal them within non-primary/low-resource languages. Because LLMs are still able to interpret and execute such hidden instructions with knowledge obtained during pre-training, obfuscation enables adversaries to circumvent naïve, pattern-based defenses [58, 95]. Prior work further demonstrates that these attacks can exploit weaknesses such as language-specific system prompts or inconsistencies in tokenizer handling [95].

3.1.6 Payload Splitting

Payload splitting refers to attacks where an adversary intentionally fragments malicious content across several benign-seeming inputs, then prompts the LLM to aggregate them, thus unveiling the harmful payload only upon recombination [96]. Distributing a malicious instruction over several inputs such that its adversarial effect only manifests when the model combines or processes them all together is a complementary tactic. An LLM-powered screening agent, for instance, may concatenate or jointly summarize resumes that contain fragments of a malicious prompt strewn throughout sections to manipulate the model into giving positive evaluations regardless of the actual qualifications [58, 57]. This attack essentially takes advantage of the aggregation stage in multi-document or retrieval-based workflows [94] and has thus been identified as a major weakness in resume-screening assistants and related LLM-based HR processes [57]. Note that payload splitting, as opposed to direct prompt injections, makes it significantly more challenging to detect malicious information in any one input but still allows the attacker to accomplish their goal when the pieces are reassembled [58].

3.2 Autonomous Cyber-Exploitation and Tool Abuse

When LLM agents are given access to code execution or system-level tools, they can carry out adversarial cybersecurity attacks on their own, giving birth to autonomous *cyber-exploitation*. In contrast to quick injection or jailbreak attacks, which require an outside actor manipulating the model, autonomous exploitation entails agents themselves identifying, organizing, and carrying out attacks without direct human supervision [94, 37, 97]. Past works have shown that these adversarial agents are capable of successfully compromising websites in sandboxed settings [81] and executing one-day vulnerability exploitation [98]. Moreover, the aims of attackers in these situations can include data theft, fraud, ransomware deployment, and network lateral movement, according to various industry assessments [16].

It is especially important to recognize that the *economics* of autonomous cyber-exploitation benefit adversaries significantly [94, 37, 97]. For instance, adversaries can use GPT-4 to execute effective one-day exploits for a few dollars each time, making the attack cost less than employing human attackers. Additionally, the parallelizable nature of LLM-driven attacks compounds upon this issue as it is both possible and economical to scale to high volumes of attack attempts [81]. We now delve into three subcategorizations for these attacks, and provide more details on each below:



圖 5：根據模態展示不同的提示注入攻擊：(a) 圖像基，(b) 基於文字的程式碼注入，以及 (c) 混合攻擊。

inputs [58]。為規避內容審核流程，攻擊者可能使用 Base64 字串、HTML 實體、表情符號，或將指令隱藏在非主要/低資源語言中。由於大型語言模型（LLM）仍能利用預訓練期間獲得的知識來解讀並執行這些隱藏指令，因此混淆技術使攻擊者得以繞過基於模式的簡單防禦 [58, 95]。先前的研究進一步證明，這些攻擊可利用語言特定的系統提示或分詞器處理不一致等弱點 [95]。

3.1.6 載體分割

載入分割是指攻擊者有意將惡意內容分片到幾個看似無害的輸入中，然後促使 LLM 進行聚合，從而只有在重新組合後才揭露有害的載入內容[96]。將惡意指令分佈到多個輸入中，使其對抗效應僅在模型結合或處理它們時才會顯現，是一種補充策略。例如，一個基於 LLM 的篩選代理可能會拼接或聯合總結包含散佈於各段中的惡意提示片段的履歷，以此操縱模型無論實際資歷如何都給予正面評價 [58, 57]。此攻擊本質上利用了多文檔或檢索工作流中的聚合階段 [94] ，因此已被識別為履歷篩選助手及相關基於 LLM 的人力資源流程中的重大弱點 [57]。請注意，與直接提示注入不同，載入分割使得在單一輸入中檢測惡意信息變得更加困難，但當這些片段被重新組裝時，攻擊者仍能實現其目標 [58]。

3.2 自主網絡攻擊與工具濫用

當大型語言模型（LLM）代理被賦予程式碼執行或系統級工具的權限時，它們可能自行實施惡意網路安全攻擊，從而催生自主式網路攻擊。與需要外部操作者操控模型的快速注入或越獄攻擊不同，自主式攻擊涉及代理自行識別、組織並執行攻擊，無需直接的人類監督 [94, 37, 97]。先前的研究顯示，這些惡意代理在沙箱環境中能夠成功入侵網站 [81] ，並執行單日漏洞利用 [98]。此外，根據多項產業評估，攻擊者在此類情境下的目標可能包括資料竊取、詐騙、勒索軟體部署以及網路橫向移動 [16]。

特別重要的是要認識到，自主網路攻擊的經濟效益對敵對方有顯著助益 [94, 37, 97]。例如，敵對方可利用 GPT-4 執行有效的一日攻擊，每次僅需幾美元，使得攻擊成本低於雇用人類攻擊者。此外，大型語言模型驅動的攻擊具有可並行特性，這進一步加劇了該問題，因為將攻擊嘗試規模擴大至高體量既可行又經濟 [81]。以下我們將探討這三類攻擊的細分，並提供更多細節：

3.2.1 Exploitation of One-Day Vulnerabilities

Recent work has shown that LLM agents, especially those built on top of GPT-4, are capable of autonomously exploiting real-world one-day vulnerabilities, including unpatched `CVEs` in Python packages, online platforms, and container management systems [98]. To carry out sophisticated exploits such as SQL injection, Remote Code Execution (RCE), and concurrent/coordinated attacks, adversarial agents can leverage tool usage, planning, and document retrieval. Notably, GPT-4 has generally outperformed all other examined models and conventional vulnerability scanners like `OWASP ZAP` [99] and `Metasploit` [100], achieving an 87% success rate when given `CVE` descriptions [98].

3.2.2 Autonomous Website Hacking

In recent work, Fang et al. [81] demonstrate how GPT-4 agents are capable of independently breaching sandboxed websites without being aware of certain vulnerabilities beforehand. These agents carry out multi-step attacks, such as utilizing Cross-Site Scripting (XSS) and Cross-Site Request Forgery (CSRF) for XSS+CSRF chaining [101], server-side template injection (SSTI) [102], and blind SQL union injections [103]. The study showcases that agentic capabilities such as context management, tool integration, and strategic planning are crucial to attack success. In general, performance is dramatically reduced when document access or detailed prompting is not provided to agents.

3.2.3 Emergent Tool Abuse

Recent research has also shown that autonomous LLM agents can undertake cooperative and adaptive tool usage behaviors to conduct cyberattacks. For instance, in [81], the authors design LLM agents capable of performing intricate multi-step website exploits via strategic combinations of tool calls and dynamic planning. Shi et al.'s *ConAgents* [104] framework highlights structured cooperation among specialized agents for tool selection, execution, and action calibration, allowing agents to iteratively recover from failures and refine their actions. On the tool-integration front, Wang et al.'s *ToolGen* [105] framework enables LLMs to invoke tools as part of next-token generation, simplifying chaining across extensive tool sets without external retrieval modules. Together, these works underscore the importance of deploying robust containment and runtime monitoring mechanisms when implementing autonomous agent systems with tool access.

3.3 Multi-agent and Protocol-level Threats

In general, multi-agent systems introduce unique attack vectors that stem from the need for standardized communication, interoperability, and distributed task execution. Unlike single-agent settings, where threats are largely confined to prompt injection or unsafe tool use, multi-agent ecosystems amplify risk through protocol-mediated interactions. Message tampering, role spoofing, and protocol exploitation create opportunities for adversaries to compromise not only a single agent but entire coordinated workflows [37, 106]. We visualize these attacks in Figure 6 and discuss them in detail next.

3.3.1 Protocol-level MCP and A2A attacks

Several recent works have investigated security threats emanating from emerging protocol-level standards. Notably, Ferrag et al. [107] have examined vulnerabilities in the popular Model Context Protocol (MCP) [108] and Agent-to-Agent (A2A) protocol [109] frameworks, as well as broader protocol families such as Agent Network Protocol (ANP) [110] and Agent Communication Protocol (ACP) [111]. We restrict our discussion below to MCP and A2A threats, given their prominence and popularity in enabling agent–tool integration and multi-agent ecosystems.

MCP-induced attacks *MCP-induced attacks* exploit the design of the Model Context Protocol itself, which uses a client–server architecture to link language models with external resources such as file systems, APIs, or databases [108]. By separating access from model logic, MCP broadens agent functionality but exposes several *protocol-level* attack vectors.

The most common attacks are *flooding and replay exploits*, where adversaries exploit request flooding or infinite loops to disrupt operations, leading to Denial of Service (DoS) [112]. An adjacent but distinct attack comprises *credential compromise*, which occurs through insecure proxies or leaked tokens, and enables impersonation of agents [107].

Other MCP attacks result from the way agents interact with MCP-mediated resources, and not from the protocol structure solely. For instance, *embedded backdoors* are malicious triggers hidden in prompts or model parameters that misuse MCP-enabled tool access [107, 113]. Other work on retrieval corruption and federated training manipulation, studies scenarios where adversaries distort contextual inputs in retrieval-augmented generation pipelines [114] or inject malicious

3.2.1 利用一日漏洞

近期研究顯示，基於 GPT-4 等基礎架構構建的 LLM 代理，能夠自主利用現實世界中的單日漏洞，包括未修復的 Python 套件、線上平台及容器管理系統中的 CVE [98]。為執行如 SQL 注入、遠端程式碼執行（RCE）及並行/協調攻擊等複雜攻擊，對抗性代理可善用工具使用、規劃與文檔檢索功能。值得注意的是，GPT-4 在表現上普遍優於其他所有受測模型及傳統漏洞掃描器（如 OWASP ZAP [99] 與 Metasploit [100],），在獲得 CVE 描述 [98] 的情況下，成功率高達 87%。

3.2.2 自主網站駭客

在最近的研究中，Fang 等人 [81] 展示了 GPT-4 代理如何能够在未事先了解某些漏洞的情況下，独立突破沙箱化网站。这些代理执行多步骤攻击，例如利用跨站脚本（XSS）和跨站请求伪造（CSRF）进行 XSS+CSRF 链式攻击 [101],服务端模板注入（SSTI） [102], 以及盲 SQL 联合注入 [103]。该研究表明，代理能力如上下文管理、工具集成和战略规划对于攻击成功至关重要。总体而言，若未向代理提供文档访问权限或详细提示，其性能将大幅下降。

3.2.3 突發工具濫用

近期研究也顯示，自主的 LLM 代理能夠執行協作與適應性的工具使用行為以進行網路攻擊。例如，在 [81], 中，作者設計了能夠透過工具呼叫的戰略性組合與動態規劃，執行複雜多步驟網站漏洞利用的 LLM 代理。Shi 等人提出的 ConAgents[104] 框架強調了專責代理之間在工具選擇、執行與行動校準方面的結構化協作，使代理能夠迭代式地從失敗中恢復並優化其行動。在工具整合方面，Wang 等人提出的 ToolGen [105] 框架使 LLM 能夠將工具調用納入下一個 token 的生成過程中，簡化了跨大量工具集的鏈接，無需外部檢索模組。這些作品共同強調，在實施具有工具存取權的自主代理系統時，部署堅實的封鎖與運行時監控機制至關重要。

3.3 多代理與協議層威脅

一般而言，多智能體系統引入了獨特的攻擊向量，這些向量源於對標準化通信、互操作性以及分發式任務執行的需求。與單智能體環境不同，後者威脅主要局限於提示注入或不安全工具使用，多智能體生態系統則透過協議介導的互動放大了風險。訊息篡改、角色偽造及協議濫用為攻擊者提供了機會，使其不僅能竊取單一智能體，更能破壞整個協同工作流 [37, 106]。我們在圖 6 中展示了這些攻擊，並將在接下來的內容中詳細討論。

3.3.1 協議層 MCP 與 A2A 攻擊

近期多項研究探討了源自新興協議層級標準的安全威脅。特別地，Ferrag 等人 [107] 檢視了廣受歡迎的模型上下文協議（MCP） [108] 以及 Agent-to-Agent（A2A）協議 [109] 框架中的漏洞，並涵蓋更廣泛的協議家族，例如 Agent Network Protocol（ANP）[110] 與 Agent Communication Protocol（ACP） [111]。由於 MCP 與 A2A 在促進代理與工具整合及多代理生態系統方面的顯著地位與普及度，我們在下文將討論範圍限制於這兩種協議的威脅。

MCP 誘發的攻擊 MCP 誘發的攻擊利用模型上下文協議（Model Context Protocol）本身的设计，該協議採用客戶端 - 伺服器架構，將語言模型與外部資源（如檔案系統、API 或資料庫）[108] 相連。透過將存取權限與模型邏輯分離，MCP 擴大了代理的功能，但也暴露了若干協議層級的攻擊向量。

最常見的攻擊是淹沒與重放攻擊，攻擊者利用請求淹沒或無限迴圈來攔阻運作，導致服務中斷 (DoS) [112]。另一種相關但不同的攻擊是憑證洩漏，此類攻擊透過不安全的代理伺服器或洩漏的令牌發生，並使攻擊者能夠偽裝成代理 [107]。

其他 MCP 攻擊源於代理與 MCP 介接資源的互動方式，而非僅限於協議結構。例如，嵌入式後門是隱藏在提示詞或模型參數中的惡意觸發器，會濫用 MCP 啟用的工具存取權限 [107, 113]。其他研究則探討檢索腐敗與聯邦訓練操縱，分析敵對者如何在檢索增強生成管道中扭曲上下文輸入 [114] ，或注入惡意



Figure 6: Visualizing different protocol-level attacks for multi-agent systems: (a) *MCP-induced*, (b) *A2A-induced*.

updates in federated learning settings to corrupt distributed training data [115]. Further, *confidentiality breaches* are inference and side-channel timing exploits that leak sensitive contextual data exposed through MCP interfaces [116, 117].

As illustrated in Figure 6(a), an agent may issue a request to retrieve the contact information of a business from the internet using MCP protocol. An attacker can exploit a leaked or compromised response token to tamper with the returned contact details. Because the agent treats the token as valid, it subsequently trusts and acts upon the manipulated information, leading to insecure downstream behavior. On the other hand, if an attacker gains access to the database or file system consulted by the agent through MCP protocol, they can directly poison the underlying data, thereby influencing the agent's behavior when it consumes and acts upon this compromised information.

A2A-induced attacks *A2A-induced attacks* exploit vulnerabilities in the Agent-to-Agent (A2A) protocol, which coordinates interactions between MCP, capacity identification, and task delegation via JSON exchanges [109]. The scalable design of A2A introduces several protocol-specific threats, such as *fake agent advertisement and unauthorized registration*, which allow adversaries to impersonate agents or take over delegated tasks [118], and *recursive DoS attacks*, which are triggered by repeated task delegation that causes deadlocks or unbounded loops [119].



圖 6：視覺化多智能體系統中不同協議層攻擊：(a) MCP 誘發，(b) A2A 誘發。

更新聯邦學習環境下的分佈式訓練數據腐敗 [115]。此外，保密洩漏包括推斷和側信道時序利用，這些手段會洩漏透過 MCP 介面暴露的敏感上下文數據 [116, 117]。

如圖 6(a) 所示，代理可透過 MCP 協議向網際網路發出請求，以檢索企業的聯絡資訊。攻擊者可利用洩漏或遭入侵的回應金鑰，篡改返回的聯絡資料。由於代理將該金鑰視為有效，後續會信任並依據被篡改的資訊行事，進而導致不安全的下游行為。另一方面，若攻擊者透過 MCP 協議取得代理所查詢的資料庫或檔案系統存取權，可直接污染底層資料，進而影響代理在消費並處理此受污染資訊時的行為。

A2A 誘發攻擊 A2A 誘發攻擊利用代理對代理（A2A）協議中的漏洞，該協議透過 JSON 交換 [109] 協調 MCP、容量識別與任務委派之間的互動。A2A 的可擴展設計引入了若干特定於協議的威脅，例如偽造代理廣告與未經授權註冊，這些漏洞允許攻擊者偽裝成代理或接管委派的任務 [118]，以及遞迴型拒絕服務攻擊，其由重複的任務委派所觸發，導致死鎖或無界迴圈 [119]。

Other agent-induced attacks under A2A exploit the dynamics of agent–agent communication, such as *transitive prompt injection*, where harmful inputs spread through interconnected agent workflows [77]; *context tampering*, which involves manipulation of payloads to misguide execution or leak sensitive information [107]; and *memory manipulation*, where malicious inputs compromise internal agent state or corrupt persistent memory of AI agents [120].

The vulnerabilities across these agentic protocols highlight the fragility of protocol-level assumptions in multi-agent ecosystems. By compromising discovery, authentication, or task orchestration, adversaries can escalate from local manipulation to system-level compromise. These risks underscore the need for protocol-hardening, secure agent identity management, and robust monitoring to mitigate cascading failures in multi-agent AI systems. Next, we discuss other attacks/threats unique to multi-agent LLM systems.

In a multi-agent system where the responsibilities are divided, as depicted in Figure 6(b), when an existing agent issues a discovery request to identify an agent for email summarization, an adversary can inject a malicious agent by forging a discovery response through the A2A protocol. Similarly, an attacker may hijack A2A-based interactions to induce other agents to store malicious websites as trusted user preferences (e.g., a favorite shopping site), thereby influencing subsequent agent decisions and actions.

3.3.2 Threat Actor Perspective

Building on the taxonomy proposed by Ko et al. [106], we reorganize the security challenges of cross-domain multi-agent LLM systems explicitly from the *threat actor's perspective*. This framing highlights how malicious actors can exploit inter-agent trust, coordination, learning, and data flows. We identify six broad classes of threats: *Impersonation & Role Abuse*, *Coordination Manipulation*, *Knowledge & Learning Manipulation*, *Inference & Policy Evasion*, *Accountability Obfuscation*, and *Confidentiality & Integrity Breaches* which we will discuss next.

Impersonation and Role Abuse Adversaries can exploit the absence of centralized identity and trust management to assume false roles or override intended privileges. By spoofing an agent's identity or posing as a trusted collaborator, an attacker gains entry into workflows that would otherwise be restricted [121, 122]. Once embedded, malicious agents can collude to form a hidden consensus, amplifying their influence until legitimate safeguards collapse [123, 124]. Conflicting incentives across domains/organizations (e.g. competing corporate interests), further provide cover for adversarial agents and enable them to mask their aims under the guise of organizational goals [106].

Coordination Manipulation Cross-domain/organizational systems dynamically group agents into task-specific teams, often with no prior vetting [125]. While this capability improves system adaptability and efficiency, it also weakens clear trust boundaries. Malicious or unverified agents can be introduced during runtime as part of task-specific teams, as evidenced by backdoor attacks [126–129]. Recursive delegation amplifies the attack: a compromised agent can offload subtasks to additional agents, spreading adversarial influence deeper into the workflow [106]. Unlike static attacks (e.g. traditional malware), these attacks exploit the very framework of *multi-agent* systems [130, 131].

Knowledge and Learning Manipulation Cross-domain multi-agent LLMs allow agents to self-improve via shared learning and distributed fine-tuning [106, 132]. Without unified oversight, an adversary can subtly manipulate one agent's reward signals, causing misaligned behavior to propagate across agents [133, 131]. Positive feedback loops may amplify unsafe objectives, enabling policy drift and authority overreach. Unlike prompt or memory injection, this attack exploits the learning process itself and can remain undetected across domains [106].

Inference and Policy Evasion Federated multi-agent LLM systems are transforming enterprise operations by enabling agents with access to sensitive data in one organization to interact with agents managed by external partners. However, once information flows across organizational boundaries, no single entity maintains complete oversight of the interaction, even though internal policies (e.g., *"do not disclose individual salaries,"* or *"share only aggregate statistics"*) remain in effect. This allows a threat actor to perform cross-agent inference, reconstructing sensitive data by reasoning over multiple partial outputs that individually appear innocuous. Traditional safety mechanisms assume full visibility of the prompt within a single agent [122, 37], but in federated settings, context is split across agents and their respective prompts. This fragmentation introduces opportunities for policy evasion. For example, an adversary might request the highest salary in a department from one agent and then ask another for the name of the person earning it, effectively reconstructing restricted information. Similarly, separate queries issued to different agents can be strategically combined to fulfill otherwise prohibited requests. Conventional defenses, such as static keyword filtering and role-based access controls [134], fail to capture these distributed inference attacks. Techniques such as zero-knowledge proofs [135] or differential privacy [136] also face limitations in dealing with the dynamic and compositional nature of natural language interactions [137]. Although recent research has shown that multi-turn attacks can circumvent protections that succeed in isolated settings, most enterprise tooling still treats agent interactions under an independence assumption [138].

其他在 A2A 下誘發的攻擊利用代理間通信的動態，例如遞進式提示注入，其中有害輸入通過互聯的代理工作流傳播 [77]；上下文篡改，涉及對載入項的操控以誤導執行或洩露敏感資訊 [107]；以及記憶操控，其中惡意輸入損害內部代理狀態或腐敗 AI 代理的持久記憶 [120]。

這些代理協議中的漏洞突顯了多智能體生態系統中協議層面假設的脆弱性。通過竊取發現、驗證或任務調度，攻擊者可能從本地操控升級為系統層面的滲透。這些風險強調了對協議加固、安全智能體身份管理以及堅實的監控的必要性，以減輕多智能體 AI 系統中的連鎖故障。接下來，我們將討論多智能體 LLM 系統所特有的其他攻擊/威脅。

在責任分工如圖 6(b) 所示的多代理系統中，當現有代理透過 A2A 協定發出發現請求以識別負責郵件摘要的代理時，攻擊者可透過偽造發現回應注入惡意代理。同樣地，攻擊者可能劫持基於 A2A 的互動，誘導其他代理將惡意網站儲存為受信任的使用者偏好（例如最喜愛的購物網站），進而影響後續代理的決策與行動。

3.3.2 威脅行為者視角

基於 Ko 等人提出的分類法 [106]，我們從威脅行為者的角度，明確重新組織跨領域多智能體大語言模型系統的安全挑戰。此框架突顯惡意行為者如何利用智能體間的信任、協調、學習及數據流進行攻擊。我們識別出六類廣泛的威脅：偽裝與角色濫用、協調操縱、知識與學習操縱、推斷與策略規避、責任模糊化，以及機密與完整性侵害，接下來我們將討論這些內容。

偽造身份與角色濫用攻擊者可以利用缺乏集中式身份與信任管理，假扮成假身份或覆蓋預設權限。透過偽造代理人的身份或冒充受信任的協作者，攻擊者得以進入原本受限的工作流程 [121, 122]。一旦滲透，惡意代理人可串聯形成隱蔽共識，擴大其影響力，直至合法防護機制崩潰 [123, 124]。跨領域/組織的衝突性動機（例如競爭的企業利益），進一步為惡意代理人提供掩護，並使其得以以組織目標為藉口來掩蓋其意圖 [106]。

協調操控會動態將跨領域/組織系統中的代理分組為特定任務團隊，通常無需事先驗證 [125]。雖然此能力提升了系統的適應性和效率，但也削弱了清晰的信任邊界。惡意或未驗證的代理可在運行時作為特定任務團隊的一部分被引入，後門攻擊 [126–129] 即為此提供了證據。遞歸委託會放大攻擊：被攻陷的代理可將子任務轉交給額外代理，使敵對影響深入工作流 [106]。與靜態攻擊（例如傳統惡意軟體）不同，這些攻擊利用了多代理系統本身的框架 [130, 131]。

知識與學習操控：跨領域多智能體大語言模型允許智能體透過共享學習與分佈式微調進行自我提升 [106, 132]。若缺乏統一的監督，攻擊者可以微妙地操控單一智能體的獎勵信號，導致行為對齊失效在智能體間傳播 [133, 131]。正向回饋循環可能放大不安全目標，引發策略漂移與權限濫用。與提示注入或記憶注入不同，此攻擊利用學習過程本身，且可能跨領域未被察覺 [106]。

推論與策略規避 聯邦多智能體 LLM 系統正在改變企業運營，使具備敏感數據訪問權限的組織內智能體能夠與外部合作夥伴管理的智能體進行互動。然而，一旦資訊跨越組織邊界，單一實體便無法對互動保持完整監管，儘管內部政策（例如「不得洩露個人薪資」或「僅分享聚合統計數據」）依然生效。這使得威脅行為者能夠執行跨智能體推論，透過推演多個看似無害的局部輸出，重建敏感資訊。傳統安全機制假設單一智能體內提示詞具有完整可見性 [122, 37]，但在聯邦環境中，上下文被分割至多個智能體及其各自的提示詞中。這種碎片化為策略規避提供了機會。例如，攻擊者可能向一個智能體請求某個部門的最高薪資，再向另一個智能體詢問該薪資由何人獲得，從而有效重建受限資訊。同樣地，針對不同智能體提出的獨立查詢可被策略性組合，以滿足原本被禁止的請求。傳統防禦手段，如靜態關鍵字過濾與基於角色的訪問控制 [134]，無法捕捉這些分佈式推論攻擊。零知識證明 [135] 或差分隱私 [136] 等技術在應對自然語言互動的動態與組合特性時 [137] 亦面臨限制。儘管近期研究顯示，多輪攻擊可繞過在孤立環境中有效的防護，但大多數企業工具仍基於獨立性假設來處理智能體互動 [138]。

Accountability Obfuscation From the perspective of a threat actor, multi-agent systems spanning multiple organizational domains provide significant opportunities to conceal responsibility for malicious actions. Each domain typically enforces independent logging, retention, and auditing policies, preventing a unified trace of activity [106]. Once input data is processed by an LLM, it is transformed into distributed latent representations, eliminating persistent identifiers that could link actions to their source [139]. Unlike conventional software systems that can implement *taint checking* or explicit information flow tracking [140], these latent representations make tracing infeasible [141]. Adversaries can exploit this by compromising an agent in Domain A, injecting deceptive but plausible instructions, and indirectly triggering harmful actions in Domain B, all while masking their identity and intent [142–144]. Even with auditing at the agent level, inter-agent relationships and cross-domain causality remain hidden, significantly complicating accountability. Current interpretability tools, such as influence functions [145, 146], activation tracing [147], or model-source attribution queries [148–150], provide limited visibility and often fail in these complex multi-agent settings.

Confidential Data Tampering/Exfiltration Threat actors can also target the cryptographic and workflow limitations of multi-agent systems. Even in privacy-preserving deployments where inputs and outputs remain encrypted [151–153], attackers may exploit the lack of complete plaintext visibility across domains. For instance, in cloud-hosted medical pipelines, encrypted patient scans are processed by multiple agents managed by different vendors, and intermediate outputs are never exposed [154]. While this design reduces direct exposure, adversaries could attempt to modify decrypted results or interfere with intermediate computations to inject harmful outcomes. Unlike local systems with centralized logging and signing, distributed encrypted workflows leave all participants exposed to attacks. Techniques such as fully homomorphic encryption [155], multi-party computation [156], and zero-knowledge proofs [157] offer partial mitigation, but they are computationally expensive and do not fully prevent manipulation in large-scale and multi-domain agentic networks. Thus, confidentiality and integrity gaps remain exploitable avenues for attackers in real-world multi-agent deployments.

3.4 Interface and Environment Risks

In the context of AI agents, particularly those operating in web-based or embodied environments, interface and environment risks refer to the vulnerabilities and limitations that arise from the interaction between the agent and its external operational environment context [158]. These risks are not rooted in the agent's internal reasoning or learning capabilities, but rather in the mismatch, fragility, or variability of the interfaces and environments through which the agent perceives and acts [159–161].

Three key dimensions characterize this risk category:

3.4.1 Observation and Action Space Misalignment

Although deployed agents frequently need grounded operations such as scrolling, hovering, or tab manipulation, LLMs are pretrained on static text corpora. Both perception and execution problems result from this mismatch in training data. Adversaries can also target these extant observation-action space misalignments and robustness issues to attack agentic systems. For instance, in benchmarks like WebArena, which evaluates general-purpose web interaction tasks, GPT-4's performance illustrates some of these challenges [159] where fine-grained actions like scrolling, hovering, and tab switching add needless complexity for the model and are frequently misused. AgentOccam also demonstrates that trajectory stability and task success can be greatly enhanced by streamlining the action space (e.g., eliminating commands with low utility, abstracting compound actions) and altering the observation space (e.g., trimming duplicate histories, supplying complete page states) [161]. All of these results reflect the need to match LLM reasoning biases to observation and action spaces for strong agent performance and to ensure a greater degree of robustness/trustworthiness.

3.4.2 Perception-Action Fragility in Realistic Environments

WebArena's error analysis exposes three tightly linked fragilities in LLM-based agents in real environments [159].

Misinterpretation of prior inputs Agents in realistic environments often misinterpret inputs, showcasing a lack of robustness. For instance, GPT-4 often reissues an already entered search phrase ("*DMV area*") until it reaches the step limit, demonstrating a failure to incorporate short-term state and past actions into decision-making. Agents also typically disregard previously entered inputs or action history [159]. Modern pretraining and supervised fine-tuning paradigms on dialogue-style data, which trains the model to learn short-term instruction-response behavior (while deprioritizing long-term embodied sequential state tracking), are likely resulting in these shortcomings [162, 159].

Premature termination and achievability misjudgement Another significant robustness issue in realistic environments is *unsafe early stopping*, which is often caused by *perception biases* in agents. For instance, in the WebArena

責任歸屬隱蔽從威脅行為者的角度來看，跨多個組織領域的多智能體系統提供了掩蓋惡意行為責任的重大機會。每個領域通常執行獨立的日誌記錄、保留和審計政策，阻礙了活動的統一追蹤 [106]。一旦輸入數據由大型語言模型處理，它就會被轉換為分佈式潛在表示，消除了可能將行為與其來源關聯的持久識別符 [139]。與能夠實施污點檢查或明確信息流追蹤的傳統軟件系統不同 [140]，這些潛在表示使得追蹤變得不可行 [141]。攻擊者可以通過此途徑，竊取領域 A 中的智能體，注入具有欺騙性但合理的指令，間接觸發領域 B 中的有害行為，同時掩蓋其身份和意圖 [142–144]。即使進行智能體層級的審計，智能體之間的關係以及跨領域的因果關係仍然隱藏，顯著增加了責任歸屬的複雜性。當前的可解釋性工具，例如影響函數 [145, 146]、激活追蹤 [147], 或模型來源歸因查詢 [148–150]，僅提供有限的可見性，且在這些複雜的多智能體環境中往往失效。

機密資料篡改/洩漏威脅：攻擊者也可能針對多代理系統的加密與工作流限制。即使在保護隱私的部署中，輸入與輸出保持加密狀態 [151–153]，攻擊者仍可能利用跨領域缺乏完整明文可見性的漏洞。例如，在雲端託管的醫療流程中，加密的病患掃描影像由不同廠商管理的多個代理進行處理，且中間輸出從未暴露 [154]。雖然此設計降低了直接暴露風險，但敵對方仍可能嘗試修改解密結果或干擾中間計算，以注入有害結果。與具備集中式日誌記錄與簽名的本地系統不同，分佈式加密工作流使所有參與者均暴露於攻擊風險之下。技術如全域同態加密 [155]、多方計算 [156], 與零知識證明 [157] 可提供部分緩解，但計算成本高昂，且無法完全防止大型多領域代理網絡中的篡改。因此，在現實世界的多代理部署中，機密性與完整性缺口仍成為攻擊者可利用的途徑。

3.4 介面與環境風險

在 AI 代理的語境中，特別是那些在基於網頁或具身環境中運作的代理，介面與環境風險指的是代理與其外部操作環境上下文 [158] 互動時所產生的漏洞與限制。這些風險並非源於代理內部推理或學習能力，而是源於代理感知與行動所依賴的介面與環境之間的失配、脆弱性或變異性 [159–161]。

此風險類別有三個關鍵維度：

3.4.1 觀察與動作空間對齊問題

儘管部署的代理經常需要接地操作，例如滾動、懸停或標籤操作，但大型語言模型（LLM）是在靜態文本語料庫上預訓練的。感知與執行問題均源於此訓練數據的失配。攻擊者亦可針對現有的觀察 - 動作空間對齊問題及魯棒性問題，來攻擊代理系統。例如，在 WebArena 等評估通用網頁互動任務的基準測試中，GPT-4 的表現就體現了這些挑戰 [159]，其中細粒度操作（如滾動、懸停和標籤切換）為模型增添了不必要的複雜性，且常被誤用。AgentOccam 也表明，透過簡化動作空間（例如，剔除低效用命令、抽象複合動作）以及調整觀察空間（例如，刪減重複歷史、提供完整的頁面狀態） [161]，可顯著提升軌道穩定性與任務成功率。所有這些結果都反映了將 LLM 的推理偏見與觀察空間和動作空間相匹配，以實現強大代理性能並確保更高程度的魯棒性/可信度的必要性。

3.4.2 真實環境中的感知 - 行動脆弱性

WebArena 的錯誤分析揭示了 LLM 基代理在真實環境 [159] 中存在的三個緊密相連的脆弱性。

誤解先前輸入 在真實環境中，代理常會誤解輸入，展現出缺乏魯棒性。例如，GPT-4 常會重新發出已輸入的搜尋詞句（「DMV 區域」），直到達到步驟限制，這顯示其未能將短期狀態與過往行動納入決策考量。代理也通常會忽略先前輸入或行動歷史 [159]。基於對話式數據的現代預訓練與監督微調範式，訓練模型學習短期指令 - 回應行為（同時降低對長期具身序列狀態追蹤的優先級），很可能導致這些不足 [162, 159]。

提早終止與可達成性誤判另一個在真實環境中顯著的問題是不安全的中止，這通常是由於代理的感知偏見所導致。例如，在 WebArena

benchmark, the authors provide *Unachievable (UA) Hints* in the agent prompts for tasks that are impossible to achieve given the lack of evidence. However, the removal of the explicit UA hint improves overall GPT-4 task success by 14.41% while decreasing the model's true positive detection of impossible tasks (to 44.44%). Moreover, GPT-4 mislabels 54.9% of actually feasible tasks as impossible under this instruction setting. This shows that even minor instruction changes have a significant impact on *stop/continue* behavior [159]. In contrast, instead of producing organized non-achievability reasoning, the smaller sized GPT-3.5 tends to further exhaust step limitations, repeat incorrect actions, or produce hallucinatory responses [159, 163].

Brittleness of templates, feedback, and memory LLM agents demonstrate brittle generalization when faced with repeated, long-horizon, or slightly varied tasks. Even when tasks are derived from the same underlying template, performance variance is significant: GPT-4 succeeds consistently on only 4 out of 61 templates in WebArena [159]. Similar brittleness has been observed in other benchmarks: Mind2Web reports that template-derived variations in web tasks often lead to sharp drops in success rates [163], while BrowserGym identifies instability in reproducing outcomes across different environments and interface states [160]. These findings underscore the limitations of relying on surface-level patterns without robust memory or adaptive feedback mechanisms. To bridge this gap the WebArena benchmark was proposed as a testbed for approaches that explicitly incorporate memory and feedback to improve reliability [159]. Complementary work such as AgentOccam has further shown that long-horizon coordination and trajectory stability can be enhanced through better planning primitives [161].

3.4.3 Dynamic Content, Localization, and Robot Detection

For autonomous agents, web environments present major accessibility and reproducibility challenges. Localization factors such as time zones, default languages, and geographic settings alter how websites are rendered resulting in varying agent behavior, thereby compromising consistency across trials [163]. Dynamic interface elements, including ads, pop-ups, and non-deterministic updates, further increase stochasticity, leading to unstable performance even on mostly identical tasks [159]. Creating additional friction, CAPTCHA and other robot-detection mechanisms often create significant issues for agentic systems. Studies such as Open CaptchaWorld [164] show that even advanced multimodal agents struggle with CAPTCHAs, achieving at best a 40% success rate compared to nearly 100% for humans. These limitations make reproducibility, reliability, and scalability persistent challenges for agentic AI security research in realistic environments (and more specifically, web-based systems) [160].

3.5 Governance and Autonomy Concerns

Owing to minimal human oversight and reduced control as AI agents become more independent, it is important to propose better governance/regulation of these systems. Fully autonomous systems that can write and run code on their own present increased risks in the areas of safety, security, and trust [165, 97, 166]. These agents have the potential to act in unpredictable ways, overcome human limitations, and expose users to a series of negative consequences, such as disinformation and hijacking [167, 168]. Ethical questions concerning power and responsibility are brought up by ineffective oversight, especially in high-stakes mission-critical applications such as autonomous weapons [169]. Researchers have recommended ensuring *human-in-the-loop* control and using structured autonomy levels to define agent capabilities and restrictions in order to reduce potential dangers [170, 171]. Moreover, it is of the utmost importance to develop governance frameworks that can guarantee and establish acceptable bounds for self-directed agent behavior in practice.

4 Defenses and Security Controls

To safeguard agentic AI systems from threats, various defense strategies and frameworks have been proposed. However, due to the constant evolution of attack vectors and threats, defense methods need to be continuously optimized and evaluated. To facilitate progress in developing better agentic AI defense mechanisms, we now discuss existing and current approaches. We also delineate potential shortcomings of these approaches. Moreover, we present Table 1, which shows secure-by-design coverage of security-critical defense components across defense approaches.

4.1 Prompt-Injection-Resistant Designs

Prompt injection remains one of the most persistent attack vectors against LLM agents, as adversarial inputs can override intended behavior and subvert downstream actions [61]. In general, prompt injection defenses [57, 95, 172] can be broadly grouped into three distinct classes: *agent-focused*, *system-focused*, *user-focused*. An additional classification can be made based on whether the system-focused methods are *training-based* or *training-free*. Some of these defense strategies are visualized in Figure 7. We discuss these categories (and their sub-classifications) in further detail, below:

在基準測試中，作者在代理提示中為無法達成（因缺乏證據）的任務提供了不可達成（UA）提示。然而，移除明確的 UA 提示使 GPT-4 的任務成功率提升 14.41%，同時降低了模型對不可能任務的真實陽性檢測率（至 44.44%）。此外，在此指令設定下，GPT-4 將 54.9% 實際上可執行的任務誤標為不可能。這表明，即使是微小的指令變更也會對停止/繼續行為產生顯著影響 [159]。相比之下，較小尺寸的 GPT-3.5 傾向於產生組織化的非達成性推理，而非進一步耗盡步驟限制、重複錯誤動作或產生幻覺回應 [159, 163]。

模板、反饋與記憶的 LLM 代理在面對重複、長時限或略有變化的任務時，會展現出脆弱的泛化能力。即使任務源自相同的底層模板，表現差異仍顯著：GPT-4 在 WebArena [159] 中僅能穩定成功於 61 個模板中的 4 個。其他評估指標也觀察到類似的脆弱性：Mind2Web 報告指出，源自模板的網頁任務變體常導致成功率急劇下降 [163]，；而 BrowserGym 則識別出在不同環境與介面狀態下重現結果的不穩定性 [160]。這些發現強調了僅依賴表面模式而缺乏穩健記憶或適配反饋機制所帶來的局限。為填補此缺口，WebArena 評估指標被提出作為測試場，用以驗證明確整合記憶與反饋機制以提升可靠性的方法 [159]。此外，如 AgentOccam 等相關研究進一步表明，透過更優化的規劃原語，可增強長時限協調與軌道穩定性 [161]。

3.4.3 動態內容、本地化與機器人偵測

對於自主代理而言，網頁環境帶來了重大的可訪問性和可重複性挑戰。時區、預設語言和地理設置等本地化因素會改變網站的渲染方式，導致代理行為產生差異，從而影響試驗間的一致性 [163]。動態介面元素，包括廣告、彈出視窗和非確定性更新，進一步增加了隨機性，導致即使在大部分相同的任務 [159]上，表現也不穩定。此外，CAPTCHA 及其他機器人偵測機制會增加額外障礙，經常對代理系統造成重大問題。例如 Open CaptchaWorld [164] 的研究顯示，即使是先進的多模態代理在處理 CAPTCHA 時也難以應對，最佳成功率僅為 40%，而人類則接近 100%。這些限制使得在真實環境（特別是基於網頁的系統）中，代理式 AI 安全研究的可重複性、可靠性和可擴展性持續面臨挑戰 [160]。

3.5 治理與自主權議題

由於人類監督極少且控制力隨 AI 代理日益獨立而減弱，因此有必要提出更完善的治理/監管機制。能夠自主撰寫並執行程式碼的完全自主系統，在安全、安全與信任方面帶來了更高的風險 [165, 97, 166]。這些代理可能以不可預測的方式行動，突破人類限制，並將用戶暴露於一系列負面後果之中，例如假訊息與劫持 [167, 168]。監督不力所引發的權力與責任倫理問題，特別是在自主武器等高風險關鍵任務應用中尤為突出 [169]。研究人員建議確保人類在環控制，並採用結構化的自主層級來定義代理的能力與限制，以減少潛在危險 [170, 171]。此外，開發能夠在實踐中確保並確立自我導向代理行為可接受邊界的治理框架，至關重要。

4 防護與安全控制

為保障代理式 AI 系統免受威脅，已提出多種防禦策略與框架。然而，由於攻擊向量與威脅不斷演變，防禦方法需持續優化與評估。為促進開發更優代理式 AI 防禦機制之進展，本文現探討現有及當前方法，並闡述這些方法潛在之不足。此外，本文還提供表 1，展示各防禦方法中「安全設計」覆蓋率，涵蓋安全關鍵之防禦組件。

4.1 防提示注入設計

提示注入仍是針對 LLM 代理最持久的攻擊向量之一，因為惡意輸入可覆蓋預期行為並顛覆後續動作 [61]。一般而言，提示注入防禦 [57, 95, 172] 可大致歸為三類：代理導向、系統導向、使用者導向。此外，若根據系統導向方法是否基於訓練來分類，則可進一步區分為訓練基於或無訓練方法。部分防禦策略已在圖 7 中展示。以下我們將詳細討論這些類別（及其子類別）：



Figure 7: Defenses Against Prompt Injection Attacks: (a) Agent-Focused, (b) User-Focused, and (c) System-Focused.

4.1.1 Agent-Focused

Agent-focused defenses aim to enhance the model itself, either through training interventions or prompt engineering, in order to reduce susceptibility to prompt injection as it learns to identify and handle such inputs [173–175, 147, 176, 177]. There are two main approaches for doing so:

Prompt engineering and runtime output behavior The authors in [173] propose an instruction hierarchy, which establishes priority levels for different instruction sources so that user-provided instructions are always prioritized over potentially malicious instructions embedded in retrieved content. Other works introduce limitations of executable actions by agent to resist prompt injection attacks such as *Action-Selector* and *Plan-then-Execute* design patterns [57]. Complementary to these efforts, research has also been undertaken to utilize *circuit breaking* or *task drifting* approaches to recognize and reject adversarial patterns while preserving intended functionality [175, 147].

Supervised fine-tuning with curated datasets A second class of agent-focused defenses involves fine-tuning backend LLMs with injection-aware datasets. Chen et al. [176] propose *StruQ*, a method that augments datasets with both normal and prompt injection contaminated prompts, enabling models to *learn* to ignore injected instructions while maintaining responsiveness to legitimate ones. Similarly, in [177], the authors introduce *SecAlign*, which leverages alignment training via direct preference optimization (DPO) [178] to align agents toward preferring benign instructions over adversarial ones.

Despite their promise, training-based defenses come with potential trade-offs in performance. For instance, recent evaluations by Jia et al. [179] have shown that defensive fine-tuning can degrade the general-purpose capabilities of LLMs without providing significant defensive capabilities against adaptive attacks, raising concerns about the usability of this strategy.

4.1.2 User-Focused

Contrary to agent-focused defense frameworks, *user-focused* defenses place responsibility on end-users or human operators to provide verification signals that help prevent prompt injection attacks [57, 95]. Although these defenses can be highly effective in theory, they also introduce trade-offs in terms of automation and reliability [57].

One approach requires human confirmation before executing *sensitive* actions [180], though this can reduce automation efficiency and increase risk of inattentive approvals. Techniques such as data attribution and control-flow extraction aim to ease the verification burden [141, 181]. Complementarily, known-answer detection uses cryptographic tokens embedded in user commands; if the LLM fails to return the token, this signals a system-wide prompt injection compromise [182].



圖 7：針對提示注入攻擊的防禦：(a) 以代理為中心，(b) 以使用者為中心，以及 (c) 以系統為中心。

4.1.1 以代理為中心

以代理為核心的防禦旨在透過訓練干預或提示工程來增強模型本身，從而降低其對提示注入的易感性，因為模型會學習識別並處理這類輸入 [173–175, 147, 176, 177]。主要有兩種方法：

提示工程與運時輸出行為 [173] 的作者提出了一個指令階層架構，該架構為不同來源的指令確立優先級，確保使用者提供的指令始終優於嵌入於檢索內容中可能具有惡意性的指令。其他研究則透過限制代理可執行的動作來抵禦提示注入攻擊，例如 Action-Selector 與 Plan-then-Execute 設計模式 [57]。作為這些努力的補充，研究人員也致力於利用電路斷開或任務漂移方法來識別並拒絕對抗性模式，同時保留預期的功能 [175, 147]。

使用精選數據集進行監督微調第二類針對代理的防禦方法涉及使用注入意識數據集微調後端大型語言模型。Chen 等人 [176] 提出了 StruQ，一種方法，該方法通過在數據集中添加正常提示和提示注入污染提示來增強數據集，使模型能夠學習忽略注入的指令，同時對合法指令保持響應。同樣地，在 [177], 中，作者引入了 SecAlign，該方法利用通過直接偏好優化（DPO） [178] 進行對齊訓練，使代理傾向於偏好良性指令而非對抗性指令。

儘管具有潛力，基於訓練的防禦措施在效能上可能存在權衡。例如，Jia 等人 [179] 最近的評估顯示，防禦性微調可能會降低大型語言模型的通用能力，卻無法提供針對適應性攻擊的顯著防禦能力，從而引發對該策略可用性的擔憂。

4.1.2 以使用者為中心

與以代理為核心的防禦框架不同，以使用者為核心的防禦將責任歸於終端使用者或人類操作員，要求其提供驗證信號以協助防止提示注入攻擊 [57, 95]。儘管這些防禦在理論上可能非常有效，但也會帶來自動化與可靠性的權衡 [57]。

一種方法是在執行敏感動作 [180], 前需要人類確認，但這可能會降低自動化效率並增加疏忽批准的風險。數據歸屬和流程提取等技術旨在減輕驗證負擔 [141, 181]。此外，已知答案檢測使用嵌入在用戶命令中的加密令牌；如果 LLM 未能返回該令牌，這將表明系統範圍內的提示注入攻擊 [182]。

4.1.3 System-Focused

System-level defenses aim to safeguard LLM agents by integrating external verification, control mechanisms, and constrained execution environments [57]. However, designing agent systems inherently robust to attacks remains a challenging technical problem. Analogous to defending against traditional ML/AI adversarial examples in computer vision, completely preventing prompt injection is an open problem [183]. Despite this issue, recent works have introduced design patterns for system-focused protection, such as *LLM Map-Reduce*, *Code-Then-Execute*, *Dual-LLM*, and *Context-Minimization* patterns [57]. With a similar view, *TrustAgent* [184] introduces an Agent-Constitution–guided framework that enforces safety in LLM-based agent planning through pre-, in-, and post-planning safeguards, demonstrating improved safety and helpfulness across domains. Other system-focused defenses, such as *Melon*, employ training-free runtime detection approach that performs masked re-execution and tool-call similarity checks and verification loops to limit the impact of potentially malicious instructions on downstream systems, serving as a defense against IPI attacks [70]. We will now discuss some sub-categories of system-focused defenses.

Detection-based defenses Detection-based defenses seek to detect malicious inputs or outputs *without* modifying the fundamental LLM. *Input detection* methods often rely on separate filters, such as guardrail models, that screen prompts before they reach the target system [172]. These approaches fine-tune smaller LLMs to distinguish legitimate instructions from injected ones [185, 186]. For example, *DataSentinel* formulates detection as a minimax optimization problem, exploiting an intentionally vulnerable LLM to reveal contaminated inputs [186]. *Response detection* methods analyze generated outputs to flag anomalies. By checking for invalid or unexpected responses, such as forced tokens (e.g., “HACKED”), these approaches can identify compromised generations [95, 187]. However, they struggle with more complex or subtle attacks [95].

Isolation defenses Isolation defense methods restrict the possible impact of harmful instructions by limiting an agent’s capabilities while engaging with untrusted input [57]. A simple approach is requiring the LLM to *commit* to a predefined set of tools for a task, with the system controller disabling access to others [188, 57].

Prompt augmentation defenses Prompt augmentation offers a lightweight and easily deployable defense against prompt injection, relying on carefully crafted system prompts or input modifications rather than model retraining or architectural changes. Typical strategies include inserting delimiters between user input and retrieved content [189], removing injected parts from the prompts [172], and embedding explicit system-level instructions that instruct the model to disregard conflicting directives [190]. The appeal of this approach lies in its simplicity and low deployment cost. However, in their work, *PromptArmor* [172], the authors show that such strategies (though effective in baseline scenarios), can be bypassed under adaptive attacks, underscoring the limitations of prompt augmentation as a standalone defense.

Quality-based defenses Quality-based defenses evaluate the statistical properties of model inputs or outputs to identify anomalies indicative of prompt injection. A representative approach is the use of the *perplexity* metric (essentially, the exponent of the cross-entropy autoregressive language modeling loss) as a signal, where unexpectedly high values suggest unnatural or out-of-context phrasing often correlated with injected instructions [191].

Trade-off comparison of agent-, user-, and system-focused defenses. In summary, each defense category presents distinct trade-offs between robustness, automation, and deployment cost. User-focused defenses provide strong guarantees through explicit human verification, yet sacrifice scalability and automation, making them unsuitable for autonomous agents [180, 57]. They also fail when the attacker is the user themselves. In contrast, offering seamless protection without human intervention, agent-focused defenses internalize security within the model but often require retraining and may degrade general-purpose capabilities or fail against adaptive attacks [179]. System-focused defenses strike a middle ground by preserving model generality while enforcing external controls and verification; however, they increase system complexity and remain vulnerable to sophisticated multi-stage or multi-agent based attacks [172, 183]. Consequently, practical deployments increasingly favor hybrid designs that combine complementary defenses across these categories rather than relying on a single strategy.

4.1.4 Training-based and Training-free Defenses

Defenses against (indirect) prompt injection in agentic AI systems can be further organized by *resource requirements*, resulting in two categories: *training-based* and *training-free* methods, as implicitly mentioned by zhu et. al. [70].

Training-based Training-based defenses strengthen agents against prompt injection through additional learning or auxiliary models. Common approaches include adversarial training of the underlying LLM [173, 176, 192], or the use of dedicated detection models that flag injected inputs before execution [185, 193]. While effective in controlled

4.1.3 系統導向

系統層面的防禦旨在透過整合外部驗證、控制機制以及受限的執行環境 [57] 來保護大型語言模型（LLM）代理。然而，設計出本質上具有抗攻擊能力的代理系統仍是一個具有挑戰性的技術問題。這類似於在電腦視覺中防禦傳統機器學習/人工智慧對抗範例，完全防止提示注入仍是一個未解之謎 [183]。儘管存在此問題，近期研究已針對系統防護引入了設計模式，例如 LLM Map-Reduce、Code-Then-Execute、Dual-LLM 以及 Context-Minimization 模式 [57]。持同樣觀點的 TrustAgent [184] 引入了一個由 Agent-Constitution 引導的框架，透過事前、事中和事後規劃保障措施，強制執行基於 LLM 的代理規劃中的安全性，並展現出跨領域的改善安全性與有用性。其他系統層面的防禦，例如 Melon，採用無訓練的運行時檢測方法，執行遮罩重執行與工具調用相似性檢查及驗證迴圈，以限制潛在惡意指令對下游系統的影響，作為對抗 IPI 攻擊的防禦 [70]。接下來我們將討論系統層面防禦的一些子類別。

基於檢測的防禦 基於檢測的防禦旨在不修改基礎大語言模型（LLM）的前提下，檢測惡意輸入或輸出。輸入檢測方法通常依賴獨立的過濾器，例如防護欄模型，在提示詞到達目標系統前進行篩查 [172]。這些方法通過微調較小規模的 LLM 來區分合法指令與注入內容 [185, 186]。例如，DataSentinel 將檢測構建為最小化最大（minimax）優化問題，利用故意存在漏洞的 LLM 來揭露受污染的輸入 [186]。輸出檢測方法則分析生成的回應以標記異常。通過檢查無效或意外回應（例如強制生成的 token，如"HACKED"），這些方法可以識別受損的生成內容 [95, 187]。然而，它們在應對更複雜或更隱晦的攻擊時表現乏力 [95]。

隔離防護 隔離防護方法透過限制代理在處理未受信任輸入 [57] 時的權限，來限制有害指令可能造成的影響。一種簡單的方法是要求大型語言模型（LLM）承諾僅使用預定義的工具集來執行任務，並由系統控制器禁用對其他工具的存取權限 [188, 57]。

提示增強防禦 提示增強提供了一種輕量級且易於部署的提示注入防禦方法，依賴於精心設計的系統提示或輸入修改，而非模型重訓練或架構變更。典型策略包括在用戶輸入和檢索內容之間插入分隔符 [189],從提示中移除注入部分 [172], 以及嵌入明確的系統級指令，指示模型忽略衝突的指令 [190]。此方法的吸引力在於其簡單性和低部署成本。然而，在他們的工作中，PromptArmor [172], 的作者表明，這些策略（儘管在基準場景中有效）可能會在適應性攻擊下被繞過，這強調了提示增強作為獨立防禦手段的局限性。

基於品質的防禦 基於品質的防禦評估模型輸入或輸出的統計特性，以識別提示注入的異常跡象。一種代表性方法是使用困惑度指標（本質上為交叉熵自回歸語言建模損失的指數）作為信號，其中意外過高的數值往往暗示不自然或脫離語境的措辭，這通常與注入的指令相關 [191]。

代理、用戶與系統導向防禦的權衡比較。總之，每類防禦在魯棒性、自動化與部署成本之間呈現不同的權衡。用戶導向防禦透過明確的人類驗證提供強有力的保證，但犧牲了可擴展性與自動化，因此不適合用於自主代理 [180, 57]；它們在攻擊者為用戶自身時也會失效。相比之下，代理導向防禦提供無需人類介入的無縫保護，將安全性內化於模型中，但往往需要重新訓練，且可能降低通用能力或無法抵禦適應性攻擊 [179]。系統導向防禦則取中間路線，在保留模型通用性的同時強制執行外部控制與驗證；然而，它們增加了系統複雜度，且仍易受複雜的多階段或多代理攻擊 [172, 183]。因此，實際部署越來越傾向採用混合設計，結合這些類別中相互補充的防禦，而非依賴單一策略。

4.1.4 基於訓練的與無訓練的防禦

針對代理式 AI 系統中的（間接）提示注入防禦措施，可進一步依據資源需求進行分類，形成兩類：基於訓練的方法與免訓練方法，此分類方式正如 zhu 等人 [70] 所隱含提及。

基於訓練的防禦機制透過額外學習或輔助模型來強化代理，以抵禦提示注入攻擊。常見方法包括對底層大型語言模型進行對抗性訓練 [173, 176, 192], ，或使用專門的檢測模型在執行前標記注入的輸入 [185, 193]。雖然這些方法在受控環境中有效



Figure 8: Policy Filtering and Enforcement Defense Strategies: (a) Governance-Centric, (b) Signal-Centric.

settings, these methods demand substantial computational resources and training data, and may reduce an agent's utility across broader application domains [70].

Training-free Training-free defenses avoid retraining costs by modifying prompts or constraining agent behavior. Ignorance strategies, such as delimiters between user and retrieved content [189], aim to weaken injection attempts but remain fragile against adaptive attacks [61]. *Known-answer detection* [194] introduces control questions to identify compromised executions, although this method can only be applied post-hoc. At the system level, tool filtering [188] restricts agent calls to predefined tool sets, and *TaskShield* [195] validates tool-use alignment with user intent. While lightweight, such defenses can reduce agent utility and still remain vulnerable to tailored attacks [70].

4.2 Policy Filtering and Enforcement

An essential safeguard for AI agent security is *strict policy enforcement*, that is, making sure agents reliably operate within established behavioral and safety limits, even when facing adversarial challenges. Rather than merely detecting issues, enforcement frameworks proactively restrict, intervene in, or adjust agent actions to ensure alignment with security and ethical standards. In practice, industry guidance has begun to outline deployment patterns for such guardrails, emphasizing layered and modular approaches to real-world alignment [196, 197]. Recent work on agent guardrails reveals two main enforcement paradigms: *governance-centric* and *signal-centric* approaches. We visualize both of these defense strategies in Figure 8.

4.2.1 Governance-Centric (Runtime) Enforcement

Governance-centric methods explicitly regulate the actions and decision sequences of agents by embedding policies directly into the agent loop or by delegating oversight to a supervisory agent. For example, by converting guard requests into executable code, *GuardAgent* applies safety constraints during runtime without altering agents or retraining models [198]. Its benchmark accuracy is high, but the need for manual configuration of toolboxes and memory examples for each agent reduces scalability significantly [198, 199]. Another methods, *AgentSpec*, introduces a domain-specific language to specify runtime constraints, enabling systematic enforcement of customizable policies such as tool access limitations and permissible data operations [199]. Additionally, *ShieldAgent* [200] operates as an oversight agent that audits multimodal action sequences and applies probabilistic policy reasoning to block, repair, or approve them. This provides explicit, sequence-level enforcement rather than relying only on filtering mechanisms. Furthermore, *R^2-Guard* [201] enhances policy guardrails by combining data-driven detection with embedded logical inference, where defined safety knowledge rules are encoded as first-order logic within a probabilistic graphical model, yielding improved resilience to adversarial or jailbreaking prompts. Such methods enforce governance by integrating a policy validation-and-approval stage directly into the agent's decision pipeline.



圖 8：政策過濾與執行防禦策略：(a) 以治理為中心，(b) 以訊號為中心。

設定中，這些方法需要大量的計算資源和訓練數據，可能會降低代理在更廣泛應用領域中的效用 [70]。

無需重新訓練的防禦機制透過修改提示或限制代理行為來避免重新訓練成本。無知策略（例如使用者與檢索內容之間的分隔符號 [189], ）旨在削弱注入嘗試，但對適應性攻擊 [61]仍顯脆弱。已知答案檢測 [194] 引入控制問題以識別受污染的執行，儘管此方法僅能事後應用。在系統層面，工具過濾 [188]限制代理調用至預定義工具集，而 TaskShield [195] 則驗證工具使用與使用者意圖的一致性。儘管這些防禦機制輕量，但仍可能降低代理效用，且仍易受量身打造的攻擊 [70]影響。

4.2 策略過濾與執行

AI 代理安全的一項關鍵防護措施是嚴格執行策略，即確保代理即使在面對對抗性挑戰時，也能可靠地在既定的行為與安全限制內運作。執行框架不僅僅是檢測問題，而是主動限制、介入或調整代理行動，以確保其與安全和倫理標準保持一致。實際上，產業指引已開始概述這類防護欄的部署模式，強調針對現實世界對齊的層級化與模組化方法 [196, 197]。近期關於代理防護欄的研究揭示了兩種主要的執行範式：以治理為中心和以訊號為中心的方法。我們在圖 8 中展示了這兩種防禦策略。

4.2.1 以治理為核心的（運行時）執行

以治理為核心的方法透過將策略直接嵌入代理迴路，或將監督權限委託給監督代理，來明確規範代理的行為與決策序列。例如，GuardAgent 透過將守衛請求轉換為可執行程式碼，在執行時應用安全限制，而無需修改代理或重新訓練模型[198]。其基準準確度高，但需為每個代理手動配置工具箱與記憶示例，顯著降低了可擴展性 [198, 199]。另一種方法 AgentSpec 引入領域特定語言來指定執行時限制，從而系統性地執行可自定義的策略，例如工具存取限制與允許的資料操作 [199]。此外，ShieldAgent [200] 作為監督代理運作，審查多模態行為序列，並應用機率性策略推理來阻擋、修復或批准這些序列。這提供了明確的序列級執行，而非僅依賴過濾機制。此外，R2-Guard [201] 透過結合資料驅動檢測與嵌入式邏輯推理來增強策略防護欄，其中定義的安全知識規則被編碼為機率圖形模型中的一階邏輯，從而提升對抗性或越獄提示的韌性。這些方法透過將策略驗證與批准階段直接整合進代理的決策流程來執行治理。



Figure 9: An Example of Sandboxing as a Defense Strategy.

4.2.2 Signal-Centric (Non-runtime) Enforcement

Signal-centric methods ensure compliance by scanning inputs and outputs for violations, flagging them as compromise signals. Instead of restricting internal behavior, they block harmful prompts or unsafe outputs before execution. For instance, *Llama Guard* [193] targets text-based LLMs, *LlavaGuard* [202] extends to image-based multimodal models, and *Safewatch* [203] addresses video generation. Furthermore, Gosmar et al. [95] proposed a framework that rejects or sanitizes generated outputs containing prompt injections, ensuring only policy-compliant responses are returned.

4.3 Sandboxing and Capability Confinement

Sandboxing has been widely adopted as a practical means of testing whether LLM-generated or third-party code behaves securely under real-world constraints. For instance, *SandboxEval* introduces a test suite of handcrafted scenarios that simulate unsafe code execution, including file-system manipulation and network calls, to evaluate LLM safety under untrusted execution conditions [204]. In related efforts, Chen et al.[205] and Siddiq et al. [206] employ containerized environments (e.g., gVisor or Docker) to execute LLM-generated code against unit tests, thereby confining execution vulnerabilities without exposing the host system. Similarly, Iqbal et al.[207] isolate OpenAI plugins in separate sandboxes to prevent cascading failures from a compromised plugin. These approaches emphasize *runtime testing and isolation* as mechanisms to identify and mitigate unsafe behavior before real-world deployment. We visualize the standard sandboxing defense in Figure 9.

Recent work has also proposed sandboxing *architectures* to enforce least privilege and confine agent capabilities. Ruan et al. [208] introduced a dual-agent framework in which one LLM acts as an emulator and another as a safety evaluator, thereby ensuring *untrusted* code can only execute within predefined sandbox boundaries. Wu et al. [180] proposed execution isolation architectures that integrate sandbox layers into LLM-based systems, addressing vulnerabilities in integration components such as file isolation across sessions. Similarly, the framework of Huang et al. [209] emphasizes that airtight sandboxing is *indispensable* for reinforcement learning based alignment: reward computation occurs entirely inside a deterministic and confined execution environment that envelopes every REST call, database mutation, and file operation, thereby eliminating reward hacking and preserving training convergence. By confining execution contexts, these designs prevent leakage of sensitive data and reduce the attack surface for adversarial code injection [204, 180]. Mushsharat et al. introduce a *neural sandbox* for classification, which evaluates outputs against predefined label concepts using similarity to *cop-words*, bolstering classification robustness in non-code tasks [210].

Although most sandboxing defenses emphasize practical isolation, recent research has begun to pursue formal safety guarantees. For example, Zhong et al. propose an architecture that sandboxes unverified AI controllers while offering provable assurances of safety and security in continuous control systems [211]. In contrast to reward-shaping methods that integrate safety into the training process, their approach separates enforcement from controller design, allowing formal guarantees independent of the underlying AI model. This shifts the paradigm from reactive containment to proactive confinement by embedding formal verification *within* sandboxing.

Unlike policy enforcement methods that operate on the level of agent reasoning or output filtering, sandboxing-based defenses focus on isolating execution contexts to contain risks, prevent privilege escalation, and minimize damage if an agent is compromised. Although sandboxing and confinement provide strong isolation guarantees, several challenges



圖 9：沙盒作為防禦策略的範例。

4.2.2 信號導向（非執行時）強制

以信號為核心的方法透過掃描輸入與輸出以偵測違規，並將違規標記為妥協信號。與限制內部行為不同，它們會在執行前阻擋有害提示或不安全輸出。例如，Llama Guard [193] 針對基於文字的 LLM，LlavaGuard [202] 擴展至基於圖像的多模態模型，而 Safewatch [203] 則處理影片生成。此外，Gosmar 等人 [95] 提出一個框架，可拒絕或清理包含提示注入的生成輸出，確保僅返回符合政策規範的回應。

4.3 沙箱與能力限制

沙箱化已廣泛採用為一種實用的方法，用於測試在真實世界約束下，LLM 生成或第三方代碼是否能安全運行。例如，SandboxEval 引入了一套手動構建的測試場景，模擬不安全代碼執行，包括文件系統操作和網絡調用，以評估 LLM 在不可信執行環境下的安全性 [204]。在相關工作中，Chen 等人[205] 和 Siddiq 等人 [206] 使用容器化環境（例如 gVisor 或 Docker）來執行 LLM 生成的代碼並對其進行單元測試，從而限制執行漏洞的擴散，同時不暴露主機系統。同樣地，Iqbal 等人[207] 將 OpenAI 插件隔離在獨立的沙箱中，以防止受攻陷插件引發的連鎖故障。這些方法強調運行時測試和隔離，作為在真實世界部署前識別和緩解不安全行為的機制。我們在圖 9 中展示了標準沙箱防禦機制。

近期研究也提出了沙箱架構，以強制最小權限並限制代理能力。Ruan 等人 [208] 引入了一個雙代理框架，其中一個大型語言模型（LLM）作為模擬器，另一個作為安全評估者，從而確保不可信代碼僅能在預定義的沙箱邊界內執行。Wu 等人 [180] 提出了執行隔離架構，將沙箱層整合進基於 LLM 的系統中，解決了整合組件（如跨會話的文件隔離）中的漏洞。同樣地，Huang 等人 [209] 的框架強調，嚴密的沙箱對於基於強化學習的對齊至關重要：獎勵計算完全發生在一個確定且受限的執行環境內，該環境包圍了所有 REST 調用、數據庫變更和文件操作，從而消除獎勵欺騙並保持訓練收斂。通過限制執行上下文，這些設計防止了敏感數據洩漏，並降低了惡意代碼注入 [204, 180] 的攻擊面。Mushsharat 等人引入了一個用於分類的神經沙箱，該沙箱使用與 cop-words 的相似度將輸出與預定義標籤概念進行比對，從而增強了非代碼任務的分類魯棒性 [210]。

儘管大多數沙盒防護機制強調實際隔離，近期研究開始轉向追求形式化安全保證。例如，Zhong 等人提出一種架構，可在對未驗證的 AI 控制器進行沙盒隔離的同時，為連續控制系統提供可證明的安全與安全保證 [211]。與將安全納入訓練過程的獎勵塑形方法不同，其方法將執行與控制器設計分離，從而實現與底層 AI 模型無關的形式化保證。這通過在沙盒中嵌入形式驗證，將範式從被動封閉轉變為主動限制。

與基於代理推理或輸出過濾的政策執行方法不同，基於沙箱的防禦機制專注於隔離執行環境，以限制風險、防止權限提升，並在代理被攻陷時將損害降至最低。儘管沙箱與限制機制能提供強大的隔離保證，但也存在若干挑戰

still remain. Vulnerabilities in sandbox implementations themselves have been documented: Wu et al. [212] found missing file isolation constraints that allowed cross-session leakage, and researchers have reported flaws in dependency installation pipelines that enabled large-scale code execution attacks [213]. Finally, sandboxing may introduce overhead and reduce system efficiency, raising trade-offs between safety and agentic AI usability. In multi-agent settings, Peigné et al. [142] show that confining agent interactions reduces exposure to infectious malicious prompts, but at the cost of collaborative efficiency. These limitations suggest that sandboxing is most effective when combined with complementary defenses such as policy enforcement or runtime monitoring.

4.4 Detection and Monitoring

Defenses must also evolve alongside threats, making continuous monitoring and adaptive filtering essential for safeguarding AI agents. Traditional runtime enforcement mechanisms tend to be reactive, and intervene only once unsafe behavior manifests, which limits foresight under distribution shifts [199, 198, 214]. *Pro2Guard* addresses this gap by employing probabilistic reachability analysis to model agent behavior as symbolic abstractions and anticipate violations before they occur, enabling proactive intervention with statistical reliability across heterogeneous domains [214]. In multi-agent systems, decentralized runtime enforcement enables individual agents to generate safety-preserving adaptations locally, sidestepping the scalability limits and information-sharing constraints inherent to centralized design-time approaches [215]. These enforcers ensure correctness, bounded deviation, and completeness, which makes them well-suited for applications like collision avoidance and cooperative planning. Yet, static monitoring strategies remain insufficient against adaptive adversaries, which can evolve policies to bypass fixed defenses. To this end, adaptive monitoring frameworks such as Adversarial Markov Games cast detection as a dynamic interaction between attackers and defenders, showing that reinforcement learning can optimize both evasive attacks and responsive defenses in black-box settings [216]. These results demonstrate that in addition to runtime enforcement and decentralization, successful monitoring also necessitates the flexibility to adjust to adversarial *co-evolution*.

4.5 Standards and Organizational Measures

In addition to technical defenses, organizational frameworks and standards play a crucial role in shaping secure deployment of agentic AI in practice. These measures provide common guidelines, risk management practices, and reference architectures that organizations can adopt to prevent systemic vulnerabilities. For instance, the NIST AI Risk Management Framework (AI RMF) Generative AI Profile [53], developed under Executive Order *14110*, provides a cross-sectoral reference for managing risks specific to generative and agentic AI. It extends the AI RMF by defining risks that are novel to or exacerbated by generative AI, such as the misuse of LLMs, unverified tool access, and autonomy-driven escalation. It outlines governance, mapping, measuring, and management practices to mitigate these risks. Complementary initiatives include the NCCoE Cyber AI Profile [217], which offers implementation guidance, Cybersecurity Framework, for integrating cybersecurity controls into AI systems; the OWASP Agentic AI Threats project [218], which catalogs common vulnerabilities such as insecure orchestration and prompt injection; and the CSA MAESTRO framework [219], which introduces a multi-layered threat modeling methodology tailored for agentic AI, providing structured analysis of risks across the AI lifecycle, from foundation models to multi-agent ecosystems. Together, these standards and organizational frameworks establish structural safeguards, embedding AI agents within broader ecosystems of regulation, compliance, and risk management.

5 Benchmarks and Evaluation

To assess the impact of various agentic AI security vulnerabilities associated we discussed previously (as well the potency of defense strategies) it is necessary to undertake system evaluation via robust benchmarks. The first benchmarks proposed for agentic AI primarily focused on *competence* and sought to study *whether an agent could complete a specified task under controlled conditions*. Lately, as deployments edge closer to production, evaluation has shifted toward *reliability*, *safety*, and *control*. Consequently, recently *DoomArena* [221] has introduced security-oriented evaluation frameworks, a modular and configurable platform that enables cross-environment attack composition and fine-grained threat modeling for systematically probing agent failure modes and defense limitations. Thus, in this section, we cover: (i) landscape benchmarks used to gauge general capability, (ii) security–specific frameworks that probe failure modes such as harmful misuse, and (iii) methodological advances that improve fidelity, comparability, and reproducibility. Table 2 summarizes existing benchmarks spanning both capability and security-specific focuses, highlighting their domains, safety focus, and evaluation methodologies.

仍存留。沙箱實現本身的漏洞已有文獻記錄：Wu 等人 [212] 發現缺少檔案隔離限制，導致跨會話洩漏；研究人員也報告了依賴安裝管道中的缺陷，這些缺陷使得大規模程式碼執行攻擊成為可能 [213]。最後，沙箱可能會引入額外負載並降低系統效率，從而產生安全性與代理 AI 可用性之間的權衡。在多方代理環境中，Peigné 等人 [142] 指出，限制代理互動可減少暴露於感染性惡意提示的風險，但代價是降低協作效率。這些限制表明，沙箱在與政策執行或運行時監控等輔助防禦措施結合時效果最佳。

4.4 檢測與監控

防護機制也必須隨威脅演進，使持續監控與適應性過濾成為保障 AI 代理安全的關鍵。傳統執行時強制機制往往具有反應性，僅在不安全行為顯現時才介入，這限制了在分佈式偏移下的前瞻性 [199, 198, 214]。Pro2Guard 透過採用機率性可達性分析，將代理行為建模為符號抽象，並在違規發生前預測違規，從而實現跨異質領域的統計可靠性主動干預。在多方代理系統中，分散式執行時強制允許個別代理在本地產生維持安全性的適應，避開集中式設計時方法固有的可擴展性限制與資訊共享約束 [215]。這些強制器確保正確性、有界偏差與完整性，使其適用於碰撞避免與協同規劃等應用。然而，靜態監控策略仍不足以應對適應性對手，後者可能演化策略以繞過固定防護。為此，適應式監控框架（如對抗馬可夫遊戲）將檢測視為攻擊者與防禦者之間的動態互動，顯示強化學習可在黑盒環境中優化逃避式攻擊與回應式防護 [216]。這些結果證明，除了執行時強制與分散化之外，成功的監控還需要具備適應對抗共同演化的靈活性。

4.5 標準與組織措施

除技術防禦外，組織架構與標準在實際應用中塑造代理型 AI 的安全部署方面發揮關鍵作用。這些措施提供通用指導方針、風險管理實踐及參考架構，供組織採用以預防系統性漏洞。例如，NIST AI 風險管理框架（AI RMF）生成式 AI 檔案 [53],（依據行政命令 14110 制定）為管理生成式與代理型 AI 特定風險提供跨部門參考。該框架擴展了 AI RMF，定義了生成式 AI 所特有或加劇的風險，例如大語言模型（LLM）濫用、未經驗證的工具存取及由自主性驅動的升級。它概述了治理、映射、衡量及管理實踐，以減輕這些風險。補充性計劃包括 NCCoE 網路 AI 檔案 [217],（提供實施指導與網路安全框架，用於將網路安全控制整合至 AI 系統）、OWASP 代理型 AI 威脅專案 [218],（彙整常見漏洞，如不安全編排與提示注入）以及 CSA MAESTRO 框架 [219],（針對代理型 AI 引入多層威脅建模方法，提供從基礎模型至多代理生態系統的 AI 全生命週期風險結構化分析）。這些標準與組織架構共同建立結構性防護，將 AI 代理嵌入更廣泛的監管、合規與風險管理生態系統中。

5 基準測試與評估

為評估前述討論中各種代理式 AI 安全漏洞的影響（以及防禦策略的有效性），必須透過堅實的基準進行系統評估。針對代理式 AI 提出的首批基準主要聚焦於能力，旨在研究代理在受控條件下是否能完成指定任務。近期，隨著部署日益接近生產環境，評估重點已轉向可靠性、安全性與可控性。因此，最近 DoomArena [221] 引入了以安全為導向的評估框架，這是一個模組化且可配置的平臺，支持跨環境攻擊組裝與細粒度威脅建模，用於系統性地探測代理失效模式與防禦限制。因此，在本節中，我們將涵蓋：(i) 用於衡量一般能力的景觀基準，(ii) 探測如有害濫用等失效模式的特定安全框架，以及 (iii) 提升忠實度、可比性與可重複性的方法論進展。表 2 總結了涵蓋能力與特定安全焦點的現有基準，並突出其領域、安全重點與評估方法。

Table 1: Secure-by-Design Defense Mechanisms Coverage Across Agentic AI Security Approaches.

Defense Approach	Input Governance	Tool-Call Guards	Policy Engine	Sandboxing/ Isolation	Rate Limiting	Audit Trails	Rollback/ Recovery
Prompt-Injection-Resistant Designs							
PromptArmor [172]	✓	✗	✗	✗	✗	✗	✗
StruQ [176]	✓	✗	✗	✗	✗	✗	✗
SecAlign [177]	✓	✗	✓	✗	✗	✗	✗
Sign-Prompt [182]	✓	✗	✓	✗	✗	✗	✗
Attn. Tracker [220]	✓	✗	✗	✗	✗	✗	✗
JATMO [187]	✓	✗	✓	✗	✗	✗	✗
TaskShield [195]	✓	✓	✓	✗	✗	✓	✗
Melon [70]	✗	✓	✗	✗	✗	✓	✗
Policy Filtering & Enforcement							
LlamaGuard [193]	✓	✗	✓	✗	✗	✗	✗
LlavaGuard [202]	✓	✗	✓	✗	✗	✗	✗
GuardAgent [198]	✗	✓	✓	✗	✗	✓	✗
AgentSpec [199]	✗	✓	✓	✗	✓	✓	✗
ShieldAgent [200]	✗	✓	✓	✗	✗	✓	✗
R^2-Guard [201]	✓	✗	✓	✗	✗	✓	✗
Sandboxing & Capability Confinement							
SandboxEval [204]	✓	✓	✓	✓	✓	✓	✗
IsolateGPT [180]	✗	✓	✓	✓	✓	✓	✗
ToolEmu [208]	✓	✓	✗	✓	✗	✓	✗
Monitoring & Adaptive Systems							
Pro2Guard [214]	✗	✓	✓	✗	✗	✓	✓
Arms Race [216]	✗	✓	✓	✗	✗	✓	✗
Dec. RE [215]	✗	✓	✓	✗	✗	✓	✓
CB [175]	✗	✓	✗	✗	✗	✗	✓

Input Governance: Input validation, sanitization, and prompt injection detection mechanisms to prevent malicious inputs from reaching the agent. **Tool-Call Guards:** Runtime verification and constraints on tool/API invocations to prevent unauthorized or dangerous actions. **Policy Engine:** Formal policy specification and enforcement mechanisms to ensure agent behavior aligns with safety requirements. **Sandboxing/Isolation:** Isolated execution environments that contain potential damage from risky operations. **Rate Limiting:** Request throttling and resource usage controls to prevent denial-of-service and resource exhaustion. **Audit Trails:** Logging and traceability of agent actions for accountability and post-incident analysis. **Rollback/Recovery:** Mechanisms to reverse harmful actions or restore the system to safe states after detection of violations.
Annotations ✓= Explicitly supported; ✗= Not addressed or not applicable.

5.1 Landscape benchmarks for capability

A number of realistic and interactive testbeds for web and computer-use agents have been developed. *BrowserGym* brings many such tasks under one consistent interface and scoring protocol (e.g., MiniWoB++, WorkArena, WebArena, among others), reducing fragmentation and enabling like-for-like comparisons across LLMs and agent designs [160]. In particular, BrowserGym emphasizes unified observation and action spaces and experiments showcase cross-model evidence that agent performance is sensitive to both model choices and the environments [160]. On the long-standing MiniWoB/MiniWoB++ benchmarks, proposed methods have continued to make progress [222, 248, 249].

Moving to even more dynamic interactions and environments, τ-BENCH explicitly targets *multi-turn* tool-using agents interacting with simulated users under domain policies (e.g., retail and airline) and introduces the *pass*$\wedge k$ metric to quantify consistency across repeated runs of the same task [223]. In general, relatively recent models (e.g. GPT-4o) still do not succeed on under half the tasks in realistic domains, and pass$\wedge 8$ can drop below 25% on the *retail* setting [223]. On the other hand, VisualWebArena [227] tests multimodal understanding by evaluating agents on visual web interfaces. Extending evaluation across execution environments, AndroidWorld [228] assesses touch-based mobile interactions, broadening coverage to comprehensive cross-platform scenarios. While these capability-oriented benchmarks are not framed as security tests per se, they expose control and reliability deficits that strongly interact with overall model safety.

5.2 Security-Specific and safety-specific benchmarks

Several benchmarks now also aim to evaluate *agentic* safety, i.e., risks arising from autonomous action, tool use, and long-horizon interaction, rather than from static chat completion. We discuss these next.

表 1：代理式 AI 安全方法中的「安全設計」防禦機制覆蓋範圍。

防禦策略	輸入政府 - 治理	工具調用防護	政策引擎	沙盒/隔離	速率限制	審計日誌	回滾/恢復
具有抗提示注入的設計							
PromptArmor [172]	✓	✗	✗	✗	✗	✗	✗
StruQ [176]	✓	✗	✗	✗	✗	✗	✗
SecAlign [177]	✓	✗	✓	✗	✗	✗	✗
Sign-Prompt [182]	✓	✗	✓	✗	✗	✗	✗
致追蹤員 [220]	✓	✗	✗	✗	✗	✗	✗
JATMO [187]	✓	✗	✓	✗	✗	✗	✗
任務防護罩 [195]	✓	✓	✓	✗	✗	✓	✗
西瓜 [70]	✗	✓	✗	✗	✗	✓	✗
策略過濾與執行							
LlamaGuard [193]	✓	✗	✓	✗	✗	✗	✗
LlavaGuard [202]	✓	✗	✓	✗	✗	✗	✗
GuardAgent [198]	✗	✓	✓	✗	✗	✓	✗
AgentSpec [199]	✗	✓	✓	✗	✓	✓	✗
防護代理 [200]	✗	✓	✓	✗	✗	✓	✗
R2-Guard [201]	✓	✗	✓	✗	✗	✓	✗
沙盒與能力限制							
SandboxEval [204]	✓	✓	✓	✓	✓	✓	✗
IsolateGPT [180]	✗	✓	✓	✓	✓	✓	✗
工具模擬 [208]	✓	✓	✗	✓	✗	✓	✗
監控與適配系統							
Pro2Guard [214]	✗	✓	✓	✗	✗	✓	✓
軍備競賽 [216]	✗	✓	✓	✗	✗	✓	✗
12 月。RE [215]	✗	✓	✓	✗	✗	✓	✓
CB [175]	✗	✓	✗	✗	✗	✗	✓

輸入治理：輸入驗證、清洗及提示注入檢測機制，防止惡意輸入傳送至代理。工具呼叫防護：對工具/API 呼叫進行時序驗證與限制，防止未經授權或危險的操作。策略引擎：形式化策略規範與執行機制，確保代理行為符合安全要求。沙箱/隔離：隔離的執行環境，可限制風險操作可能造成的損害。速率限制：請求限流與資源使用控制，防止服務中斷與資源耗盡。審計日誌：記錄並追蹤代理操作，以確保責任歸屬及事後分析。回滾/恢復：機制用於逆轉有害操作，或在檢測違規後將系統恢復至安全狀態。註解 ✓= 明確支援；= 未處理或不適用。

5.1 能力景觀基準

已開發出許多用於網頁和電腦使用代理的真實且互動的測試環境。BrowserGym 將許多這類任務整合至單一一致的介面與評分協議（例如 MiniWoB++、WorkArena、WebArena 等），減少碎片化，並使不同大型語言模型與代理設計之間能夠進行同等條件的比較 [160]。特別地，BrowserGym 強調統一的觀察空間與動作空間，實驗成果亦顯示出跨模型的證據，證明代理表現既受模型選擇影響，也受環境影響 [160]。在長期存在的 MiniWoB/MiniWoB++ 基準測試中，所提出的方法持續取得進展 [222, 248, 249]。
轉向更具動態的互動與環境，τ-BENCH 明確針對在領域政策（例如零售與航空）下與模擬用戶互動的多輪工具使用型代理，並引入 pass$\wedge k$ 指標以量化同一任務重複執行時的一致性 [223]。一般而言，較近期的模型（例如 GPT-4o）在真實領域中仍無法成功完成少於一半的任務，且在零售場景下 pass$\wedge 8$ 可能低於 25% [223]。另一方面，VisualWebArena [227]透過評估代理在視覺網頁介面上的表現，測試多模態理解能力。擴展至執行環境的評估，AndroidWorld [228]評估基於觸控的移動裝置互動，將覆蓋範圍擴大至全面的跨平台情境。雖然這些以能力為導向的基準測試並非本質上為安全測試，但它們揭示了與整體模型安全性密切相關的操控與可靠性缺陷。

5.2 安全特定與安全基準

現在，許多基準測試也旨在評估代理安全性，即來自自主行動、工具使用及長時限互動的風險，而非來自靜態聊天完成。我們接下來討論這些內容。

Table 2: Agentic AI Security and Capability Evaluation Benchmarks.

Benchmark	Domain	Safety Focus	Process-Aware	Multi-Turn	Sandboxed	Judge Type	Reliability Metric	Keypoints
Capability Benchmarks								
BrowserGym [160]	Web	–	–	✓	✓	Rule-based	End-state	Unified interface
MiniWoB++ [222]	Web	–	–	–	✓	Rule-based	End-state	Baseline
τ-bench [223]	Multi-domain	–	–	✓	✓	Rule-based	pass^k, pass@k	Consistency
GTA [224]	Multi-domain	–	✓	–	✓	Rule-based	End-state, step-wise	Tool agent
OSWorld [225]	Computer	–	✓	–	✓	Rule-based	End-state, scripted	Computer environment
OSWorld-Human [226]	Computer	–	✓	–	✓	Rule-based	Weighted efficiency score	Temporal performance
VisualWebArena [227]	Web	–	–	✓	✓	∼	End-state, fuzzy	Visually grounded
AndroidWorld [228]	Android	–	–	✓	✓	Rule-based	End-state	Dynamic parameterization
WebShop [229]	E-commerce	–	–	✓	✓	Rule-based	End-state, Programmatic Reward	Scalable
AgentBench [230]	Multi-domain	–	✓	✓	✓	Rule-based	End-state, step-wise	Eight environments
WCA [231]	Web	–	✓	✓	✓	∼	End-state, fuzzy	Labor-intensive "chores"
CRAB [232]	Multi-domain	–	✓	✓	✓	Rule-based	Graph-based	Graph-based evaluation
AssistantBench [233]	Open web	–	–	✓	–	∼	Realistic & time-consuming	
Security-Specific Benchmarks								
ST-WebAgent-Bench [234]	Enterprise	✓	✓	✓	✓	–	CuP, Risk	Policy compliance
AgentHarm [44]	Open-domain	✓	–	✓	✓	–	Compliance	Jailbreak + competence
OS-Harm [235]	Computer	✓	✓	✓	✓	LLM	Safety, Accuracy	Desktop effects
R-Judge [236]	Meta-eval	✓	✓	∼	–	LLM	Risk recognition	Risk assessment
ToolEmu [208]	Tool-use	✓	–	✓	✓	–	Side-effects	Emulation
AgentDojo [188]	Tool-use	✓	–	✓	✓	Rule-based	Utility, ASR	Dynamic Framework
InjecAgent [36]	Tool-use	✓	–	–	✓	Rule-based	ASR	Indirect Prompt Injection
ASB [237]	Multi-domain	✓	✓	✓	✓	Rule-based	ASR, RR, BP, PNA, NRP	Multi-scenario
PrivacyLens [238]	Personalized Comm	✓	✓	✓	✓	∼	LR, Helpfulness	Privacy norm awareness
Agent-SafetyBench [239]	Tool-use	✓	✓	✓	✓	LLM	Safety Score, Helpfulness	Comprehensive
SAB [240]	Embodied AI	✓	✓	✓	✓	∼	Rejection Rate, Risk Rate	Embodied agents in simulated environment
CAIBench [241]	Cybersecurity	✓	✓	✓	✓	Rule-based	∼	Simultaneous offense and defense evaluation
WASP [242]	Web	✓	✓	✓	✓	∼	ASR (intermediate & end-to-end), Utility	Security by incompetence
SafeArena [243]	Web	✓	✓	✓	✓	∼	TSR, RR, NSS, ARIA	Deliberate misuse focused
OAS [244]	Multi-domain	✓	✓	✓	✓	∼	FR, DR	Multi-user dynamics
MCP-SafetyB [245]	MCP	✓	✓	✓	–	Rule-based	TSR, ASR	Real MCP servers
MCP-SecB [246]	MCP	✓	–	–	–	Rule-based	ASR, RR, PSR	Real MCP servers
MAGPIE [247]	Multi-domain	✓	✓	✓	–	∼	LR, TSR (Constraints), MR, Consensus	Multi-agent

Annotations: ✓ = fully supported; – = not applicable/not supported; ∼ = varies by implementation or framework-dependent. Full forms: Leakage Rate (LR), Misclassification Rate (MR), Refusal Rate (RR), Protection Success Rate (PSR), Task Success Rate (TSR), Failure Rate(FR), Disagreement Rate (DR), Normalized Safety Score (NSS), ARIA risk levels, Performance under No Attack (PNA), Benign performance (BP), and Net Resilient Performance (NRP).

表 2：代理式 AI 安全與能力評估基準。

基準測試	領域	安全重點	具備流程感知能力	多轉	封閉式審判官	Type	可靠性指標	關鍵點
能力基準								
瀏覽器健身房 [160]	Web	–	–	✓	✓	規則 - 基於	終態	統一介面
MiniWoB++ [222]	Web	–	–	–	✓	規則 - 基於	終態	基準線
τ-bench [223]	多項式領域	–	–	✓	✓	規則 - 基於	pass^k，pass@k	一致性
GTA [224]	多項式領域	–	✓	–	✓	規則 - 基於	終態，逐步	工具代理
OSWorld [225]	電腦	–	✓	–	✓	規則 - 基於	終態，腳本化	電腦環境
OSWorld-人類 [226]	電腦	–	✓	–	✓	規則 - 基於	加權效率	時間性能
VisualWebArena [227]	Web	–	–	✓	✓	基於 ∼	終態，模糊 分數	視覺為基礎
AndroidWorld [228]	Android	–	–	✓	✓	規則 - 基於	終態	動態參數化 - tion
網路商店 [229]	電子商務	–	–	✓	✓	規則 - 基於	終態，程式 - matic 獎勵	可擴展
AgentBench [230]	多 - 領域	–	✓	✓	✓	規則 - 基於	終態，逐步	八個環境
WCA [231]	Web	–	✓	✓	✓	基於 ∼	終態，模糊	勞動密集型 "家務"
螃蟹 [232]	多項式領域	–	✓	✓	✓	規則 - 基於	基於圖的	基於圖的評估
AssistantBench [233]	開啟網頁	–	–	✓	–	基於 ∼	寫實 & 時間 - 消耗中	
安全特定基準								
ST-WebAgent-工作台 [234]	企業	✓	✓	✓	✓	–	CuP，風險	合規政策
AgentHarm [44]	Open-領域	✓	–	✓	✓	–	合規	Jailbreak + 能力
OS-造成 [235] 的傷害	電腦	✓	✓	✓	✓	LLM	安全，準確	桌面特效
R 法官 [236]	Meta 評估	✓	✓	∼	–	LLM	風險識別	風險評估
工具模擬 [208]	工具使用	✓	–	✓	✓	–	副作用	模擬
AgentDojo [188]	工具使用	✓	–	✓	✓	規則 - 基於	工具，語言識別	動態框架
InjecAgent [36]	工具使用	✓	–	–	✓	規則 - 基於	ASR	間接提示注入 - tion
ASB [237]	多項式領域	✓	✓	✓	✓	規則 - 基於	ASR, RR, BP, PNA, NRP	多場景
隱私透鏡 [238]	個人化 Comm	✓	✓	✓	✓	基於 ∼	LR，幫助性	隱私規範意識
代理 - SafetyBench [239]	工具使用	✓	✓	✓	✓	LLM	安全分數，協助 - 圓滿	全面
SAB [240]	具身 AI	✓	✓	✓	✓	∼	拒絕 費用，風險率	具身代理在模擬中 - 模擬環境
CAIBench [241]	網路安全	✓	✓	✓	✓	規則 - 基於 ∼	同時攻擊	以及防禦評估
WASP [242]	Web	✓	✓	✓	✓	∼	ASR（中間 & 端到端), Utility	透過無能之安全 tence
SafeArena [243]	Web	✓	✓	✓	✓	∼	TSR, RR, NSS, ARIA	故意濫用 fo- cused
OAS [244]	多項式領域	✓	✓	✓	✓	∼	FR, DR	多用戶動態
MCP-安全 [245]	MCP	✓	✓	✓	–	規則 - 基於	TSR, ASR	真實的 MCP 伺服器
MCP-SecB [246]	MCP	✓	–	–	–	規則 - 基於	ASR, RR, PSR	真實的 MCP 伺服器
MAGPIE [247]	多項式領域	✓	✓	✓	–	∼	LR, TSR (Constraints), MR, 共識	多智能體

註解：✓ = 完全支援； – =不適用/不支援； ∼ = 依實作或框架而定。完整名稱：洩漏率 (LR)、誤分類率 (MR)、拒絕率 (RR)、保護成功率 (PSR)、任務成功率 (TSR)、失敗率 (FR)、不一致率 (DR)、歸一化安全分數 (NSS)、ARIA 風險等級、無攻擊 (NoAttack) 下的表現 (PNA)、良性表現 (BP) 以及淨韌性表現 (NRP)。

Web agent safety in enterprise contexts. *ST-WebAgentBench* is an online, enterprise-focused benchmark for testing whether web agents avoid unsafe actions (e.g., destructive operations in business systems) while pursuing goals [234]. Unlike legacy suites that only score end-task success, ST-WebAgentBench emphasizes *trustworthiness* under realistic web front ends (such as DevOps workflows, e-commerce, and enterprise CRM). The authors also propose novel evaluation metrics such as (1) *Completion Under Policy (CuP)* (task completions that adhere to acceptable policies) and (2) *Risk Ratio* (quantifies security breaches). In this manner, this benchmark highlights two distinct error classes that are useful for deployment: (i) task success/failure and (ii) unsafe/non-compliant decision-making, with the latter often being under-measured in prior work [234].

Open-domain harmful behavior and misuse. *AgentHarm* measures whether tool-using agents comply with harmful requests across multiple harm categories and whether jailbreaks preserve *agentic competence* (i.e., the ability to carry out multi-step harmful tool sequences once refusal is bypassed) [44]. AgentHarm relies on *synthetic* tools to safely simulate realistic actions (e.g., email, search, etc.) while evaluating safety during evaluation. Reported results indicate that simple jailbreak templates can markedly increase compliance while leaving task-execution ability largely intact, an especially concerning finding for the security of autonomous agents [44].

General computer-use safety. *OS-Harm* builds on OSWorld's [225] full desktop environment to evaluate agent safety across office applications and file operations, scoring both accuracy and adherence to safety guidelines via LLM-based judges with validated agreement levels to human annotations [235]. Compared to pure web benchmarks, OS-Harm stresses desktop-level side-effects (e.g., unintentional data exfiltration or copyright infringement edits) and probes how trace format (screenshots and accessibility trees) affects automatic judging reliability [235].

Risk awareness and trace-level assessment. Rather than elicit harmful behavior, *R-Judge* assesses whether LLMs (and by extension, agents) can recognize *safety risks* in agent trajectories, providing a complementary lens for building better judge or guard(rail) components [236]. Meanwhile, *ToolEmu* evaluates agents within an *LLM-emulated* tool sandbox, enabling scalable probing of risky behaviors and potential negative side-effects [208]. The author's findings via the emulator reveal that several LLM agents are prone to the aforementioned issues, thereby hindering real-world deployment.

Red-team corpora, dynamic web testbeds, and OS-agent sandboxes. Beyond the benchmarks discussed above, additional frameworks strengthen these evaluation dimensions. Red-team corpora like HarmBench [250] and JailbreakBench [251], though primarily LLM-focused, provide adversarial baselines applicable to agent-underlying models. Extending evaluation to realistic web interaction scenarios, dynamic web testbeds such as AgentDojo [188] and WASP [242] assess prompt injection vulnerabilities in web agents. OS-agent sandboxes including ToolEmu [208] and OS-Harm [235] further enable safe evaluation across desktop platforms.

5.3 Evolution of Agentic Security Evaluation

We now discuss some potential directions for the evolution of benchmarks being proposed for agentic AI security evaluation. Alongside insights based on current advances and progress, we discuss how new benchmarks can further augment evaluations by incorporating additional information or adopting relevant strategies.

Process-aware evaluations. End-state metrics (success/fail) miss important aspects of agent safety such as near-misses, unsafe tool invocations later rolled back, or brittle plans that succeed only stochastically. Newer benchmarks therefore score *trajectory segments* (plans, tool calls, and intermediate states) and use *trace-level* judges to detect policy violations or side-effects [237, 242, 234, 236, 208, 235]. The shift to process-aware evaluation unlocks finer-grained feedback for training guardrails and control measures, especially relevant for security-critical domains.

Repeated trial metrics. The τ-BENCH pass$\wedge k$ metric operationalizes reliability under repeated trials with minor stochasticity [223]. In particular, this is crucial for *security* evaluations: a system that is safe in expectation but occasionally executes a destructive action is unacceptable for any mission-critical scenarios. On the other hand, for tasks such as code generation, obtaining one correct solution (out of many possible generations) is feasible (and quantified as the pass@k metric [252]). Thus, it is imperative that evaluations and benchmarks for the security of agentic AI frameworks move towards reporting performance via *distributions* (e.g., pass$\wedge$1, pass$\wedge k$ for several k) rather than one single average.

Standardizing judges and reducing judge bias. *LLM-as-a-judge* [253] is attractive for scale but can be biased by prompt design, trace format, or model choice. Several papers investigate how to structure judges (rubrics, multi-criteria prompts), validate them against humans, and reduce hallucinated assessments [235, 236]. An organic evolution of the judge approach, AGENT-AS-A-JUDGE, embeds an evaluative agent that reasons over trajectories and provides structured critique and scoring [254]. For safety-critical scenarios, when judges are used for evaluation, it is important to report:

企業環境中的 Web 代理安全性。ST-WebAgentBench 是一個專注於企業的線上基準測試，用於評估 Web 代理在追求目標 [234]時是否能避免不安全行為（例如在業務系統中執行破壞性操作）。與僅評估終端任務成功率的傳統套件不同，ST-WebAgentBench 強調在真實的 Web 前端（如 DevOps 工作流、電商及企業 CRM）下的可信度。作者還提出了新的評估指標，包括 (1) 合規完成度 (CuP)（指符合可接受政策之任務完成）以及 (2) 風險比率（量化安全違規事件）。藉此，該基準測試突出了兩種對部署有用的錯誤類別：(i) 任務成功/失敗，以及 (ii) 不安全/不合規的決策，後者往往在既有研究中未被充分衡量 [234]。

跨領域有害行為與濫用。AgentHarm 衡量使用工具的代理是否遵守多項危害類別中的有害請求，以及越獄是否保留代理能力（即繞過拒絕後，執行多步驟有害工具序列的能力） [44]。AgentHarm 依賴合成工具來安全模擬真實動作（例如電子郵件、搜尋等），同時在評估過程中進行安全評估。報告結果顯示，簡單的越獄模板可顯著提高合規率，同時基本保持任務執行能力，這對自主代理的安全性而言是一個特別令人擔憂的發現 [44]。

通用電腦使用安全性。OS-Harm 基於 OSWorld 的 [225] 完整桌面環境，評估代理在辦公應用與檔案操作中的安全性，透過基於 LLM 的評審（經驗證與人類標註的一致性）對準確度與安全準則遵循度進行評分 [235]。與純網頁基準相比，OS-Harm 強調桌面級側效應（例如非故意資料洩漏或侵犯版權的編輯），並探測追蹤格式（截圖與可訪問性樹狀結構）如何影響自動評審的可靠性 [235]。

風險意識與追蹤層評估。與其誘發有害行為，R-Judge 評估大型語言模型（LLM）（並由此推及代理）是否能識別代理軌跡中的安全風險，為構建更佳的評審或防護欄（guardrail）組件提供補充視角 [236]。同時，ToolEmu 在模擬 LLM 的工具沙盒中評估代理，實現對風險行為及潛在負面後果的可擴展探測 [208]。作者透過模擬器得出的發現顯示，若干 LLM 代理易受上述問題困擾，從而阻礙其在現實世界中的部署。

紅隊語料庫、動態網頁測試床以及 OS 代理沙盒。除上述評估指標外，其他框架進一步強化了這些評估維度。類似 HarmBench [250] 和 JailbreakBench[251], 的紅隊語料庫雖主要針對大語言模型，但提供了適用於代理底層模型的對抗基準線。將評估擴展至真實的網頁互動場景，動態網頁測試床如 AgentDojo [188] 和 WASP [242] 用於評估網頁代理中的提示注入漏洞。包括 ToolEmu [208] 和 OS-Harm[235] 在內的 OS 代理沙盒進一步實現了跨桌面平台的安全評估。

5.3 代理安全評估的演進

我們現在討論一些關於針對代理式 AI 安全評估所提出基準演進的潛在方向。結合基於當前進展與成果的見解，我們探討新基準如何透過納入額外資訊或採用相關策略，進一步強化評估。

具備過程意識的評估。終端狀態指標（成功/失敗）會遺漏關於代理安全的重要面向，例如險境未遂、後被回滾的不安全工具調用，或僅在隨機情況下成功的脆弱計畫。因此，較新的基準會對軌跡片段（計畫、工具調用與中間狀態）進行評分，並使用追蹤層級的評審來檢測政策違規或副作用 [237, 242, 234, 236, 208, 235]。轉向具備過程意識的評估，能為訓練防護欄與控制措施提供更細緻的回饋，這對於安全至關重要的領域尤為相關。

重複試驗指標。 τ-BENCH pass$\wedge k$ 指標將重複試驗下的可靠性操作化，並引入微小隨機性 [223]。特別是，這對於安全評估至關重要：一個在期望上安全但偶爾執行破壞性操作的系統，對於任何關鍵任務場景都是不可接受的。另一方面，對於代碼生成等任務，從許多可能的生成結果中獲得一個正確解是可行的（並量化為 pass@k 指標 [252]）。因此，對於智能體 AI 框架的安全評估與基準測試，必須轉向通過分佈（例如 pass$\wedge$1、pass$\wedge k$ 針對多個 k）報告性能，而非單一平均值。

標準化評審並減少評審偏見。LLM-as-a-judge [253] 在擴展規模方面具有吸引力，但可能受提示設計、追蹤格式或模型選擇的影響。多篇論文探討如何構建評審（如評分表、多標準提示）、將其與人類對照驗證，以及減少虛構評估 [235, 236]。AGENT-AS-A-JUDGE 是評審方法的自然演進，它嵌入一個評估代理，對軌跡進行推理，並提供結構化的批評與評分 [254]。在對安全性至關重要的場景中，當使用評審進行評估時，必須報告：

(i) inter-rater agreement with humans, (ii) sensitivity to trace redaction/format, as well as (iii) stability across random seeds and slight task paraphrases.

Sandboxing and emulation to contain risk. Security evaluation often requires testing unsafe prompts or tool sequences; executing these against live systems is risky and irreproducible [208, 235, 255, 243, 256]. Emulation (ToolEmu) and VM-backed sandboxes (OSWorld/OS-Harm) provide safe, deterministic environments for repeatable experiments [208, 235]. A desirable property is *fidelity*: the closer the emulator's API/latency/error modes are to the real use-case, the more useful the results. In general, for security evaluations of agentic AI frameworks, it is especially important that upcoming benchmarks aim to report these fidelity assumptions explicitly.

Reproducibility and comparability. Recent *meta*-benchmarks (e.g. BrowserGym [160]) emphasize unified logging, seeded randomness, and fixed observation/action spaces to avoid apples-to-oranges comparisons. For security applications, future benchmarks should continue to provide: (i) public release of *attack templates* and *defense configurations*; (ii) reporting *cost* and *latency* (in particular safety systems that often add overhead); (iii) documenting environment *determinism* (web UIs and APIs can potentially be dynamic); and (iv) dataset *hygiene* to prevent contamination.

6 Open Challenges

We now discuss some open challenges in the field of agentic AI security. More specifically, we cover issues associated with measuring long-horizon safety in agentic systems, approaches for multi-agent system security, and developing better benchmarks for security evaluation of AI agents, among other considerations.

6.1 Long-Horizon Security

In general, LLM performance across long-horizon tasks (i.e. those that require planning, tool-use, sequential context management, and memory interactions across long episodes) suffers in comparison to shorter-term tasks [257, 258]. Recent computer use testbeds such as OSWorld [225] and OSWorld-Human [226] expose substantial performance and reliability gaps across long workflows and heterogeneous apps, even for strong agents. Similarly, agents struggle to manage memory appropriately over long horizons, leading to erroneous or redundant context [259]. This deficiency is only compounded for security considerations [260] as security risks can surface on multi-step tasks with tool use and partial observability that otherwise might not appear for shorter tasks. The open challenge thus is to measure and improve agentic AI safety across very *long time/episode horizons*. More specifically, progress can be made in two directions: (i) *temporal robustness*: whether agents can maintain safe behavior across multi-step subgoals, interruptions, and/or distribution shifts; and (ii) *latent misbehavior detection*: recent work [261] has shown that deceptive policies can persist through standard safety training and only activate under triggers, undermining short-episode audits.

6.2 Novel Multi-Agent Security Considerations

Multi-agent designs promise fault tolerance and specialization, but collaborations across agents also amplify attack surfaces and introduce novel security threats. Past work [262] has shown that even a single faulty or adversarial agent can cascade failures across different multi-agent organization topologies, and resilience varies sharply with *organizational structure/hierarchy*. Moreover, the presence of *reviewers* or *challenge mechanisms* [262] can improve error recovery significantly. Other work [263] has highlighted vulnerabilities in inter-agent communication protocols (such as *message interception and manipulation* attacks) and shown that these threats can compromise real-world agentic AI applications. Thus, future work can drive progress along the following directions: (1) robust messaging channels with authentication/verification that do not degrade performance (e.g. by introducing additional latency); (2) safety mechanisms for disagreement, contestation, and rollback that limit the potential for attacks caused by adversarial agents; and (3) developing *sentinel* agents that can better regulate the actions of *worker* agents, to safeguard the system against those that are malicious or faulty.

6.3 Improved Safety and Security Benchmarks

A more realistic evaluation of current safety vulnerabilities and deficiencies of agentic systems can only be undertaken if safety/security benchmarks can capture all possible attack scenarios and evaluate threat paradigms rigorously. There are many potential directions for future work to augment safety evaluations for agentic AI systems. (1) New distributional coverage metrics that score trajectory segments, as opposed to only considering the end-state (i.e. whether a task was completed successfully) and capture the entire distribution of performance (instead of average performance or a single run). (2) LLMs-as-a-judge are increasingly being used for agentic AI evaluation [254], but it is not clear how reliable or resilient the judge framework is, given that past work has shown LLM judges can suffer from critical security issues

(i) 與人類的一致性，(ii) 對追蹤刪改/格式的敏感度，以及 (iii) 在隨機種子與任務同義重述下的穩定性。

沙箱化與模擬用於限制風險。安全評估經常需要測試不安全提示或工具序列；在真實系統上執行這些操作具有風險且難以重複 [208, 235, 255, 243, 256]。模擬（ToolEmu）與基於虛擬機的沙箱（OSWorld/OS-Harm）提供了安全、確定性的環境，以進行可重複實驗 [208, 235]。一個理想的特性是忠實度：模擬器的 API/延遲/錯誤模式越接近真實使用場景，結果就越有用。一般而言，對於代理 AI 框架的安全評估，未來的基準測試特別應明確報告這些忠實度假設。

可重複性與可比性。最近的元基準測試（例如 BrowserGym [160]）強調統一記錄、種子隨機性以及固定的觀察/動作空間，以避免「李逵李鬼」式的比較。對於安全應用，未來的基準測試應繼續提供：(i) 公開發布攻擊模板與防禦配置；(ii) 報告成本與延遲（特別是常會增加額外負載的安全系統）；(iii) 記錄環境的確定性（網頁介面與 API 可能具有動態特性）；以及 (iv) 數據集衛生，以防止污染。

6 開放挑戰

我們現在討論代理 AI 安全領域的一些開放性挑戰。更具體地說，我們涵蓋了與衡量代理系統長期安全性相關的議題、多代理系統安全的解決方案，以及開發更佳的 AI 代理安全評估基準，以及其他相關考量。

6.1 長期安全

一般而言，大型語言模型（LLM）在長時限任務（即需要規劃、工具使用、序列上下文管理及跨長時程的記憶互動的任務）上的表現，相較於短期任務會顯著下降 [257, 258]。近期的電腦使用測試環境，如 OSWorld [225] 與 OSWorld-Human [226]，已揭露即使在強勁的代理（agents）情況下，長流程與異質應用程式之間仍存在顯著的效能與可靠性差距。同樣地，代理在長時限下難以恰當地管理記憶，導致產生錯誤或冗餘的上下文 [259]。此缺陷在安全考量下更為嚴重 [260]，因為安全風險可能出現在涉及工具使用與部分可觀測性的多步驟任務中，而這些風險在較短的任務中本就不易顯現。因此，當前的挑戰在於衡量並改善代理式人工智慧在極長時間/時程範圍內的安全性。更具體而言，進展可從兩個方向著手：(i) 時間魯棒性：代理能否在多步驟子目標、中斷及/或分佈偏移下維持安全行為；以及 (ii) 潛在不當行為檢測：近期研究 [261] 顯示，欺騙性策略可透過標準的安全訓練持續存在，僅在特定觸發條件下才會啟動，從而破壞短時程的審計機制。

6.2 新型多代理安全考量

多代理設計承諾了容錯與專業化，但跨代理的協作也會擴大攻擊面並引入新型安全威脅。過去的研究 [262] 顯示，即使單一有缺陷或惡意代理也能導致不同多代理組織架構中的失敗連鎖反應，且其韌性隨組織結構/層級變化而顯著差異。此外，審查員或挑戰機制 [262] 的存在可顯著改善錯誤恢復。其他研究 [263] 則指出代理間通信協議的漏洞（例如訊息攔截與操縱攻擊），並證明這些威脅可能損害現實世界的代理 AI 應用。因此，未來工作可沿以下方向推動進展：(1) 具備身份驗證/驗證且不會降低性能（例如避免引入額外延遲）的堅固訊息通道；(2) 針對分歧、爭議與回滾的安全機制，以限制惡意代理所引發攻擊的潛在風險；以及 (3) 開發哨兵代理，以更有效地規範工作代理的行為，從而保護系統免受惡意或有缺陷代理的侵害。

6.3 改進的安全與安全基準

對當前代理系統的安全漏洞與缺陷進行更真實的評估，僅在安全/安全基準能夠捕捉所有可能的攻擊情境並嚴謹評估威脅範式的情況下才能進行。未來工作有許多潛在方向可用於增強代理 AI 系統的安全評估。(1) 開發新的分佈覆蓋度指標，用於評分軌跡片段，而非僅考慮終端狀態（即任務是否成功完成），並捕捉整個性能分佈（而非平均性能或單一運行的表現）。(2) 將大型語言模型作為評審者 (LLMs-as-a-judge) 越來越常被用於代理 AI 評估 [254]，但鑑於過去的研究顯示大型語言模型評審者可能面臨關鍵安全問題，尚不清楚該評審框架的可靠性與韌性如何。

themselves [264]. Future work can thus work towards developing judges that are standardizes and robust to adversarial influence. (3) To truly assess how damaging potential attacks against agent systems can be, it is important to undertake rigorous testing in sandbox and emulated environments – future research work can aim to uncover whether or not current environments possess high *fidelity* with the *real-world*, and propose alternatives where current systems are inadequate.

6.4 Safety Against Adaptive Attacks

Adaptive attacks constitute a stronger threat model, where the attackers already have knowledge of the defense method employed by the system [61]. Recent studies show that adaptive attacks have been largely unexplored and ignored, as most work undertakes *static* (i.e., non-adaptive) defense evaluations for AI agents [61, 179, 220]. More generally, in adversarial attack research in ML/AI, many defenses initially reported as effective are commonly undermined soon after their release, primarily because they lack thorough evaluation against adaptive attack strategies [179, 265, 266]. In the same vein, although different studies are being done to consider, defend, and evaluate adaptive attacks [172, 216], their potential impacts across agentic AI systems merit further exploration. Hence, future works can can explore the following directions: (i) proposing and defining novel evaluation methods specific to adaptive attacks, and (ii) exploring the impact of current defenses against adaptive attacks, and (iii) developing stronger *adaptive* defenses that can co-evolve and thwart adaptive attackers.

6.5 Agentic AI Security in the Physical World

While this survey primarily focuses on software-based agents, physically embodied agents introduce additional and largely unexplored security risks due to their dependence on hardware and direct interaction with the physical environment. (1) Such risks involve adversaries manipulating robot perception through sensor spoofing, including GPS spoofing that redirects vehicles into restricted zones [267, 268], LiDAR laser projection spoofing that injects phantom obstacles triggering emergency braking [269, 270], and adversarial patches on road signs and persons causing threats through misclassification [271, 272]. (2) Ensuring robust and secure operation of physically embodied agents remains a critical challenge, as agent architecture increasingly determines vulnerability. End-to-end foundation models (e.g., RT-2 [273], OpenVLA [274]) map raw sensory inputs directly to motor actions, eliminating defensive separation and prioritizing zero-shot generalization, but without corresponding improvements in adversarial robustness [275]. Addressing this trade-off between generalization and safety, requires new methods to preserve internal defenses and safeguard agents against real-world sensor and hardware attacks. (3) Beyond mobile robotics, LLM-based agents are increasingly deployed in smart home environments for device control and automation [276], yet systematic security evaluation and benchmark in these environments remains underexplored.

6.6 Human-Agent Security Interfaces

The boundary between humans and agentic AI systems introduces a unique security frontier. On one hand, agents are often deployed to interact directly with end-users, who may provide instructions, corrections, or verification of system behavior. On the other hand, human oversight itself can be *adversarially influenced*. For instance, users can be socially engineered by an attacker into approving unsafe actions[2], or become overwhelmed by the complexity of long execution traces. These potential vulnerabilities highlight the need to better understand and secure the *interface layer* between agents and human operators. Thus, future work can investigate several problems to bridge this gap, such as: (i) designing user interaction mechanisms that are robust to manipulation and do not overly burden the human with verification tasks; (ii) developing auditing and summarization tools that make long-horizon agent behavior interpretable enough for reliable user verification; and (iii) studying how attackers can exploit user trust, particularly in multi-step workflows where human approval serves as a safety check. We posit that progress on this front will require not only technical defenses but also empirical studies on human factors, as the security of agentic systems depends as both *human susceptibility* as well as *algorithmic robustness*.

7 Conclusion

In this survey, we provided an in-depth analysis of current work in agentic AI security. Our paper first discussed the unique landscape of security threats that agentic AI systems are susceptible to via a comprehensive taxonomy of related work (Section 3). Then, we have discussed several defense strategies and security controls that can be employed to mitigate known attack vectors (Section 4) as well as various benchmarks and evaluation metrics to guide rigorous testing of proposed agentic attack/defense approaches (Section 5). Finally, we discussed a number of open challenges

[2]Consider an example from [55] where the attacker lures the user by saying: *"you won't believe ChatGPT's response to this prompt!"* followed by the prompt injection text in another language or `Base64` so the user cannot ascertain its adversarial nature.

它們 [264]。因此，未來工作可以致力於開發標準化且對對抗性影響具有魯棒性的評估者。(3) 要真正評估針對代理系統的潛在攻擊可能造成的損害，必須在沙箱和模擬環境中進行嚴謹的測試；未來的研究工作可以旨在揭示當前環境是否與現實世界具有高保真度，並在當前系統不足之處提出替代方案。

6.4 安全防護：針對適應性攻擊

適應性攻擊構成更強的威脅模型，其中攻擊者已掌握系統所採用的防禦方法 [61]。近期研究顯示，適應性攻擊尚未得到充分探討且常被忽視，因為大多數工作針對 AI 代理 [61, 179, 220] 進行的是靜態（即非適應性）防禦評估。更廣泛而言，在機器學習/AI 的對抗攻擊研究中，許多最初被報告為有效的防禦手段，在發布後不久便常被削弱，主要原因在於它們缺乏針對適應性攻擊策略的徹底評估 [179, 265, 266]。同樣地，儘管已有不同研究致力於考慮、防禦和評估適應性攻擊 [172, 216]，但其在代理 AI 系統中的潛在影響仍值得進一步探索。因此，未來工作可探索以下方向：(i) 提出並定義專為適應性攻擊設計的創新評估方法，以及 (ii) 探討現有防禦手段對適應性攻擊的影響，以及 (iii) 開發更強大的適應性防禦機制，使其能與適應性攻擊者共同演化並予以抵禦。

6.5 智能體 AI 在實體世界中的安全

雖然本調查主要聚焦於軟體代理，但具物理載體的代理因其對硬體及與物理環境直接互動的依賴，引入了額外的且 largely 未探索的安全風險。(1) 這些風險涉及敵對方透過感測器偽裝操控機器人感知，包括 GPS 偽裝導向車輛進入限制區域 [267, 268]，、LiDAR 雷射投影偽裝注入虛幻障礙物觸發緊急煞車 [269, 270]，、以及道路標誌與人員上的敵對方貼片導致分類錯誤而引發威脅 [271, 272]。(2) 確保具物理載體代理的穩健與安全運作仍是一大挑戰，因為代理架構日益決定脆弱性。端到端基礎模型（例如 RT-2 [273], OpenVLA [274]）將原始感測輸入直接映射為運動動作，消除了防禦性隔離並優先追求零樣本泛化能力，但缺乏相應的對抗魯棒性提升 [275]。解決泛化與安全之間的權衡，需要新方法來保留內部防禦並保護代理免受現實世界的感測器與硬體攻擊。(3) 除移動機器人外，基於 LLM 的代理正日益部署於智慧家居環境以進行裝置控制與自動化 [276]，，然而這些環境中的系統性安全評估與基準測試仍屬未充分探索。

6.6 人類 - 代理安全介面

人類與具自主性 AI 系統之間的界線，帶來了獨特的安全前沿。一方面，代理常被部署以直接與終端用戶互動，用戶可能提供指令、修正或驗證系統行為。另一方面，人類監督本身也可能受到對抗性影響。例如，攻擊者可能透過社會工程學手段誘導用戶批准不安全動作[2]，，或使用戶因長期執行軌跡的複雜性而不知所措。這些潛在漏洞突顯了我們需要更深入地理解並加強代理與人類操作員之間介面層的安全。因此，未來工作可針對以下幾個問題進行研究以填補此差距：(i) 設計對操控具有韌性的用戶互動機制，且不過度增加人類的驗證負擔；(ii) 開發審計與摘要工具，使長期視角的代理行為足以讓用戶進行可靠驗證；以及 (iii) 研究攻擊者如何利用用戶信任，特別是在多步驟工作流中，人類批准作為安全檢查的場合。我們認為，在此領域的進展不僅需要技術防禦，還需進行關於人類因素的事實研究，因為具自主性系統的安全性既取決於人類的易受性，也取決於演算法的韌性。

7 結論

在本調查中，我們深入分析了當前代理式 AI 安全領域的研究現狀。我們的論文首先透過相關研究的綜合分類法，探討了代理式 AI 系統所面臨的獨特安全威脅景觀（第 3 節）。接著，我們討論了若干可採用以緩解已知攻擊向量的防禦策略與安全控制措施（第 4 節），以及各種基準與評估指標，用以指導對所提議的代理式攻擊/防禦方法進行嚴謹測試（第 5 節）。最後，我們探討了若干尚未解決的挑戰。

[2]考慮 [55] 中的一個範例，攻擊者會這樣誘導使用者：「你絕對不敢相信 ChatGPT 對這個提示的回應！」，接著在另一種語言或 Base64 編碼中附上提示注入文字，使使用者無法察覺其對抗性本質。

where progress can be made, and how doing so will significantly augment the safety properties of future agentic AI systems (Section 6). Our goal through this survey article is to add to the existing body of work on agentic AI security by providing a distilled introduction to the field, and to galvanize research progress in making agentic frameworks more safe and secure for large-scale societal use.

References

[1] Sachin Kumar, Ajit Kumar Verma, and Amna Mirza. *Digital transformation, artificial intelligence and society*. Springer, 2024.

[2] William J Clancey. The epistemology of a rule-based expert system—a framework for explanation. *Artificial intelligence*, 20(3):215–251, 1983.

[3] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[4] Stuart Russell, Peter Norvig, and Artificial Intelligence. A modern approach. *Artificial Intelligence. Prentice-Hall, Egnlewood Cliffs*, 25(27):79–80, 1995.

[5] Tom B. Brown, Benjamin Mann, Nick Ryder, et al. Language models are few-shot learners. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[6] OpenAI. Gpt-4 technical report, 2023. arXiv:2303.08774.

[7] Hugo Touvron et al. Llama 2: Open foundation and fine-tuned chat models, 2023. arXiv:2307.09288.

[8] Tianyi Bai, Hao Liang, Binwang Wan, Yanran Xu, Xi Li, Shiyu Li, Ling Yang, Bozhou Li, Yifan Wang, Bin Cui, et al. A survey of multimodal large language model from a data-centric perspective. *arXiv preprint arXiv:2405.16640*, 2024.

[9] Bo Li, Yuanhan Zhang, Liangyu Chen, Jinghao Wang, Fanyi Pu, Joshua Adrian Cahyono, Jingkang Yang, Chunyuan Li, and Ziwei Liu. Otter: A multi-modal model with in-context instruction tuning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2025.

[10] Marco Cascella, Federico Semeraro, Jonathan Montomoli, Valentina Bellini, Ornella Piazza, and Elena Bignami. The breakthrough of large language models release for medical applications: 1-year timeline and perspectives. *Journal of Medical Systems*, 48(1):22, 2024.

[11] Spyros Makridakis, Fotios Petropoulos, and Yanfei Kang. Large language models: Their success and impact. *Forecasting*, 5(3):536–549, 2023.

[12] Humza Naveed, Asad Ullah Khan, Shi Qiu, Muhammad Saqib, Saeed Anwar, Muhammad Usman, Naveed Akhtar, Nick Barnes, and Ajmal Mian. A comprehensive overview of large language models. *ACM Transactions on Intelligent Systems and Technology*, 2023.

[13] How LLMs Work. Ai what do large language models "understand"? *Image*, 21:1, 2024.

[14] Andrei Kucharavy. Fundamental limitations of generative llms. In *Large Language Models in Cybersecurity: Threats, Exposure and Mitigation*, pages 55–64. Springer Nature Switzerland Cham, 2024.

[15] Thomas Kwa, Ben West, Joel Becker, Amy Deng, Katharyn Garcia, Max Hasin, Sami Jawhar, Megan Kinniment, Nate Rush, Sydney Von Arx, et al. Measuring ai ability to complete long tasks. *arXiv preprint arXiv:2503.14499*, 2025.

[16] Palo Alto Networks (Unit 42). Ai agents are here. so are the threats., 2025.

[17] LangChain. Langchain documentation. `https://python.langchain.com/`, 2024.

[18] Toran Bruce Richards. Autogpt: An autonomous gpt experiment. `https://github.com/Torantulino/Auto-GPT`, 2024.

[19] Guanzhi Wang et al. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*, 2023.

[20] Paolo Dal Cin, Daniel Kendzior, Yusof Seedat, and Renato Marinho. Three essentials for agentic ai security. *MIT Sloan Management Review (Online)*, pages 1–4, 2025.

[21] Reuters. Just in time? manufacturers turn to ai to weather tariff storm, 2025. URL `https://www.reuters.com/business/just-time-manufacturers-turn-ai-weather-tariff-storm-2025-08-13/`.

[22] Wired. Forget chatbots. ai agents are the future, 2025. URL `https://www.wired.com/story/fast-forward-forget-chatbots-ai-agents-are-the-future/`. Accessed: 2025-08-16.

[23] Joon Sung Park et al. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the ACM Symposium on User Interface Software and Technology (UIST)*, 2023.

在可取得進展之處，以及這將如何顯著提升未來代理式 AI 系統的安全性屬性（第 6 節）。本調查文檔的目標是透過提供該領域的精簡介紹，增補現有關於代理式 AI 安全的文獻，並激勵研究進展，使代理式框架更安全可靠，以適用於大規模社會應用。

參考資料

[1] Sachin Kumar, Ajit Kumar Verma, and Amna Mirza. *Digital transformation, artificial intelligence and society*. Springer, 2024.

[2] William J Clancey. The epistemology of a rule-based expert system—a framework for explanation. *Artificial intelligence*, 20(3):215–251, 1983.

[3] Yann LeCun, Yoshua Bengio, and Geoffrey Hinton. Deep learning. *nature*, 521(7553):436–444, 2015.

[4] Stuart Russell, Peter Norvig, and Artificial Intelligence. A modern approach. *Artificial Intelligence. Prentice-Hall, Egnlewood Cliffs*, 25(27):79–80, 1995.

[5] Tom B. Brown, Benjamin Mann, Nick Ryder, et al. Language models are few-shot learners. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[6] OpenAI. Gpt-4 technical report, 2023. arXiv:2303.08774.

[7] Hugo Touvron et al. Llama 2: Open foundation and fine-tuned chat models, 2023. arXiv:2307.09288.

[8] Tianyi Bai, Hao Liang, Binwang Wan, Yanran Xu, Xi Li, Shiyu Li, Ling Yang, Bozhou Li, Yifan Wang, Bin Cui, et al. A survey of multimodal large language model from a data-centric perspective. *arXiv preprint arXiv:2405.16640*, 2024.

[9] Bo Li, Yuanhan Zhang, Liangyu Chen, Jinghao Wang, Fanyi Pu, Joshua Adrian Cahyono, Jingkang Yang, Chunyuan Li, and Ziwei Liu. Otter: A multi-modal model with in-context instruction tuning. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2025.

[10] Marco Cascella, Federico Semeraro, Jonathan Montomoli, Valentina Bellini, Ornella Piazza, and Elena Bignami. The breakthrough of large language models release for medical applications: 1-year timeline and perspectives. *Journal of Medical Systems*, 48(1):22, 2024.

[11] Spyros Makridakis, Fotios Petropoulos, and Yanfei Kang. Large language models: Their success and impact. *Forecasting*, 5(3):536–549, 2023.

[12] Humza Naveed, Asad Ullah Khan, Shi Qiu, Muhammad Saqib, Saeed Anwar, Muhammad Usman, Naveed Akhtar, Nick Barnes, and Ajmal Mian. A comprehensive overview of large language models. *ACM Transactions on Intelligent Systems and Technology*, 2023.

[13] How LLMs Work. Ai what do large language models "understand"? *Image*, 21:1, 2024.

[14] Andrei Kucharavy. Fundamental limitations of generative llms. In *Large Language Models in Cybersecurity: Threats, Exposure and Mitigation*, pages 55–64. Springer Nature Switzerland Cham, 2024.

[15] Thomas Kwa, Ben West, Joel Becker, Amy Deng, Katharyn Garcia, Max Hasin, Sami Jawhar, Megan Kinniment, Nate Rush, Sydney Von Arx, et al. Measuring ai ability to complete long tasks. *arXiv preprint arXiv:2503.14499*, 2025.

[16] Palo Alto Networks (Unit 42). Ai agents are here. so are the threats., 2025.

[17] LangChain. Langchain documentation. `https://python.langchain.com/`, 2024.

[18] Toran Bruce Richards. Autogpt: An autonomous gpt experiment. `https://github.com/Torantulino/Auto-GPT`, 2024.

[19] Guanzhi Wang et al. Voyager: An open-ended embodied agent with large language models. *arXiv preprint arXiv:2305.16291*, 2023.

[20] Paolo Dal Cin, Daniel Kendzior, Yusof Seedat, and Renato Marinho. Three essentials for agentic ai security. *MIT Sloan Management Review (Online)*, pages 1–4, 2025.

[21] Reuters. Just in time? manufacturers turn to ai to weather tariff storm, 2025. URL `https://www.reuters.com/business/just-time-manufacturers-turn-ai-weather-tariff-storm-2025-08-13/`.

[22] Wired. Forget chatbots. ai agents are the future, 2025. URL `https://www.wired.com/story/fast-forward-forget-chatbots-ai-agents-are-the-future/`. Accessed: 2025-08-16.

[23] Joon Sung Park et al. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the ACM Symposium on User Interface Software and Technology (UIST)*, 2023.

[24] Shanghua Gao, Ada Fang, Yepeng Huang, Valentina Giunchiglia, Ayush Noori, Jonathan Richard Schwarz, Yasha Ektefaie, Jovana Kondic, and Marinka Zitnik. Empowering biomedical discovery with ai agents. *Cell*, 187 (22):6125–6151, 2024.

[25] Mourad Gridach, Jay Nanavati, Khaldoun Zine El Abidine, Lenon Mendes, and Christina Mack. Agentic ai for scientific discovery: A survey of progress, challenges, and future directions. *arXiv preprint arXiv:2503.08979*, 2025.

[26] Verge. Inside the automated warehouse where robots are packing your groceries, 2025. URL `https://www.theverge.com/robot/719880/ocado-online-grocery-automation-krogers-luton-ogrp-robot-grid`. Accessed: 2025-08-16.

[27] Zihan Chen, Yixin Wu, et al. Autoagents: A framework for automatic agent generation. *arXiv preprint arXiv:2309.17288*, 2023. URL `https://arxiv.org/abs/2309.17288`.

[28] Reuters. Amazon's delivery, logistics get ai boost, 2025. URL `https://www.reuters.com/business/retail-consumer/amazons-delivery-logistics-will-get-an-ai-boost-2025-06-04/`. Accessed: 2025-08-16.

[29] Subash Neupane, Sudip Mittal, and Shahram Rahimi. Towards a hipaa compliant agentic ai system in healthcare. *arXiv preprint arXiv:2504.17669*, 2025.

[30] Ken Huang. Ai agents in healthcare. In *Agentic AI: Theories and Practices*, pages 303–321. Springer, 2025.

[31] Nalan Karunanayake. Next-generation agentic ai for transforming healthcare. *Informatics and Health*, 2(2): 73–83, 2025.

[32] Michael Moritz, Eric Topol, and Pranav Rajpurkar. Coordinated ai agents for advancing healthcare. *Nature Biomedical Engineering*, pages 1–7, 2025.

[33] James Zou and Eric J Topol. The rise of agentic ai teammates in medicine. *The Lancet*, 405(10477):457, 2025.

[34] Trend Micro. Preventing zero-click ai threats: Insights from echoleak, 2025. URL `https://www.trendmicro.com/en_us/research/25/g/preventing-zero-click-ai-threats-insights-from-echoleak.html`. Accessed: 2025-08-16.

[35] Symantec and Carbon Black. Ai: Advent of agents opens new possibilities for attackers, 2025. URL `https://www.security.com/threat-intelligence/ai-agent-attacks`. Accessed: 2025-08-16.

[36] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10471–10506, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi:10.18653/v1/2024.findings-acl.624. URL `https://aclanthology.org/2024.findings-acl.624/`.

[37] Donghyun Lee and Mo Tiwari. Prompt infection: Llm-to-llm prompt injection within multi-agent systems. *arXiv preprint arXiv:2410.07283*, 2024.

[38] Matteo Lupinacci, Francesco Aurelio Pironti, Francesco Blefari, Francesco Romeo, Luigi Arena, and Angelo Furfaro. The dark side of llms agent-based attacks for complete computer takeover. *arXiv preprint arXiv:2507.06850*, 2025.

[39] Anthropic Research Team. Agentic misalignment: How llms could be insider threats, 2025.

[40] Shen Dong, Shaochen Xu, Pengfei He, Yige Li, Jiliang Tang, Tianming Liu, Hui Liu, and Zhen Xiang. A practical memory injection attack against llm agents. *arXiv preprint arXiv:2503.03704*, 2025.

[41] Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. *Advances in Neural Information Processing Systems*, 37:130185–130213, 2024.

[42] Ang Li, Yin Zhou, Vethavikashini Chithrra Raghuram, Tom Goldstein, and Micah Goldblum. Commercial llm agents are already vulnerable to simple yet dangerous attacks. *arXiv preprint arXiv:2502.08586*, 2025.

[43] Xiaohan Fu, Shuheng Li, Zihan Wang, Yihao Liu, Rajesh K Gupta, Taylor Berg-Kirkpatrick, and Earlence Fernandes. Imprompter: Tricking llm agents into improper tool use. *arXiv preprint arXiv:2410.14923*, 2024.

[44] Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, et al. Agentharm: A benchmark for measuring harmfulness of llm agents. *arXiv preprint arXiv:2410.09024*, 2024.

[24] Shanghua Gao, Ada Fang, Yepeng Huang, Valentina Giunchiglia, Ayush Noori, Jonathan Richard Schwarz, Yasha Ektefaie, Jovana Kondic, and Marinka Zitnik. Empowering biomedical discovery with ai agents. *Cell*, 187 (22):6125–6151, 2024.

[25] Mourad Gridach, Jay Nanavati, Khaldoun Zine El Abidine, Lenon Mendes, and Christina Mack. Agentic ai for scientific discovery: A survey of progress, challenges, and future directions. *arXiv preprint arXiv:2503.08979*, 2025.

[26] Verge. Inside the automated warehouse where robots are packing your groceries, 2025. URL `https://www.theverge.com/robot/719880/ocado-online-grocery-automation-krogers-luton-ogrp-robot-grid`. Accessed: 2025-08-16.

[27] Zihan Chen, Yixin Wu, et al. Autoagents: A framework for automatic agent generation. *arXiv preprint arXiv:2309.17288*, 2023. URL `https://arxiv.org/abs/2309.17288`.

[28] Reuters. Amazon's delivery, logistics get ai boost, 2025. URL `https://www.reuters.com/business/retail-consumer/amazons-delivery-logistics-will-get-an-ai-boost-2025-06-04/`. Accessed: 2025-08-16.

[29] Subash Neupane, Sudip Mittal, and Shahram Rahimi. Towards a hipaa compliant agentic ai system in healthcare. *arXiv preprint arXiv:2504.17669*, 2025.

[30] Ken Huang. Ai agents in healthcare. In *Agentic AI: Theories and Practices*, pages 303–321. Springer, 2025.

[31] Nalan Karunanayake. Next-generation agentic ai for transforming healthcare. *Informatics and Health*, 2(2): 73–83, 2025.

[32] Michael Moritz, Eric Topol, and Pranav Rajpurkar. Coordinated ai agents for advancing healthcare. *Nature Biomedical Engineering*, pages 1–7, 2025.

[33] James Zou and Eric J Topol. The rise of agentic ai teammates in medicine. *The Lancet*, 405(10477):457, 2025.

[34] Trend Micro. Preventing zero-click ai threats: Insights from echoleak, 2025. URL `https://www.trendmicro.com/en_us/research/25/g/preventing-zero-click-ai-threats-insights-from-echoleak.html`. Accessed: 2025-08-16.

[35] Symantec and Carbon Black. Ai: Advent of agents opens new possibilities for attackers, 2025. URL `https://www.security.com/threat-intelligence/ai-agent-attacks`. Accessed: 2025-08-16.

[36] Qiusi Zhan, Zhixiang Liang, Zifan Ying, and Daniel Kang. InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, *Findings of the Association for Computational Linguistics: ACL 2024*, pages 10471–10506, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi:10.18653/v1/2024.findings-acl.624. URL `https://aclanthology.org/2024.findings-acl.624/`.

[37] Donghyun Lee and Mo Tiwari. Prompt infection: Llm-to-llm prompt injection within multi-agent systems. *arXiv preprint arXiv:2410.07283*, 2024.

[38] Matteo Lupinacci, Francesco Aurelio Pironti, Francesco Blefari, Francesco Romeo, Luigi Arena, and Angelo Furfaro. The dark side of llms agent-based attacks for complete computer takeover. *arXiv preprint arXiv:2507.06850*, 2025.

[39] Anthropic Research Team. Agentic misalignment: How llms could be insider threats, 2025.

[40] Shen Dong, Shaochen Xu, Pengfei He, Yige Li, Jiliang Tang, Tianming Liu, Hui Liu, and Zhen Xiang. A practical memory injection attack against llm agents. *arXiv preprint arXiv:2503.03704*, 2025.

[41] Zhaorun Chen, Zhen Xiang, Chaowei Xiao, Dawn Song, and Bo Li. Agentpoison: Red-teaming llm agents via poisoning memory or knowledge bases. *Advances in Neural Information Processing Systems*, 37:130185–130213, 2024.

[42] Ang Li, Yin Zhou, Vethavikashini Chithrra Raghuram, Tom Goldstein, and Micah Goldblum. Commercial llm agents are already vulnerable to simple yet dangerous attacks. *arXiv preprint arXiv:2502.08586*, 2025.

[43] Xiaohan Fu, Shuheng Li, Zihan Wang, Yihao Liu, Rajesh K Gupta, Taylor Berg-Kirkpatrick, and Earlence Fernandes. Imprompter: Tricking llm agents into improper tool use. *arXiv preprint arXiv:2410.14923*, 2024.

[44] Maksym Andriushchenko, Alexandra Souly, Mateusz Dziemian, Derek Duenas, Maxwell Lin, Justin Wang, Dan Hendrycks, Andy Zou, Zico Kolter, Matt Fredrikson, et al. Agentharm: A benchmark for measuring harmfulness of llm agents. *arXiv preprint arXiv:2410.09024*, 2024.

[45] Boyang Zhang, Yicong Tan, Yun Shen, Ahmed Salem, Michael Backes, Savvas Zannettou, and Yang Zhang. Breaking agents: Compromising autonomous llm agents through malfunction amplification. *arXiv preprint arXiv:2407.20859*, 2024.

[46] Carnegie Mellon University. When llms autonomously attack, 2025. `https://engineering.cmu.edu/news-events/news/2025/07/24-when-llms-autonomously-attack.html`.

[47] Johannes Schneider. Generative to agentic AI: Survey, Conceptualization, and Challenges. *arXiv preprint arXiv:2504.18875*, 2025.

[48] Mahmoud Mohammadi, Yipeng Li, Jane Lo, and Wendy Yip. Evaluation and benchmarking of llm agents: A survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6129–6139, 2025.

[49] Bang Liu, Xinfeng Li, Jiayi Zhang, Jinlin Wang, Tanjin He, Sirui Hong, Hongzhang Liu, Shaokun Zhang, Kaitao Song, Kunlun Zhu, et al. Advances and challenges in foundation agents: From brain-inspired intelligence to evolutionary, collaborative, and safe systems. *arXiv preprint arXiv:2504.01990*, 2025.

[50] Huan-ang Gao, Jiayi Geng, Wenyue Hua, Mengkang Hu, Xinzhe Juan, Hongzhang Liu, Shilong Liu, Jiahao Qiu, Xuan Qi, Yiran Wu, et al. A survey of self-evolving agents: On path to artificial super intelligence. *arXiv preprint arXiv:2507.21046*, 2025.

[51] Deepak Bhaskar Acharya, Karthigeyan Kuppan, and B Divya. Agentic ai: Autonomous intelligence for complex goals–a comprehensive survey. *IEEe Access*, 2025.

[52] Shaina Raza, Ranjan Sapkota, Manoj Karkee, and Christos Emmanouilidis. Trism for agentic ai: A review of trust, risk, and security management in llm-based agentic multi-agent systems. *arXiv preprint arXiv:2506.04133*, 2025.

[53] NIST AI. Artificial intelligence risk management framework: Generative artificial intelligence profile. *NIST Trustworthy and Responsible AI Gaithersburg, MD, USA*, 2024.

[54] Jules White, Quchen Fu, Sam Hays, Michael Sandborn, Carlos Olea, Henry Gilbert, Ashraf Elnashar, Jesse Spencer-Smith, and Douglas C Schmidt. A prompt pattern catalog to enhance prompt engineering with chatgpt. *arXiv preprint arXiv:2302.11382*, 2023.

[55] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated Applications with indirect prompt injection. *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, 2023. URL `https://api.semanticscholar.org/CorpusID:258546941`.

[56] Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. *ArXiv*, abs/2211.09527, 2022. URL `https://api.semanticscholar.org/CorpusID:253581710`.

[57] Luca Beurer-Kellner, Beat Buesser, Ana-Maria Creţu, Edoardo Debenedetti, Daniel Dobos, Daniel Fabian, Marc Fischer, David Froelicher, Kathrin Grosse, Daniel Naeff, et al. Design Patterns for Securing LLM Agents against Prompt Injections. *arXiv preprint arXiv:2506.08837*, 2025.

[58] OWASP GenAI Project. Owasp genai llm01: Prompt injection, 2025.

[59] Jeremy McHugh, Kristina Sekrst, and Jonathan Rodriguez Cefalu. Prompt injection 2.0: Hybrid ai threats. *ArXiv*, abs/2507.13169, 2025. URL `https://api.semanticscholar.org/CorpusID:280296803`.

[60] Yulin Chen, Haoran Li, Yuan Sui, Yufei He, Yue Liu, Yangqiu Song, and Bryan Hooi. Can indirect prompt injection attacks be detected and removed? *arXiv preprint arXiv:2502.16580*, 2025.

[61] Qiusi Zhan, Richard Fang, Henil Shalin Panchal, and Daniel Kang. Adaptive attacks break defenses against indirect prompt injection attacks on llm agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 7101–7117, 2025.

[62] Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023. URL `https://arxiv.org/abs/2307.15043`.

[63] Xiaogeng Liu, Zhiyuan Yu, Yizhe Zhang, Ning Zhang, and Chaowei Xiao. Automatic and universal prompt injection attacks against large language models. *arXiv preprint arXiv:2403.04957*, 2024.

[64] Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint arXiv:2309.00614*, 2023.

[45] Boyang Zhang, Yicong Tan, Yun Shen, Ahmed Salem, Michael Backes, Savvas Zannettou, and Yang Zhang. Breaking agents: Compromising autonomous llm agents through malfunction amplification. *arXiv preprint arXiv:2407.20859*, 2024.

[46] Carnegie Mellon University. When llms autonomously attack, 2025. `https://engineering.cmu.edu/news-events/news/2025/07/24-when-llms-autonomously-attack.html`.

[47] Johannes Schneider. Generative to agentic AI: Survey, Conceptualization, and Challenges. *arXiv preprint arXiv:2504.18875*, 2025.

[48] Mahmoud Mohammadi, Yipeng Li, Jane Lo, and Wendy Yip. Evaluation and benchmarking of llm agents: A survey. In *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V. 2*, pages 6129–6139, 2025.

[49] Bang Liu, Xinfeng Li, Jiayi Zhang, Jinlin Wang, Tanjin He, Sirui Hong, Hongzhang Liu, Shaokun Zhang, Kaitao Song, Kunlun Zhu, et al. Advances and challenges in foundation agents: From brain-inspired intelligence to evolutionary, collaborative, and safe systems. *arXiv preprint arXiv:2504.01990*, 2025.

[50] Huan-ang Gao, Jiayi Geng, Wenyue Hua, Mengkang Hu, Xinzhe Juan, Hongzhang Liu, Shilong Liu, Jiahao Qiu, Xuan Qi, Yiran Wu, et al. A survey of self-evolving agents: On path to artificial super intelligence. *arXiv preprint arXiv:2507.21046*, 2025.

[51] Deepak Bhaskar Acharya, Karthigeyan Kuppan, and B Divya. Agentic ai: Autonomous intelligence for complex goals–a comprehensive survey. *IEEe Access*, 2025.

[52] Shaina Raza, Ranjan Sapkota, Manoj Karkee, and Christos Emmanouilidis. Trism for agentic ai: A review of trust, risk, and security management in llm-based agentic multi-agent systems. *arXiv preprint arXiv:2506.04133*, 2025.

[53] NIST AI. Artificial intelligence risk management framework: Generative artificial intelligence profile. *NIST Trustworthy and Responsible AI Gaithersburg, MD, USA*, 2024.

[54] Jules White, Quchen Fu, Sam Hays, Michael Sandborn, Carlos Olea, Henry Gilbert, Ashraf Elnashar, Jesse Spencer-Smith, and Douglas C Schmidt. A prompt pattern catalog to enhance prompt engineering with chatgpt. *arXiv preprint arXiv:2302.11382*, 2023.

[55] Kai Greshake, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. Not what you've signed up for: Compromising real-world llm-integrated Applications with indirect prompt injection. *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*, 2023. URL `https://api.semanticscholar.org/CorpusID:258546941`.

[56] Fábio Perez and Ian Ribeiro. Ignore previous prompt: Attack techniques for language models. *ArXiv*, abs/2211.09527, 2022. URL `https://api.semanticscholar.org/CorpusID:253581710`.

[57] Luca Beurer-Kellner, Beat Buesser, Ana-Maria Creţu, Edoardo Debenedetti, Daniel Dobos, Daniel Fabian, Marc Fischer, David Froelicher, Kathrin Grosse, Daniel Naeff, et al. Design Patterns for Securing LLM Agents against Prompt Injections. *arXiv preprint arXiv:2506.08837*, 2025.

[58] OWASP GenAI Project. Owasp genai llm01: Prompt injection, 2025.

[59] Jeremy McHugh, Kristina Sekrst, and Jonathan Rodriguez Cefalu. Prompt injection 2.0: Hybrid ai threats. *ArXiv*, abs/2507.13169, 2025. URL `https://api.semanticscholar.org/CorpusID:280296803`.

[60] Yulin Chen, Haoran Li, Yuan Sui, Yufei He, Yue Liu, Yangqiu Song, and Bryan Hooi. Can indirect prompt injection attacks be detected and removed? *arXiv preprint arXiv:2502.16580*, 2025.

[61] Qiusi Zhan, Richard Fang, Henil Shalin Panchal, and Daniel Kang. Adaptive attacks break defenses against indirect prompt injection attacks on llm agents. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 7101–7117, 2025.

[62] Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023. URL `https://arxiv.org/abs/2307.15043`.

[63] Xiaogeng Liu, Zhiyuan Yu, Yizhe Zhang, Ning Zhang, and Chaowei Xiao. Automatic and universal prompt injection attacks against large language models. *arXiv preprint arXiv:2403.04957*, 2024.

[64] Neel Jain, Avi Schwarzschild, Yuxin Wen, Gowthami Somepalli, John Kirchenbauer, Ping-yeh Chiang, Micah Goldblum, Aniruddha Saha, Jonas Geiping, and Tom Goldstein. Baseline defenses for adversarial attacks against aligned language models. *arXiv preprint arXiv:2309.00614*, 2023.

[65] Sicheng Zhu, Ruiyi Zhang, Bang An, Gang Wu, Joe Barrow, Zichao Wang, Furong Huang, Ani Nenkova, and Tong Sun. Autodan: interpretable gradient-based adversarial attacks on large language models. *arXiv preprint arXiv:2310.15140*, 2023.

[66] Zexuan Zhong, Ziqing Huang, Alexander Wettig, and Danqi Chen. Poisoning retrieval corpora by injecting adversarial passages. *arXiv preprint arXiv:2310.19156*, 2023.

[67] Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. Eia: Environmental injection attack on generalist web agents for privacy leakage. *arXiv preprint arXiv:2409.11295*, 2024.

[68] Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. Advagent: Controllable blackbox red-teaming on web agents. *arXiv preprint arXiv:2410.17401*, 2024.

[69] Chen Henry Wu, Rishi Shah, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. Dissecting adversarial robustness of multimodal lm agents. *arXiv preprint arXiv:2406.12814*, 2024.

[70] Kaijie Zhu, Xianjun Yang, Jindong Wang, Wenbo Guo, and William Yang Wang. Melon: Provable defense against indirect prompt injection attacks in ai agents. *arXiv preprint arXiv:2502.05174*, 2025.

[71] Yanzhe Zhang, Tao Yu, and Diyi Yang. Attacking vision-language computer agents via pop-ups. *arXiv preprint arXiv:2411.02391*, 2024.

[72] Sam Johnson, Viet Pham, and Thai Le. Manipulating llm web agents with indirect prompt injection attack via html accessibility tree. *arXiv preprint arXiv:2507.14799*, 2025.

[73] Junhyuk Choi, Yeseon Hong, Minju Kim, and Bugeun Kim. Examining identity drift in conversations of llm agents, 2025. URL `https://arxiv.org/abs/2412.00804`.

[74] Jiawei Guo and Haipeng Cai. System prompt poisoning: Persistent attacks on large language models beyond user injection. *arXiv preprint*, 2025. URL `https://arxiv.org/abs/2505.06493`. Demonstrates how poisoning the system prompt can persistently compromise agent behavior across sessions.

[75] Quan Zhang, Binqi Zeng, Chijin Zhou, Gwihwan Go, Heyuan Shi, and Yu Jiang. Human-imperceptible retrieval poisoning attacks in llm-powered applications. In *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering*, pages 502–506, 2024.

[76] Cody Clop and Yannick Teglia. Backdoored retrievers for prompt injection attacks on retrieval augmented generation of large language models. *arXiv preprint arXiv:2410.14479*, 2024.

[77] Le Wang, Zonghao Ying, Tianyuan Zhang, Siyuan Liang, Shengshan Hu, Mingchuan Zhang, Aishan Liu, and Xianglong Liu. Manipulating multimodal agents via cross-modal prompt injection. *arXiv preprint arXiv:2504.14348*, 2025.

[78] Sean Park. Unveiling ai agent vulnerabilities part ii: Code execution. Trend Micro Research Report, 2025. URL `https://www.trendmicro.com/vinfo/br/security/news/cybercrime-and-digital-threats/unveiling-ai-agent-vulnerabilities-code-execution`. Examines vulnerabilities in LLM-powered agents with code execution, document upload, and internet access.

[79] Eugene Bagdasaryan, Tsung-Yin Hsieh, Ben Nassi, and Vitaly Shmatikov. Abusing images and sounds for indirect instruction injection in multi-modal llms. *arXiv preprint arXiv:2307.10490*, 2023.

[80] Rodrigo Pedro, Daniel Castro, Paulo Carreira, and Nuno Santos. From prompt injections to sql injection attacks: How protected is your llm-integrated web application? *arXiv preprint arXiv:2308.01990*, 2023.

[81] Richard Fang, Rohan Bindu, Akul Gupta, Qiusi Zhan, and Daniel Kang. LLM agents can autonomously hack websites. *arXiv preprint arXiv:2402.06664*, 2024.

[82] Rodrigo Pedro, Miguel E. Coimbra, Daniel Castro, Paulo Carreira, and Nuno Santos. Prompt-to-sql injections in llm-integrated web applications: Risks and defenses. *2025 IEEE/ACM 47th International Conference on Software Engineering (ICSE)*, pages 1768–1780, 2025. URL `https://api.semanticscholar.org/CorpusID:272856332`.

[83] MITRE Corporation. CVE-2024-5565: Vanna.AI Remote Code Execution Vulnerability, 2024. URL `https://cve.org/CVERecord?id=CVE-2024-5565`. CVE Database entry by MITRE Corporation.

[84] Anshuman Chhabra, Kartik Patwari, Chandana Kuntala, Deepak Kumar Sharma, Prasant Mohapatra, et al. Towards fair video summarization. *Transactions on Machine Learning Research*, 2023.

[85] Xingxing Wei, Siyuan Liang, Ning Chen, and Xiaochun Cao. Transferable adversarial attacks for image and video object detection. *arXiv preprint arXiv:1811.12641*, 2018.

[65] Sicheng Zhu, Ruiyi Zhang, Bang An, Gang Wu, Joe Barrow, Zichao Wang, Furong Huang, Ani Nenkova, and Tong Sun. Autodan: interpretable gradient-based adversarial attacks on large language models. *arXiv preprint arXiv:2310.15140*, 2023.

[66] Zexuan Zhong, Ziqing Huang, Alexander Wettig, and Danqi Chen. Poisoning retrieval corpora by injecting adversarial passages. *arXiv preprint arXiv:2310.19156*, 2023.

[67] Zeyi Liao, Lingbo Mo, Chejian Xu, Mintong Kang, Jiawei Zhang, Chaowei Xiao, Yuan Tian, Bo Li, and Huan Sun. Eia: Environmental injection attack on generalist web agents for privacy leakage. *arXiv preprint arXiv:2409.11295*, 2024.

[68] Chejian Xu, Mintong Kang, Jiawei Zhang, Zeyi Liao, Lingbo Mo, Mengqi Yuan, Huan Sun, and Bo Li. Advagent: Controllable blackbox red-teaming on web agents. *arXiv preprint arXiv:2410.17401*, 2024.

[69] Chen Henry Wu, Rishi Shah, Jing Yu Koh, Ruslan Salakhutdinov, Daniel Fried, and Aditi Raghunathan. Dissecting adversarial robustness of multimodal lm agents. *arXiv preprint arXiv:2406.12814*, 2024.

[70] Kaijie Zhu, Xianjun Yang, Jindong Wang, Wenbo Guo, and William Yang Wang. Melon: Provable defense against indirect prompt injection attacks in ai agents. *arXiv preprint arXiv:2502.05174*, 2025.

[71] Yanzhe Zhang, Tao Yu, and Diyi Yang. Attacking vision-language computer agents via pop-ups. *arXiv preprint arXiv:2411.02391*, 2024.

[72] Sam Johnson, Viet Pham, and Thai Le. Manipulating llm web agents with indirect prompt injection attack via html accessibility tree. *arXiv preprint arXiv:2507.14799*, 2025.

[73] Junhyuk Choi, Yeseon Hong, Minju Kim, and Bugeun Kim. Examining identity drift in conversations of llm agents, 2025. URL `https://arxiv.org/abs/2412.00804`.

[74] Jiawei Guo and Haipeng Cai. System prompt poisoning: Persistent attacks on large language models beyond user injection. *arXiv preprint*, 2025. URL `https://arxiv.org/abs/2505.06493`. Demonstrates how poisoning the system prompt can persistently compromise agent behavior across sessions.

[75] Quan Zhang, Binqi Zeng, Chijin Zhou, Gwihwan Go, Heyuan Shi, and Yu Jiang. Human-imperceptible retrieval poisoning attacks in llm-powered applications. In *Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering*, pages 502–506, 2024.

[76] Cody Clop and Yannick Teglia. Backdoored retrievers for prompt injection attacks on retrieval augmented generation of large language models. *arXiv preprint arXiv:2410.14479*, 2024.

[77] Le Wang, Zonghao Ying, Tianyuan Zhang, Siyuan Liang, Shengshan Hu, Mingchuan Zhang, Aishan Liu, and Xianglong Liu. Manipulating multimodal agents via cross-modal prompt injection. *arXiv preprint arXiv:2504.14348*, 2025.

[78] Sean Park. Unveiling ai agent vulnerabilities part ii: Code execution. Trend Micro Research Report, 2025. URL `https://www.trendmicro.com/vinfo/br/security/news/cybercrime-and-digital-threats/unveiling-ai-agent-vulnerabilities-code-execution`. Examines vulnerabilities in LLM-powered agents with code execution, document upload, and internet access.

[79] Eugene Bagdasaryan, Tsung-Yin Hsieh, Ben Nassi, and Vitaly Shmatikov. Abusing images and sounds for indirect instruction injection in multi-modal llms. *arXiv preprint arXiv:2307.10490*, 2023.

[80] Rodrigo Pedro, Daniel Castro, Paulo Carreira, and Nuno Santos. From prompt injections to sql injection attacks: How protected is your llm-integrated web application? *arXiv preprint arXiv:2308.01990*, 2023.

[81] Richard Fang, Rohan Bindu, Akul Gupta, Qiusi Zhan, and Daniel Kang. LLM agents can autonomously hack websites. *arXiv preprint arXiv:2402.06664*, 2024.

[82] Rodrigo Pedro, Miguel E. Coimbra, Daniel Castro, Paulo Carreira, and Nuno Santos. Prompt-to-sql injections in llm-integrated web applications: Risks and defenses. *2025 IEEE/ACM 47th International Conference on Software Engineering (ICSE)*, pages 1768–1780, 2025. URL `https://api.semanticscholar.org/CorpusID:272856332`.

[83] MITRE Corporation. CVE-2024-5565: Vanna.AI Remote Code Execution Vulnerability, 2024. URL `https://cve.org/CVERecord?id=CVE-2024-5565`. CVE Database entry by MITRE Corporation.

[84] Anshuman Chhabra, Kartik Patwari, Chandana Kuntala, Deepak Kumar Sharma, Prasant Mohapatra, et al. Towards fair video summarization. *Transactions on Machine Learning Research*, 2023.

[85] Xingxing Wei, Siyuan Liang, Ning Chen, and Xiaochun Cao. Transferable adversarial attacks for image and video object detection. *arXiv preprint arXiv:1811.12641*, 2018.

[86] Zhipeng Wei, Jingjing Chen, Xingxing Wei, Linxi Jiang, Tat-Seng Chua, Fengfeng Zhou, and Yu-Gang Jiang. Heuristic black-box adversarial attacks on video recognition models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 12338–12345, 2020.

[87] Linxi Jiang, Xingjun Ma, Shaoxiang Chen, James Bailey, and Yu-Gang Jiang. Black-box adversarial attacks on video recognition models. In *Proceedings of the 27th ACM International Conference on Multimedia*, pages 864–872, 2019.

[88] Guangke Chen, Fu Song, Zhe Zhao, Xiaojun Jia, Yang Liu, Yanchen Qiao, and Weizhe Zhang. Audiojailbreak: Jailbreak attacks against end-to-end large audio-language models. *arXiv preprint arXiv:2505.14103*, 2025.

[89] Eugene Bagdasaryan, Rishi Jha, Vitaly Shmatikov, and Tingwei Zhang. Adversarial illusions in multi-modal embeddings. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 3009–3025, 2024.

[90] Lukas Aichberger, Alasdair Paren, Yarin Gal, Philip Torr, and Adel Bibi. Attacking multimodal os agents with malicious image patches, 2025. URL `https://arxiv.org/abs/2503.10809`.

[91] Cristian Pinzon, Juan F. De Paz, Javier Bajo, Alvaro Herrero, and Emilio Corchado. Aiida-sql: An adaptive intelligent intrusion detector agent for detecting sql injection attacks. In *2010 10th International Conference on Hybrid Intelligent Systems*, pages 73–78, 2010. doi:10.1109/HIS.2010.5600026.

[92] Johann Rehberger. Deepseek ai: From prompt injection to account takeover, 2024. URL `https://embracethered.com/blog/posts/2024/deepseek-ai-prompt-injection-to-xss-and-account-takeover/`. Embrace The Red blog.

[93] Sander Schulhoff, Jeremy Pinto, Anaum Khan, L-F Bouchard, Chenglei Si, Svetlina Anati, Valen Tagliabue, Anson Liu Kost, Christopher Carnahan, and Jordan Boyd-Graber. Ignore this title and hackaprompt: Exposing systemic vulnerabilities of llms through a global scale prompt hacking competition. In *The 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics (ACL), 2023.

[94] Stav Cohen, Ron Bitton, and Ben Nassi. Here comes the ai worm: Unleashing zero-click worms that target genai-powered applications. *arXiv preprint arXiv:2403.02817*, 2024.

[95] Diego Gosmar, Deborah A Dahl, and Dario Gosmar. Prompt injection detection and mitigation via ai multi-agent nlp frameworks. *arXiv preprint arXiv:2503.11517*, 2025.

[96] Sippo Rossi, Alisia Marianne Michel, Raghava Rao Mukkamala, and Jason Bennett Thatcher. An early categorization of prompt injection attacks on large language models, 2024. URL `https://arxiv.org/abs/2402.00898`.

[97] U.S. AI Safety Institute. Technical blog: Strengthening ai agent hijacking evaluations. `https://www.nist.gov/news-events/news/2025/01/technical-blog-strengthening-ai-agent-hijacking-evaluations`, January 2025. Accessed: January 29, 2025.

[98] Richard Fang, Rohan Bindu, Akul Gupta, and Daniel Kang. Llm agents can autonomously exploit one-day vulnerabilities. *arXiv preprint arXiv:2404.08144*, 2024.

[99] Simon Bennetts. Owasp zed attack proxy. *AppSec USA*, 2013.

[100] David Kennedy, Jim O'gorman, Devon Kearns, and Mati Aharoni. *Metasploit: the penetration tester's guide*. No Starch Press, 2011.

[101] Nathalie Muehlberger. Csrf and xss: Practical examples using burp suite. Seminararbeit, Ausgewählte Kapitel der IT-Security, 2020. URL `https://wiki.elvis.science/images/b/b3/Thesis.pdf`. Accessed: 2026-02-05.

[102] Rushi Mamtora, DP Sharma, and Jatin Patel. Server-side template injection with custom exploit. *International Journal of Scientific Research in Science, Engineering and Technology*, 2021.

[103] Jean Rosemond Dora, Ladislav Hluchỳ, and Karol Nemoga. Ontology for blind sql injection. *Computing and Informatics*, 42(2):480–500, 2023.

[104] Zhengliang Shi, Shen Gao, Xiuyi Chen, Yue Feng, Lingyong Yan, Haibo Shi, Dawei Yin, Pengjie Ren, Suzan Verberne, and Zhaochun Ren. Learning to use tools via cooperative and interactive agents. *arXiv preprint arXiv:2403.03031*, 2024.

[105] Renxi Wang, Xudong Han, Lei Ji, Shu Wang, Timothy Baldwin, and Haonan Li. Toolgen: Unified tool retrieval and calling via generation. *arXiv preprint arXiv:2410.03439*, 2024.

[106] Ronny Ko, Jiseong Jeong, Shuyuan Zheng, Chuan Xiao, Tae-Wan Kim, Makoto Onizuka, and Won-Yong Shin. Seven security challenges that must be solved in cross-domain multi-agent llm systems. *arXiv preprint arXiv:2505.23847*, 2025.

[86] Zhipeng Wei, Jingjing Chen, Xingxing Wei, Linxi Jiang, Tat-Seng Chua, Fengfeng Zhou, and Yu-Gang Jiang. Heuristic black-box adversarial attacks on video recognition models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 12338–12345, 2020.

[87] Linxi Jiang, Xingjun Ma, Shaoxiang Chen, James Bailey, and Yu-Gang Jiang. Black-box adversarial attacks on video recognition models. In *Proceedings of the 27th ACM International Conference on Multimedia*, pages 864–872, 2019.

[88] Guangke Chen, Fu Song, Zhe Zhao, Xiaojun Jia, Yang Liu, Yanchen Qiao, and Weizhe Zhang. Audiojailbreak: Jailbreak attacks against end-to-end large audio-language models. *arXiv preprint arXiv:2505.14103*, 2025.

[89] Eugene Bagdasaryan, Rishi Jha, Vitaly Shmatikov, and Tingwei Zhang. Adversarial illusions in multi-modal embeddings. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 3009–3025, 2024.

[90] Lukas Aichberger, Alasdair Paren, Yarin Gal, Philip Torr, and Adel Bibi. Attacking multimodal os agents with malicious image patches, 2025. URL `https://arxiv.org/abs/2503.10809`.

[91] Cristian Pinzon, Juan F. De Paz, Javier Bajo, Alvaro Herrero, and Emilio Corchado. Aiida-sql: An adaptive intelligent intrusion detector agent for detecting sql injection attacks. In *2010 10th International Conference on Hybrid Intelligent Systems*, pages 73–78, 2010. doi:10.1109/HIS.2010.5600026.

[92] Johann Rehberger. Deepseek ai: From prompt injection to account takeover, 2024. URL `https://embracethered.com/blog/posts/2024/deepseek-ai-prompt-injection-to-xss-and-account-takeover/`. Embrace The Red blog.

[93] Sander Schulhoff, Jeremy Pinto, Anaum Khan, L-F Bouchard, Chenglei Si, Svetlina Anati, Valen Tagliabue, Anson Liu Kost, Christopher Carnahan, and Jordan Boyd-Graber. Ignore this title and hackaprompt: Exposing systemic vulnerabilities of llms through a global scale prompt hacking competition. In *The 2023 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics (ACL), 2023.

[94] Stav Cohen, Ron Bitton, and Ben Nassi. Here comes the ai worm: Unleashing zero-click worms that target genai-powered applications. *arXiv preprint arXiv:2403.02817*, 2024.

[95] Diego Gosmar, Deborah A Dahl, and Dario Gosmar. Prompt injection detection and mitigation via ai multi-agent nlp frameworks. *arXiv preprint arXiv:2503.11517*, 2025.

[96] Sippo Rossi, Alisia Marianne Michel, Raghava Rao Mukkamala, and Jason Bennett Thatcher. An early categorization of prompt injection attacks on large language models, 2024. URL `https://arxiv.org/abs/2402.00898`.

[97] U.S. AI Safety Institute. Technical blog: Strengthening ai agent hijacking evaluations. `https://www.nist.gov/news-events/news/2025/01/technical-blog-strengthening-ai-agent-hijacking-evaluations`, January 2025. Accessed: January 29, 2025.

[98] Richard Fang, Rohan Bindu, Akul Gupta, and Daniel Kang. Llm agents can autonomously exploit one-day vulnerabilities. *arXiv preprint arXiv:2404.08144*, 2024.

[99] Simon Bennetts. Owasp zed attack proxy. *AppSec USA*, 2013.

[100] David Kennedy, Jim O'gorman, Devon Kearns, and Mati Aharoni. *Metasploit: the penetration tester's guide*. No Starch Press, 2011.

[101] Nathalie Muehlberger. Csrf and xss: Practical examples using burp suite. Seminararbeit, Ausgewählte Kapitel der IT-Security, 2020. URL `https://wiki.elvis.science/images/b/b3/Thesis.pdf`. Accessed: 2026-02-05.

[102] Rushi Mamtora, DP Sharma, and Jatin Patel. Server-side template injection with custom exploit. *International Journal of Scientific Research in Science, Engineering and Technology*, 2021.

[103] Jean Rosemond Dora, Ladislav Hluchỳ, and Karol Nemoga. Ontology for blind sql injection. *Computing and Informatics*, 42(2):480–500, 2023.

[104] Zhengliang Shi, Shen Gao, Xiuyi Chen, Yue Feng, Lingyong Yan, Haibo Shi, Dawei Yin, Pengjie Ren, Suzan Verberne, and Zhaochun Ren. Learning to use tools via cooperative and interactive agents. *arXiv preprint arXiv:2403.03031*, 2024.

[105] Renxi Wang, Xudong Han, Lei Ji, Shu Wang, Timothy Baldwin, and Haonan Li. Toolgen: Unified tool retrieval and calling via generation. *arXiv preprint arXiv:2410.03439*, 2024.

[106] Ronny Ko, Jiseong Jeong, Shuyuan Zheng, Chuan Xiao, Tae-Wan Kim, Makoto Onizuka, and Won-Yong Shin. Seven security challenges that must be solved in cross-domain multi-agent llm systems. *arXiv preprint arXiv:2505.23847*, 2025.

[107] Mohamed Amine Ferrag, Norbert Tihanyi, Djallel Hamouda, Leandros Maglaras, and Merouane Debbah. From prompt injections to protocol exploits: Threats in llm-powered ai agents workflows. *arXiv preprint arXiv:2506.23260*, 2025.

[108] Introduction to mcp, 2025. URL https://modelcontextprotocol.io/introduction. Accessed: 2025-06-04.

[109] Rao Surapaneni, Miku Jha, Michael Vakoc, and Todd Segal. A2a: A new era of agent interoperability, April 2025. URL https://developers.googleblog.com/en/a2a-a-new-era-of-agent-interoperability/. Accessed: 2025-06-04.

[110] Gaowei Chang. Agentnetworkprotocol (anp) github repository. https://github.com/agent-network-protocol/AgentNetworkProtocol, 2024. Accessed: 2025-06-04.

[111] Agent communication protocol: Welcome, 2024. URL https://agentcommunicationprotocol.dev/introduction/welcome. Accessed: 2025-06-04.

[112] Saman Taghavi Zargar, James Joshi, and David Tipper. A survey of defense mechanisms against distributed denial of service (ddos) flooding attacks. *IEEE communications surveys & tutorials*, 15(4):2046–2069, 2013.

[113] Shaofeng Li, Hui Liu, Tian Dong, Benjamin Zi Hao Zhao, Minhui Xue, Haojin Zhu, and Jialiang Lu. Hidden backdoors in human-centric language models. In *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, pages 3123–3140, 2021.

[114] Wei Zou, Runpeng Geng, Binghui Wang, and Jinyuan Jia. Poisonedrag: Knowledge poisoning attacks to retrieval-augmented generation of large language models. *ArXiv*, abs/2402.07867, 2024. URL https://api.semanticscholar.org/CorpusID:267626957.

[115] Vale Tolpegin, Stacey Truex, Mehmet Emre Gursoy, and Ling Liu. Data poisoning attacks against federated learning systems. In *European symposium on research in computer security*, pages 480–501. Springer, 2020.

[116] Shubhi Shukla, Manaar Alam, Sarani Bhattacharya, Pabitra Mitra, and Debdeep Mukhopadhyay. "whispering mlaas": Exploiting timing channels to compromise user privacy in deep neural networks. *IACR Transactions on Cryptographic Hardware and Embedded Systems*, pages 587–613, 2023.

[117] Edoardo Debenedetti, Giorgio Severi, Nicholas Carlini, Christopher A Choquette-Choo, Matthew Jagielski, Milad Nasr, Eric Wallace, and Florian Tramèr. Privacy side channels in machine learning systems. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 6861–6848, 2024.

[118] Venkatraman Renganathan and Tyler Holt Summers. Spoof resilient coordination for distributed multi-robot systems. *2017 International Symposium on Multi-Robot and Multi-Agent Systems (MRS)*, pages 135–141, 2017. URL https://api.semanticscholar.org/CorpusID:7897062.

[119] Richard M. Chang, Guofei Jiang, Franjo Ivancic, Sriram Sankaranarayanan, and Vitaly Shmatikov. Inputs of coma: Static detection of denial-of-service vulnerabilities. *2009 22nd IEEE Computer Security Foundations Symposium*, pages 186–199, 2009. URL https://api.semanticscholar.org/CorpusID:6355518.

[120] Shiyi Yang, Zhibo Hu, Xinshu Li, Chen Wang, Tong Yu, Xiwei Xu, Liming Zhu, and Lina Yao. Drunkagent: Stealthy memory corruption in llm-powered recommender agents. *arXiv preprint arXiv:2503.23804*, 2025.

[121] Sumeet Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among ai agents: Multi-agent deception via steganography. *Advances in Neural Information Processing Systems*, 37:73439–73486, 2024.

[122] Rana Shahroz, Zhen Tan, Sukwon Yun, Charles Fleming, and Tianlong Chen. Agents under siege: Breaking pragmatic multi-agent llm systems with optimized prompt attacks. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9661–9674, 2025.

[123] Yang Li, Wenhao Zhang, Jianhong Wang, Shao Zhang, Yali Du, Ying Wen, and Wei Pan. Aligning individual and collective objectives in multi-agent cooperation. *Advances in Neural Information Processing Systems*, 37: 44735–44760, 2024.

[124] Bei Chen, Gaolei Li, Xi Lin, Zheng Wang, and Jianhua Li. Blockagents: Towards byzantine-robust llm-based multi-agent coordination via blockchain. In *Proceedings of the ACM Turing Award Celebration Conference-China 2024*, pages 187–192, 2024.

[125] Zijun Liu, Yanzhe Zhang, Peng Li, Yang Liu, and Diyi Yang. A dynamic llm-powered agent network for task-oriented agent collaboration. In *First Conference on Language Modeling*, 2024.

[126] Jun Yan, Vikas Yadav, Shiyang Li, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hongxia Jin. Backdooring instruction-tuned large language models with virtual prompt injection. *arXiv preprint arXiv:2307.16888*, 2023.

[107] Mohamed Amine Ferrag, Norbert Tihanyi, Djallel Hamouda, Leandros Maglaras, and Merouane Debbah. From prompt injections to protocol exploits: Threats in llm-powered ai agents workflows. *arXiv preprint arXiv:2506.23260*, 2025.

[108] Introduction to mcp, 2025. URL https://modelcontextprotocol.io/introduction. Accessed: 2025-06-04.

[109] Rao Surapaneni, Miku Jha, Michael Vakoc, and Todd Segal. A2a: A new era of agent interoperability, April 2025. URL https://developers.googleblog.com/en/a2a-a-new-era-of-agent-interoperability/. Accessed: 2025-06-04.

[110] Gaowei Chang. Agentnetworkprotocol (anp) github repository. https://github.com/agent-network-protocol/AgentNetworkProtocol, 2024. Accessed: 2025-06-04.

[111] Agent communication protocol: Welcome, 2024. URL https://agentcommunicationprotocol.dev/introduction/welcome. Accessed: 2025-06-04.

[112] Saman Taghavi Zargar, James Joshi, and David Tipper. A survey of defense mechanisms against distributed denial of service (ddos) flooding attacks. *IEEE communications surveys & tutorials*, 15(4):2046–2069, 2013.

[113] Shaofeng Li, Hui Liu, Tian Dong, Benjamin Zi Hao Zhao, Minhui Xue, Haojin Zhu, and Jialiang Lu. Hidden backdoors in human-centric language models. In *Proceedings of the 2021 ACM SIGSAC Conference on Computer and Communications Security*, pages 3123–3140, 2021.

[114] Wei Zou, Runpeng Geng, Binghui Wang, and Jinyuan Jia. Poisonedrag: Knowledge poisoning attacks to retrieval-augmented generation of large language models. *ArXiv*, abs/2402.07867, 2024. URL https://api.semanticscholar.org/CorpusID:267626957.

[115] Vale Tolpegin, Stacey Truex, Mehmet Emre Gursoy, and Ling Liu. Data poisoning attacks against federated learning systems. In *European symposium on research in computer security*, pages 480–501. Springer, 2020.

[116] Shubhi Shukla, Manaar Alam, Sarani Bhattacharya, Pabitra Mitra, and Debdeep Mukhopadhyay. "whispering mlaas": Exploiting timing channels to compromise user privacy in deep neural networks. *IACR Transactions on Cryptographic Hardware and Embedded Systems*, pages 587–613, 2023.

[117] Edoardo Debenedetti, Giorgio Severi, Nicholas Carlini, Christopher A Choquette-Choo, Matthew Jagielski, Milad Nasr, Eric Wallace, and Florian Tramèr. Privacy side channels in machine learning systems. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 6861–6848, 2024.

[118] Venkatraman Renganathan and Tyler Holt Summers. Spoof resilient coordination for distributed multi-robot systems. *2017 International Symposium on Multi-Robot and Multi-Agent Systems (MRS)*, pages 135–141, 2017. URL https://api.semanticscholar.org/CorpusID:7897062.

[119] Richard M. Chang, Guofei Jiang, Franjo Ivancic, Sriram Sankaranarayanan, and Vitaly Shmatikov. Inputs of coma: Static detection of denial-of-service vulnerabilities. *2009 22nd IEEE Computer Security Foundations Symposium*, pages 186–199, 2009. URL https://api.semanticscholar.org/CorpusID:6355518.

[120] Shiyi Yang, Zhibo Hu, Xinshu Li, Chen Wang, Tong Yu, Xiwei Xu, Liming Zhu, and Lina Yao. Drunkagent: Stealthy memory corruption in llm-powered recommender agents. *arXiv preprint arXiv:2503.23804*, 2025.

[121] Sumeet Motwani, Mikhail Baranchuk, Martin Strohmeier, Vijay Bolina, Philip Torr, Lewis Hammond, and Christian Schroeder de Witt. Secret collusion among ai agents: Multi-agent deception via steganography. *Advances in Neural Information Processing Systems*, 37:73439–73486, 2024.

[122] Rana Shahroz, Zhen Tan, Sukwon Yun, Charles Fleming, and Tianlong Chen. Agents under siege: Breaking pragmatic multi-agent llm systems with optimized prompt attacks. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 9661–9674, 2025.

[123] Yang Li, Wenhao Zhang, Jianhong Wang, Shao Zhang, Yali Du, Ying Wen, and Wei Pan. Aligning individual and collective objectives in multi-agent cooperation. *Advances in Neural Information Processing Systems*, 37: 44735–44760, 2024.

[124] Bei Chen, Gaolei Li, Xi Lin, Zheng Wang, and Jianhua Li. Blockagents: Towards byzantine-robust llm-based multi-agent coordination via blockchain. In *Proceedings of the ACM Turing Award Celebration Conference-China 2024*, pages 187–192, 2024.

[125] Zijun Liu, Yanzhe Zhang, Peng Li, Yang Liu, and Diyi Yang. A dynamic llm-powered agent network for task-oriented agent collaboration. In *First Conference on Language Modeling*, 2024.

[126] Jun Yan, Vikas Yadav, Shiyang Li, Lichang Chen, Zheng Tang, Hai Wang, Vijay Srinivasan, Xiang Ren, and Hongxia Jin. Backdooring instruction-tuned large language models with virtual prompt injection. *arXiv preprint arXiv:2307.16888*, 2023.

[127] Jinyuan Jia, Yupei Liu, and Neil Zhenqiang Gong. Badencoder: Backdoor attacks to pre-trained encoders in self-supervised learning. In *2022 IEEE Symposium on Security and Privacy (SP)*, pages 2043–2059. IEEE, 2022.

[128] Rui Zeng, Xi Chen, Yuwen Pu, Xuhong Zhang, Tianyu Du, and Shouling Ji. Clibe: detecting dynamic backdoors in transformer-based nlp models. *arXiv preprint arXiv:2409.01193*, 2024.

[129] JFrog Security Research Team. Jfrog and hugging face join forces to expose malicious ml models, March 2025. URL `https://jfrog.com/community/ai/jfrog-and-hugging-face-join-forces-to-expose-malicious-ml-models/`. Accessed: 2025-06-04.

[130] Wei Duan, Jie Lu, and Junyu Xuan. Group-aware coordination graph for multi-agent reinforcement learning. *arXiv preprint arXiv:2404.10976*, 2024.

[131] Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, et al. Why do multi-agent llm systems fail? *arXiv preprint arXiv:2503.13657*, 2025.

[132] Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, et al. Autogen: Enabling next-gen llm applications via multi-agent conversations. In *First Conference on Language Modeling*, 2024.

[133] Xuezhou Zhang, Yuzhe Ma, Adish Singla, and Xiaojin Zhu. Adaptive reward-poisoning attacks against reinforcement learning. In *International Conference on Machine Learning*, pages 11225–11234. PMLR, 2020.

[134] David F Ferraiolo, Ravi Sandhu, Serban Gavrila, D Richard Kuhn, and Ramaswamy Chandramouli. Proposed nist standard for role-based access control. *ACM Transactions on Information and System Security (TISSEC)*, 4 (3):224–274, 2001.

[135] Boyi Zeng, Lizheng Wang, Yuncong Hu, Yi Xu, Chenghu Zhou, Xinbing Wang, Yu Yu, and Zhouhan Lin. Huref: Human-readable fingerprint for large language models. *Advances in Neural Information Processing Systems*, 37: 126332–126362, 2024.

[136] Timour Igamberdiev, Thomas Arnold, and Ivan Habernal. Dp-rewrite: Towards reproducibility and transparency in differentially private text rewriting. *arXiv preprint arXiv:2208.10400*, 2022.

[137] Weiyan Shi, Ryan Shea, Si Chen, Chiyuan Zhang, Ruoxi Jia, and Zhou Yu. Just fine-tune twice: Selective differential privacy for large language models. *arXiv preprint arXiv:2204.07667*, 2022.

[138] Jie Huang, Hanyin Shao, and Kevin Chen-Chuan Chang. Are large pre-trained language models leaking your personal information? *arXiv preprint arXiv:2205.12628*, 2022.

[139] Feng He, Tianqing Zhu, Dayong Ye, Bo Liu, Wanlei Zhou, and Philip S Yu. The emerged security and privacy of llm agent: A survey with case studies. *arXiv preprint arXiv:2407.19354*, 2024.

[140] William Enck, Peter Gilbert, Seungyeop Han, Vasant Tendulkar, Byung-Gon Chun, Landon P Cox, Jaeyeon Jung, Patrick McDaniel, and Anmol N Sheth. Taintdroid: an information-flow tracking system for realtime privacy monitoring on smartphones. *ACM Transactions on Computer Systems (TOCS)*, 32(2):1–29, 2014.

[141] Shoaib Ahmed Siddiqui, Radhika Gaonkar, Boris Köpf, David Krueger, Andrew Paverd, Ahmed Salem, Shruti Tople, Lukas Wutschitz, Menglin Xia, and Santiago Zanella-Béguelin. Permissive information-flow analysis for large language models. *arXiv preprint arXiv:2410.03055*, 2024.

[142] Pierre Peigné, Mikolaj Kniejski, Filip Sondej, Matthieu David, Jason Hoelscher-Obermaier, Christian Schroeder de Witt, and Esben Kran. Multi-agent security tax: Trading off security and collaboration capabilities in multi-agent systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 27573–27581, 2025.

[143] Satbir Singh. Llm-based agents: The benefits and the risks. `https://www.enkryptai.com/blog/llmâĂŚagentsâĂŚbenefitsâĂŚrisks`, February 2025. Accessed: 2025-08-21.

[144] Christian Schroeder de Witt. Open challenges in multi-agent security: Towards secure systems of interacting ai agents. *arXiv preprint arXiv:2505.02077*, 2025.

[145] Anshuman Chhabra, Peizhao Li, Prasant Mohapatra, and Hongfu Liu. " what data benefits my classifier?" enhancing model performance and interpretability through influence-based data selection. In *ICLR*, 2024.

[146] Anshuman Chhabra, Bo Li, Jian Chen, Prasant Mohapatra, and Hongfu Liu. Outlier gradient analysis: Efficiently identifying detrimental training samples for deep learning models. In *ICML*, 2025.

[147] Sahar Abdelnabi, Aideen Fay, Giovanni Cherubin, Ahmed Salem, Mario Fritz, and Andrew Paverd. Get my drift? catching llm task drift with activation deltas. *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pages 43–67, 2024. URL `https://api.semanticscholar.org/CorpusID:270211056`.

[127] Jinyuan Jia, Yupei Liu, and Neil Zhenqiang Gong. Badencoder: Backdoor attacks to pre-trained encoders in self-supervised learning. In *2022 IEEE Symposium on Security and Privacy (SP)*, pages 2043–2059. IEEE, 2022.

[128] Rui Zeng, Xi Chen, Yuwen Pu, Xuhong Zhang, Tianyu Du, and Shouling Ji. Clibe: detecting dynamic backdoors in transformer-based nlp models. *arXiv preprint arXiv:2409.01193*, 2024.

[129] JFrog Security Research Team. Jfrog and hugging face join forces to expose malicious ml models, March 2025. URL `https://jfrog.com/community/ai/jfrog-and-hugging-face-join-forces-to-expose-malicious-ml-models/`. Accessed: 2025-06-04.

[130] Wei Duan, Jie Lu, and Junyu Xuan. Group-aware coordination graph for multi-agent reinforcement learning. *arXiv preprint arXiv:2404.10976*, 2024.

[131] Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, et al. Why do multi-agent llm systems fail? *arXiv preprint arXiv:2503.13657*, 2025.

[132] Qingyun Wu, Gagan Bansal, Jieyu Zhang, Yiran Wu, Beibin Li, Erkang Zhu, Li Jiang, Xiaoyun Zhang, Shaokun Zhang, Jiale Liu, et al. Autogen: Enabling next-gen llm applications via multi-agent conversations. In *First Conference on Language Modeling*, 2024.

[133] Xuezhou Zhang, Yuzhe Ma, Adish Singla, and Xiaojin Zhu. Adaptive reward-poisoning attacks against reinforcement learning. In *International Conference on Machine Learning*, pages 11225–11234. PMLR, 2020.

[134] David F Ferraiolo, Ravi Sandhu, Serban Gavrila, D Richard Kuhn, and Ramaswamy Chandramouli. Proposed nist standard for role-based access control. *ACM Transactions on Information and System Security (TISSEC)*, 4 (3):224–274, 2001.

[135] Boyi Zeng, Lizheng Wang, Yuncong Hu, Yi Xu, Chenghu Zhou, Xinbing Wang, Yu Yu, and Zhouhan Lin. Huref: Human-readable fingerprint for large language models. *Advances in Neural Information Processing Systems*, 37: 126332–126362, 2024.

[136] Timour Igamberdiev, Thomas Arnold, and Ivan Habernal. Dp-rewrite: Towards reproducibility and transparency in differentially private text rewriting. *arXiv preprint arXiv:2208.10400*, 2022.

[137] Weiyan Shi, Ryan Shea, Si Chen, Chiyuan Zhang, Ruoxi Jia, and Zhou Yu. Just fine-tune twice: Selective differential privacy for large language models. *arXiv preprint arXiv:2204.07667*, 2022.

[138] Jie Huang, Hanyin Shao, and Kevin Chen-Chuan Chang. Are large pre-trained language models leaking your personal information? *arXiv preprint arXiv:2205.12628*, 2022.

[139] Feng He, Tianqing Zhu, Dayong Ye, Bo Liu, Wanlei Zhou, and Philip S Yu. The emerged security and privacy of llm agent: A survey with case studies. *arXiv preprint arXiv:2407.19354*, 2024.

[140] William Enck, Peter Gilbert, Seungyeop Han, Vasant Tendulkar, Byung-Gon Chun, Landon P Cox, Jaeyeon Jung, Patrick McDaniel, and Anmol N Sheth. Taintdroid: an information-flow tracking system for realtime privacy monitoring on smartphones. *ACM Transactions on Computer Systems (TOCS)*, 32(2):1–29, 2014.

[141] Shoaib Ahmed Siddiqui, Radhika Gaonkar, Boris Köpf, David Krueger, Andrew Paverd, Ahmed Salem, Shruti Tople, Lukas Wutschitz, Menglin Xia, and Santiago Zanella-Béguelin. Permissive information-flow analysis for large language models. *arXiv preprint arXiv:2410.03055*, 2024.

[142] Pierre Peigné, Mikolaj Kniejski, Filip Sondej, Matthieu David, Jason Hoelscher-Obermaier, Christian Schroeder de Witt, and Esben Kran. Multi-agent security tax: Trading off security and collaboration capabilities in multi-agent systems. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pages 27573–27581, 2025.

[143] Satbir Singh. Llm-based agents: The benefits and the risks. `https://www.enkryptai.com/blog/llmâĂŚagentsâĂŚbenefitsâĂŚrisks`, February 2025. Accessed: 2025-08-21.

[144] Christian Schroeder de Witt. Open challenges in multi-agent security: Towards secure systems of interacting ai agents. *arXiv preprint arXiv:2505.02077*, 2025.

[145] Anshuman Chhabra, Peizhao Li, Prasant Mohapatra, and Hongfu Liu. " what data benefits my classifier?" enhancing model performance and interpretability through influence-based data selection. In *ICLR*, 2024.

[146] Anshuman Chhabra, Bo Li, Jian Chen, Prasant Mohapatra, and Hongfu Liu. Outlier gradient analysis: Efficiently identifying detrimental training samples for deep learning models. In *ICML*, 2025.

[147] Sahar Abdelnabi, Aideen Fay, Giovanni Cherubin, Ahmed Salem, Mario Fritz, and Andrew Paverd. Get my drift? catching llm task drift with activation deltas. *2025 IEEE Conference on Secure and Trustworthy Machine Learning (SaTML)*, pages 43–67, 2024. URL `https://api.semanticscholar.org/CorpusID:270211056`.

[148] Dami Choi, Yonadav Shavit, and David K Duvenaud. Tools for verifying neural models' training data. *Advances in Neural Information Processing Systems*, 36:1154–1188, 2023.

[149] Dan Petrovic. Advanced interpretability techniques for tracing llm activations. `https://dejan.ai/blog/advanced-interpretability-techniques-for-tracing-llm-activations/`, March 2025. Accessed: 2025-08-21.

[150] Tom Sander, Pierre Fernandez, Alain Durmus, Matthijs Douze, and Teddy Furon. Watermarking makes language models radioactive. *Advances in Neural Information Processing Systems*, 37:21079–21113, 2024.

[151] Meng Hao, Hongwei Li, Hanxiao Chen, Pengzhi Xing, Guowen Xu, and Tianwei Zhang. Iron: Private inference on transformers. *Advances in neural information processing systems*, 35:15718–15731, 2022.

[152] Georgios A Kaissis, Marcus R Makowski, Daniel Rückert, and Rickmer F Braren. Secure, privacy-preserving and federated machine learning in medical imaging. *Nature Machine Intelligence*, 2(6):305–311, 2020.

[153] Francis Dutil, Alexandre See, Lisa Di Jorio, and Florent Chandelier. Application of homomorphic encryption in medical imaging. *arXiv preprint arXiv:2110.07768*, 2021.

[154] Harshal Tupsamudre, Arun Kumar, Vikas Agarwal, Nisha Gupta, and Sneha Mondal. Ai-assisted controls change management for cybersecurity in the cloud. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 12629–12635, 2022.

[155] Leo de Castro, Antigoni Polychroniadou, and Daniel Escudero. Privacy-preserving large language model inference via gpu-accelerated fully homomorphic encryption. In *Neurips Safe Generative AI Workshop 2024*, 2024.

[156] Deevashwer Rathee, Dacheng Li, Ion Stoica, Hao Zhang, and Raluca Popa. Mpc-minimized secure llm inference. *arXiv preprint arXiv:2408.03561*, 2024.

[157] Tao Lu, Haoyu Wang, Wenjie Qu, Zonghui Wang, Jinye He, Tianyang Tao, Wenzhi Chen, and Jiaheng Zhang. An efficient and extensible zero-knowledge proof framework for neural networks. *Cryptology ePrint Archive*, 2024.

[158] Yurun Chen, Xavier Hu, Keting Yin, Juncheng Li, and Shengyu Zhang. Evaluating the robustness of multimodal agents against active environmental injection attacks. *arXiv preprint arXiv:2502.13053*, 2025.

[159] Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, et al. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.

[160] De Chezelles, Thibault Le Sellier, Sahar Omidi Shayegan, Lawrence Keunho Jang, Xing Han Lù, Ori Yoran, Dehan Kong, Frank F Xu, Siva Reddy, Quentin Cappart, et al. The browsergym ecosystem for web agent research. *arXiv preprint arXiv:2412.05467*, 2024.

[161] Ke Yang, Yao Liu, Sapana Chaudhary, Rasool Fakoor, Pratik Chaudhari, George Karypis, and Huzefa Rangwala. Agentoccam: A simple yet strong baseline for llm-based web agents. *arXiv preprint arXiv:2410.13825*, 2024.

[162] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

[163] Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samuel Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2web: Towards a generalist agent for the web, 2023. URL `https://arxiv.org/abs/2306.06070`.

[164] Yaxin Luo, Zhaoyi Li, Jiacheng Liu, Jiacheng Cui, Xiaohan Zhao, and Zhiqiang Shen. Open captchaworld: A comprehensive web-based platform for testing and benchmarking multimodal llm agents. *arXiv preprint arXiv:2505.24878*, 2025.

[165] Alan Chan, Rebecca Salganik, Alva Markelius, Chris Pang, Nitarshan Rajkumar, Dmitrii Krasheninnikov, Lauro Langosco, Zhonghao He, Yawen Duan, Micah Carroll, et al. Harms from increasingly agentic algorithmic systems. In *Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency*, pages 651–666, 2023.

[166] Margaret Mitchell, Avijit Ghosh, Alexandra Sasha Luccioni, and Giada Pistilli. Fully autonomous ai agents should not be developed. *arXiv preprint arXiv:2502.02649*, 2025.

[167] Maryanne Garry, Way Ming Chan, Jeffrey Foster, and Linda A Henkel. Large language models (llms) and the institutionalization of misinformation. *Trends in cognitive sciences*, 2024.

[148] Dami Choi, Yonadav Shavit, and David K Duvenaud. Tools for verifying neural models' training data. *Advances in Neural Information Processing Systems*, 36:1154–1188, 2023.

[149] Dan Petrovic. Advanced interpretability techniques for tracing llm activations. `https://dejan.ai/blog/advanced-interpretability-techniques-for-tracing-llm-activations/`, March 2025. Accessed: 2025-08-21.

[150] Tom Sander, Pierre Fernandez, Alain Durmus, Matthijs Douze, and Teddy Furon. Watermarking makes language models radioactive. *Advances in Neural Information Processing Systems*, 37:21079–21113, 2024.

[151] Meng Hao, Hongwei Li, Hanxiao Chen, Pengzhi Xing, Guowen Xu, and Tianwei Zhang. Iron: Private inference on transformers. *Advances in neural information processing systems*, 35:15718–15731, 2022.

[152] Georgios A Kaissis, Marcus R Makowski, Daniel Rückert, and Rickmer F Braren. Secure, privacy-preserving and federated machine learning in medical imaging. *Nature Machine Intelligence*, 2(6):305–311, 2020.

[153] Francis Dutil, Alexandre See, Lisa Di Jorio, and Florent Chandelier. Application of homomorphic encryption in medical imaging. *arXiv preprint arXiv:2110.07768*, 2021.

[154] Harshal Tupsamudre, Arun Kumar, Vikas Agarwal, Nisha Gupta, and Sneha Mondal. Ai-assisted controls change management for cybersecurity in the cloud. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 36, pages 12629–12635, 2022.

[155] Leo de Castro, Antigoni Polychroniadou, and Daniel Escudero. Privacy-preserving large language model inference via gpu-accelerated fully homomorphic encryption. In *Neurips Safe Generative AI Workshop 2024*, 2024.

[156] Deevashwer Rathee, Dacheng Li, Ion Stoica, Hao Zhang, and Raluca Popa. Mpc-minimized secure llm inference. *arXiv preprint arXiv:2408.03561*, 2024.

[157] Tao Lu, Haoyu Wang, Wenjie Qu, Zonghui Wang, Jinye He, Tianyang Tao, Wenzhi Chen, and Jiaheng Zhang. An efficient and extensible zero-knowledge proof framework for neural networks. *Cryptology ePrint Archive*, 2024.

[158] Yurun Chen, Xavier Hu, Keting Yin, Juncheng Li, and Shengyu Zhang. Evaluating the robustness of multimodal agents against active environmental injection attacks. *arXiv preprint arXiv:2502.13053*, 2025.

[159] Shuyan Zhou, Frank F Xu, Hao Zhu, Xuhui Zhou, Robert Lo, Abishek Sridhar, Xianyi Cheng, Tianyue Ou, Yonatan Bisk, Daniel Fried, et al. Webarena: A realistic web environment for building autonomous agents. *arXiv preprint arXiv:2307.13854*, 2023.

[160] De Chezelles, Thibault Le Sellier, Sahar Omidi Shayegan, Lawrence Keunho Jang, Xing Han Lù, Ori Yoran, Dehan Kong, Frank F Xu, Siva Reddy, Quentin Cappart, et al. The browsergym ecosystem for web agent research. *arXiv preprint arXiv:2412.05467*, 2024.

[161] Ke Yang, Yao Liu, Sapana Chaudhary, Rasool Fakoor, Pratik Chaudhari, George Karypis, and Huzefa Rangwala. Agentoccam: A simple yet strong baseline for llm-based web agents. *arXiv preprint arXiv:2410.13825*, 2024.

[162] Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in neural information processing systems*, 35:27730–27744, 2022.

[163] Xiang Deng, Yu Gu, Boyuan Zheng, Shijie Chen, Samuel Stevens, Boshi Wang, Huan Sun, and Yu Su. Mind2web: Towards a generalist agent for the web, 2023. URL `https://arxiv.org/abs/2306.06070`.

[164] Yaxin Luo, Zhaoyi Li, Jiacheng Liu, Jiacheng Cui, Xiaohan Zhao, and Zhiqiang Shen. Open captchaworld: A comprehensive web-based platform for testing and benchmarking multimodal llm agents. *arXiv preprint arXiv:2505.24878*, 2025.

[165] Alan Chan, Rebecca Salganik, Alva Markelius, Chris Pang, Nitarshan Rajkumar, Dmitrii Krasheninnikov, Lauro Langosco, Zhonghao He, Yawen Duan, Micah Carroll, et al. Harms from increasingly agentic algorithmic systems. In *Proceedings of the 2023 ACM Conference on Fairness, Accountability, and Transparency*, pages 651–666, 2023.

[166] Margaret Mitchell, Avijit Ghosh, Alexandra Sasha Luccioni, and Giada Pistilli. Fully autonomous ai agents should not be developed. *arXiv preprint arXiv:2502.02649*, 2025.

[167] Maryanne Garry, Way Ming Chan, Jeffrey Foster, and Linda A Henkel. Large language models (llms) and the institutionalization of misinformation. *Trends in cognitive sciences*, 2024.

[168] E. Bloch, A. Conn, D. Garcia, A. Gill, A. Llorens, M. Noorma, and H. Roff. Ethical and technical challenges in the development, use, and governance of autonomous weapons systems. Technical report, IEEE Standards Association, 2020. URL https://standards.ieee.org/wp-content/uploads/import/documents/other/ethical-technical-challenges-autonomous-weapons-systems.pdf.

[169] Esther Chavannes, Klaudia Klonowska, and Tim Sweijs. Governing autonomous weapon systems. *The Hague: The Hague Centre For Strategic Studies*, 2020.

[170] Peter Cihon. Chilling autonomy: Policy enforcement for human oversight of ai agents. In *41st International Conference on Machine Learning, Workshop on Generative AI and Law*, 2024.

[171] Sayash Kapoor, Benedikt Stroebl, Zachary S Siegel, Nitya Nadgir, and Arvind Narayanan. Ai agents that matter. *arXiv preprint arXiv:2407.01502*, 2024.

[172] Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, et al. Promptarmor: Simple yet effective prompt injection defenses. *arXiv preprint arXiv:2507.15219*, 2025.

[173] Eric Wallace, Kai Xiao, Reimar H. Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *ArXiv*, abs/2404.13208, 2024. URL https://api.semanticscholar.org/CorpusID:269294048.

[174] Jingwei Yi, Yueqi Xie, Bin Zhu, Keegan Hines, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. Benchmarking and defending against indirect prompt injection attacks on large language models. *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.1*, 2023. URL https://api.semanticscholar.org/CorpusID:266521508.

[175] Andy Zou, Long Phan, Justin Wang, Derek Duenas, Maxwell Lin, Maksym Andriushchenko, Rowan Wang, Zico Kolter, Matt Fredrikson, and Dan Hendrycks. Improving alignment and robustness with circuit breakers. *ArXiv*, abs/2406.04313, 2024. URL https://api.semanticscholar.org/CorpusID:270286008.

[176] Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. Struq: Defending against prompt injection with structured queries. *ArXiv*, abs/2402.06363, 2024. URL https://api.semanticscholar.org/CorpusID:267616771.

[177] Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. Secalign: Defending against prompt injection with preference optimization. *arXiv preprint arXiv:2410.05451*, 2024.

[178] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *ArXiv*, abs/2305.18290, 2023. URL https://api.semanticscholar.org/CorpusID:258959321.

[179] Yuqi Jia, Zedian Shao, Yupei Liu, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. A critical evaluation of defenses against prompt injection attacks. *ArXiv*, abs/2505.18333, 2025. URL https://api.semanticscholar.org/CorpusID:278905371.

[180] Yuhao Wu, Franziska Roesner, Tadayoshi Kohno, Ning Zhang, and Umar Iqbal. IsolateGPT: An Execution Isolation Architecture for LLM-Based Agentic Systems. In *Network and Distributed System Security (NDSS) Symposium*, 2025.

[181] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. *ArXiv*, abs/2503.18813, 2025. URL https://api.semanticscholar.org/CorpusID:277940706.

[182] Xuchen Suo. Signed-prompt: A new approach to prevent prompt injection attacks against llm-integrated applications. *ArXiv*, abs/2401.07612, 2024. URL https://api.semanticscholar.org/CorpusID:266999840.

[183] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, D. Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *CoRR*, abs/1312.6199, 2013. URL https://api.semanticscholar.org/CorpusID:604334.

[184] Wenyue Hua, Xianjun Yang, Mingyu Jin, Zelong Li, Wei Cheng, Ruixiang Tang, and Yongfeng Zhang. Trustagent: Towards safe and trustworthy LLM-based agents through agent constitution. In *Trustworthy Multi-modal Foundation Models and AI Agents (TiFA)*, 2024. URL https://openreview.net/forum?id=ejl3NCLQBj.

[185] ProtectAI.com. Fine-tuned deberta-v3-base for prompt injection detection, 2024. URL https://huggingface.co/ProtectAI/deberta-v3-base-prompt-injection-v2.

[186] Yupei Liu, Yuqi Jia, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. Datasentinel: A game-theoretic detection of prompt injection attacks. *2025 IEEE Symposium on Security and Privacy (SP)*, pages 2190–2208, 2025. URL https://api.semanticscholar.org/CorpusID:277787029.

[168] E. Bloch, A. Conn, D. Garcia, A. Gill, A. Llorens, M. Noorma, and H. Roff. Ethical and technical challenges in the development, use, and governance of autonomous weapons systems. Technical report, IEEE Standards Association, 2020. URL https://standards.ieee.org/wp-content/uploads/import/documents/other/ethical-technical-challenges-autonomous-weapons-systems.pdf.

[169] Esther Chavannes, Klaudia Klonowska, and Tim Sweijs. Governing autonomous weapon systems. *The Hague: The Hague Centre For Strategic Studies*, 2020.

[170] Peter Cihon. Chilling autonomy: Policy enforcement for human oversight of ai agents. In *41st International Conference on Machine Learning, Workshop on Generative AI and Law*, 2024.

[171] Sayash Kapoor, Benedikt Stroebl, Zachary S Siegel, Nitya Nadgir, and Arvind Narayanan. Ai agents that matter. *arXiv preprint arXiv:2407.01502*, 2024.

[172] Tianneng Shi, Kaijie Zhu, Zhun Wang, Yuqi Jia, Will Cai, Weida Liang, Haonan Wang, Hend Alzahrani, Joshua Lu, Kenji Kawaguchi, et al. Promptarmor: Simple yet effective prompt injection defenses. *arXiv preprint arXiv:2507.15219*, 2025.

[173] Eric Wallace, Kai Xiao, Reimar H. Leike, Lilian Weng, Johannes Heidecke, and Alex Beutel. The instruction hierarchy: Training llms to prioritize privileged instructions. *ArXiv*, abs/2404.13208, 2024. URL https://api.semanticscholar.org/CorpusID:269294048.

[174] Jingwei Yi, Yueqi Xie, Bin Zhu, Keegan Hines, Emre Kiciman, Guangzhong Sun, Xing Xie, and Fangzhao Wu. Benchmarking and defending against indirect prompt injection attacks on large language models. *Proceedings of the 31st ACM SIGKDD Conference on Knowledge Discovery and Data Mining V.1*, 2023. URL https://api.semanticscholar.org/CorpusID:266521508.

[175] Andy Zou, Long Phan, Justin Wang, Derek Duenas, Maxwell Lin, Maksym Andriushchenko, Rowan Wang, Zico Kolter, Matt Fredrikson, and Dan Hendrycks. Improving alignment and robustness with circuit breakers. *ArXiv*, abs/2406.04313, 2024. URL https://api.semanticscholar.org/CorpusID:270286008.

[176] Sizhe Chen, Julien Piet, Chawin Sitawarin, and David Wagner. Struq: Defending against prompt injection with structured queries. *ArXiv*, abs/2402.06363, 2024. URL https://api.semanticscholar.org/CorpusID:267616771.

[177] Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, David Wagner, and Chuan Guo. Secalign: Defending against prompt injection with preference optimization. *arXiv preprint arXiv:2410.05451*, 2024.

[178] Rafael Rafailov, Archit Sharma, Eric Mitchell, Stefano Ermon, Christopher D. Manning, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. *ArXiv*, abs/2305.18290, 2023. URL https://api.semanticscholar.org/CorpusID:258959321.

[179] Yuqi Jia, Zedian Shao, Yupei Liu, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. A critical evaluation of defenses against prompt injection attacks. *ArXiv*, abs/2505.18333, 2025. URL https://api.semanticscholar.org/CorpusID:278905371.

[180] Yuhao Wu, Franziska Roesner, Tadayoshi Kohno, Ning Zhang, and Umar Iqbal. IsolateGPT: An Execution Isolation Architecture for LLM-Based Agentic Systems. In *Network and Distributed System Security (NDSS) Symposium*, 2025.

[181] Edoardo Debenedetti, Ilia Shumailov, Tianqi Fan, Jamie Hayes, Nicholas Carlini, Daniel Fabian, Christoph Kern, Chongyang Shi, Andreas Terzis, and Florian Tramèr. Defeating prompt injections by design. *ArXiv*, abs/2503.18813, 2025. URL https://api.semanticscholar.org/CorpusID:277940706.

[182] Xuchen Suo. Signed-prompt: A new approach to prevent prompt injection attacks against llm-integrated applications. *ArXiv*, abs/2401.07612, 2024. URL https://api.semanticscholar.org/CorpusID:266999840.

[183] Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, D. Erhan, Ian J. Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *CoRR*, abs/1312.6199, 2013. URL https://api.semanticscholar.org/CorpusID:604334.

[184] Wenyue Hua, Xianjun Yang, Mingyu Jin, Zelong Li, Wei Cheng, Ruixiang Tang, and Yongfeng Zhang. Trustagent: Towards safe and trustworthy LLM-based agents through agent constitution. In *Trustworthy Multi-modal Foundation Models and AI Agents (TiFA)*, 2024. URL https://openreview.net/forum?id=ejl3NCLQBj.

[185] ProtectAI.com. Fine-tuned deberta-v3-base for prompt injection detection, 2024. URL https://huggingface.co/ProtectAI/deberta-v3-base-prompt-injection-v2.

[186] Yupei Liu, Yuqi Jia, Jinyuan Jia, Dawn Song, and Neil Zhenqiang Gong. Datasentinel: A game-theoretic detection of prompt injection attacks. *2025 IEEE Symposium on Security and Privacy (SP)*, pages 2190–2208, 2025. URL https://api.semanticscholar.org/CorpusID:277787029.

[187] Julien Piet, Maha Alrashed, Chawin Sitawarin, Sizhe Chen, Zeming Wei, Elizabeth Sun, Basel Alomair, and David Wagner. Jatmo: Prompt injection defense by task-specific finetuning. In *European Symposium on Research in Computer Security*, 2023. URL https://api.semanticscholar.org/CorpusID:266690784.

[188] Edoardo Debenedetti, Jie Zhang, Mislav Balunovi'c, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate attacks and defenses for llm agents. *ArXiv*, abs/2406.13352, 2024. URL https://api.semanticscholar.org/CorpusID:270619628.

[189] Keegan Hines, Gary Lopez, Matthew Hall, Federico Zarfati, Yonatan Zunger, and Emre Kiciman. Defending against indirect prompt injection attacks with spotlighting, 2024. URL https://arxiv.org/abs/2403.14720.

[190] Yulin Chen, Haoran Li, Yuan Sui, Yue Liu, Yufei He, Yangqiu Song, and Bryan Hooi. Robustness via referencing: Defending against prompt injection attacks by referencing the executed instruction. *ArXiv*, abs/2504.20472, 2025. URL https://api.semanticscholar.org/CorpusID:278170857.

[191] Gabriel Alon and Michael Kamfonas. Detecting language model attacks with perplexity. *ArXiv*, abs/2308.14132, 2023. URL https://api.semanticscholar.org/CorpusID:261245172.

[192] Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, and Chuan Guo. Aligning llms to be robust against prompt injection. *arXiv e-prints*, pages arXiv–2410, 2024.

[193] Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, et al. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*, 2023.

[194] Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. Formalizing and benchmarking prompt injection attacks and defenses. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 1831–1847, 2024.

[195] Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. The task shield: Enforcing task alignment to defend against indirect prompt injection in llm agents. *arXiv preprint arXiv:2412.16682*, 2024.

[196] Suriya Ganesh Ayyamperumal and Limin Ge. Current state of llm risks and ai guardrails. *arXiv preprint arXiv:2406.12934*, 2024.

[197] Mateus Devino, Evaline Ju, and Paulo Marques Caldeira Junior. Designing and implementing llm guardrails components in production environments. In *2025 IEEE/ACM 4th International Conference on AI Engineering–Software Engineering for AI (CAIN)*, pages 12–17. IEEE, 2025.

[198] Zhen Xiang, Linzhi Zheng, Yanjie Li, Junyuan Hong, Qinbin Li, Han Xie, Jiawei Zhang, Zidi Xiong, Chulin Xie, Carl Yang, et al. Guardagent: Safeguard llm agents by a guard agent via knowledge-enabled reasoning. *arXiv preprint arXiv:2406.09187*, 2024.

[199] Haoyu Wang, Christopher M Poskitt, and Jun Sun. Agentspec: Customizable runtime enforcement for safe and reliable llm agents. *arXiv preprint arXiv:2503.18666*, 2025.

[200] Zhaorun Chen, Mintong Kang, and Bo Li. Shieldagent: Shielding agents via verifiable safety policy reasoning. *arXiv preprint arXiv:2503.22738*, 2025.

[201] Mintong Kang and Bo Li. R^2-guard: Robust reasoning enabled llm guardrail via knowledge-enhanced logical reasoning. *arXiv preprint arXiv:2407.05557*, 2024.

[202] Lukas Helff, Felix Friedrich, Manuel Brack, Patrick Schramowski, and Kristian Kersting. Llavaguard: Vlm-based safeguard for vision dataset curation and safety assessment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8322–8326, 2024.

[203] Zhaorun Chen, Francesco Pinto, Minzhou Pan, and Bo Li. Safewatch: An efficient safety-policy following video guardrail model with transparent explanations. *arXiv preprint arXiv:2412.06878*, 2024.

[204] Rafiqul Rabin, Jesse Hostetler, Sean McGregor, Brett Weir, and Nick Judd. Sandboxeval: Towards securing test environment for untrusted code. *arXiv preprint arXiv:2504.00018*, 2025.

[205] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

[206] Mohammed Latif Siddiq, Joanna Cecilia da Silva Santos, Sajith Devareddy, and Anna Muller. Sallm: Security assessment of generated code. In *Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering Workshops*, pages 54–65, 2024.

[187] Julien Piet, Maha Alrashed, Chawin Sitawarin, Sizhe Chen, Zeming Wei, Elizabeth Sun, Basel Alomair, and David Wagner. Jatmo: Prompt injection defense by task-specific finetuning. In *European Symposium on Research in Computer Security*, 2023. URL https://api.semanticscholar.org/CorpusID:266690784.

[188] Edoardo Debenedetti, Jie Zhang, Mislav Balunovi'c, Luca Beurer-Kellner, Marc Fischer, and Florian Tramèr. Agentdojo: A dynamic environment to evaluate attacks and defenses for llm agents. *ArXiv*, abs/2406.13352, 2024. URL https://api.semanticscholar.org/CorpusID:270619628.

[189] Keegan Hines, Gary Lopez, Matthew Hall, Federico Zarfati, Yonatan Zunger, and Emre Kiciman. Defending against indirect prompt injection attacks with spotlighting, 2024. URL https://arxiv.org/abs/2403.14720.

[190] Yulin Chen, Haoran Li, Yuan Sui, Yue Liu, Yufei He, Yangqiu Song, and Bryan Hooi. Robustness via referencing: Defending against prompt injection attacks by referencing the executed instruction. *ArXiv*, abs/2504.20472, 2025. URL https://api.semanticscholar.org/CorpusID:278170857.

[191] Gabriel Alon and Michael Kamfonas. Detecting language model attacks with perplexity. *ArXiv*, abs/2308.14132, 2023. URL https://api.semanticscholar.org/CorpusID:261245172.

[192] Sizhe Chen, Arman Zharmagambetov, Saeed Mahloujifar, Kamalika Chaudhuri, and Chuan Guo. Aligning llms to be robust against prompt injection. *arXiv e-prints*, pages arXiv–2410, 2024.

[193] Hakan Inan, Kartikeya Upasani, Jianfeng Chi, Rashi Rungta, Krithika Iyer, Yuning Mao, Michael Tontchev, Qing Hu, Brian Fuller, Davide Testuggine, et al. Llama guard: Llm-based input-output safeguard for human-ai conversations. *arXiv preprint arXiv:2312.06674*, 2023.

[194] Yupei Liu, Yuqi Jia, Runpeng Geng, Jinyuan Jia, and Neil Zhenqiang Gong. Formalizing and benchmarking prompt injection attacks and defenses. In *33rd USENIX Security Symposium (USENIX Security 24)*, pages 1831–1847, 2024.

[195] Feiran Jia, Tong Wu, Xin Qin, and Anna Squicciarini. The task shield: Enforcing task alignment to defend against indirect prompt injection in llm agents. *arXiv preprint arXiv:2412.16682*, 2024.

[196] Suriya Ganesh Ayyamperumal and Limin Ge. Current state of llm risks and ai guardrails. *arXiv preprint arXiv:2406.12934*, 2024.

[197] Mateus Devino, Evaline Ju, and Paulo Marques Caldeira Junior. Designing and implementing llm guardrails components in production environments. In *2025 IEEE/ACM 4th International Conference on AI Engineering–Software Engineering for AI (CAIN)*, pages 12–17. IEEE, 2025.

[198] Zhen Xiang, Linzhi Zheng, Yanjie Li, Junyuan Hong, Qinbin Li, Han Xie, Jiawei Zhang, Zidi Xiong, Chulin Xie, Carl Yang, et al. Guardagent: Safeguard llm agents by a guard agent via knowledge-enabled reasoning. *arXiv preprint arXiv:2406.09187*, 2024.

[199] Haoyu Wang, Christopher M Poskitt, and Jun Sun. Agentspec: Customizable runtime enforcement for safe and reliable llm agents. *arXiv preprint arXiv:2503.18666*, 2025.

[200] Zhaorun Chen, Mintong Kang, and Bo Li. Shieldagent: Shielding agents via verifiable safety policy reasoning. *arXiv preprint arXiv:2503.22738*, 2025.

[201] Mintong Kang and Bo Li. R^2-guard: Robust reasoning enabled llm guardrail via knowledge-enhanced logical reasoning. *arXiv preprint arXiv:2407.05557*, 2024.

[202] Lukas Helff, Felix Friedrich, Manuel Brack, Patrick Schramowski, and Kristian Kersting. Llavaguard: Vlm-based safeguard for vision dataset curation and safety assessment. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8322–8326, 2024.

[203] Zhaorun Chen, Francesco Pinto, Minzhou Pan, and Bo Li. Safewatch: An efficient safety-policy following video guardrail model with transparent explanations. *arXiv preprint arXiv:2412.06878*, 2024.

[204] Rafiqul Rabin, Jesse Hostetler, Sean McGregor, Brett Weir, and Nick Judd. Sandboxeval: Towards securing test environment for untrusted code. *arXiv preprint arXiv:2504.00018*, 2025.

[205] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374*, 2021.

[206] Mohammed Latif Siddiq, Joanna Cecilia da Silva Santos, Sajith Devareddy, and Anna Muller. Sallm: Security assessment of generated code. In *Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering Workshops*, pages 54–65, 2024.

[207] Umar Iqbal, Tadayoshi Kohno, and Franziska Roesner. Llm platform security: Applying a systematic evaluation framework to openai's chatgpt plugins. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 7, pages 611–623, 2024.

[208] Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. Identifying the risks of lm agents with an lm-emulated sandbox. *arXiv preprint arXiv:2309.15817*, 2023. URL https://arxiv.org/abs/2309.15817.

[209] Roy Huang. Reinforcement learning for safe llm code generation, 2025.

[210] Manyafa Mushsharat, Nazmus Mohammed, and Md Rashedul Amin. A neural sandbox framework for discovering spurious concepts in llm decisions. In *OpenReview Preprint*, 2024. URL https://openreview.net/forum?id=1tDoI2WBGE. [Online; accessed 27-August-2025].

[211] Bingzhuo Zhong, Siyuan Liu, Marco Caccamo, and Majid Zamani. Towards trustworthy ai: Sandboxing ai-based unverified controllers for safe and secure cyber-physical systems. In *2023 62nd IEEE Conference on Decision and Control (CDC)*, pages 1833–1840, 2023. doi:10.1109/CDC49753.2023.10384154.

[212] Fangzhou Wu, Ning Zhang, Somesh Jha, Patrick McDaniel, and Chaowei Xiao. A new era in llm security: Exploring security concerns in real-world llm-based systems. *arXiv preprint arXiv:2402.18649*, 2024.

[213] Tenable. Cloudimposer: Executing code on millions of google servers with a single malicious package. https://www.tenable.com/blog/cloudimposer-executing-code-on-millions-of-google-servers-with-a-single-malicious-package, 2024. Accessed: 2025-08-28.

[214] Haoyu Wang, Chris M Poskitt, Jun Sun, and Jiali Wei. Pro2guard: Proactive runtime enforcement of llm agent safety via probabilistic model checking. *arXiv preprint arXiv:2508.00500*, 2025.

[215] Dhananjay Raju, Sudarshanan Bharadwaj, Franck Djeumou, and Ufuk Topcu. Online synthesis for runtime enforcement of safety in multiagent systems. *IEEE Transactions on Control of Network Systems*, 8(2):621–632, 2021.

[216] Ilias Tsingenopoulos, Vera Rimmer, Davy Preuveneers, Fabio Pierazzi, Lorenzo Cavallaro, and Wouter Joosen. The adaptive arms race: Redefining robustness in ai security, 2025. URL https://arxiv.org/abs/2312.13435.

[217] NCCoE, NIST. Nccoe cyber ai profile, 2025.

[218] OWASP GenAI. Agentic ai - threats & mitigations, 2025.

[219] Cloud Security Alliance. Maestro: Agentic ai threat modeling framework | csa, 2025.

[220] Kuo-Han Hung, Ching-Yun Ko, Ambrish Rawat, I Chung, Winston H Hsu, Pin-Yu Chen, et al. Attention tracker: Detecting prompt injection attacks in llms. *arXiv preprint arXiv:2411.00348*, 2024.

[221] Leo Boisvert, Mihir Bansal, Chandra Kiran Reddy Evuru, Gabriel Huang, Abhay Puri, Avinandan Bose, Maryam Fazel, Quentin Cappart, Jason Stanley, Alexandre Lacoste, et al. Doomarena: A framework for testing ai agents against evolving security threats. In *The Conference on Language Modeling*, Palais des Congrès, Canada, October 2025.

[222] Edward Z. Liu, Tian Shi, Panupong Pasupat, Andrew McCallum, William W. Cohen, et al. Reinforcement learning on web interfaces using workflow-guided exploration. In *International Conference on Learning Representations*, 2018. URL https://arxiv.org/abs/1802.08802.

[223] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024. URL https://arxiv.org/abs/2406.12045.

[224] Jize Wang, Zerun Ma, Yining Li, Songyang Zhang, Cailian Chen, Kai Chen, and Xinyi Le. Gta: A benchmark for general tool agents, 2024. URL https://arxiv.org/abs/2407.08713.

[225] Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh J Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Advances in Neural Information Processing Systems*, 37:52040–52094, 2024.

[226] Reyna Abhyankar, Qi Qi, and Yiying Zhang. Osworld-human: Benchmarking the efficiency of computer-use agents. *arXiv preprint arXiv:2506.16042*, 2025.

[227] Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 881–905, 2024.

[207] Umar Iqbal, Tadayoshi Kohno, and Franziska Roesner. Llm platform security: Applying a systematic evaluation framework to openai's chatgpt plugins. In *Proceedings of the AAAI/ACM Conference on AI, Ethics, and Society*, volume 7, pages 611–623, 2024.

[208] Yangjun Ruan, Honghua Dong, Andrew Wang, Silviu Pitis, Yongchao Zhou, Jimmy Ba, Yann Dubois, Chris J. Maddison, and Tatsunori Hashimoto. Identifying the risks of lm agents with an lm-emulated sandbox. *arXiv preprint arXiv:2309.15817*, 2023. URL https://arxiv.org/abs/2309.15817.

[209] Roy Huang. Reinforcement learning for safe llm code generation, 2025.

[210] Manyafa Mushsharat, Nazmus Mohammed, and Md Rashedul Amin. A neural sandbox framework for discovering spurious concepts in llm decisions. In *OpenReview Preprint*, 2024. URL https://openreview.net/forum?id=1tDoI2WBGE. [Online; accessed 27-August-2025].

[211] Bingzhuo Zhong, Siyuan Liu, Marco Caccamo, and Majid Zamani. Towards trustworthy ai: Sandboxing ai-based unverified controllers for safe and secure cyber-physical systems. In *2023 62nd IEEE Conference on Decision and Control (CDC)*, pages 1833–1840, 2023. doi:10.1109/CDC49753.2023.10384154.

[212] Fangzhou Wu, Ning Zhang, Somesh Jha, Patrick McDaniel, and Chaowei Xiao. A new era in llm security: Exploring security concerns in real-world llm-based systems. *arXiv preprint arXiv:2402.18649*, 2024.

[213] Tenable. Cloudimposer: Executing code on millions of google servers with a single malicious package. https://www.tenable.com/blog/cloudimposer-executing-code-on-millions-of-google-servers-with-a-single-malicious-package, 2024. Accessed: 2025-08-28.

[214] Haoyu Wang, Chris M Poskitt, Jun Sun, and Jiali Wei. Pro2guard: Proactive runtime enforcement of llm agent safety via probabilistic model checking. *arXiv preprint arXiv:2508.00500*, 2025.

[215] Dhananjay Raju, Sudarshanan Bharadwaj, Franck Djeumou, and Ufuk Topcu. Online synthesis for runtime enforcement of safety in multiagent systems. *IEEE Transactions on Control of Network Systems*, 8(2):621–632, 2021.

[216] Ilias Tsingenopoulos, Vera Rimmer, Davy Preuveneers, Fabio Pierazzi, Lorenzo Cavallaro, and Wouter Joosen. The adaptive arms race: Redefining robustness in ai security, 2025. URL https://arxiv.org/abs/2312.13435.

[217] NCCoE, NIST. Nccoe cyber ai profile, 2025.

[218] OWASP GenAI. Agentic ai - threats & mitigations, 2025.

[219] Cloud Security Alliance. Maestro: Agentic ai threat modeling framework | csa, 2025.

[220] Kuo-Han Hung, Ching-Yun Ko, Ambrish Rawat, I Chung, Winston H Hsu, Pin-Yu Chen, et al. Attention tracker: Detecting prompt injection attacks in llms. *arXiv preprint arXiv:2411.00348*, 2024.

[221] Leo Boisvert, Mihir Bansal, Chandra Kiran Reddy Evuru, Gabriel Huang, Abhay Puri, Avinandan Bose, Maryam Fazel, Quentin Cappart, Jason Stanley, Alexandre Lacoste, et al. Doomarena: A framework for testing ai agents against evolving security threats. In *The Conference on Language Modeling*, Palais des Congrès, Canada, October 2025.

[222] Edward Z. Liu, Tian Shi, Panupong Pasupat, Andrew McCallum, William W. Cohen, et al. Reinforcement learning on web interfaces using workflow-guided exploration. In *International Conference on Learning Representations*, 2018. URL https://arxiv.org/abs/1802.08802.

[223] Shunyu Yao, Noah Shinn, Pedram Razavi, and Karthik Narasimhan. τ-bench: A benchmark for tool-agent-user interaction in real-world domains. *arXiv preprint arXiv:2406.12045*, 2024. URL https://arxiv.org/abs/2406.12045.

[224] Jize Wang, Zerun Ma, Yining Li, Songyang Zhang, Cailian Chen, Kai Chen, and Xinyi Le. Gta: A benchmark for general tool agents, 2024. URL https://arxiv.org/abs/2407.08713.

[225] Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Toh J Hua, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Advances in Neural Information Processing Systems*, 37:52040–52094, 2024.

[226] Reyna Abhyankar, Qi Qi, and Yiying Zhang. Osworld-human: Benchmarking the efficiency of computer-use agents. *arXiv preprint arXiv:2506.16042*, 2025.

[227] Jing Yu Koh, Robert Lo, Lawrence Jang, Vikram Duvvur, Ming Lim, Po-Yu Huang, Graham Neubig, Shuyan Zhou, Russ Salakhutdinov, and Daniel Fried. Visualwebarena: Evaluating multimodal agents on realistic visual web tasks. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 881–905, 2024.

[228] Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William E Bishop, Wei Li, Folawiyo Campbell-Ajala, et al. Androidworld: A dynamic benchmarking environment for autonomous agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[229] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35: 20744–20757, 2022.

[230] Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, et al. Agentbench: Evaluating llms as agents. In *The Twelfth International Conference on Learning Representations*, 2024.

[231] Atsuyuki Miyai, Zaiying Zhao, Kazuki Egashira, Atsuki Sato, Tatsumi Sunada, Shota Onohara, Hiromasa Yamanishi, Mashiro Toyooka, Kunato Nishina, Ryoma Maeda, Kiyoharu Aizawa, and Toshihiko Yamasaki. Webchorearena: Evaluating web browsing agents on realistic tedious web tasks, 2025. URL `https://arxiv.org/abs/2506.01952`.

[232] Tianqi Xu, Linyao Chen, Dai-Jie Wu, Yanjun Chen, Zecheng Zhang, Xiang Yao, Zhiqiang Xie, Yongchao Chen, Shilong Liu, Bochen Qian, et al. Crab: Cross-environment agent benchmark for multimodal language model agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 21607–21647, 2025.

[233] Ori Yoran, Samuel Joseph Amouyal, Chaitanya Malaviya, Ben Bogin, Ofir Press, and Jonathan Berant. AssistantBench: Can web agents solve realistic and time-consuming tasks? In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen, editors, *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 8938–8968, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi:10.18653/v1/2024.emnlp-main.505. URL `https://aclanthology.org/2024.emnlp-main.505/`.

[234] Ido Levy, Ben Wiesel, Sami Marreed, Alon Oved, Avi Yaeli, and Segev Shlomov. St-webagentbench: A benchmark for evaluating safety and trustworthiness in web agents. *arXiv preprint arXiv:2410.06703*, 2024.

[235] Maksym Andriushchenko, Aditi Kumar, et al. Os-harm: A benchmark for measuring safety of computer use agents. *arXiv preprint arXiv:2506.14866*, 2025. URL `https://arxiv.org/abs/2506.14866`.

[236] Tongxin Yuan, Zhiwei He, Lingzhong Dong, Yiming Wang, Ruijie Zhao, Tian Xia, Lizhen Xu, Fangqi Li, Zhuosheng Zhang, Rui Wang, and Gongshen Liu. R-judge: Benchmarking safety risk awareness for llm agents. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, 2024. URL `https://aclanthology.org/2024.findings-emnlp.92`.

[237] Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. Agent security bench (asb): Formalizing and benchmarking attacks and defenses in llm-based agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[238] Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. Privacylens: Evaluating privacy norm awareness of language models in action. *Advances in Neural Information Processing Systems*, 37:89373–89407, 2024.

[239] Zhexin Zhang, Shiyao Cui, Yida Lu, Jingzhuo Zhou, Junxiao Yang, Hongning Wang, and Minlie Huang. Agent-safetybench: Evaluating the safety of llm agents, 2025. URL `https://arxiv.org/abs/2412.14470`.

[240] Sheng Yin, Xianghe Pang, Yuanzhuo Ding, Menglan Chen, Yutong Bi, Yichen Xiong, Wenhao Huang, Zhen Xiang, Jing Shao, and Siheng Chen. SafeAgentBench: A benchmark for safe task planning of embodied llm agents. *arXiv preprint arXiv:2412.13178*, 2024.

[241] María Sanz-Gómez, Víctor Mayoral-Vilches, Francesco Balassone, Luis Javier Navarrete-Lozano, Cristóbal RJ Chavez, and Maite del Mundo de Torres. Cybersecurity ai benchmark (caibench): A meta-benchmark for evaluating cybersecurity ai agents. *arXiv preprint arXiv:2510.24317*, 2025.

[242] Ivan Evtimov, Arman Zharmagambetov, Aaron Grattafiori, Chuan Guo, and Kamalika Chaudhuri. Wasp: Benchmarking web agent security against prompt injection attacks. In *ICML 2025 Workshop on Computer Use Agents*, 2025.

[243] Ada Defne Tur, Nicholas Meade, Xing Han Lù, Alejandra Zambrano, Arkil Patel, Esin DURMUS, Spandana Gella, Karolina Stanczak, and Siva Reddy. Safearena: Evaluating the safety of autonomous web agents. In *Forty-second International Conference on Machine Learning*, 2025.

[244] Sanidhya Vijayvargiya, Aditya Bharat Soni, Xuhui Zhou, Zora Zhiruo Wang, Nouha Dziri, Graham Neubig, and Maarten Sap. Openagentsafety: A comprehensive framework for evaluating real-world ai agent safety. *arXiv preprint arXiv:2507.06134*, 2025.

[228] Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William E Bishop, Wei Li, Folawiyo Campbell-Ajala, et al. Androidworld: A dynamic benchmarking environment for autonomous agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[229] Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35: 20744–20757, 2022.

[230] Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, et al. Agentbench: Evaluating llms as agents. In *The Twelfth International Conference on Learning Representations*, 2024.

[231] Atsuyuki Miyai, Zaiying Zhao, Kazuki Egashira, Atsuki Sato, Tatsumi Sunada, Shota Onohara, Hiromasa Yamanishi, Mashiro Toyooka, Kunato Nishina, Ryoma Maeda, Kiyoharu Aizawa, and Toshihiko Yamasaki. Webchorearena: Evaluating web browsing agents on realistic tedious web tasks, 2025. URL `https://arxiv.org/abs/2506.01952`.

[232] Tianqi Xu, Linyao Chen, Dai-Jie Wu, Yanjun Chen, Zecheng Zhang, Xiang Yao, Zhiqiang Xie, Yongchao Chen, Shilong Liu, Bochen Qian, et al. Crab: Cross-environment agent benchmark for multimodal language model agents. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 21607–21647, 2025.

[233] Ori Yoran, Samuel Joseph Amouyal, Chaitanya Malaviya, Ben Bogin, Ofir Press, and Jonathan Berant. AssistantBench: Can web agents solve realistic and time-consuming tasks? In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen, editors, *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 8938–8968, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi:10.18653/v1/2024.emnlp-main.505. URL `https://aclanthology.org/2024.emnlp-main.505/`.

[234] Ido Levy, Ben Wiesel, Sami Marreed, Alon Oved, Avi Yaeli, and Segev Shlomov. St-webagentbench: A benchmark for evaluating safety and trustworthiness in web agents. *arXiv preprint arXiv:2410.06703*, 2024.

[235] Maksym Andriushchenko, Aditi Kumar, et al. Os-harm: A benchmark for measuring safety of computer use agents. *arXiv preprint arXiv:2506.14866*, 2025. URL `https://arxiv.org/abs/2506.14866`.

[236] Tongxin Yuan, Zhiwei He, Lingzhong Dong, Yiming Wang, Ruijie Zhao, Tian Xia, Lizhen Xu, Fangqi Li, Zhuosheng Zhang, Rui Wang, and Gongshen Liu. R-judge: Benchmarking safety risk awareness for llm agents. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, 2024. URL `https://aclanthology.org/2024.findings-emnlp.92`.

[237] Hanrong Zhang, Jingyuan Huang, Kai Mei, Yifei Yao, Zhenting Wang, Chenlu Zhan, Hongwei Wang, and Yongfeng Zhang. Agent security bench (asb): Formalizing and benchmarking attacks and defenses in llm-based agents. In *The Thirteenth International Conference on Learning Representations*, 2025.

[238] Yijia Shao, Tianshi Li, Weiyan Shi, Yanchen Liu, and Diyi Yang. Privacylens: Evaluating privacy norm awareness of language models in action. *Advances in Neural Information Processing Systems*, 37:89373–89407, 2024.

[239] Zhexin Zhang, Shiyao Cui, Yida Lu, Jingzhuo Zhou, Junxiao Yang, Hongning Wang, and Minlie Huang. Agent-safetybench: Evaluating the safety of llm agents, 2025. URL `https://arxiv.org/abs/2412.14470`.

[240] Sheng Yin, Xianghe Pang, Yuanzhuo Ding, Menglan Chen, Yutong Bi, Yichen Xiong, Wenhao Huang, Zhen Xiang, Jing Shao, and Siheng Chen. SafeAgentBench: A benchmark for safe task planning of embodied llm agents. *arXiv preprint arXiv:2412.13178*, 2024.

[241] María Sanz-Gómez, Víctor Mayoral-Vilches, Francesco Balassone, Luis Javier Navarrete-Lozano, Cristóbal RJ Chavez, and Maite del Mundo de Torres. Cybersecurity ai benchmark (caibench): A meta-benchmark for evaluating cybersecurity ai agents. *arXiv preprint arXiv:2510.24317*, 2025.

[242] Ivan Evtimov, Arman Zharmagambetov, Aaron Grattafiori, Chuan Guo, and Kamalika Chaudhuri. Wasp: Benchmarking web agent security against prompt injection attacks. In *ICML 2025 Workshop on Computer Use Agents*, 2025.

[243] Ada Defne Tur, Nicholas Meade, Xing Han Lù, Alejandra Zambrano, Arkil Patel, Esin DURMUS, Spandana Gella, Karolina Stanczak, and Siva Reddy. Safearena: Evaluating the safety of autonomous web agents. In *Forty-second International Conference on Machine Learning*, 2025.

[244] Sanidhya Vijayvargiya, Aditya Bharat Soni, Xuhui Zhou, Zora Zhiruo Wang, Nouha Dziri, Graham Neubig, and Maarten Sap. Openagentsafety: A comprehensive framework for evaluating real-world ai agent safety. *arXiv preprint arXiv:2507.06134*, 2025.

[245] Xuanjun Zong, Zhiqi Shen, Lei Wang, Yunshi Lan, and Chao Yang. Mcp-safetybench: A benchmark for safety evaluation of large language models with real-world mcp servers, 2025. URL https://arxiv.org/abs/2512.15163.

[246] Yixuan Yang, Daoyuan Wu, and Yufan Chen. Mcpsecbench: A systematic security benchmark and playground for testing model context protocols, 2025. URL https://arxiv.org/abs/2508.13220.

[247] Gurusha Juneja, Alon Albalak, Wenyue Hua, and William Yang Wang. Magpie: A dataset for multi-agent contextual privacy evaluation. *arXiv preprint arXiv:2506.20737*, 2025.

[248] Hiroki Furuta, Izzeddin Gur, Fangchen Liu, Xiaolong Wang, Trevor Darrell, and Anna Rohrbach. Multimodal web navigation with instruction-finetuned foundation models. *arXiv preprint arXiv:2305.11854*, 2023. URL https://arxiv.org/abs/2305.11854.

[249] Peter Shaw, Mandar Joshi, James Cohan, Jonathan Berant, Panupong Pasupat, Hexiang Hu, Urvashi Khandelwal, Kenton Lee, and Kristina N Toutanova. From pixels to ui actions: Learning to follow instructions via graphical user interfaces. *Advances in Neural Information Processing Systems*, 36:34354–34370, 2023.

[250] Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, et al. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. In *International Conference on Machine Learning*, pages 35181–35224. PMLR, 2024.

[251] Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, George J Pappas, Florian Tramer, et al. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *Advances in Neural Information Processing Systems*, 37:55005–55029, 2024.

[252] Zeeshan Rasheed, Muhammad Waseem, Kari Systä, and Pekka Abrahamsson. Large language model evaluation via multi ai agents: Preliminary results. *arXiv preprint arXiv:2404.01023*, 2024.

[253] Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, et al. A survey on llm-as-a-judge. *arXiv preprint arXiv:2411.15594*, 2024.

[254] Mingchen Zhuge, Changsheng Zhao, Dylan Ashley, Wenyi Wang, Dmitrii Khizbullin, Yunyang Xiong, Zechun Liu, Ernie Chang, Raghuraman Krishnamoorthi, Yuandong Tian, et al. Agent-as-a-judge: Evaluate agents with agents. *arXiv preprint arXiv:2410.10934*, 2024.

[255] Sejin Lee, Jian Kim, Haon Park, Ashkan Yousefpour, Sangyoon Yu, and Min Song. sudo rm-rf agentic_security. *arXiv preprint arXiv:2503.20279*, 2025.

[256] Xing Han Lù, Amirhossein Kazemnejad, Nicholas Meade, Arkil Patel, Dongchan Shin, Alejandra Zambrano, Karolina Stańczak, Peter Shaw, Christopher J Pal, and Siva Reddy. Agentrewardbench: Evaluating automatic evaluations of web agent trajectories. *arXiv preprint arXiv:2504.08942*, 2025.

[257] Yanan Chen, Ali Pesaranghader, Tanmana Sadhu, and Dong Hoon Yi. Can we rely on llm agents to draft long-horizon plans? let's take travelplanner as an example. *arXiv preprint arXiv:2408.06318*, 2024.

[258] Tianle Li, Ge Zhang, Quy Duc Do, Xiang Yue, and Wenhu Chen. Long-context llms struggle with long in-context learning. *arXiv preprint arXiv:2404.02060*, 2024.

[259] Mengkang Hu, Tianxing Chen, Qiguang Chen, Yao Mu, Wenqi Shao, and Ping Luo. Hiagent: Hierarchical working memory management for solving long-horizon agent tasks with large language model. *arXiv preprint arXiv:2408.09559*, 2024.

[260] Chenkai Sun, Denghui Zhang, ChengXiang Zhai, and Heng Ji. Beyond reactive safety: Risk-aware llm alignment via long-horizon simulation. *arXiv preprint arXiv:2506.20949*, 2025.

[261] Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M Ziegler, Tim Maxwell, Newton Cheng, et al. Sleeper agents: Training deceptive llms that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[262] Jen-tse Huang, Jiaxu Zhou, Tailin Jin, Xuhui Zhou, Zixi Chen, Wenxuan Wang, Youliang Yuan, Michael R Lyu, and Maarten Sap. On the resilience of llm-based multi-agent collaboration with faulty agents. *arXiv preprint arXiv:2408.00989*, 2024.

[263] Pengfei He, Yupin Lin, Shen Dong, Han Xu, Yue Xing, and Hui Liu. Red-teaming llm multi-agent systems via communication attacks. *arXiv preprint arXiv:2502.14847*, 2025.

[264] Terry Tong, Fei Wang, Zhe Zhao, and Muhao Chen. Badjudge: Backdoor vulnerabilities of llm-as-a-judge. In *ICLR*, 2025.

[245] Xuanjun Zong, Zhiqi Shen, Lei Wang, Yunshi Lan, and Chao Yang. Mcp-safetybench: A benchmark for safety evaluation of large language models with real-world mcp servers, 2025. URL https://arxiv.org/abs/2512.15163.

[246] Yixuan Yang, Daoyuan Wu, and Yufan Chen. Mcpsecbench: A systematic security benchmark and playground for testing model context protocols, 2025. URL https://arxiv.org/abs/2508.13220.

[247] Gurusha Juneja, Alon Albalak, Wenyue Hua, and William Yang Wang. Magpie: A dataset for multi-agent contextual privacy evaluation. *arXiv preprint arXiv:2506.20737*, 2025.

[248] Hiroki Furuta, Izzeddin Gur, Fangchen Liu, Xiaolong Wang, Trevor Darrell, and Anna Rohrbach. Multimodal web navigation with instruction-finetuned foundation models. *arXiv preprint arXiv:2305.11854*, 2023. URL https://arxiv.org/abs/2305.11854.

[249] Peter Shaw, Mandar Joshi, James Cohan, Jonathan Berant, Panupong Pasupat, Hexiang Hu, Urvashi Khandelwal, Kenton Lee, and Kristina N Toutanova. From pixels to ui actions: Learning to follow instructions via graphical user interfaces. *Advances in Neural Information Processing Systems*, 36:34354–34370, 2023.

[250] Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, et al. Harmbench: A standardized evaluation framework for automated red teaming and robust refusal. In *International Conference on Machine Learning*, pages 35181–35224. PMLR, 2024.

[251] Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, George J Pappas, Florian Tramer, et al. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *Advances in Neural Information Processing Systems*, 37:55005–55029, 2024.

[252] Zeeshan Rasheed, Muhammad Waseem, Kari Systä, and Pekka Abrahamsson. Large language model evaluation via multi ai agents: Preliminary results. *arXiv preprint arXiv:2404.01023*, 2024.

[253] Jiawei Gu, Xuhui Jiang, Zhichao Shi, Hexiang Tan, Xuehao Zhai, Chengjin Xu, Wei Li, Yinghan Shen, Shengjie Ma, Honghao Liu, et al. A survey on llm-as-a-judge. *arXiv preprint arXiv:2411.15594*, 2024.

[254] Mingchen Zhuge, Changsheng Zhao, Dylan Ashley, Wenyi Wang, Dmitrii Khizbullin, Yunyang Xiong, Zechun Liu, Ernie Chang, Raghuraman Krishnamoorthi, Yuandong Tian, et al. Agent-as-a-judge: Evaluate agents with agents. *arXiv preprint arXiv:2410.10934*, 2024.

[255] Sejin Lee, Jian Kim, Haon Park, Ashkan Yousefpour, Sangyoon Yu, and Min Song. sudo rm-rf agentic_security. *arXiv preprint arXiv:2503.20279*, 2025.

[256] Xing Han Lù, Amirhossein Kazemnejad, Nicholas Meade, Arkil Patel, Dongchan Shin, Alejandra Zambrano, Karolina Stańczak, Peter Shaw, Christopher J Pal, and Siva Reddy. Agentrewardbench: Evaluating automatic evaluations of web agent trajectories. *arXiv preprint arXiv:2504.08942*, 2025.

[257] Yanan Chen, Ali Pesaranghader, Tanmana Sadhu, and Dong Hoon Yi. Can we rely on llm agents to draft long-horizon plans? let's take travelplanner as an example. *arXiv preprint arXiv:2408.06318*, 2024.

[258] Tianle Li, Ge Zhang, Quy Duc Do, Xiang Yue, and Wenhu Chen. Long-context llms struggle with long in-context learning. *arXiv preprint arXiv:2404.02060*, 2024.

[259] Mengkang Hu, Tianxing Chen, Qiguang Chen, Yao Mu, Wenqi Shao, and Ping Luo. Hiagent: Hierarchical working memory management for solving long-horizon agent tasks with large language model. *arXiv preprint arXiv:2408.09559*, 2024.

[260] Chenkai Sun, Denghui Zhang, ChengXiang Zhai, and Heng Ji. Beyond reactive safety: Risk-aware llm alignment via long-horizon simulation. *arXiv preprint arXiv:2506.20949*, 2025.

[261] Evan Hubinger, Carson Denison, Jesse Mu, Mike Lambert, Meg Tong, Monte MacDiarmid, Tamera Lanham, Daniel M Ziegler, Tim Maxwell, Newton Cheng, et al. Sleeper agents: Training deceptive llms that persist through safety training. *arXiv preprint arXiv:2401.05566*, 2024.

[262] Jen-tse Huang, Jiaxu Zhou, Tailin Jin, Xuhui Zhou, Zixi Chen, Wenxuan Wang, Youliang Yuan, Michael R Lyu, and Maarten Sap. On the resilience of llm-based multi-agent collaboration with faulty agents. *arXiv preprint arXiv:2408.00989*, 2024.

[263] Pengfei He, Yupin Lin, Shen Dong, Han Xu, Yue Xing, and Hui Liu. Red-teaming llm multi-agent systems via communication attacks. *arXiv preprint arXiv:2502.14847*, 2025.

[264] Terry Tong, Fei Wang, Zhe Zhao, and Muhao Chen. Badjudge: Backdoor vulnerabilities of llm-as-a-judge. In *ICLR*, 2025.

[265] Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pages 274–283. PMLR, 2018.

[266] Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pages 3–14, 2017.

[267] Andrew J Kerns, Daniel P Shepard, Jahshan A Bhatti, and Todd E Humphreys. Unmanned aircraft capture and control via gps spoofing. *Journal of field robotics*, 31(4):617–636, 2014.

[268] Nils Ole Tippenhauer, Christina Pöpper, Kasper Bonne Rasmussen, and Srdjan Capkun. On the requirements for successful gps spoofing attacks. In *Proceedings of the 18th ACM conference on Computer and communications security*, pages 75–86, 2011.

[269] Yulong Cao, Chaowei Xiao, Dawei Yang, Jing Fang, Ruigang Yang, Mingyan Liu, and Bo Li. Adversarial objects against lidar-based autonomous driving systems. *arXiv preprint arXiv:1907.05418*, 2019.

[270] Hocheol Shin, Dohyun Kim, Yujin Kwon, and Yongdae Kim. Illusion and dazzle: Adversarial optical channel exploits against lidars for automotive applications. In *International conference on cryptographic hardware and embedded systems*, pages 445–467. Springer, 2017.

[271] Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1625–1634, 2018.

[272] Simen Thys, Wiebe Van Ranst, and Toon Goedemé. Fooling automated surveillance cameras: adversarial patches to attack person detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, 2019.

[273] Brianna Zitkovich, Tianhe Yu, Sichun Xu, Peng Xu, Ted Xiao, Fei Xia, Jialin Wu, Paul Wohlhart, Stefan Welker, Ayzaan Wahid, et al. Rt-2: Vision-language-action models transfer web knowledge to robotic control. In *Conference on Robot Learning*, pages 2165–2183. PMLR, 2023.

[274] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan P Foster, Pannag R Sanketi, Quan Vuong, et al. Openvla: An open-source vision-language-action model. In *Conference on Robot Learning*, pages 2679–2713. PMLR, 2025.

[275] Chen Yifan, Mingjie Wei, Xuesong Wang, Yuanxing Liu, Jizhe Wang, Hao Song, Longxuan Ma, Donglin Di, Churui Sun, Kaifeng Liu, et al. Embodied ai: A survey on the evolution from perceptive to behavioral intelligence. *SmartBot*, 1(3):e70003, 2025.

[276] Dmitriy Rivkin, Francois Hogan, Amal Feriani, Abhisek Konar, Adam Sigal, Xue Liu, and Gregory Dudek. Aiot smart home via autonomous llm agents. *IEEE Internet of Things Journal*, 2024.

[265] Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International conference on machine learning*, pages 274–283. PMLR, 2018.

[266] Nicholas Carlini and David Wagner. Adversarial examples are not easily detected: Bypassing ten detection methods. In *Proceedings of the 10th ACM workshop on artificial intelligence and security*, pages 3–14, 2017.

[267] Andrew J Kerns, Daniel P Shepard, Jahshan A Bhatti, and Todd E Humphreys. Unmanned aircraft capture and control via gps spoofing. *Journal of field robotics*, 31(4):617–636, 2014.

[268] Nils Ole Tippenhauer, Christina Pöpper, Kasper Bonne Rasmussen, and Srdjan Capkun. On the requirements for successful gps spoofing attacks. In *Proceedings of the 18th ACM conference on Computer and communications security*, pages 75–86, 2011.

[269] Yulong Cao, Chaowei Xiao, Dawei Yang, Jing Fang, Ruigang Yang, Mingyan Liu, and Bo Li. Adversarial objects against lidar-based autonomous driving systems. *arXiv preprint arXiv:1907.05418*, 2019.

[270] Hocheol Shin, Dohyun Kim, Yujin Kwon, and Yongdae Kim. Illusion and dazzle: Adversarial optical channel exploits against lidars for automotive applications. In *International conference on cryptographic hardware and embedded systems*, pages 445–467. Springer, 2017.

[271] Kevin Eykholt, Ivan Evtimov, Earlence Fernandes, Bo Li, Amir Rahmati, Chaowei Xiao, Atul Prakash, Tadayoshi Kohno, and Dawn Song. Robust physical-world attacks on deep learning visual classification. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 1625–1634, 2018.

[272] Simen Thys, Wiebe Van Ranst, and Toon Goedemé. Fooling automated surveillance cameras: adversarial patches to attack person detection. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition workshops*, 2019.

[273] Brianna Zitkovich, Tianhe Yu, Sichun Xu, Peng Xu, Ted Xiao, Fei Xia, Jialin Wu, Paul Wohlhart, Stefan Welker, Ayzaan Wahid, et al. Rt-2: Vision-language-action models transfer web knowledge to robotic control. In *Conference on Robot Learning*, pages 2165–2183. PMLR, 2023.

[274] Moo Jin Kim, Karl Pertsch, Siddharth Karamcheti, Ted Xiao, Ashwin Balakrishna, Suraj Nair, Rafael Rafailov, Ethan P Foster, Pannag R Sanketi, Quan Vuong, et al. Openvla: An open-source vision-language-action model. In *Conference on Robot Learning*, pages 2679–2713. PMLR, 2025.

[275] Chen Yifan, Mingjie Wei, Xuesong Wang, Yuanxing Liu, Jizhe Wang, Hao Song, Longxuan Ma, Donglin Di, Churui Sun, Kaifeng Liu, et al. Embodied ai: A survey on the evolution from perceptive to behavioral intelligence. *SmartBot*, 1(3):e70003, 2025.

[276] Dmitriy Rivkin, Francois Hogan, Amal Feriani, Abhisek Konar, Adam Sigal, Xue Liu, and Gregory Dudek. Aiot smart home via autonomous llm agents. *IEEE Internet of Things Journal*, 2024.