C++ Programming

Multidimensional Arrays

Homework 3: Tic Tac Toe

Mostafa S. Ibrahim
Teaching, Training and Coaching since more than a decade!

Artificial Intelligence & Computer Vision Researcher
PhD from Simon Fraser University - Canada
Bachelor / Msc from Cairo University - Egypt
Ex-(Software Engineer / ICPC World Finalist)

NxN tic-tac-toe

- Read integer N for the dimension of tic-tac-toe (3 <= N <= 9). Then run a game of 2 users who keep playing till one of them wins or tie. Print the grid after each round. Checkout below

```
3
Player x turn. Enter empty location (r, c): 1 1
x..
...
...
Player o turn. Enter empty location (r, c): 3 1
x..
...
o..
Player x turn. Enter empty location (r, c): 2 2
x..
.x.
o
```

```
Player o turn. Enter empty location (r, c): 2 1
x..
ox.
o..
Player x turn. Enter empty location (r, c): 2 2
Invalid input. Try again
Player x turn. Enter empty location (r, c): 5 5
Invalid input. Try again
Player x turn. Enter empty location (r, c): 3 3
x..
ox.
o.x
Player x won
|
```

"Acquire knowledge and impart it to the people."

"Seek knowledge from the Cradle to the Grave."