
Partial Marks toward Total Marks Unmarked or yet-to-be-marked submissions are considered 0 for now!


Discussion Board toward Bonus Closes before Final Exam Please do not post spams!
















Digital Design (Logic Circuits)
Computer Architecture
Assembly Language
Operating Systems

John von Neumann

(<u>/vpn 'nɔɪmən/</u>) 1903 –1957


Mathematician, Physicist, Computer Scientist, Engineer

Polymath

He integrated pure and applied sciences. He made major contributions to many fields, including:

- Mathematics
- Physics
- Economics (game theory)
- Computing
- Statistics









Operating System

A program for programs! System-level Program





Computer

Memory

Kernel: Device Manager

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager

Bus





```
Storage Device == String of Bytes == File
fcntl.h: create(), open(): O_CREAT, O_EXCL, O_APPEND, ...
unistd.h: read(), write(), lseek(), close()
File Descriptor: Standard FDs, dup() vs. open()
I/O Redirection
```

Storage File System: i-Node, Data Blocks, Groups, Partitions, Files, Directories, Deleting/Moving/Copying Fragmentation

Computer

Memory

Kernel: Device Manage

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manage

Kernel: Process Manager













Bootstrapping a program: main(), memory layout and the segments: cs, ds, bss, ss,

Stack and return addresses

Heap and dynamic allocation

Process Identifier: getpid()

Process Termination, Exit Status, Normal vs. Abnormal Exit

Multiprocessing:

Why? Processor Sharing/Scheduling, fork(), parent vs. child, Orphan, Zombie, wait()

Child generation models

Grandchild, Multiple children

fork() VS. exec()

Process Life Cycle: Program, Ready, Run, Blocked, Terminated



Computer

Memory

Kernel: Device Manage

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager









Inter-Process Communication (IPC)

One way parent to child

Two way but harsh: signaling, kill(), signal handling, default action, ignoring, ...

Two way but normal: Sharing a single file, unnamed file: pipe(), named file: FIFO,

Synchronized: Producer-Consumer

Computer

Memory

Kernel: Device Manager

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager







Network Inter-Process Communication (IPC) Network Protocol: TCP/IP, UDP, TCP, IP, PORT

UDP: shoot a mail

Sender-Receiver: socket(), bind(), sendto(), recvfrom()

TCP: a phone call

The Server: socket(), bind(), listen(), accept(), recv(), send() Clients: socket(), bind(), connect(), send(), recv()

signal handling, default action, ignoring, ...

Two way but normal: Sharing a single file, unnamed file: pipe(), named file: FIFO,

Synchronized: Producer-Consumer

Computer

Memory

Kernel: Device Manager

Kernel: Memory Manager

Kernel: File Manage

Kernel: Network Manager

Kernel: Process Manager









Design Patterns

Daemon: Active/Passive, Background, Memory-resident

Daemonize: Orphan child with logfile

Shared Library: Daemon Library, Web Service

Computer

Memory

Kernel: Device Manager

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager







Design Patterns for Application-Level Programs

Shared Libraries

Is it possible to share standard library routines for all processes, inside or outside a computer?

https://cs-fundamentals.com/c-programming/static-and-dynamic-linking-in-c

STATIC LINK

At compile time, using linker include!



OP Code stdio.h

OP Code

```
      0001
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      00000
      0000
      0000
      0000
      0000
```

Linker

```
      0001
      0000
      0000
      0010
      0000
      0000
      0000
      1100

      00f1
      0000
      0003
      0000
      0000
      0000
      0000
      0000
      0000

      0000
      0000
      0000
      0000
      0300
      0110
      0111
      0000


      0046
      0000
      0220
      0000
      0000
      0000
      0000
      2200

      0111
      0000
      0000
      0000
      0000
      0000
      0000
      0000

      0011
      0000
      0003
      0000
      0000
      0000
      0000
      0000
      0000

      0001
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000

      0001
      0000
      0000
      0000
      0000
      0000
      0000
      0000
      0000
```



Computer


Memory

Kernel

Shell

Bus





Computer

Memory

Kernel

Shell

Process1: Program + Data sys

Bus




STATIC LINK

From Kernel's POV, everything is the same!

1) Building the Static Library



Roots of a quadratic equation!



2) Using the Static Library

```
#include <stdio.h>
int add(int, int);
int sub(int, int);
int multi(int, int);
int sqrt(int);
...

void main(void) {
    printf("2 + 3 = %d\n", add(2,3));
    printf("2 - 3 = %d\n", sub(2,3));
    ...
}
Function calls
```

```
#include <stdio.h>
```

```
int add(int, int);
int sub(int, int);
int multi(int, int);
int sqrt(int);
...
```

Functions prototypes into another file → Library Header File → mathlib.h

```
void main(void) {
        printf("2 + 3 = %d\n", add(2,3));
        printf("2 - 3 = %d\n", sub(2,3));
        ...
}
```

```
:~$ vi mathlib.h
int add(int, int);
int sub(int, int);
int multi(int, int);
int sqrt(int);
//...
```

```
#include <stdio.h>

#include "mathlib.h"

void main(void) {
        printf("2 + 3 = %d\n", add(2,3));
        printf("2 - 3 = %d\n", sub(2,3));
}
```

```
:~$ vi mathlib.h
int add(int, int);
int sub(int, int);
int multi(int, int);
int sqrt(int);
//...
```

```
#include <stdio.h>
#include "mathlib.h"
void main(void) {
      printf("2 + 3 = d^n, add(2,3));
      printf("2 - 3 = dn, sub(2,3));
hfani@alpha:~$ cc main.c -c
hfani@alpha:~$ cc main.o mathlib.a -o main
hfani@alpha:~$ ./main
2 + 3 = 5
2 - 3 = -1
hfani@alpha:~$ size ./main
           data
                              dec
                                       hex filename
   text
                     bss
                                       8bf ./main
   1647
             584
                        8
                             2239
```


Includes main.o as well as object files of mathlib.a <u>that are used</u>

main.o add.o

sub.o

DYNAMIC LINK

At run time, using kernel call!




Memory

Kernel

Shell

Bus





Memory


Kernel

Shell

Process1: Program + Data

Bus





Memory


Kernel

Shell

Process1: Program + Data

Bus





Memory

Kernel


Shell

Sys

Process1: Program + Data

Bus





Memory

Kernel


Shell

Sys

Process1: Program + Data

Bus





Memory

Kernel


Shell


Sys

Process1: Program + Data

Bus







Memory

Kernel

Shell



Process1: Program + Data


Bus



1) Building the Dynamic Library cc *.c -c -fPIC
Position Independent Code (PIC)







Convention: *.so

so: Shared Objects

2) Using the Dynamic Library

```
#include <stdio.h>

#include "mathlib.h"

void main(void) {
    printf("2 + 3 = %d\n", add(2,3));
    printf("2 - 3 = %d\n", sub(2,3));
}
```

The same as in using static library!

```
:~$ vi mathlib.h
int add(int, int);
int sub(int, int);
int multi(int, int);
int sqrt(int);
//...
```

```
#include <stdio.h>
#include "mathlib.h"
void main (void) {
      printf("2 + 3 = d^n, add(2,3));
      printf("2 - 3 = dn, sub(2,3));
hfani@alpha:~$ cc main.c -c
hfani@alpha:~$ cc main.o mathlib.so -o main
hfani@alpha:~$ ./main
./main: error while loading shared libraries: mathlib.so: cannot open shared o
```

Either put your lib in the standard location Or tell the shell the kernel where to find it

```
#include <stdio.h>
#include "mathlib.h"
void main (void) {
      printf("2 + 3 = d^n, add(2,3));
      printf("2 - 3 = dn, sub(2,3));
hfani@alpha:~$ cc main.c -c
hfani@alpha:~$ cc main.o mathlib.so -o main
hfani@alpha:~$ ./main
./main: error while loading shared libraries: mathlib.so: cannot open shared o
hfani@alpha:~$ LD LIBRARY PATH=$LD LIBRARY PATH:./
hfani@alpha:~$ export LD LIBRARY PATH
hfani@alpha:~$ ./main
2 + 3 = 5
2 - 3 = -1
```


System Variable for the path of shared libs

```
#include <stdio.h>
#include "mathlib.h"
void main (void) {
       printf("2 + 3 = d^n, add(2,3));
       printf("2 - 3 = dn, sub(2,3));
hfani@alpha:~$ cc main.c -c
hfani@alpha:~$ cc main.o mathlib.so -o main
hfani@alpha:~$ ./main
./main: error while loading shared libraries: mathlib.so: cannot open shared o
hfani@alpha:~$ LD LIBRARY PATH=$LD LIBRARY PATH:./
hfani@alpha:~$ export LD LIBRARY PATH
hfani@alpha:~$ ./main
2 + 3 = 5
                                                          Does it include main.o only
2 - 3 = -1
                                                          Or also includes add.o, sub.o, ...?
hfani@alpha:~$ size ./main
                                      hex filename
            data-
                     bss
                              dec
   text
                                      8f6 ./main
             616
                       8
                             2294
```

STATIC vs. DYNAMIC

Speed vs. Memory

Whether Static When the process ends, the library is removed from memory!



Memory

Kernel


Shell

Process1: Program + Data sys

Bus



or Dynamic When the process ends, the library is removed from memory!



Memory

Kernel


Shell

Sys

Process1: Program + Data

Bus





Memory

Kernel


Shell



Process1: Program + Data

Bus





Memory

Kernel


Shell

Bus



Is it possible to daemanize a library?

Is it possible to daemanize a library? Static Library: No (Why?)



Memory

Kernel


Shell

Process1: Program + Data sys

Bus



Is it possible to daemanize a library? Dynamic Library: Yes (Why?)



Memory

Kernel

Shell

Sys

Process1: Program + Data

Bus



Shared Libraries Daemon Dynamic Libraries

Shared Libraries Daemon Dynamic Libraries

The sharing scope is within the computer!

Globally Shared Libraries

All around the world, processes can use a single shared library

Is it possible to share the library with other computers? sample final exam question

The Server (TCP) uses a Shared Library

Clients all around the word send their math questions to The Server and get the results.

The Server can charge a fee!

The Server (TCP) Web Services Cloud Services