


LEC02


Lectures > Lec02: Shell > Lec02


LAB02


Labs > Lab02: Working Environment Setup > Lab02






















Boot is short for bootstrap pull oneself up by one's bootstraps

Computer

Memory





1. Fetch

Must be an instruction Otherwise, raise error Memory

Current OP Code

Next OP Code

Instruction Pointer (IP) Program Counter (PC)



$$2. IP = IP + 1$$

Memory

Current OP Code

Next OP Code

Instruction Pointer (IP)
Program Counter (PC)

Processor



Current OP Code



Could be in parallel to fetch

Memory


Current OP Code

Next OP Code

Instruction Pointer (IP) Program Counter (PC) Processor



Current OP Code



$$2. IP = IP + 1$$

Memory

Current OP Code

Next OP Code

Instruction Pointer (IP)
Program Counter (PC)

Processor



Next OP Code

3. Execute

Memory

Current OP Code

Next OP Code


Instruction Pointer (IP)
Program Counter (PC)

Processor



Next OP Code

What happens?




0000





Turn ON





BIOS


Basic I/O System













MBR

Master Boot Record


Master Boot Record (MBR)




Kernel



Kernel





Memory

Kernel: Device Manager

Kernel: Memory Manager


Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager

Bus





Memory

Kernel: Device Manager

Kernel: Memory Manager

Kernel: File Manager

Kernel: Network Manager

Kernel: Process Manager

Bus



Keystroke

mouse click, usb plug, graphic show,

E.g., Keystroke Backspace Caps Lock A Win Key Menu Ctrl

Computer

Memory


Kernel

Bus



E.g., Keystroke

1. Electric Signal



Computer

Memory

Kernel

Bus




E.g., Keystroke

Win Key


2. Kernel's Device Manager for Keyboard

Backspace

Menu Ctrl



E.g., Keystroke 3. IP = F01A0Backspace Caps Lock A Win Key Menu Ctrl



E.g., Keystroke Who does IP = F01A0? Backspace Caps Lock A Win Key Menu Ctrl

Computer

Memory

Kernel

Device Manager

F01A0 Keyboard

Bus


Processor

?



E.g., Keystroke

Who does IP = F01A0? Electrical Signal → Kernel's Program



Computer

Memory

Kernel

Device Manager

Keyboard

Bus

Processor


7

F01A0



E.g., Keystroke

Interrupt Request (IRQ)
Interrupt Request Handler



Computer

Memory

Kernel

Device Manager

Keyboard

Bus

Processor


?


F01A0




bob@suse	1:~> sudo	cat /proc/interrup	ots	IRQ	Usage
	CPUO			0	system timer (cannot be changed)
ä.		TO ADTO	28	1	keyboard controller (cannot be changed)
0:	78	IO-APIC-edge	timer	2	cascaded signals from IRQs 8–15
1:	9012	IO-APIC-edge	18042	3	second RS-232 serial port (COM2: in Windows)
3:	1	IO-APIC-edge		4	first RS-232 serial port (COM1: in Windows)
		1000 1000 1000 1000 1000 1000 1000 100		5	parallel port 2 and 3 or sound card
4:	6609	IO-APIC-edge	63 000 000 000	6	floppy disk controller
6:	7	IO-APIC-edge	floppy	7	first parallel port
7:	0	IO-APIC-edge	parport0	8	real-time clock
8:	1	IO-APIC-edge	rtc0	9	open interrupt
			370.333	10	open interrupt
9:	0	IO-APIC-fasteoi	acpı	11 12	open interrupt
12:	101705	IO-APIC-edge	18042	13	PS/2 mouse
14:	1374	IO-APIC-edge	ata_piix	14	math coprocessor primary ATA channel
15:	28050	IO-APIC-edge	ata piix	15	secondary ATA channel
16:	893	IO-APIC-fasteoi	Ensoniq AudioP(CI	
17:	77088	IO-APIC-fasteoi	ioco, ehci hcd:	usb1	
18:	112	IO-APIC-fasteoi	uhci hcd:usb2		
19:	5167	IO-APIC-fasteoi	eth0		
40:	0	PCI-MSI-edge	PCIe PME, pcieł	np	
41:	0	PCI-MSI-edge	PCIe PME, pcieł	np	
42:	0	PCI - MSI - edge	PCIe PME, pcieł	np	
43:	0	PCI-MSI-edge	PCIe PME, pcieł		
44:	0	PCI-MSI-edge	PCIe PME, pcieł	250	
45:	0	PCI-MSI-edge	PCIe PME, pciel	1000	
46:	0	PCI-MSI-edge	PCIe PME, pcieł	1.44	

hfani	i@ch	narlie:~\$ pro	cinfo			(3)	IRQ	Usage
Memor	cy:	Total	Used	Free	But	ffer	0	system timer (cannot be changed)
RAM:		264118524	22664004	241454520	105	5852	1	keyboard controller (cannot be changed)
Swap		67378172		67378172			2	cascaded signals from IRQs 8–15
owep.		0/5/01/2	·	0/3/01/2		22	3	second RS-232 serial port (COM2: in Windows)
_							4	first RS-232 serial port (COM1: in Windows)
Booti	ıp:	Thu Aug 19 1	5:26:13 2021	Load avera	ige: 0	17 0	5	parallel port 2 and 3 or sound card
							6	floppy disk controller
user		lw 1d 12	:02:18.71 5.	3% page in	1 :		7	first parallel port
nice	:	00	:33:45.08 0.	0% page ou	it:		8	real-time clock
syste			:48:23.42 14.			25	9	open interrupt
							10	open interrupt
IOwai				0% page de			11	open interrupt
hw i				0% page fl		3_	12	PS/2 mouse
sw i	rq:	09	:31:11.65 0.	2% swap in	1 :	-	13	math coprocessor
idle	= 1	18w 1d 12	:22:16.05 79.	9% swap ou	it:	22	14	primary ATA channel
uptir	ne:	1w 2d 23	:19:40.99	context	: :	2 3	15	secondary ATA channel
irq	0:	49	2-edge timer	irq	33:	363	6919	1572868-edge eth0
irq	1:	4	1-edge i8042	irq	34:	1253	4197	1572869-edge eth0
irq	8:	1	8-edge rtc0	irq	35:	372	8604	1572870-edge eth0
irq	9:	. 0	9-fasteoi acp	i irq	36:	606	4430	1572871-edge eth0
irq	12:	6	12-edge i8042	irq	37:	553	5547	1572872-edge eth0
irq	14:	. 0	14-edge pata_	atii irq	39:	626	4652	1048576-edge mega
irq	15:	. 0	15-edge pata	atii irq	41:		0	1574912-edge eth1
irq	16:	6	16-fasteoi oh	ci h irq	42:	43	0781	1574913-edge eth1
irq	17:	. 0	17-fasteoi eh	ci h irq	43:	43	0781	1574914-edge eth1
irq	18:	37	18-fasteoi oh	ci h irq	44:	43	0781	1574915-edge eth1
irq	19:	2	19-fasteoi eh	ci h irq	45:	43	0781	1574916-edge ethl









Keystroke Hack keylogger

Application-level vs. System-level





Keystroke Hack Shutdown

Application-level vs. System-level

Program → Process





Program → Process Hello World!

"Then the LORD God formed a man from the dust of the ground and breathed into his nostrils the breath of life, and the man became a living being." - Genesis 2:7

hfani@alpha:~\$ vi hello.c

Assembly

Compiler

Assembler

```
#include <stdio.h>
void main() {
    printf("hello world!");
}
```

<printf@plt>:

jmpq 401000 <.plt>

<main>:

push %rbp
mov %rsp,%rbp

lea 0xfd5(%rip),%rdi

mov \$0x0, %eax

callq 401010 <printf@plt>

nop


pop %rbp

retq

OP Code

hfani@alpha:~\$ cc hello.c -o hello

 0001
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 0000
 00000
 0000
 0000
 0000
 0000



Computer

Memory to Store

Kernel

FF1C0


Process Manager
Program → Process

Bus


Processor

?





- 1. Locate the program: /home/hfani/...
- 2. Call Process Manager for loading the program IP = FF1C0
- 3. Point IP to the first line of the program IP = &first opcode



SHELL

Application-level program to act as a Dispatcher