



DETAIL E

SCALE 2 : 1

J1705 PinOut (Recommended cable P/N hCBL0035)

Pin	Type (Hardware name)	Type (Software name)
1	CANFD1_P	can0
2	CANFD1_N	can0
3	CANFD2_P	can1
4	CANFD2_N	can1
5	CANFD3_P	can2
6	CANFD3_N	can2
7	START_1	IN_START
8	NC	---
9	NC	---
10	ETH2_RX_P	eth0
11	ETH2_RX_N	eth0
12	Digital_output_ETH2_ACT	ETH2_ACT

Pin	Type (Hardware name)	Type (Software name)
13	CANFD4_P	can3
14	CANFD4_N	can3
15	CANFD5_P	can4
16	CANFD5_N	can4
17	NC	---
18	NC	---
19	START_2	IN_START
20	NC	---
21	NC	---
22	ETH0_TX_P	eth0
23	ETH0_TX_N	eth0
24	GND	---





DETAIL F

SCALE 2 : 1

J1700 PinOut (Recommended cable P/N hLCB0037)

Pin	Type (Hardware name)	Type (Software name)
1	Digital_input_pulldown_1	IN_PULLDOWN1
2	Digital_input_pulldown_2	IN_PULLDOWN2
3	Digital_input_pullup_1	IN_PULLUP1
4	Digital_input_pullup_2	IN_PULLUP2
5	NC	---
6	NC	---
7	SOURCE_OUT_4	pwr_out_active
8	GND	---
9	SOURCE_Digital_OUT_1	OUT_SOURCE1
10	SOURCE_Digital_OUT_2	OUT_SOURCE2
11	SINK_OUT_1	OUT_SINK1
12	SINK_OUT_2	OUT_SINK2
13	NC	---
14	NC	---
15	SOURCE_OUT_5	pwr_out_active
16	GND	---

J1703 Pinout (Recommended cable P/N hCBL0038)

Pin	Type (Hardware name)	Type (Software name)
1	CANFD6_P	can5
2	CANFD6_N	can5
3	NC	---
4	START_3	IN_START
5	SOURCE_OUT_7	---
6	GND	---
7	NC	---
8	NC	---
9	NC	---
10	SOURCE_Digital_OUT_6	pwr_out_active
11	SOURCE_Digital_OUT_8	pwr_out_equipment
12	GND	---



DETAIL G

SCALE 2 : 1

J1701 Pinout (Recommended cable P/N hCBL0036)

Pin	Type (Hardware name)	Type (Software name)
1	Digital_input_HMI_1	IN_HMI1
2	GND	---
3	SOURCE_PWR_OUT_LED_1	pwr_out_led_1
4	Digital_input_HMI_2	IN_HMI2
5	SOURCE_PWR_OUT_LED_2	pwr_out_led_2
6	A_MIC_IN (future stakeholder)	---
7	A_GND (future stakeholder)	---
8	SOURCE_PWR_OUT_BUZZER	pwr_out_buzzer

J1702 Pinout (Recommended cable P/N hCBL0033)

Pin	Type (Hardware name)	Type (Software name)
1	SOURCE_OUT_3	---
2	START_5	IN_START
3	GND	---

HOST Mobility

General surface rough: N/A
General tolerance SS-ISO 2768-1
Surface Treatment:
Material:

Description: Host Monitor X connectors and buttons
Scale: 1:1
Orientation:
Finish:

Project	Host ArtNo	Variant	Format
HMX	HM010	00111 / 11111	A2

Author	Date	Drw. No.	Weight	Sheet	Revision
ViktorB	2024-05-23	800125		1	V6B

C:_PDM\Host Mobility\Host Monitor X (HM010-00111 & 11111)\800125_HMX assembly ports





DETAIL M

SCALE 2 : 1

J1704 Pinout (Recommended cable P/N hCBL0034)

Pin	Type (Hardware name)	Type (Software name)
1	VCC_PJ_IN	---
2	START_4	IN_START
3	VCC_PJ_IN	---
4	GND	---
5	GND	---



HOST Mobility

General surface rough: N/A		Surface Treatment:	
General tolerance SS-ISO 2768-1		Material:	
Description: Host Monitor X connectors and buttons		Scale: 1:1	Orientation:
		Finish:	
Project: HMX	Host ArtNo: HM010	Variant: 00111 / 11111	Format: A2
Author: ViktorB	Date: 2024-05-23	Drw. No.: 800125	Weight: / Sheet: 2 / Revision: V6B

C:_PDM\Host Mobility\Host Monitor X (HM010-00111 & 11111)\800125_HMX assembly ports