

Classification of a Melanoma with Deep Learning

Silvan Hostettler, Urs Mayr, Vera Jäggi

1 Introduction - Classes

Goal to classify three types of skin growth.

Class	Nevus	Seborrheic keratosis	Melanoma
Appears at	Birth (congenital)	Increased age	Increased age
<u>Risk</u>	Benign (harmless)	Benign (harmless)	malign (harmfull cancer)
<u>Characet</u> <u>ristics</u>	 hyperpigmented mostly single colored mostly arised skin Can turn into a Melanoma! 	 Flat/raised papule /plaque mostly one single smooth, waxy or warty surface Can look similar to a Melanoma 	ABCDE Rule (vs. Nevus) - Asymmetry - Border irregular in shape. - Color multicolored - Diameter > 6mm in diameter, - Evolution change characteristics over time.

2 Data

Melanoma Detection Dataset from Kaggle.

- Unbalanced data

	# total images
test	600
train	2000
valid	150

3 Models and Methods

- 1. Baseline Model (with RandomForest [RF])
- 2. Pretrained Neuronal Network [NN]
- 3. Train a ConvolutionalNN from scratch

RF and pretrained NN used the weights of the CNN VGG:

4 Results and Discussion

Model	Loss	Accuracy
Baseline model with RF	NA	0.70
Pretrained VGG	1.52	0.63
CNN from Scratch	0.80	0.68

1. Baseline model with RF

The Baseline model using the Random Forest as classification lead to the highest accuracy with 70 %.

RF uses no distribution assumption and can handle well imbalanced data sets (weighted random forest, balanced random forest).


2. Pretrained VGG with

The pretrained VGG has the highest loss function and the lowest accuracy of all the trained models. This is surprising as the model provides 4096 features for the final densely connected classifier.

[...] 4 Results and Discussion


3. CNN from Scratch:

Overfitting (accuracy of Train data > test data)
Solution: data augmentation, neuronal dropout






9 Sample Images of "Seborrheic Keratosis" Missqualifie



9 Sample Images of "Melanoma" Missqualified



4 Conclusion

Data difficulties:

- Different pixel size/coloring of images
- Imbalanced data
- Cumbersome data load -> writing of new data import function
 Language/Versioning difficulties:
- Tensorflow/Keras better documented for Python than for R
- Image data augmentation seems to depend on the version of keras and tensorflow. -> data augmentation skipped

Findings:

- Baseline model with RF best classification accuracy
- From scratch trained CNN: Minimization of loss and the accuracy vary among the batch_sizes.
 - -> Effect is not completely understood.
 - Hypothesis: model optimization algorithm ADAM aims for solution with larger weights -> lower test accuracy

5 Base script

Skript: https://github.com/hosts1/ethz-deepl-melanoma

References

- 1. https://www.kaggle.com/datasets/wanderdust/skin-lesion-analysis-toward-melanoma-detection/code.
- $2.\ \underline{\text{https://tensorchiefs.github.io/dl\ rcourse\ 2022/}}.$
- 3. https://tensorflow.rstudio.com/.
- ${\bf 4.} \ \underline{https://tensorflow.rstudio.com/guides/keras/preprocessing_layers.}$
- 5. https://medium.com/mini-distill/effect-of-batch-size-on-training-dynamics-21c14f7a716e