

13.14 — Converting constructors, explicit, and delete

ALEX JULY 25, 2021

By default, C++ will treat any constructor as an implicit conversion operator. Consider the following case:

```
1  #include <cassert>
2  #include <iostream>
3
4  class Fraction
5  {
6  private:
7      int m_numerator;
8      int m_denominator;
9
10 public:
11     // Default constructor
12     Fraction(int numerator = 0, int denominator = 1)
13         : m_numerator(numerator), m_denominator(denominator)
14     {
15         assert(denominator != 0);
16     }
17
18     // Copy constructor
19     Fraction(const Fraction& copy)
20         : m_numerator(copy.m_numerator), m_denominator(copy.m_denominator)
21     {
22         // no need to check for a denominator of 0 here since copy must already be a valid
23         // Fraction
24         std::cout << "Copy constructor called\n"; // just to prove it works
25     }
26
27     friend std::ostream& operator<<(std::ostream& out, const Fraction& f1);
28     int getNumerator() { return m_numerator; }
29     void setNumerator(int numerator) { m_numerator = numerator; }
30 };
31
32 void printFraction(const Fraction& f)
33 {
34     std::cout << f;
35 }
36
37 std::ostream& operator<<(std::ostream& out, const Fraction& f1)
38 {
39     out << f1.m_numerator << "/" << f1.m_denominator;
40     return out;
41 }
42
43 int main()
44 {
45     printFraction(6);
46
47     return 0;
48 }
```

Although function `printFraction()` is expecting a `Fraction`, we've given it the integer literal `6` instead. Because `Fraction` has a constructor willing to take a single integer, the compiler will implicitly convert the literal `6` into a `Fraction` object. It does this by initializing `printFraction()` parameter `f` using the `Fraction(int, int)` constructor.

Consequently, the above program prints:

```
6/1
```

This implicit conversion works for all kinds of initialization (direct, uniform, and copy).

Constructors eligible to be used for implicit conversions are called **converting constructors** (or **conversion constructors**).

The explicit keyword

While doing implicit conversions makes sense in the `Fraction` case, in other cases, this may be undesirable, or lead to unexpected behaviors:

```
1  #include <string>
2  #include <iostream>
3
4  class MyString
5  {
6  private:
7      std::string m_string;
8  public:
9      MyString(int x) // allocate string of size x
10     {
11         m_string.resize(x);
12     }
13
14     MyString(const char* string) // allocate string to hold string
15     value
16     {
17         m_string = string;
18     }
19
20     friend std::ostream& operator<<(std::ostream& out, const MyString&
21     s);
22
23     };
24
25     std::ostream& operator<<(std::ostream& out, const MyString& s)
26     {
27         out << s.m_string;
28         return out;
29     }
30
31     void printString(const MyString& s)
32     {
33         std::cout << s;
34     }
35
36     int main()
37     {
38         MyString mine = 'x'; // Will compile and use MyString(int)
39         std::cout << mine << '\n';
40
41         printString('x'); // Will compile and use MyString(int)
42         return 0;
43     }
```

In the above example, the user is trying to initialize a string with a char. Because chars are part of the integer family, the compiler will use the converting constructor `MyString(int)` constructor to implicitly convert the char to a `MyString`. The program will then print this `MyString`, to unexpected results. Similarly, a call to `printString('x')` causes an implicit conversion that results in the same issue.

One way to address this issue is to make constructors (and conversion functions) explicit via the `explicit` keyword, which is placed in front of the function's name. Constructors and conversion functions made explicit will not be used for *implicit* conversions or copy initialization:

```
1  #include <string>
2  #include <iostream>
3
4  class MyString
5  {
6  private:
7      std::string m_string;
8  public:
9      // explicit keyword makes this constructor ineligible for implicit conversions
10     explicit MyString(int x) // allocate string of size x
11     {
12         m_string.resize(x);
13     }
14
15     MyString(const char* string) // allocate string to hold string value
16     {
17         m_string = string;
18     }
19
20     friend std::ostream& operator<<(std::ostream& out, const MyString& s);
21 };
22
23 std::ostream& operator<<(std::ostream& out, const MyString& s)
24 {
25     out << s.m_string;
26     return out;
27 }
28
29 void printString(const MyString& s)
30 {
31     std::cout << s;
32 }
33
34 int main()
35 {
36     MyString mine = 'x'; // compile error, since MyString(int) is now explicit and nothing will match
37     this
38     std::cout << mine;
39
40     printString('x'); // compile error, since MyString(int) can't be used for implicit conversions
41
42     return 0;
43 }
```

The above program will not compile, since `MyString(int)` was made explicit, and an appropriate converting constructor could not be found to implicitly convert 'x' to a `MyString`.

However, note that making a constructor explicit only prevents *implicit* conversions. Explicit conversions (via casting) are still allowed:

```
1  std::cout << static_cast<MyString>(5); // Allowed: explicit cast of 5 to
    MyString(int)
```

Direct or uniform initialization will also still convert parameters to match (uniform initialization will not do narrowing conversions, but it will happily do other types of conversions).

```
1  MyString str{'x'}; // Allowed: initialization parameters may still be implicitly converted to
    match
```

Best practice

Consider making your constructors and user-defined conversion member functions explicit to prevent implicit conversion errors.

The delete keyword

In our `MyString` case, we really want to completely disallow 'x' from being converted to a `MyString` (whether implicit or explicit, since the results aren't going to be intuitive). One way to partially do this is to add a `MyString(char)` constructor, and make it private:

```
1  #include <string>
2  #include <iostream>
3
4  class MyString
5  {
6  private:
7      std::string m_string;
8
9      MyString(char) // objects of type MyString(char) can't be constructed from outside the
      class
      {
      }
10
11  public:
12      // explicit keyword makes this constructor ineligible for implicit conversions
13      explicit MyString(int x) // allocate string of size x
14      {
15          m_string.resize(x);
16      }
17
18      MyString(const char* string) // allocate string to hold string value
19      {
20          m_string = string;
21      }
22
23      friend std::ostream& operator<<(std::ostream& out, const MyString& s);
24
25      std::ostream& operator<<(std::ostream& out, const MyString& s)
26      {
27          out << s.m_string;
28          return out;
29      }
30
31  int main()
32  {
33      MyString mine('x'); // compile error, since MyString(char) is private
34      std::cout << mine;
35      return 0;
36  }
```

However, this constructor can still be used from inside the class (private access only prevents non-members from calling this function).

A better way to resolve the issue is to use the “delete” keyword to delete the function:

```

1  #include <string>
2  #include <iostream>
3
4  class MyString
5  {
6  private:
7      std::string m_string;
8
9  public:
10     MyString(char) = delete; // any use of this constructor is an error
11
12     // explicit keyword makes this constructor ineligible for implicit
13     conversions
14     explicit MyString(int x) // allocate string of size x /
15     {
16         m_string.resize(x);
17     }
18
19     MyString(const char* string) // allocate string to hold string value
20     {
21         m_string = string;
22     }
23
24     friend std::ostream& operator<<(std::ostream& out, const MyString& s);
25
26 };
27
28 std::ostream& operator<<(std::ostream& out, const MyString& s)
29 {
30     out << s.m_string;
31     return out;
32 }
33
34 int main()
35 {
36     MyString mine('x'); // compile error, since MyString(char) is deleted
37     std::cout << mine;
38     return 0;
39 }

```

When a function has been deleted, any use of that function is considered a compile error.

Note that the copy constructor and overloaded operators may also be deleted in order to prevent those functions from being used.



Next lesson

13.15 Overloading the assignment operator



Back to table of contents



Previous lesson

13.13 Copy initialization

Leave a comment... Put C++ code between triple-backticks (markdown style):````Your C++ code here````

 Name*

 Email*



Avatars from <https://gravatar.com/> are connected to your provided email address.

Notify me about replies:



POST COMMENT

DP N N FOUT

Newest ▼

