

7.4 — Switch statement basics

ALEX JUNE 29, 2021

Although it is possible to chain many if-else statements together, this is both difficult to read and inefficient. Consider the following program:

```
1 #include <iostream>
2 void printDigitName(int x)
3 {
4     if (x == 1)
5         std::cout << "One";
6     else if (x == 2)
7         std::cout << "Two";
8     else if (x == 3)
9         std::cout << "Three";
10    else
11        std::cout <<
12    "Unknown";
13 }
14
15 int main()
16 {
17     printDigitName(2);
18
19     return 0;
20 }
```

While this example isn't too complex, `x` is evaluated up to three times (which is inefficient), and the reader has to be sure that it is `x` being evaluated each time (not some other variable).

Because testing a variable or expression for equality against a set of different values is common, C++ provides an alternative conditional statement called a **switch statement** that is specialized for this purpose. Here is the same program as above using a switch:

```

1  #include <iostream>
2
3  void printDigitName(int x)
4  {
5      switch (x)
6      {
7          case 1:
8              std::cout << "One";
9              return;
10             case 2:
11                 std::cout << "Two";
12                 return;
13             case 3:
14                 std::cout << "Three";
15                 return;
16             default:
17                 std::cout <<
18                 "Unknown";
19                 return;
20         }
21     }
22
23     int main()
24     {
25         printDigitName(2);
26
27         return 0;
28     }

```

The idea behind a **switch statement** is simple: an expression (sometimes called the **condition**) is evaluated to produce a value. If the expression's value is equal to the value after any of the **case labels**, the statements after the matching **case label** are executed. If no matching value can be found and a **default label** exists, the statements after the **default label** are executed instead.

Compared to the original **if statement**, the **switch statement** has the advantage of only evaluating the expression once (making it more efficient), and the **switch statement** also makes it clearer to the reader that it is the same expression being tested for equality in each case.

Best practice

Prefer **switch statements** over if-else chains when there is a choice.

Let's examine each of these concepts in more detail.

Starting a switch

We start a **switch statement** by using the **switch** keyword, followed by parentheses with the conditional expression that we would like to evaluate inside. Often the expression is just a single variable, but it can be any valid expression.

The one restriction is that the condition must evaluate to an integral type (see [lesson 4.1 -- Introduction to fundamental data types](#) if you need a reminder which fundamental types are considered integral types) or an enumerated type (covered in future [lesson 9.2 -- Enumerated types](#)), or be convertible to one. Expressions that evaluate to floating point types, strings, and most other non-integral types may not be used here.

For advanced readers

Why does the switch type only allow for integral (or enumerated) types? The answer is because switch statements are designed to be highly optimized. Historically, the most common way for compilers to implement switch statements is via a [jump tables](#) -- and jump tables

only work with integral values.

For those of you already familiar with arrays, a jump table works much like an array, an integral value is used as the array index to “jump” directly to a result. This can be much more efficient than doing a bunch of sequential comparisons.

Of course, compilers don’t have to implement switches using jump tables, and sometimes they don’t. There is technically no reason that C++ couldn’t relax the restriction so that other types could be used as well, they just haven’t done so yet (as of C++20).

Following the conditional expression, we declare a block. Inside the block, we use labels to define all of the values we want to test for equality. There are two kinds of labels.

Case labels

The first kind of label is the **case label**, which is declared using the `case` keyword and followed by a constant expression. The constant expression must either match the type of the condition or must be convertible to that type.

If the value of the conditional expression equals the expression after a `case label`, execution begins at the first statement after that `case label` and then continues sequentially.

Here’s an example of the condition matching a `case label` :

```
1  #include <iostream>
2  void printDigitName(int x)
3  {
4      switch (x) // x is evaluated to produce value 2
5      {
6          case 1:
7              std::cout << "One";
8              return;
9          case 2: // which matches the case statement here
10             std::cout << "Two"; // so execution starts
11             here
12             return; // and then we return to the caller
13          case 3:
14             std::cout << "Three";
15             return;
16          default:
17             std::cout << "Unknown";
18             return;
19      }
20  }
21
22  int main()
23  {
24      printDigitName(2);
25
26      return 0;
27  }
```

This code prints:

Two

In the above program, `x` is evaluated to produce value `2`. Because there is a case label with value `2`, execution jumps to the statement underneath that matching case label. The program prints `Two`, and then the `return statement` is executed, which returns back to the caller.

There is no practical limit to the number of case labels you can have, but all case labels in a switch must be unique. That is, you can not do this:

```

1 | switch (x)
  | {
2 |     case 54:
3 |     case 54: // error: already used value 54!
4 |     case '6': // error: '6' converts to integer value 54, which is already
   | used
   | }

```

The default label

The second kind of label is the **default label** (often called the **default case**), which is declared using the `default` keyword. If the conditional expression does not match any case label and a default label exists, execution begins at the first statement after the default label.

Here's an example of the condition matching the default label:

```

1 | #include <iostream>
2 | void printDigitName(int x)
3 | {
4 |     switch (x) // x is evaluated to produce value 5
5 |     {
6 |         case 1:
7 |             std::cout << "One";
8 |             return;
9 |         case 2:
10 |             std::cout << "Two";
11 |             return;
12 |         case 3:
13 |             std::cout << "Three";
14 |             return;
15 |         default: // which does not match to any case labels
16 |             std::cout << "Unknown"; // so execution starts
17 |             here
18 |             return; // and then we return to the caller
19 |     }
20 | }
21 |
22 | int main()
23 | {
24 |     printDigitName(5);
25 |     return 0;
26 | }

```

This code prints:

```
Unknown
```

The default label is optional, and there can only be one default label per switch statement. By convention, the `default case` is placed last in the switch block.

Best practice

Place the default case last in the switch block.

Taking a break

In the above examples, we used `return statements` to stop execution of the statements after our labels. However, this also exits the entire function.

A **break statement** (declared using the `break` keyword) tells the compiler that we are done executing statements within the switch, and that execution should continue with the statement after the end of the switch block. This allows us to exit a `switch statement` without exiting the entire function.

Here's a slightly modified example rewritten using `break` instead of `return`:

```
1  #include <iostream>
2  void printDigitName(int x)
3  {
4      switch (x) // x evaluates to 3
5      {
6          case 1:
7              std::cout << "One";
8              break;
9          case 2:
10             std::cout << "Two";
11             break;
12          case 3:
13             std::cout << "Three"; // execution starts
14             here
15             break; // jump to the end of the switch
16             block
17             default:
18                 std::cout << "Unknown";
19                 break;
20         }
21         // execution continues here
22         std::cout << " Ah-Ah-Ah!";
23     }
24
25 int main()
26 {
27     printDigitName(3);
28
29     return 0;
30 }
```

The above example prints:

```
Three Ah-Ah-Ah!
```

Best practice

Each set of statements underneath a label should end in a `break statement` or a `return statement`.

So what happens if you don't end a set of statements under a label with a `break` or `return`? We'll explore that topic, and others, in the next lesson.



Next lesson

7.5 Switch fallthrough and scoping



Back to table of contents



Previous lesson

7.3 Common if statement problems

Leave a comment... Put C++ code between triple-backticks (markdown style):````Your C++ code````



Name*



Email*



Avatars from <https://gravatar.com/> are connected to your provided email address.

Notify me about replies:



POST COMMENT

DP N N FOUT

Newest ▼

