

16.4 — Association

ALEX AUGUST 2, 2021

In the previous two lessons, we've looked at two types of object composition, composition and aggregation. Object composition is used to model relationships where a complex object is built from one or more simpler objects (parts).

In this lesson, we'll take a look at a weaker type of relationship between two otherwise unrelated objects, called an association. Unlike object composition relationships, in an association, there is no implied whole/part relationship.

Association

To qualify as an association, an object and another object must have the following relationship:

- The associated object (member) is otherwise unrelated to the object (class)
- The associated object (member) can belong to more than one object (class) at a time
- The associated object (member) does *not* have its existence managed by the object (class)
- The associated object (member) may or may not know about the existence of the object (class)

Unlike a composition or aggregation, where the part is a part of the whole object, in an association, the associated object is otherwise unrelated to the object. Just like an aggregation, the associated object can belong to multiple objects simultaneously, and isn't managed by those objects. However, unlike an aggregation, where the relationship is always unidirectional, in an association, the relationship may be unidirectional or bidirectional (where the two objects are aware of each other).

The relationship between doctors and patients is a great example of an association. The doctor clearly has a relationship with his patients, but conceptually it's not a part/whole (object composition) relationship. A doctor can see many patients in a day, and a patient can see many doctors (perhaps they want a second opinion, or they are visiting different types of doctors). Neither of the object's lifespans are tied to the other.

We can say that association models as "uses-a" relationship. The doctor "uses" the patient (to earn income). The patient uses the doctor (for whatever health purposes they need).

Implementing associations

Because associations are a broad type of relationship, they can be implemented in many different ways. However, most often, associations are implemented using pointers, where the object points at the associated object.

In this example, we'll implement a bi-directional Doctor/Patient relationship, since it makes sense for the Doctors to know who their Patients are, and vice-versa.

```

1  #include <functional> // reference_wrapper
2  #include <iostream>
3  #include <string>
4  #include <vector>
5
6  // Since Doctor and Patient have a circular dependency, we're going to forward declare Patient
7  class Patient;
8
9  class Doctor
10 {
11 private:
12     std::string m_name{};
13     std::vector<std::reference_wrapper<const Patient>> m_patient{};
14
15 public:
16     Doctor(const std::string& name) :
17         m_name{ name }
18     {
19     }
20
21     void addPatient(Patient& patient);
22
23     // We'll implement this function below Patient since we need Patient to be defined at that
24     point
25     friend std::ostream& operator<<(std::ostream& out, const Doctor& doctor);
26
27     const std::string& getName() const { return m_name; }
28 };
29
30 class Patient
31 {
32 private:
33     std::string m_name{};
34     std::vector<std::reference_wrapper<const Doctor>> m_doctor{}; // so that we can use it here
35
36     // We're going to make addDoctor private because we don't want the public to use it.
37     // They should use Doctor::addPatient() instead, which is publicly exposed
38     void addDoctor(const Doctor& doctor)
39     {
40         m_doctor.push_back(doctor);
41     }
42
43 public:
44     Patient(const std::string& name)
45         : m_name{ name }
46     {
47     }
48
49     // We'll implement this function below Doctor since we need Doctor to be defined at that
50     point
51     friend std::ostream& operator<<(std::ostream& out, const Patient& patient);
52
53     const std::string& getName() const { return m_name; }
54
55     // We'll friend Doctor::addPatient() so it can access the private function
56     Patient::addDoctor()
57     friend void Doctor::addPatient(Patient& patient);
58 };
59
60 void Doctor::addPatient(Patient& patient)
61 {
62     // Our doctor will add this patient
63     m_patient.push_back(patient);
64
65     // and the patient will also add this doctor
66     patient.addDoctor(*this);
67 }
68
69 std::ostream& operator<<(std::ostream& out, const Doctor& doctor)
70 {
71     if (doctor.m_patient.empty())
72     {
73         out << doctor.m_name << " has no patients right now";
74         return out;
75     }
76
77     out << doctor.m_name << " is seeing patients: ";
78     for (const auto& patient : doctor.m_patient)
79         out << patient.get().getName() << ' ';
80
81     return out;

```

```

57     return out;
58 }
59 std::ostream& operator<<(std::ostream& out, const Patient& patient)
60 {
61     if (patient.m_doctor.empty())
62     {
63         out << patient.getName() << " has no doctors right now";
64         return out;
65     }
66     out << patient.m_name << " is seeing doctors: ";
67     for (const auto& doctor : patient.m_doctor)
68         out << doctor.get().getName() << ' ';
69     return out;
70 }
71
72 int main()
73 {
74     // Create a Patient outside the scope of the Doctor
75     Patient dave{ "Dave" };
76     Patient frank{ "Frank" };
77     Patient betsy{ "Betsy" };
78
79     Doctor james{ "James" };
80     Doctor scott{ "Scott" };
81
82     james.addPatient(dave);
83
84     scott.addPatient(dave);
85     scott.addPatient(betsy);
86
87     std::cout << james << '\n';
88     std::cout << scott << '\n';
89     std::cout << dave << '\n';
90     std::cout << frank << '\n';
91     std::cout << betsy << '\n';
92
93     return 0;
94 }

```

This prints:

```

James is seeing patients: Dave
Scott is seeing patients: Dave Betsy
Dave is seeing doctors: James Scott
Frank has no doctors right now
Betsy is seeing doctors: Scott

```

In general, you should avoid bidirectional associations if a unidirectional one will do, as they add complexity and tend to be harder to write without making errors.

Reflexive association

Sometimes objects may have a relationship with other objects of the same type. This is called a reflexive association. A good example of a reflexive association is the relationship between a university course and its prerequisites (which are also university courses).

Consider the simplified case where a Course can only have one prerequisite. We can do something like this:

```

1  #include <string>
2  class Course
3  {
4  private:
5      std::string m_name;
6      const Course* m_prerequisite;
7
8  public:
9      Course(const std::string& name, const Course* prerequisite =
10         nullptr):
11         m_name{ name }, m_prerequisite{ prerequisite }
12     {
13     }
14 };

```

This can lead to a chain of associations (a course has a prerequisite, which has a prerequisite, etc...)

Associations can be indirect

In all of the previous cases, we've used either pointers or references to directly link objects together. However, in an association, this is not strictly required. Any kind of data that allows you to link two objects together suffices. In the following example, we show how a Driver class can have a unidirectional association with a Car without actually including a Car pointer or reference member:

```

1  #include <iostream>
2  #include <string>
3
4  class Car
5  {
6  private:
7      std::string m_name;
8      int m_id;
9
10 public:
11     Car(const std::string& name, int id)
12         : m_name{ name }, m_id{ id }
13     {
14     }
15
16     const std::string& getName() const { return m_name; }
17     int getId() const { return m_id; }
18 };
19
20 // Our CarLot is essentially just a static array of Cars and a lookup function to retrieve
21 // them.
22 // Because it's static, we don't need to allocate an object of type CarLot to use it
23 class CarLot
24 {
25 private:
26     static Car s_carLot[4];
27
28 public:
29     CarLot() = delete; // Ensure we don't try to create a CarLot
30
31     static Car* getCar(int id)
32     {
33         for (int count{ 0 }; count < 4; ++count)
34         {
35             if (s_carLot[count].getId() == id)
36             {
37                 return &(s_carLot[count]);
38             }
39         }
40
41         return nullptr;
42     }
43 };
44
45 Car CarLot::s_carLot[4]{ { "Prius", 4 }, { "Corolla", 17 }, { "Accord", 84 }, { "Matrix", 62 } };
46
47 class Driver
48 {
49 private:
50     std::string m_name;
51     int m_carId; // we're associated with the Car by ID rather than pointer
52
53 public:
54     Driver(const std::string& name, int carId)
55         : m_name{ name }, m_carId{ carId }
56     {
57     }
58
59     const std::string& getName() const { return m_name; }
60     int getCarId() const { return m_carId; }
61 };
62
63 int main()
64 {
65     Driver d{ "Franz", 17 }; // Franz is driving the car with ID 17
66
67     Car* car{ CarLot::getCar(d.getCarId()) }; // Get that car from the car lot
68
69     if (car)
70         std::cout << d.getName() << " is driving a " << car->getName() << '\n';
71     else
72         std::cout << d.getName() << " couldn't find his car\n";
73
74     return 0;
75 }

```

In the above example, we have a CarLot holding our cars. The Driver, who needs a car, doesn't have a pointer to his Car -- instead, he has the ID of the car, which we can use to get the Car from the CarLot when we need it.

In this particular example, doing things this way is kind of silly, since getting the Car out of the CarLot requires an inefficient lookup (a pointer connecting the two is much faster). However, there are advantages to referencing things by a unique ID instead of a pointer. For example, you can reference things that are not currently in memory (maybe they're in a file, or in a database, and can be loaded on demand). Also, pointers can take 4 or 8 bytes -- if space is at a premium and the number of unique objects is fairly low, referencing them by an 8-bit or 16-bit integer can save lots of memory.

Composition vs aggregation vs association summary

Here's a summary table to help you remember the difference between composition, aggregation, and association:

Property	Composition	Aggregation	Association
Relationship type	Whole/part	Whole/part	Otherwise unrelated
Members can belong to multiple classes	No	Yes	Yes
Members' existence managed by class	Yes	No	No
Directionality	Unidirectional	Unidirectional	Unidirectional or bidirectional
Relationship verb	Part-of	Has-a	Uses-a



Next lesson
16.5 Dependencies



Back to table of
contents



Previous lesson
16.3 Aggregation

Leave a comment... Put C++ code between triple-backticks (markdown style):````Your C++ code`



Name*



Email*



Avatars from <https://gravatar.com/> are connected to your provided email address.

Notify me about replies:



POST COMMENT

DP N N FOUT

Newest ▼

