

23.3 — Output with ostream and ios

ALEX AUGUST 2, 2021

In this section, we will look at various aspects of the ostream output class (ostream).

Note: All of the I/O functionality in this lesson lives in the std namespace. That means all I/O objects and functions either have to be prefixed with "std::", or the "using namespace std;" statement has to be used.

The insertion operator

The insertion operator (overload the insertion operator for your own classes.

In the lesson on [streams](#), you saw that both istream and ostream were derived from a class called ios. One of the jobs of ios (and ios_base) is to control the formatting options for output.

Formatting

There are two ways to change the formatting options: flags, and manipulators. You can think of flags as boolean variables that can be turned on and off. Manipulators are objects placed in a stream that affect the way things are input and output.

To switch a flag on, use the setf() function, with the appropriate flag as a parameter. For example, by default, C++ does not print a + sign in front of positive numbers. However, by using the std::ios::showpos flag, we can change this behavior:

```
1 | std::cout.setf(std::ios::showpos); // turn on the std::ios::showpos  
   | flag  
   | std::cout << 27 << '\n';
```

This results in the following output:

```
+27
```

It is possible to turn on multiple ios flags at once using the OR (|) operator:

```
1 | std::cout.setf(std::ios::showpos | std::ios::uppercase); // turn on the std::ios::showpos and  
   | std::ios::uppercase flag  
   | std::cout << 27 << '\n';
```

To turn a flag off, use the unsetf() function:

```
1 | std::cout.setf(std::ios::showpos); // turn on the std::ios::showpos flag
   | std::cout << 27 << '\n';
   | std::cout.unsetf(std::ios::showpos); // turn off the std::ios::showpos
   | flag
3 | std::cout << 28 << '\n';
```

This results in the following output:

```
+27
28
```

There's one other bit of trickiness when using `setf()` that needs to be mentioned. Many flags belong to groups, called format groups. A format group is a group of flags that perform similar (sometimes mutually exclusive) formatting options. For example, a format group named "basefield" contains the flags "oct", "dec", and "hex", which controls the base of integral values. By default, the "dec" flag is set. Consequently, if we do this:

```
1 | std::cout.setf(std::ios::hex); // try to turn on hex
   | output
2 | std::cout << 27 << '\n';
```

We get the following output:

```
27
```

It didn't work! The reason why is because `setf()` only turns flags on -- it isn't smart enough to turn mutually exclusive flags off. Consequently, when we turned `std::hex` on, `std::ios::dec` was still on, and `std::ios::dec` apparently takes precedence. There are two ways to get around this problem.

First, we can turn off `std::ios::dec` so that only `std::hex` is set:

```
1 | std::cout.unsetf(std::ios::dec); // turn off decimal
   | output
2 | std::cout.setf(std::ios::hex); // turn on hexadecimal
   | output
3 | std::cout << 27 << '\n';
```

Now we get output as expected:

```
1b
```

The second way is to use a different form of `setf()` that takes two parameters: the first parameter is the flag to set, and the second is the formatting group it belongs to. When using this form of `setf()`, all of the flags belonging to the group are turned off, and only the flag passed in is turned on. For example:

```
1 | // Turn on std::ios::hex as the only std::ios::basefield
   | flag
   | std::cout.setf(std::ios::hex, std::ios::basefield);
2 | std::cout << 27 << '\n';
```

This also produces the expected output:

```
1b
```

Using `setf()` and `unsetf()` tends to be awkward, so C++ provides a second way to change the formatting options: manipulators. The nice thing about manipulators is that they are smart enough to turn on and off the appropriate flags. Here is an example of using some manipulators to change the base:

```
1 std::cout << std::hex << 27 << '\n'; // print 27 in
  hex
  std::cout << 28 << '\n'; // we're still in hex
  std::cout << std::dec << 29 << '\n'; // back to
  decimal
```

This program produces the output:

```
1b
1c
29
```

In general, using manipulators is much easier than setting and unsetting flags. Many options are available via both flags and manipulators (such as changing the base), however, other options are only available via flags or via manipulators, so it's important to know how to use both.

Useful formatters

Here is a list of some of the more useful flags, manipulators, and member functions. Flags live in the `std::ios` class, manipulators live in the `std` namespace, and the member functions live in the `std::ostream` class.

Group	Flag	Meaning
	<code>std::ios::boolalpha</code>	If set, booleans print "true" or "false". If not set, booleans print 0 or 1

Manipulator	Meaning
<code>std::boolalpha</code>	Booleans print "true" or "false"
<code>std::noboolalpha</code>	Booleans print 0 or 1 (default)

Example:

```
1 std::cout << true << " " << false << '\n';
2 std::cout.setf(std::ios::boolalpha);
3 std::cout << true << " " << false << '\n';
4
5 std::cout << std::noboolalpha << true << " " << false <<
6 '\n';
7 std::cout << std::boolalpha << true << " " << false <<
8 '\n';
```

Result:

```
1 0
true false
1 0
true false
```

Group	Flag	Meaning
	<code>std::ios::showpos</code>	If set, prefix positive numbers with a +

Manipulator	Meaning
<code>std::showpos</code>	Prefixes positive numbers with a +
<code>std::noshowpos</code>	Doesn't prefix positive numbers with a +

Example:

```

1  std::cout << 5 << '\n';
2
3  std::cout.setf(std::ios::showpos);
4  std::cout << 5 << '\n';
5
6  std::cout << std::noshowpos << 5 <<
   '\n';
7

```

Result:

```

5
+5
5
+5

```

Group	Flag	Meaning
	<code>std::ios::uppercase</code>	If set, uses upper case letters

Manipulator	Meaning
<code>std::uppercase</code>	Uses upper case letters
<code>std::nouppercase</code>	Uses lower case letters

Example:

```

1  std::cout << 12345678.9 << '\n';
2
3  std::cout.setf(std::ios::uppercase);
4  std::cout << 12345678.9 << '\n';
5
6  std::cout << std::nouppercase << 12345678.9 <<
   '\n';
7
8  std::cout << std::uppercase << 12345678.9 <<
   '\n';

```

Result:

```

1.23457e+007
1.23457E+007
1.23457e+007
1.23457E+007

```

Group	Flag	Meaning
<code>std::ios::basefield</code>	<code>std::ios::dec</code>	Prints values in decimal (default)
<code>std::ios::basefield</code>	<code>std::ios::hex</code>	Prints values in hexadecimal
<code>std::ios::basefield</code>	<code>std::ios::oct</code>	Prints values in octal
<code>std::ios::basefield</code>	(none)	Prints values according to leading characters of value

Manipulator	Meaning
<code>std::dec</code>	Prints values in decimal
<code>std::hex</code>	Prints values in hexadecimal
<code>std::oct</code>	Prints values in octal

Example:

```

1  std::cout << 27 << '\n';
2
3  std::cout.setf(std::ios::dec,
4  std::ios::basefield);
5  std::cout << 27 << '\n';
6
7  std::cout.setf(std::ios::oct,
8  std::ios::basefield);
9  std::cout << 27 << '\n';
10
11 std::cout.setf(std::ios::hex,
12 std::ios::basefield);
13 std::cout << 27 << '\n';
14
15 std::cout << std::dec << 27 << '\n';
16 std::cout << std::oct << 27 << '\n';
17 std::cout << std::hex << 27 << '\n';

```

Result:

```

27
27
33
1b
27
33
1b

```

By now, you should be able to see the relationship between setting formatting via flag and via manipulators. In future examples, we will use manipulators unless they are not available.

Precision, notation, and decimal points

Using manipulators (or flags), it is possible to change the precision and format with which floating point numbers are displayed. There are several formatting options that combine in somewhat complex ways, so we will take a closer look at this.

Group	Flag	Meaning
<code>std::ios::floatfield</code>	<code>std::ios::fixed</code>	Uses decimal notation for floating-point numbers
<code>std::ios::floatfield</code>	<code>std::ios::scientific</code>	Uses scientific notation for floating-point numbers
<code>std::ios::floatfield</code>	(none)	Uses fixed for numbers with few digits, scientific otherwise
<code>std::ios::floatfield</code>	<code>std::ios::showpoint</code>	Always show a decimal point and trailing 0's for floating-point values

Manipulator	Meaning
<code>std::fixed</code>	Use decimal notation for values
<code>std::scientific</code>	Use scientific notation for values
<code>std::showpoint</code>	Show a decimal point and trailing 0's for floating-point values
<code>std::noshowpoint</code>	Don't show a decimal point and trailing 0's for floating-point values
<code>std::setprecision(int)</code>	Sets the precision of floating-point numbers (defined in <code>iomanip.h</code>)

Member function	Meaning
<code>std::precision()</code>	Returns the current precision of floating-point numbers
<code>std::precision(int)</code>	Sets the precision of floating-point numbers and returns old precision

If fixed or scientific notation is used, precision determines how many decimal places in the fraction is displayed. Note that if the precision is less than the number of significant digits, the number will be rounded.

```

1  std::cout << std::fixed << '\n';
   std::cout << std::setprecision(3) << 123.456 <<
2  '\n';
   std::cout << std::setprecision(4) << 123.456 <<
   '\n';
3  std::cout << std::setprecision(5) << 123.456 <<
   '\n';
   std::cout << std::setprecision(6) << 123.456 <<
4  '\n';
   std::cout << std::setprecision(7) << 123.456 <<
   '\n';
5
   std::cout << std::scientific << '\n';
   std::cout << std::setprecision(3) << 123.456 <<
6  '\n';
   std::cout << std::setprecision(4) << 123.456 <<
   '\n';
7  std::cout << std::setprecision(5) << 123.456 <<
   '\n';
8  std::cout << std::setprecision(6) << 123.456 <<
   '\n';
9  std::cout << std::setprecision(7) << 123.456 <<
   '\n';

```

Produces the result:

```

123.456
123.4560
123.45600
123.456000
123.4560000

1.235e+002
1.2346e+002
1.23456e+002
1.234560e+002
1.2345600e+002

```

If neither fixed nor scientific are being used, precision determines how many significant digits should be displayed. Again, if the precision is less than the number of significant digits, the number will be rounded.

```

1 | std::cout << std::setprecision(3) << 123.456 <<
   | '\n';
   | std::cout << std::setprecision(4) << 123.456 <<
2 | '\n';
   | std::cout << std::setprecision(5) << 123.456 <<
   | '\n';
3 | std::cout << std::setprecision(6) << 123.456 <<
   | '\n';
   | std::cout << std::setprecision(7) << 123.456 <<
4 | '\n';

```

Produces the following result:

```

123
123.5
123.46
123.456
123.456

```

Using the `showpoint` manipulator or flag, you can make the stream write a decimal point and trailing zeros.

```

1 | std::cout << std::showpoint << '\n';
   | std::cout << std::setprecision(3) << 123.456 <<
   | '\n';
   | std::cout << std::setprecision(4) << 123.456 <<
2 | '\n';
   | std::cout << std::setprecision(5) << 123.456 <<
   | '\n';
3 | std::cout << std::setprecision(6) << 123.456 <<
   | '\n';
   | std::cout << std::setprecision(7) << 123.456 <<
4 | '\n';

```

Produces the following result:

```

123.
123.5
123.46
123.456
123.4560

```

Here's a summary table with some more examples:

Option	Precision	12345.0	0.12345
Normal	3	1.23e+004	0.123
	4	1.235e+004	0.1235
	5	12345	0.12345
	6	12345	0.12345
Showpoint	3	1.23e+004	0.123
	4	1.235e+004	0.1235
	5	12345.	0.12345
	6	12345.0	0.123450
Fixed	3	12345.000	0.123
	4	12345.0000	0.1235
	5	12345.00000	0.12345
	6	12345.000000	0.123450
Scientific	3	1.235e+004	1.235e-001
	4	1.2345e+004	1.2345e-001
	5	1.23450e+004	1.23450e-001
	6	1.234500e+004	1.234500e-001

Width, fill characters, and justification

Typically when you print numbers, the numbers are printed without any regard to the space around them. However, it is possible to left or right justify the printing of numbers. In order to do this, we have to first define a field width, which defines the number of output spaces a value will have. If the actual number printed is smaller than the field width, it will be left or right justified (as specified). If the actual number is larger than the field width, it will not be truncated -- it will overflow the field.

Group	Flag	Meaning
<code>std::ios::adjustfield</code>	<code>std::ios::internal</code>	Left-justifies the sign of the number, and right-justifies the value
<code>std::ios::adjustfield</code>	<code>std::ios::left</code>	Left-justifies the sign and value
<code>std::ios::adjustfield</code>	<code>std::ios::right</code>	Right-justifies the sign and value (default)

Manipulator	Meaning
<code>std::internal</code>	Left-justifies the sign of the number, and right-justifies the value
<code>std::left</code>	Left-justifies the sign and value
<code>std::right</code>	Right-justifies the sign and value
<code>std::setfill(char)</code>	Sets the parameter as the fill character (defined in <code>iomanip.h</code>)
<code>std::setw(int)</code>	Sets the field width for input and output to the parameter (defined in <code>iomanip.h</code>)

Member function	Meaning
<code>std::fill()</code>	Returns the current fill character
<code>std::fill(char)</code>	Sets the fill character and returns the old fill character
<code>std::width()</code>	Returns the current field width
<code>std::width(int)</code>	Sets the current field width and returns old field width

In order to use any of these formatters, we first have to set a field width. This can be done via the `width(int)` member function, or the

`setw()` manipulator. Note that right justification is the default.

```
1 | std::cout << -12345 << '\n'; // print default value with no field width
   | std::cout << std::setw(10) << -12345 << '\n'; // print default with field width
   | std::cout << std::setw(10) << std::left << -12345 << '\n'; // print left justified
   | std::cout << std::setw(10) << std::right << -12345 << '\n'; // print right justified
   | std::cout << std::setw(10) << std::internal << -12345 << '\n'; // print internally
   | justified
```

This produces the result:

```
-12345
-12345
-12345
-12345
- 12345
```

One thing to note is that `setw()` and `width()` only affect the next output statement. They are not persistent like some other flags/manipulators.

Now, let's set a fill character and do the same example:

```
1 | std::cout.fill('*');
2 | std::cout << -12345 << '\n'; // print default value with no field width
   | std::cout << std::setw(10) << -12345 << '\n'; // print default with field width
   | std::cout << std::setw(10) << std::left << -12345 << '\n'; // print left justified
   | std::cout << std::setw(10) << std::right << -12345 << '\n'; // print right justified
3 | std::cout << std::setw(10) << std::internal << -12345 << '\n'; // print internally
   | justified
```

This produces the output:

```
-12345
****-12345
-12345****
****-12345
-****12345
```

Note that all the blank spaces in the field have been filled up with the fill character.

The ostream class and iostream library contain other output functions, flags, and manipulators that may be useful, depending on what you need to do. As with the istream class, those topics are really more suited for a tutorial or book focusing on the standard library (such as the excellent book “The C++ Standard Template Library” by Nicolai M. Josuttis).



Next lesson

23.4 Stream classes for strings



Back to table of contents



Previous lesson

23.2 Input with istream

Leave a comment... Put C++ code between triple-backticks (markdown style):````Your C++ code here````

 Name*

 Email* 

Avatars from <https://gravatar.com/> are connected to your provided email address.

Notify me about replies:



POST COMMENT

DP N N FOUT

Newest ▼

