

HotRod Type Resolution

STATIC TYPE SOLVER

types decided during layer generation

<code><column java-type="<class>"></code> <code><column converter="<converter>"></code>
<code><type-solver><when></code> e.g. ♦ T3
HotRod Static Dialect Rules e.g. ♦ D6

Highest precedence

Designated

Type Solver Rule

Dialect Rule

JDBC Driver

Lowest precedence

RUNTIME TYPE SOLVER

types decided at runtime

<code><expression>.type(<class>)</code> <code><expression>.type(<converter>)</code>
<code><runtime-type-solver><when></code> e.g. ♦ RT5
HotRod Runtime Dialect Rules e.g. ♦ RD9
JDBC Driver Defaults

CRUD Tables
CRUD Views
Nitro SELECTs
LiveSQL columns from Tables
LiveSQL columns from Views

Affects

LiveSQL Expressions

Legend for rules

- ♦ T3: Static Type Solver Rule #3
- ♦ D6: Static Dialect Rule #6
- ♦ RT5: Runtime Type Solver Rule #5
- ♦ RD9: Runtime Dialect Rule #9

LiveSQL Logging - Example:

```
SELECT
-- the following columns come from a table, so they always use STATIC type resolution
a.id as "id",
a.created as "created",
a.invoice_tax_codes as "invoiceTaxCodes",
a.amount as "amount",
a.paid as "paid",
-- the following columns are LiveSQL expressions, so they use RUNTIME type resolution
a.amount * 1.2 as "ag1",
case when (a.amount >= 200) then 'Y' else 'N' end as "vip",
extract(day from a.created) as "dom",
case when (a.paid = 'Y') then a.amount else 0 end as "paidAmount",
RANDOM_UUID() as "globalId"
FROM invoice a
WHERE a.id = ?
--- Query Columns (10) ---
* 1 id: java.lang.Integer, source: STATIC_DIALECT_RULE, rule #D9
* 2 created: java.sql.Timestamp, source: STATIC_DESIGNATED
* 3 invoiceTaxCodes: String[] (converter TaxCodesArrayConverter), source: STATIC_TYPESOLVER_RULE, rule #T3
* 4 amount: java.math.BigDecimal, source: STATIC_DIALECT_RULE, rule #D1
* 5 paid: java.lang.String, source: STATIC_DIALECT_RULE, rule #D13
* 6 ag1: java.lang.Double, source: RUNTIME_DESIGNATED
* 7 vip: Boolean (converter YNBooleanConverter), source: RUNTIME_DESIGNATED
* 8 dom: java.lang.Long, source: RUNTIME_TYPESOLVER_RULE, rule #RT1
* 9 paidAmount: java.math.BigDecimal, source: RUNTIME_DIALECT_RULE, rule #RD1
* 10 globalId: java.util.UUID, source: RUNTIME_JDBC_DRIVER_DEFAULT
```