SCHEDULE NOTES

1. LAP LENGTHS PER ACI 318–19 FOR GRADE 60 UNCOATED BARS
2. TOP BARS: HORIZ. BARS W/ MORE THAN 12" OF CONC. CAST BELOW
3. LIGHTWEIGHT CONC.: MULTIPLY BY 1.33

CLASS B TENSION LAP SPLICE (IN.)

BAR SIZE	f'c = 3,000 PSI		f'c = 4,000 PSI	
	OTHER	TOP	OTHER	TOP
#3	24	28	24	25
#4	29	38	25	33
#5	36	47	31	41
#6	SEE NOTE 2		37	49

NOTES:
1. VERT. BARS: USE OTHER VALUES
2. SPLICE #6 AND LARGER PER EOR

* VALUES IN INCHES

ROD	HOLE
5/8"	11/16"
3/4"	13/16"

MIN. EDGE 1 3/4"
MIN. END 7"

HOLDOWN	ANCHOR BOLT	EMBED. (IN.)	POST
HDU2	SB 5/8X24	18	DBL. 2X
	SSTB16	12 5/8	DBL. 2X
HDU8	SB 7/8X24 OR 7/8" DIA. THREADED ROD W/ PLATE WASHER	18	4X6
HDU14	SB1X30	24	6X6

1

LAP AND HOLDOWN SCHEDULES

SCALE: NTS

DETAIL	PROJECT	SCALE	DRAWN	DATE	DETAIL NO
LAP AND HOLDOWN SCHEDULES		NTS	KERF		1