


Prof. Kjersti Engan

ELE510 Image processing and computer vision

Finding depth from two views – summary (chap 13.6 Birchfield) 2023






Parts in course presentations is material from Cengage learning. It can be used for teaching, and it can be share it with students on access controlled web-sites (Canvas) for use in THIS course. **But it should not be copied or distributed further in any way** (by you or anybody).

Finding depth – known setup

- Rectified cameras: Use correspondence find disparity map
 - Remember correspondance constraints, and search the scan lines in the search space for best match. Let dp be disparity in pixels.
- Known geometry: f (focal length m) and T (baseline m), image resolution, r pixels/m in sensor.
- find depth Z from disparity in meter, d ($d = dp/r$) :

$$\begin{aligned} Z_l = Z_r = Z, \quad X_r = X_l - T \\ \left\{ \begin{array}{l} \frac{Z}{f} = \frac{X_l}{x_l} \\ \frac{Z}{f} = \frac{X_l - T}{x_r} \end{array} \right. &\Rightarrow \left\{ \begin{array}{l} X_l = \frac{Z}{f} x_l \\ X_l = \frac{Z}{f} x_r + T \end{array} \right. \\ \frac{Z}{f} (x_l - x_r) = T &\Rightarrow Z = \frac{fT}{x_l - x_r} = \frac{fT}{d} \end{aligned}$$




3D reconstruction from image pairs – unknown setup

- Find interest points (Harris-Stephens / SIFT)
 - Match interest points
 - Compute fundamental matrix F
 - Calibrate cameras (Zhangs), find K, K'
 - Estimate E from F, K and K' , find R, t
 - Compute camera matrices P and P' from K, K', R and t
- Calibrating stereo setup
- Use F to limit correspondence to 1D search. Find matching points in new image pairs (after calibration). For each matching image points x and x' , compute world point in scene using $(x,y), (x',y')$ P and P'

Optical Flow

Related to estimating disparity between stereo images is displacement between corresponding pixels in a pair of consecutive image frames in video



Optical Flow

- **Motion field** – projection onto 2D image of 3D velocity vectors of all points in the scene
- **Optical flow** – apparent motion of brightness patterns in the image plane (same as motion field if projected pixel value is the same / brightness constancy assumption)
 - **Lucas-Kanade** – all pixels in small regions share the same motion
 - **Horn-Schunck** – dense optical flow is found through regularization with the assumption that neighbouring pixels have similar displacements.
 - **FlowNet** etc - Newer methods with neural networks

Lucas Kanade




(a) Frame t



(b) Frame t+1

LUCAS-KANADE ALGORITHM



(c) Optical Flow Vectors

q_i are the pixels inside a window (around p).

I_x , I_y and I_t are partial derivatives

$$\begin{bmatrix} V_x \\ V_y \end{bmatrix} = \begin{bmatrix} \sum_i I_x(q_i)^2 & \sum_i I_x(q_i)I_y(q_i) \\ \sum_i I_y(q_i)I_x(q_i) & \sum_i I_y(q_i)^2 \end{bmatrix}^{-1} \begin{bmatrix} -\sum_i I_x(q_i)I_t(q_i) \\ -\sum_i I_y(q_i)I_t(q_i) \end{bmatrix}$$

