
Path-Gain Compressibility Determines Local Credit Assignment in Conductance-Based Dendrites

Anonymous Author(s)

Affiliation

Address

email

Abstract

Biologically plausible credit assignment requires replacing the compartment-specific errors of backpropagation with signals available to dendritic synapses. We study when a low-dimensional somatic broadcast can serve as such a substitute in conductance-based dendritic trees. We derive exact gradients showing that each synaptic update factorizes into a local eligibility term, presynaptic activity times driving force times input resistance, and a single non-local compartment error. This exposes the key approximation made by local learning: replacing the exact path-specific compartment error with a broadcast field. We show that shunting inhibition changes this approximation by modulating input resistance along dendritic paths and, when it preferentially attenuates high-gain paths, compresses the effective path-gain field. Across matched additive and shunting dendritic networks, shunting improves local-backprop gradient alignment and reduces gradient scale mismatch. Transported-error oracle experiments show that supplying the exact path-gain-transported error largely closes the local-learning gap, identifying broadcast fidelity as the dominant bottleneck. Under nonnegative conductances and rank-1 broadcast, shunting LocalCA approaches matched backpropagation ceilings on MNIST, Fashion-MNIST, and context-gating, while routed and harder-data diagnostics reveal when richer pathway-specific feedback is required. These results identify path-gain compressibility as a mechanistic condition under which simple local credit assignment is effective in dendritic networks.

1 Introduction

Credit assignment in deep networks usually depends on backpropagation: global error transport through symmetric pathways with no obvious biological substrate. Dendritic compartments suggest an alternative. Each synapse has access to rich local state such as driving force, membrane conductance, and branch voltage, while supervisory information could arrive as a low-bandwidth broadcast from the soma [14]. The question here is not whether such a broadcast can match unconstrained backpropagation in all settings, but when it is a faithful approximation to the exact dendritic credit signal.

Starting from conductance-based dendritic voltage equations [1], we derive exact gradients for dendritic trees (Theorem 1) and show that each synaptic gradient factorizes into purely local eligibility terms and a single non-local compartment error. Approximating that compartment error with a broadcast signal yields a theorem-facing local rule (3F), practical optimizer wrappers (4F/5F), and higher-rank feedback variants for tasks where different branches require different teaching signals.

34 The central finding is mechanistic: shunting can make low-bandwidth broadcast useful by improving
 35 the compressibility of the conductance-stage path-gain field. Dendritic branching creates multiple
 36 error paths from distal synapses to the soma. Excitatory and inhibitory synapse banks set the conduc-
 37 tance state of each compartment. Shunting makes inhibitory conductance enter the denominator, so
 38 inhibition changes input resistance and therefore the gain of every upstream path that passes through
 39 that compartment. This does not mean inhibition always helps. It helps rank-1 broadcast when it
 40 attenuates high-gain paths more than low-gain paths, narrowing or low-rank compressing the exact
 41 error field that the broadcast must approximate.

42 We quantify this chain with three diagnostics. First, exact-gradient reconstruction verifies that
 43 the mathematical factorization matches autograd to numerical precision. Second, gradient-fidelity
 44 measurements compare local and backprop gradients at matched parameters. Third, transported-error
 45 oracle experiments replace the broadcast with the exact path-gain-transported compartment error,
 46 isolating broadcast fidelity from other architectural factors. Across matched networks, shunting
 47 improves local-backprop alignment on MNIST (cosine 0.202 vs. 0.006) and greatly reduces scale
 48 mismatch (0.117 vs. 1.053). On noise resilience, transported error raises additive local learning from
 49 66.8% under rank-1 broadcast to 92.4–94.0%, nearly matching shunting at 94.3–95.2%.

50 **Contributions.** We make three claims: (i) exact conductance-tree credit factorizes into synapse-
 51 local eligibility and a path-specific compartment error (Theorem 1, Corollary 1); (ii) path-gain
 52 compressibility is a measurable mediator of when rank-1 broadcast approximates that compartment
 53 error, and shunting provides a biophysical route to such compression by changing input resistance
 54 along dendritic paths; and (iii) gradient-fidelity, transported-oracle, competence, and morphology
 55 experiments validate this mechanism while identifying the failure modes that require richer feedback.

56 The empirical story follows this sequence. Figure 1 defines the conductance tree, exact credit object,
 57 and broadcast taxonomy. Figure 2 verifies the exact factorization and measures local-backprop fidelity.
 58 Figure 3 links path-gain compressibility to broadcast fidelity, oracle transport, and learning. Figures 4
 59 and 5 show the practical supervised regimes and the morphology-dependent inhibitory operating
 60 point. Harder-data and routed-feedback experiments are reported as appendix diagnostics rather than
 61 headline benchmark claims.

62 2 Compartmental Voltage Model and Gradient Derivation

63 We use a steady-state conductance model derived from discretized passive cable dynamics [1, 2]. In
 64 normalized units, leak and inhibitory reversal are set to 0, the excitatory reversal is set to 1, and leak
 65 conductance is fixed at 1. Each compartment voltage is therefore a conductance-weighted average.
 66 Two properties of this form matter for what follows: local sensitivities depend on both driving force
 67 ($E - V$) and input resistance R^{tot} , and shunting inhibition corresponds to adding conductance when
 68 $E_{\text{inh}} \approx 0$. Throughout the paper we write dendritic morphologies as rooted trees $[b_1, b_2, \dots, b_D]$,
 69 where each factor gives the fan-in from one dendritic stage to the next on the path to the soma. Thus
 70 $[3, 3]$ means that each soma aggregates 3 proximal branches and each proximal branch aggregates 3
 71 distal branches, for 9 distal leaves per soma. In code, each excitatory unit is a stack of branch layers,
 72 each branch layer carries explicit excitatory and optional inhibitory synapse banks plus a branch-to-
 73 parent aggregation map, and the headline feedforward regime keeps `somatic_synapses=false`
 74 so inputs terminate on dendritic branches rather than directly on the soma. The main experiments
 75 use `input_mode=1`: the transfer layer supplies nonnegative excitatory and inhibitory input streams,
 76 and inhibition enters through learned branch-level I-to-E conductance banks. This is input-driven
 77 shunting inhibition, not a recurrent lateral inhibitory circuit. The additive and shunting cores are
 78 therefore architecture-matched at the tree level; they differ only in the branch-level voltage integration
 79 rule. These ingredients play distinct roles in the credit-assignment argument. Branching creates the
 80 path structure. E/I synapse banks determine the local conductance state. Shunting turns inhibitory
 81 conductance into a multiplicative change in input resistance. The local learning rule then asks whether
 82 a low-dimensional teaching signal can stand in for the exact path-specific error induced by that tree.




Figure 1: **Model and credit assignment.** (A) Conductance-based dendritic neuron. Nonnegative excitatory and inhibitory inputs drive distal compartments, which feed proximal branches and then the soma. In the shunting model, inhibitory conductance enters the total conductance in the denominator, so it changes the input resistance and the gain of upstream paths. (B) Exact credit versus LocalCA. Backpropagation supplies compartment-specific errors $\partial L / \partial V_n$ at every dendritic level. LocalCA keeps the synapse-local eligibility term but replaces the exact compartment error with a low-bandwidth broadcast e_n that is routed down the tree. (C) Path gain through the tree. Exact backprop supplies a path-specific compartment error; rank-1 LocalCA replaces that field with one shared broadcast. (D) Broadcast approximations. Rank-1 shared broadcast, neuron-wise broadcast, rank- K random broadcast, path-structured broadcast, and transported oracle form a ladder from low-bandwidth local learning to an exact non-local upper bound.

2.1 Voltage Equation and Local Sensitivities

Consider compartment n with synaptic inputs j (activity x_j , reversal E_j , conductance $g_j^{\text{syn}} \geq 0$) and dendritic inputs from children (voltage V_j , conductance $g_j^{\text{den}} \geq 0$). The steady-state voltage is:

$$V_n = \frac{\sum_j E_j x_j g_j^{\text{syn}} + \sum_j V_j g_j^{\text{den}}}{\underbrace{\sum_j x_j g_j^{\text{syn}} + \sum_j g_j^{\text{den}} + 1}_{g_n^{\text{tot}}}}, \quad R_n^{\text{tot}} = 1/g_n^{\text{tot}}. \quad (1)$$

V_n is a convex combination of reversal potentials, child voltages, and leak. Writing $\mathcal{S}_n = \{0\} \cup \{E_j\}_j \cup \{V_j\}_j$, we have $\min \mathcal{S}_n \leq V_n \leq \max \mathcal{S}_n$ and $0 < R_n^{\text{tot}} \leq 1$. The local sensitivities follow directly:

Proposition 1 (Local Sensitivities).

$$\frac{\partial V_n}{\partial g_i^{\text{syn}}} = x_i R_n^{\text{tot}} (E_i - V_n), \quad \frac{\partial V_n}{\partial V_i} = g_i^{\text{den}} R_n^{\text{tot}}, \quad \frac{\partial V_n}{\partial g_i^{\text{den}}} = R_n^{\text{tot}} (V_i - V_n). \quad (2)$$

2.2 Shunting Inhibition as Divisive Gain Control

An inhibitory synapse with $E_{\text{inh}} \approx 0$ contributes current $(0 - V_n)x_j g_j^{\text{syn}}$ and increases g_n^{tot} . Its sensitivity is $\partial V_n / \partial g_j^{\text{syn}} = -x_j R_n^{\text{tot}} V_n$, which corresponds to multiplicative attenuation (divisive normalization). Shunting is divisive at the voltage level, but its effect on firing rates can be subtractive in some regimes [7]. Inhibitory plasticity can balance excitation dynamically [8]; our learned inhibitory conductances serve an analogous role. The same denominator also gives the direct

95 connection to path gain. Writing $G_n^E(x)$ and $G_n^I(x)$ for the total excitatory and inhibitory synaptic
96 conductance impinging on compartment n ,

$$R_n^{\text{tot}}(x) = (1 + G_n^E(x) + G_n^I(x) + G_n^{\text{den}})^{-1}.$$

97 Increasing $G_n^I(x)$ lowers $R_n^{\text{tot}}(x)$ and therefore multiplicatively suppresses every upstream path
98 whose error must pass through compartment n . In this sense inhibition can gate credit flow by
99 changing the path gain, even when the inhibitory drive is feedforward rather than lateral. Prop. 2
100 formalizes this statement after the tree path gain is defined.

101 2.3 Exact Gradients for Dendritic Trees

102 Let V_0 be the somatic output and define the soma/core error as $\delta_0 := \partial L / \partial V_0$. For a linear decoder
103 $\hat{y} = W_{\text{dec}} V_0$, this reduces to $\delta_0 = W_{\text{dec}}^\top (\partial L / \partial \hat{y})$; for a nonlinear decoder, δ_0 is the corresponding
104 decoder-input Jacobian product.

105 **Theorem 1** (Conductance-Stage Backpropagation on a Dendritic Tree). *For a rooted dendritic tree*
106 *with soma at node 0 and unique parent $p(n)$ for each non-somatic compartment, if each branch*
107 *passes its pre-activation voltage directly to its parent, then the loss gradient satisfies*

$$\frac{\partial L}{\partial V_n} = \frac{\partial L}{\partial V_{p(n)}} R_{p(n)}^{\text{tot}} g_{n \rightarrow p(n)}^{\text{den}}, \quad (3)$$

108 with boundary condition $\partial L / \partial V_0 = \delta_0$. Because the graph is a tree, each compartment has a unique
109 path to the soma. Defining the path gain

$$\alpha_n = \prod_{(i \rightarrow k) \in \text{path}(n \rightsquigarrow 0)} R_k^{\text{tot}} g_{i \rightarrow k}^{\text{den}}, \quad \frac{\partial L}{\partial V_n} = \alpha_n \delta_0, \quad (4)$$

110 with $\alpha_0 = 1$.

111 *Proof.* Apply the chain rule on the tree-structured computation graph using Prop. 1. $\square$

112 **Proposition 2** (Inhibitory control of conductance-stage path gain). *Let $\mathcal{A}(n)$ be the set of com-*
113 *partments on the path from compartment n to the soma, excluding n and including the parent*
114 *compartments through which the error must pass. Holding dendritic coupling conductances fixed, an*
115 *added inhibitory conductance $\Delta G_k^I(x) \geq 0$ at any $k \in \mathcal{A}(n)$ changes the conductance-stage path*
116 *gain by*

$$\frac{\alpha_n(x; \Delta G^I)}{\alpha_n(x; 0)} = \prod_{k \in \mathcal{A}(n)} \frac{g_k^{\text{tot}}(x)}{g_k^{\text{tot}}(x) + \Delta G_k^I(x)}, \quad \frac{\partial \log \alpha_n}{\partial G_k^I} = \begin{cases} -R_k^{\text{tot}}, & k \in \mathcal{A}(n), \\ 0, & k \notin \mathcal{A}(n). \end{cases} \quad (5)$$

117 *Proof.* Substitute $R_k^{\text{tot}} = 1/g_k^{\text{tot}}$ into the path-gain product in Eq. 4. Adding inhibitory conductance
118 changes only the denominator at compartments on the path from n to the soma, which gives the
119 product ratio and the log derivative. $\square$

120 Prop. 2 makes two directed predictions. First, inhibition is a path gate: it attenuates all credit paths
121 below the inhibited compartment. Second, inhibition is useful for rank-1 local learning only when this
122 attenuation makes the distribution of α_n more uniform or better aligned with the task. If inhibition
123 is too strong, too heterogeneous, or generated by a poorly calibrated inhibitory population, it can
124 suppress useful signals and hurt learning. In the additive control the same I input changes voltages
125 and local eligibilities, but it does not enter the conductance-stage path recursion as a multiplicative
126 resistance gate.

127 **Proposition 3** (When shunting compresses path gains). *Let $z_n = \log \alpha_n$ be the log path gain for*
128 *compartment n . If added inhibitory conductance contributes a path-dependent attenuation*

$$\beta_n(x) = \sum_{k \in \mathcal{A}(n)} \log \left(1 + \frac{\Delta G_k^I(x)}{g_k^{\text{tot}}(x)} \right), \quad z'_n = z_n - \beta_n, \quad (6)$$

129 then, over compartments or examples,

$$\text{Var}(z') = \text{Var}(z) + \text{Var}(\beta) - 2 \text{Cov}(z, \beta). \quad (7)$$

130 Thus shunting narrows the log path-gain field exactly when

$$\text{Cov}(z, \beta) > \frac{1}{2} \text{Var}(\beta). \quad (8)$$

131 *Proof.* Eq. 6 follows by taking the logarithm of the product ratio in Prop. 2. Eq. 7 is the variance
132 identity for $z - \beta$, and rearranging gives the condition. $\square$

133 Prop. 3 is the mechanism we test empirically. Shunting is not assumed to concentrate gains by default;
134 it concentrates or low-rank compresses the credit field only when inhibitory attenuation is aligned
135 with the high-gain paths. This is why the morphology and input-mode diagnostics are reported as
136 operating-regime tests rather than as monotonic “more inhibition is better” claims.

137 **Corollary 1** (Local–Global Factorization). *The exact synaptic gradient at compartment n factorizes*
138 *as:*

$$\frac{\partial L}{\partial g_i^{\text{syn}}} = \underbrace{x_i R_n^{\text{tot}} (E_i - V_n)}_{\text{synapse-local eligibility}} \cdot \underbrace{\frac{\partial L}{\partial V_n}}_{\text{compartment error}}, \quad (9)$$

139 where the eligibility term depends only on quantities available at synapse i (presynaptic activity
140 x_i , input resistance R_n^{tot} , driving force $E_i - V_n$), and the compartment error $\partial L / \partial V_n$ is the sole
141 non-local quantity.

142 Under identity upward transfer, this factorization isolates the only non-local quantity as $\partial L / \partial V_n =$
143 $\alpha_n \delta_0$. With a post-voltage activation $a_n = f_n(V_n)$ transmitted to the parent, the exact recursion
144 becomes $\partial L / \partial V_n = f'_n(V_n) (\partial L / \partial V_{p(n)}) R_{p(n)}^{\text{tot}} g_{n \rightarrow p(n)}^{\text{den}}$, so the compartment error remains the
145 sole non-local term but the effective path gain acquires local activation-derivative factors. Any
146 practical local rule therefore depends entirely on how well a broadcast signal approximates that exact
147 compartment error, which we evaluate in Sec. 4.2. In the models studied here, shunting improves
148 this approximation by reducing and stabilizing R_n^{tot} , which narrows the spread of local sensitivities
149 across the tree. The theorem is stated for the pre-reactivation compartment voltage V_n produced by
150 the conductance stage itself. In the empirical networks, each dendritic branch layer may optionally
151 apply a post-voltage reactivation $f(V_n)$ before passing activity to the next stage; unless otherwise
152 noted, the manuscript sweeps use a learnable bounded `param_tanh` reactivation. Our exact-error
153 diagnostics are computed on the hooked pre-reactivation voltage, so the factorization check and
154 compartment-error analyses target the conductance-stage quantity defined above rather than the
155 post-reactivation activity.

156 3 Local Learning Rules

157 3.1 Broadcast Error Approximation

158 We approximate the exact compartment error $\partial L / \partial V_n$ (Corollary 1) with a broadcast signal e_n
159 derived from the somatic/core error δ_0 . For a linear readout this reduces to $\delta_0 = W_{\text{dec}}^\top (\partial L / \partial \hat{y})$; for a
160 nonlinear decoder we use the corresponding decoder-input Jacobian product $J_{\text{dec}}(h_{\text{core}})^\top (\partial L / \partial \hat{y})$
161 so that the broadcast remains defined in the same core-space coordinates. We distinguish five feedback
162 objects:

- 163 • **Rank-1 shared broadcast:** $e_n = \bar{\delta} \cdot \mathbf{1}$, where $\bar{\delta} = \text{mean}(\delta_0)$ is one scalar field delivered
164 to all compartments.
- 165 • **Neuron-wise broadcast:** $e_n = \delta_0$ when the layer width matches the core/output error
166 dimension. In our headline feedforward settings this condition usually fails, so the default
167 historical “per-soma” implementation reduces to rank-1 shared broadcast.
- 168 • **Rank- K random broadcast:** $c = P_K \delta_0 \in \mathbb{R}^K$ and $e_n = \sum_{k=1}^K q_{n,k} c_k$, where P_K is a
169 fixed random projection and $q_{n,k}$ mixes those K channels into compartment n .

- **Path-structured broadcast:** $e_n = \alpha \bar{\delta} \cdot \mathbf{1} + (1-\alpha) \Gamma_n(\delta_0)$, where Γ_n projects the somatic error into router-inferred pathway roles, gates those roles by local pathway activity, and transports the resulting vector hierarchically through the block-structured dendritic tree.
- **Transported oracle:** $e_n^{\text{transport}} = \alpha_n \delta_0 = \partial L / \partial V_n$. This is an analysis upper bound, not a proposed local rule, because it supplies the exact path gain α_n from Theorem 1.

We use the historical `per_soma` implementation for most experiments, but in the main feedforward architectures it is effectively rank-1 because hidden widths exceed the decoder error dimension (Appendix Table S18). Under shunting, that deliberately low-bandwidth field is often sufficient on standard classification tasks. Routed tasks and rank-bridge controls in the appendix test the opposite regime, where rank-1 broadcast collapses branch identity and richer feedback is needed. A local-mismatch heuristic is included only as an appendix control because it performs much worse than the somatic-error broadcasts (Appendix A).

3.2 Three-Factor Rule (3F)

Definition 1 (3F Update). *For synaptic and dendritic conductances:*

$$\Delta g_j^{\text{syn}} = \eta \langle x_j R_n^{\text{tot}} (E_j - V_n) e_n \rangle_B, \quad \Delta g_j^{\text{den}} = \eta \langle R_n^{\text{tot}} (V_j - V_n) e_n \rangle_B, \quad (10)$$

where $\langle \cdot \rangle_B$ denotes the batch average.

The three factors are presynaptic activity x_j (or a voltage difference), postsynaptic modulation through driving force and input resistance, and the broadcast error e_n . The same rule applies to excitatory and inhibitory synapses. The sign difference comes from the driving force $(E_j - V_n)$.

Additive control. Rule (10) is the local gradient of the *shunting* voltage $V_n = \sum E_j g_j x_j / g_n^{\text{tot}}$. For the additive control ($V_n = \sum g_j x_j$, no divisive normalization), the correct local gradient is simpler: $\Delta g_j^{\text{syn}} = \eta \langle x_j e_n \rangle_B$, with no driving-force or R_n^{tot} terms ($R_n^{\text{tot}} \equiv 1$ by definition since there is no denominator). Throughout, each architecture uses the learning rule derived from its own forward-pass dynamics. This keeps the comparison architecture-matched rather than applying a shunting-derived rule to an additive model.

3.3 Practical Heuristic Wrappers: 4F and 5F

4F (heuristic attenuation proxy). In the conductance-stage recursion (4), the path gain α_n attenuates the somatic error differently at each compartment. To compensate without explicitly computing that gain, 4F uses an online correlation proxy

$$\rho_n = \text{Cov}(\bar{V}_n, \bar{V}_0) / (\sqrt{\text{Var}(\bar{V}_n) \text{Var}(\bar{V}_0)} + \varepsilon).$$

High ρ_n up-weights branches whose voltages covary with the soma; low ρ_n down-weights branches where the broadcast is likely to be a poor proxy.

5F (confidence-weighted 4F). 5F adds a second heuristic factor

$$\phi_n = \text{Var}(V_n) / (\sigma_{\text{res}}^2 + \varepsilon),$$

where σ_{res}^2 is the residual variance of V_n after linear regression on the parent voltage. Operationally, ϕ_n is a branch-wise confidence gate: it becomes large when local voltages are strong and stable relative to unexplained residual fluctuations, and small when local fluctuations dominate. We clamp it to $[0.25, 4.0]$ for stability. This factor is empirical, not theorem-derived. The paper’s core claim rests on the exact factorization, path-gain compressibility, and the transported-oracle experiment; the gain from ϕ_n should be read as practical denoising rather than theoretical necessity.

Proposition 4 (5F Update).

$$\Delta g_j^{\text{syn}} = \eta \rho_n \phi_n \langle x_j R_n^{\text{tot}} (E_j - V_n) e_n \rangle_B. \quad (11)$$

A feedback-alignment-style random-broadcast argument is included in Appendix C; it is supportive but not central to the main mechanism claim.

3.4 Structured pathway feedback and branch-role plasticity

For tasks with latent pathway structure, scalar broadcast can erase the distinction between different dendritic branches that should be credited differently. Recent experimental evidence supports the existence of vectorized instructive signals in cortical dendrites [43], motivating the structured feedback variant we introduce here. We therefore augment the local rule with a structured cue-routing variant, *PV-LocalCA*.

Hierarchical pathway-vector broadcast. The encoder/router defines a low-dimensional role basis over latent pathways. Instead of collapsing δ_0 to a rank-1 or neuron-wise broadcast, we project it into this role basis and gate each role by local pathway activity:

$$e_n^{\text{PV}} = \sum_{k=1}^K q_{n,k} c_k,$$

where $c_k = \langle r_k, \delta_0 \rangle$ are role coefficients and $q_{n,k}$ are local branch-role weights. Scalar broadcast is the special case $K=1$, while PV-LocalCA is a structured rank- K extension rather than a separate learning principle.

Router-derived branch roles. Rather than assigning hand-coded apical/basal labels, each branch j receives a normalized role profile r_j inferred from router assignments and incoming block weights. Plasticity is then gated by branch selectivity and by a synapse-specific role-alignment factor $\langle r_i, r_j \rangle$, biasing learning toward pathway-consistent afferents without imposing a fixed branch taxonomy.

4 Experiments

4.1 Setup

We evaluate two settings: a *capacity-calibrated* regime, where matched architectures achieve strong backprop performance, and *controlled sweeps* that isolate inhibition strength, broadcast mode, morphology, and architecture. The main text uses MNIST, Fashion-MNIST [37], context gating, and noise resilience; cue integration and CIFAR-10 are reported as appendix diagnostics because they are most useful for probing failure modes rather than establishing the core mechanism. Formal task definitions are in Appendix I. Architectures include point MLP baselines and dendritic cores with either additive integration or shunting. Main comparisons are architecture-matched additive vs. shunting cores and local vs. backprop training; DFA appears only as a supplementary baseline. Most MNIST, Fashion-MNIST, and context-gating results use 5F with the historical `per_soma` broadcast implementation. Because the hidden widths in these feedforward settings exceed the decoder output dimension, that implementation reduces to rank-1 shared broadcast in the main mechanism and competence sweeps; higher-rank controls then use explicit low-rank, path-propagation, path-transport, or pathway-vector variants. Unless otherwise stated, dendritic layers also use the learnable post-voltage reactivation `param_tanh`; Appendix Tables S11 and S12 then audit activation shape in a more controlled setting by comparing identity (none) against a frozen `param_tanh` under matched additive/shunting initialization. All dendritic runs supporting the main claims keep synaptic and dendritic conductances nonnegative via positive parameter transforms and enforce a nonnegative first-layer synaptic drive. Image inputs are used in $[0, 1]$, noise-resilience corruption is clipped back to $[0, 1]$, and context gating uses a nonnegative contextual figure-ground MNIST construction. The inhibition sweeps additionally use a transported-error oracle derived from Theorem 1 as an upper bound rather than as the proposed biological rule. Main mechanistic, oracle, competence, morphology, and activation-audit results use 5 seeds per condition unless otherwise noted. Appendix diagnostics state their seed counts in captions or tables.

The experiments follow three questions. First, does the exact factorization explain the gradient geometry observed in code? Second, does shunting change the path-gain field in the direction predicted by Props. 2 and 3, and does exact path transport rescue learning when rank-1 broadcast is insufficient? Third, do the same ingredients remain useful in capacity-calibrated supervised tasks and across dendritic morphologies?




Figure 2: Gradient-fidelity diagnostic. (A) Weighted cosine similarity between local and backprop gradients: shunting (green) is consistently more aligned than additive (blue) on both MNIST and context gating. (B) Gradient scale mismatch on the same matched-weight comparisons. Shunting is not only better aligned, but also substantially closer in norm. (C) Per-layer cosine similarity over training epochs. Shunting proximal layers approach high positive alignment; additive layers remain near zero. (D) Exact-factorization sanity check across all theory-diagnostic conditions, reported with relative L_2 reconstruction error and scale mismatch. Reconstructed gradients match autograd to numerical precision, showing that LocalCA’s only approximation is in the broadcast substitute for the compartment error.

255 4.2 From Exact Factorization to Credit-Signal Fidelity

256 To test whether these performance differences correspond to better credit signals, we compare
 257 local and backprop gradients on the same batch at the same parameter values. For each parameter
 258 tensor p , we compute directional alignment (cosine similarity) and scale mismatch, defined as
 259 $|\log_{10}(\|g_p^{\text{local}}\|/\|g_p^{\text{bp}}\|)|$, aggregated by parameter count.

260 Across matched-weight comparisons, shunting is consistently more aligned with backprop and
 261 substantially closer in norm than the additive control: on MNIST, weighted cosine rises from 0.006
 262 to 0.202 and scale mismatch falls from 1.053 to 0.117; on context gating, cosine rises from -0.007
 263 to 0.108 and scale mismatch falls from 2.154 to 0.036. Figure 2C shows that this advantage appears
 264 throughout training, especially in proximal layers and dendritic conductances. Figure 2D confirms
 265 that the theory is operational in code under the nonnegative-input setup: reconstructing gradients
 266 from Corollary 1 using exact compartment errors yields weighted relative reconstruction error below
 267 2×10^{-7} and weighted scale mismatch below 4×10^{-8} across runs. In a few low-norm parameter
 268 blocks, cosine becomes numerically unstable even though the reconstruction itself is essentially exact,
 269 so we report the norm-based diagnostics in the figure. The only approximation made by LocalCA is
 270 therefore the broadcast substitute for $\partial L/\partial V_n$.

271 4.3 Mechanistic Chain: Path Gains, Broadcast Fidelity, and Oracle Transport

272 Figure 3 provides the paper’s central empirical chain: shunting compresses conductance-stage path
 273 gains, which improves direct compartment-error fidelity, which in turn makes low-bandwidth local
 274 learning effective; the transported-error oracle then isolates how much of the remaining gap is due to
 275 broadcast quality rather than other architectural differences.

276 Panel A measures the coefficient of variation of the exact conductance-stage path gains α_n across
 277 compartments. On MNIST, shunting keeps this distribution much more compressed across inhibition
 278 levels (CV about 0.21–0.43), whereas the additive control remains much broader (CV about 0.90–
 279 1.16). Panel B then measures the sole non-local term from Corollary 1, $\partial L/\partial V_n$, directly. On
 280 the noise-resilience sweep, rank-1 broadcast tracks the exact compartment error somewhat better
 281 under shunting than under additive integration once inhibition is present: additive remains positively
 282 aligned throughout (about 0.14–0.19 across the sweep), while shunting rises to about 0.20–0.24 in
 283 the inhibited regimes after starting from a comparable low-inhibition baseline. The transported-error
 284 oracle obtained by recursively applying those conductance-stage path gains improves fidelity sharply
 285 in both architectures, reaching about 0.95–0.99 for additive and essentially 1.0 for shunting once
 286 inhibition is present, showing that the theorem defines an operational upper bound on low-bandwidth
 287 broadcast.

288 Panel C trains the same local rule using that oracle signal. On noise resilience, additive learning
 289 rises from 66.8% at $N_I=0$ to about 81–84% across the inhibited regimes under rank-1 broadcast,
 290 and transported broadcast lifts those same conditions to about 92–94%. Shunting rises from 54.3%




Figure 3: Mechanistic chain from path gains to learning. (A) Conductance-stage path-gain dispersion on MNIST, measured as the coefficient of variation of the exact tree attenuation α_n across compartments. Shunting keeps these conductance-stage path gains much more compressed than the additive control as inhibition increases. (B) Direct compartment-error fidelity on noise resilience. Solid lines compare the rank-1 broadcast e_n to the exact compartment error $\partial L / \partial V_n$; dashed lines show the transported-error oracle obtained by recursively applying conductance-stage path gains. Under the nonnegative-input setup, shunting still improves the simple rank-1 broadcast in the inhibited regimes, while the transported oracle defines the remaining approximation gap and becomes nearly exact once inhibition is present. (C) Learning with the transported-error oracle on noise resilience. Improving the broadcast field is enough to recover near-ceiling local learning, especially in the additive architecture where rank-1 broadcast fails most severely. (D) Global mechanism summary. Rank-1 cosine alignment (x-axis) vs. test accuracy (y-axis) across all conditions (additive/shunting $\times$ five inhibition levels $\times$ two datasets, 5 seeds each). Shunting cells (squares) cluster at high alignment and high accuracy; additive cells (circles) cluster at low alignment and low accuracy. The same monotonic chain from (A) through (C) collapses cleanly into the (alignment $\rightarrow$ accuracy) relationship shown here, and it holds on both MNIST and noise resilience, confirming that the mechanistic chain is not a dataset-specific artifact. The broadcast-bandwidth / quantization control previously shown as panel D is now reported separately as Appendix Fig. S6.

291 at $N_I=0$ to about 81–86% under rank-1 broadcast and to about 94.3–95.2% under transported
 292 broadcast. On MNIST, transported broadcast reaches about 95.4–96.6% for additive and 96.5–97.3%
 293 for shunting. Appendix Fig. S8 reports the same ladder on flattened CIFAR-10 as a harder-data stress
 294 test: shunting rises from 28.8% under rank-1 broadcast to 47.4% under transported error, nearly
 295 matching its 49.5% backprop ceiling. We use that result diagnostically rather than as a hard-vision
 296 benchmark claim. Together, the oracle results support path-gain fidelity as the dominant bottleneck for
 297 LocalCA performance, while the smaller remaining additive–shunting gap under matched transported
 298 broadcast suggests an additional contribution from conductance-shaped local sensitivities.

299 Panel D collapses the chain across all conditions into a single scatter of rank-1 cosine alignment
 300 against test accuracy. Shunting cells (squares) cluster at high alignment and high accuracy; additive
 301 cells (circles) cluster at the opposite end, and the same monotonic relationship holds on both
 302 MNIST and noise resilience. This is a compact confirmation that the (path-gain compressibility $\rightarrow$
 303 compartment-error fidelity $\rightarrow$ test accuracy) chain is not a dataset-specific artifact. Appendix controls
 304 fill in the boundaries: coarse quantized broadcasts preserve performance until sign-only or sparse
 305 broadcasts remove too much information (Fig. S6); rank- K and path-propagation feedback close part
 306 of the transported-oracle gap (Table S10); additive normalization and DFA help but do not match
 307 the shunting conductance model (Figs. S10, S7); and explicit inhibitory cells can generate useful
 308 path-gain structure in a one-layer input-mode probe (Fig. S11, Table S8).

309 4.4 Capacity-Calibrated Competence

310 Having established the mechanism, we next ask whether the same conditions improve end-task
 311 learning in architectures that are already competent under backpropagation. In the capacity-calibrated
 312 regime, shunting dendritic cores remain reasonably competitive under local learning: on MNIST,
 313 Fashion-MNIST, and context gating, the best local configuration (5F, rank-1 broadcast in these
 314 architectures, local decoder) stays within about 5–6 percentage points of the matched backprop
 315 ceiling (Table S4; Fig. 4). Within the local-rule family, 5F is the strongest practical wrapper, but
 316 it remains heuristic rather than theorem-derived; Appendix Tables S1, S3, and S2 summarize that
 317 division of labor across rules and broadcast choices. Classical random-feedback baselines remain
 318 much weaker on the same task family: in the matched MNIST appendix comparison, DFA reaches
 319 66.1% on shunting and 62.2% on additive, well below the 91.4% best shunting LocalCA result, while




Figure 4: **Capacity-calibrated competence and regime dependence.** (A) Matched backprop ceilings vs. the best rank-1 5F LocalCA rule on MNIST, Fashion-MNIST, and context gating. (B,C) Inhibitory dose-response and shunting advantage on MNIST and noise resilience. (D) Fashion-MNIST confirms a smaller but consistent shunting advantage. Error bars denote ± 1 s.d. across seeds.




Figure 5: **Morphology shifts the useful inhibitory regime.** (A,B) Additive and shunting LocalCA across dendritic morphologies and inhibitory synapse counts. (C,D) The shunting advantage peaks at different inhibition levels for shallow and deeper trees, showing that conductance normalization and morphology interact rather than contributing independently.

FA is not directly compatible with the block-structured dendritic layers (Appendix Fig. S7). This helps separate the contribution of the conductance architecture from the contribution of the LocalCA rule itself.

4.5 Regime Dependence of the Shunting Advantage

The benefit of shunting varies across tasks. With matched rank-1 broadcast, shunting is modestly better on MNIST and Fashion-MNIST, and the gap grows on the inhibition-sensitive noise-resilience benchmark once inhibitory conductance is present (Fig. 4). This is the expected regime dependence: shunting helps most when input resistance is part of the useful credit geometry rather than merely an added conductance load.

4.6 Morphology Shifts the Inhibitory Operating Regime

The inhibitory regime in which shunting helps most is not fixed across dendritic trees. In the morphology $\times$ inhibition sweep (Fig. 5), depth-2 trees show their largest shunting gains near $N_I=0$, whereas depth-3 trees retain their strongest gains around $N_I=5$. This supports the broader picture that tree geometry changes how inhibitory conductance shapes effective compartment sensitivities.

Scope. The claim is mechanistic, not an unconstrained benchmark claim: CIFAR-10, routed feedback, and depth scaling are diagnostics of where rank-1 broadcast breaks, and shunting is not a universal solution for hard vision or biological learning.

References

- [1] Koch, C. (1999). *Biophysics of Computation*. Oxford University Press.
- [2] Dayan, P., & Abbott, L. F. (2001). *Theoretical Neuroscience*. MIT Press.
- [3] Poirazi, P., Brannon, T., & Mel, B. W. (2003). Pyramidal neuron as two-layer neural network. *Neuron*, 37(6), 989–999.

- [4] London, M., & Häusser, M. (2005). Dendritic computation. *Annual Review of Neuroscience*, 28, 503–532.
- [5] Urbanczik, R., & Senn, W. (2014). Learning by the dendritic prediction of somatic spiking. *Neuron*, 81(3), 521–528.
- [6] Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, 13(1), 51–62.
- [7] Holt, G. R., & Koch, C. (1997). Shunting inhibition does not have a divisive effect on firing rates. *Neural Computation*, 9(5), 1001–1013.
- [8] Vogels, T. P., Sprekeler, H., Zenke, F., Clopath, C., & Gerstner, W. (2011). Inhibitory plasticity balances excitation and inhibition in sensory pathways and memory networks. *Science*, 334(6062), 1569–1573.
- [9] Lillicrap, T. P., Cownden, D., Tweed, D. B., & Akerman, C. J. (2016). Random synaptic feedback weights support error backpropagation for deep learning. *Nature Communications*, 7, 13276.
- [10] Nøkland, A. (2016). Direct feedback alignment provides learning in deep neural networks. *NeurIPS*, 29.
- [11] Guerguiev, J., Lillicrap, T. P., & Richards, B. A. (2017). Towards deep learning with segregated dendrites. *eLife*, 6, e22901.
- [12] Sacramento, J., Costa, R. P., Bengio, Y., & Senn, W. (2018). Dendritic cortical microcircuits approximate the backpropagation algorithm. *NeurIPS*, 31.
- [13] Whittington, J. C., & Bogacz, R. (2019). Theories of error back-propagation in the brain. *Trends in Cognitive Sciences*, 23(3), 235–250.
- [14] Richards, B. A., & Lillicrap, T. P. (2019). Dendritic solutions to the credit assignment problem. *Current Opinion in Neurobiology*, 54, 28–36.
- [15] Scellier, B., & Bengio, Y. (2017). Equilibrium propagation. *Frontiers in Computational Neuroscience*, 11, 24.
- [16] Song, Y., Millidge, B., Salvatori, T., Lukasiewicz, T., Xu, Z., & Bogacz, R. (2024). Inferring neural activity before plasticity as a foundation for learning beyond backpropagation. *Nature Neuroscience*, 27, 348–358.
- [17] Gretton, A., Bousquet, O., Smola, A. J., & Schölkopf, B. (2005). Measuring statistical dependence with Hilbert-Schmidt norms. *Algorithmic Learning Theory*, 63–77.
- [18] Frémaux, N., & Gerstner, W. (2016). Neuromodulated spike-timing-dependent plasticity, and theory of three-factor learning rules. *Frontiers in Neural Circuits*, 9, 85.
- [19] Bellec, G., et al. (2020). A solution to the learning dilemma for recurrent networks of spiking neurons. *Nature Communications*, 11, 3625.
- [20] Welford, B. P. (1962). Note on a method for calculating corrected sums of squares and products. *Technometrics*, 4(3), 419–420.
- [21] Turrigiano, G. G. (2008). The self-tuning neuron: synaptic scaling of excitatory synapses. *Cell*, 135(3), 422–435.
- [22] Payeur, A., Guerguiev, J., Zenke, F., Richards, B. A., & Naud, R. (2021). Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *Nature Neuroscience*, 24(7), 1010–1019.
- [23] Greedy, W., Zhu, H. W., Pemberton, J., Mellor, J., & Ponte Costa, R. (2022). Single-phase deep learning in cortico-cortical networks. *NeurIPS*, 35, 24213–24225.

- [24] Haider, P., Ellenberger, B., Kriener, L., Jordan, J., Senn, W., & Petrovici, M. A. (2021). Latent Equilibrium: A unified learning theory for arbitrarily fast computation with arbitrarily slow neurons. *NeurIPS*, 34.
- [25] Hinton, G. (2022). The forward-forward algorithm. *arXiv:2212.13345*.
- [26] Dellaferrera, G., & Kreiman, G. (2022). Error-driven input modulation: Solving the credit assignment problem without a backward pass. *Proceedings of the 39th International Conference on Machine Learning, Proceedings of Machine Learning Research*, 162, 4937–4955.
- [27] Lee, D.-H., et al. (2015). Difference target propagation. *ECML*, 498–515.
- [28] Meulemans, A., et al. (2021). Credit assignment in neural networks through deep feedback control. *NeurIPS*, 34.
- [29] Millidge, B., Seth, A. K., & Buckley, C. L. (2021). Predictive coding: A theoretical and experimental review. *arXiv:2107.12979*.
- [30] Koch, C., Poggio, T., & Torre, V. (1983). Nonlinear interactions in a dendritic tree. *PNAS*, 80(9), 2799–2802.
- [31] Silver, R. A. (2010). Neuronal arithmetic. *Nature Reviews Neuroscience*, 11(7), 474–489.
- [32] Max, K., Kriener, L., Pineda García, G. et al. (2024). Learning efficient backprojections across cortical hierarchies in real time. *Nature Machine Intelligence*, 6(6), 619–630.
- [33] Ma, C., Wu, J., Si, C., & Tan, K. C. (2024). Scaling supervised local learning with augmented auxiliary networks. *International Conference on Learning Representations (ICLR)*.
- [34] Lv, C., Xu, J., Lu, Y., Wang, X., Wang, Z., Xu, Z., Yu, D., Du, X., Zheng, X., & Huang, X. (2025). Dendritic Localized Learning: Toward Biologically Plausible Algorithm. *Proceedings of the 42nd International Conference on Machine Learning, Proceedings of Machine Learning Research*, 267, 41682–41700.
- [35] Erdogan, M., Pehlevan, C., & Erdogan, A. T. (2025). Error broadcast and decorrelation as a potential artificial and natural learning mechanism. *OpenReview*, NeurIPS 2025 spotlight.
- [36] Kao, C.-H., & Hariharan, B. (2024). Counter-Current Learning: A Biologically Plausible Dual Network Approach for Deep Learning. *Advances in Neural Information Processing Systems*, 37.
- [37] Xiao, H., Rasul, K., & Vollgraf, R. (2017). Fashion-MNIST: A novel image dataset for benchmarking machine learning algorithms. *arXiv:1708.07747*.
- [38] Song, S., Sjöström, P. J., Reigl, M., Nelson, S., & Chklovskii, D. B. (2005). Highly nonrandom features of synaptic connectivity in local cortical circuits. *PLoS Biology*, 3(3), e68.
- [39] Buzsáki, G., & Mizuseki, K. (2014). The log-dynamic brain: How skewed distributions affect network operations. *Nature Reviews Neuroscience*, 15(4), 264–278.
- [40] The MICrONS Consortium (2025). Functional connectomics spanning multiple areas of mouse visual cortex. *Nature*, 640(8058), 435–447.
- [41] Loewenstein, Y., Kuras, A., & Rumpel, S. (2011). Multiplicative Dynamics Underlie the Emergence of the Log-Normal Distribution of Spine Sizes in the Neocortex In Vivo. *Journal of Neuroscience*, 31(26), 9481–9488.
- [42] Megías, M., et al. (2001). Total number and distribution of inhibitory and excitatory synapses on hippocampal CA1 pyramidal cells. *Neuroscience*, 102(3), 527–540.
- [43] Francioni, V., Tang, V. D., Toloza, E. H. S. et al. (2026). Vectorized instructive signals in cortical dendrites. *Nature*. <https://doi.org/10.1038/s41586-026-10190-7>
- [44] Iyer, A., Grewal, K., Velu, A., Souza, L. O., Forest, J., & Ahmad, S. (2022). Avoiding catastrophe: Active dendrites enable multi-task learning in dynamic environments. *Frontiers in Neurobotics*, 16, 846219.

Dataset	Rule	Top-10 valid	Top-10 test
MNIST	3F	0.611	0.622
MNIST	4F	0.620	0.628
MNIST	5F	0.912	0.916
Context gating	3F	0.398	0.396
Context gating	4F	0.411	0.411
Context gating	5F	0.807	0.789

Table S1: **Rule-family ranking.** Top-10 mean across completed local-competence sweeps.

432 A Supplementary Results

433 Mechanistic Support and Broadcast Controls

434 Rule-Family Ranking

435 Which Components Carry?

Component	Representative effect	Interpretation
Shunting architecture	In the nonnegative-input noise-resilience sweep, additive performs better at $N_I=0$ (0.668 vs. 0.543), but shunting overtakes it once inhibition is present (0.837 vs. 0.818 at $N_I=10$, 0.861 vs. 0.830 at $N_I=40$).	The shunting gain is operating-regime dependent rather than uniform: it appears once inhibition shapes conductance scaling strongly enough to help the shared broadcast.
Broadcast quality	On MNIST (5F), shunting per-soma reaches 0.912 ± 0.005 , while local-mismatch remains at 0.146 ± 0.046 .	Correctly matching the broadcast field to the somatic error matters far more than arbitrary local mismatch heuristics.
Transported oracle	Across inhibited noise-resilience regimes, additive local learning rises from roughly 81–84% under per-soma to 92–94% under transported broadcast; shunting rises from roughly 81–86% to 95–95.2%.	The oracle remains the strongest causal evidence that broadcast fidelity, not just architecture, is the dominant bottleneck.
Rule hierarchy	In the competence sweeps, MNIST improves from 0.622 (3F) and 0.628 (4F) to 0.916 (5F); context gating improves from 0.396/0.411 to 0.789.	5F is the strongest practical rule in this paper, though its extra factor remains heuristic rather than theorem-derived.
5F stability	Tightening the ϕ clamp to $[0.5, 2.0]$ changes MNIST by only about +0.4 pp; varying EMA from 0.05 to 0.20 changes it by less than 0.2 pp.	The practical gain from 5F is not especially brittle to its main tuning knobs.
Structured feedback	In the cue-routing rank sweep, learned-routing additive local learning remains near ceiling while learned-routing shunting rises from 0.742 at random rank-1 to 0.846 at random rank-2; the current tuned pathway-vector variant reaches 0.815.	Routed tasks remain the main failure mode of rank-1 feedback, but the robust conclusion is that higher rank helps; the best structured fix is not yet settled enough to anchor a headline claim.
Random low-rank channels	On the shunting noise-resilience bridge, random low-rank broadcast improves from 0.453 at $K=1$ to 0.764 at $K=4$ and 0.795 at $K=8$, while exact path transport reaches 0.847; on cue routing, the best unstructured low-rank setting is $K=2$ at 0.846.	Higher-rank unstructured broadcast now closes a large fraction of the rank-1 gap, but it still does not recover the transported-oracle ceiling and does not by itself establish a structure-specific advantage.
Path propagation proxy	In the shunting noise-resilience bridge, the current morphology-aware path-propagation proxy reaches 0.762 ± 0.047 , well above per-soma (0.662 ± 0.016) and close to random low-rank $K=4$ (0.764 ± 0.025), though still below exact path transport (0.847 ± 0.018).	The present recursive attenuation proxy is a meaningful constructive baseline: it closes much of the oracle gap, though a stronger strictly local approximation to transported error remains open.
Morphology regime	In the exploratory noise-resilience regime map (Fig. 5), depth-2 trees show their largest shunting gains near $N_I = 0$, whereas depth-3 trees retain their strongest gains around $N_I = 5$.	Morphology appears to shift the inhibitory operating regime in which shunting is most useful, suggesting that conductance normalization and tree geometry interact rather than contributing independently.
Activation choice	In the five-seed frozen activation audit, identity outperforms frozen <code>param_tanh</code> for LocalCA on noise resilience in both architectures (0.590/0.859 vs. 0.109/0.772 for additive at $N_I=0/10$; 0.411/0.769 vs. 0.331/0.701 for shunting), while the backprop effect remains strongly regime-dependent.	The post-voltage firing-rate transform is a real modeling variable, not just an implementation detail. Even a fixed saturating nonlinearity changes the operating point substantially, so the main paper’s mechanistic claims should be read in the learned bounded <code>param_tanh</code> regime used throughout the headline experiments.

Table S2: **Which components carry the observed gains?** A compact summary of the empirical division of labor across architecture, broadcast design, and LocalCA rule variants.

Core	Broadcast	Decoder	Test (mean $\pm$ std)
Shunting	per-soma	local	0.912 $\pm$ 0.005
Shunting	per-soma	backprop	0.909 $\pm$ 0.008
Shunting	local-mismatch	local	0.146 $\pm$ 0.046
Shunting	local-mismatch	backprop	0.146 $\pm$ 0.037
Additive	per-soma	local	0.894 $\pm$ 0.007
Additive	per-soma	backprop	0.900 $\pm$ 0.001
Additive	local-mismatch	local	0.342 $\pm$ 0.058
Additive	local-mismatch	backprop	0.348 $\pm$ 0.095

Table S3: **Local-mismatch recheck (MNIST, 5F)**. Per-soma is consistently strong; local-mismatch remains much weaker.




Figure S1: **Capacity calibration (supplementary)**. (A) Phase 1 backprop ceilings across all architectures and datasets. (B) Rule-family ranking: 5F consistently outperforms 4F and 3F. (C) Decoder mode comparison (local vs. backprop decoder, 5F MNIST). (D) Broadcast mode comparison: per-soma is required for strong performance; local-mismatch fails.

Dataset	BP ceiling	Best local (5F)	Gap
MNIST	0.971	0.914 ± 0.003	5.7%
Fashion-MNIST	0.889	0.838 ± 0.003	5.1%
Context gating	0.861	0.803 ± 0.006	5.8%

Table S4: **Local competence.** Backprop ceilings are matched-capacity shunting references from dedicated 5-seed standard-training refreshes for MNIST and context gating and from the dedicated 5-seed Fashion-MNIST competence sweep. Local values are 5F with per-soma broadcast on shunting dendritic cores. Context gating additionally uses an HSIC auxiliary objective (weight 0.01; Appendix E). Error bars on local values: ± 1 s.d. across 5 seeds.

Condition	Metric	Value
Decoder: local vs backprop vs frozen (MNIST, toy model)	test acc	0.379 vs 0.379 vs 0.176
Shunting vs additive, matched (MNIST, toy model)	Δ test	+0.210
Per-soma, path on vs off (synthetic task, toy model)	test / MI(E,I;C)	-0.003 / +0.017

Table S5: **Mechanistic ablations.** Results from controlled small-network experiments using minimal architectures to isolate individual factors. These runs use a small 2-layer dendritic network (branch factor [9]) trained for 30 epochs; they are not directly comparable to the headline capacity-calibrated results.

436 Broadcast Mode Comparison and Local-Mismatch Recheck

437 Competence, Verification, and Stress Tests

438 Phase 1 Capacity Ceilings

439 Local Competence and Regime Dependence

440 Ablation Results

441 Extended Gradient Analysis and N_I Sweep Detail

442 Verification and Reproducibility

443 Additional Stress Tests

444 Broadcast Bandwidth (Quantization) Control

445 FA/DFA Baseline Comparison

446 CIFAR-10 Results

447 Table S6 provides the exact values for the appendix CIFAR-10 figure. In this stronger compact direct-
448 I-stream family, shunting performs well under standard training (49.5% vs. 46.6% for additive), so
449 the harder-data stress test does not unfairly penalize the shunting architecture. The broadcast-fidelity
450 ladder also survives once decoder-aware soma mapping is used: additive LocalCA rises from 32.6%
451 under rank-1 per-soma broadcast to 42.3% under transported error, while shunting rises from 28.8%
452 under per-soma to 34.7% with random low-rank $K=4$ and 47.4% with transported error, nearly
453 matching the 49.5% shunting backprop ceiling.

454 **CIFAR-10 soma-on extension.** We also tested the soma-on extension on the same com-
455 pact direct-I-stream depth-4 family with quantile init (Fig. S9; Table S7; 3 seeds). With
456 `somatic_synapses=true`, path-transported LocalCA stays strong in both cores: additive reaches
457 $45.5 \pm 0.6\%$ and shunting reaches $46.6 \pm 1.0\%$. Relative to the soma-off results, the additive
458 path-transport condition improves from 42.3% to 45.5%, while shunting remains within 1 pp of its
459 soma-off path-transport ceiling (47.4%) and within 3 pp of the matched shunting backprop ceiling
460 (49.5%). Per-soma rank-1 broadcast also becomes much more competitive for additive ($41.6 \pm 0.6\%$)
461 than for shunting ($35.9 \pm 1.2\%$), while low-rank $K=4$ remains weak in both cores. Figure S9 makes




Figure S2: **Extended gradient and N_I analysis (supplementary).** (A) Scale mismatch bars: shunting achieves near-ideal scale (0.117); additive exhibits order-of-magnitude distortion (> 1.0). (B) Noise-resilience N_I dose-response with error bands (± 1 s.d.). (C) MNIST N_I dose-response detail with error bands. (D) Fashion-MNIST individual seeds for all conditions, showing consistency across runs.

Condition	Model	Test accuracy
standard	additive	46.6 ± 1.5
standard	shunting	49.5 ± 0.7
LocalCA per-soma	additive	32.6 ± 0.6
LocalCA per-soma	shunting	28.8 ± 0.8
LocalCA path transport	additive	42.3 ± 1.2
LocalCA path transport	shunting	47.4 ± 0.6
shunting low-rank	$K=4$	34.7 ± 1.1

Table S6: **Exact CIFAR-10 values for the compact mechanism extension (5 seeds, validation-best epoch).** This table gives the exact numbers for the appendix harder-data ladder in Fig. S8. The key technical detail is that LocalCA maps output error back to decoder-input/soma space through the decoder Jacobian when the decoder is nonlinear. With decoder-aware error mapping, transported error again acts as a strong upper bound, nearly matching the stronger shunting backprop ceiling, while naive rank-1 per-soma broadcast still underperforms and random low-rank feedback closes part of that gap.

462 the two useful views explicit: the absolute soma-on ordering still favors path transport strongly, and
 463 the matched soma-off to soma-on gain is largest for additive per-soma while shunting transported
 464 error is already near its soma-off ceiling. On this harder dataset, the soma channel clearly helps, but
 465 it still does not eliminate the importance of broadcast quality.




Figure S3: **5F sensitivity analysis (MNIST, shunting, per-soma broadcast)**. **(A)** Sensitivity to the ϕ_n clamp interval. The default clamp [0.25, 4.0] is already strong ($92.1 \pm 0.8\%$); tightening it to [0.5, 2.0] slightly improves performance ($92.5 \pm 0.3\%$), while widening it to [0.1, 8.0] is effectively neutral ($92.1 \pm 0.9\%$). **(B)** Sensitivity to the 4F/5F EMA rate used for online statistics. Varying α from 0.05 to 0.20 changes mean test accuracy by less than 0.2 pp. Together these results suggest that the 5F gain is not driven by a brittle single hyperparameter choice, even though the factor itself remains heuristic. Errors: ± 1 s.d. across 3 seeds.




Figure S4: **Verification and reproducibility (supplementary)**. **(A)** MNIST verification: main seeds (42–46) yield $91.4 \pm 0.3\%$; held-out seeds (47–49) yield $89.8 \pm 0.9\%$, confirming generalization. **(B)** Context gating verification: main seeds (+HSIC) $80.3 \pm 0.6\%$; held-out seeds (no HSIC) $77.2 \pm 1.5\%$. The roughly 3 pp gap reflects HSIC removal, not seed sensitivity. **(C)** HSIC weight ablation on context gating: moderate weights (0.01–0.1) perform best.




Figure S5: **Additional stress tests**. **(A)** Depth scaling: shunting local (green) degrades more gracefully from 63.5% to 57.4%; additive local (blue) drops from 54.9% to 29.7%. Backprop ceilings (dashed) remain stable. **(B)** Broadcast-noise robustness: shunting remains stable for $\sigma \leq 0.1$; additive degrades rapidly and reaches chance at $\sigma = 1$. **(C)** Fashion-MNIST: the shunting gain is modest on this cleaner benchmark (83.8% local vs. 88.9% backprop), consistent with the regime-dependent story in the main text.




Figure S6: **Coarse shared broadcast still works.** Test accuracy as a function of effective broadcast bandwidth. Full-precision, 8-bit, 4-bit, and 2-bit quantization of the shared error signal all reach essentially the same accuracy (61–62%; $p > 0.9$ for 4-bit vs. full), while a sign-only broadcast and a sparse top-30% broadcast degrade sharply. This shows that the shunting LocalCA signal carries most of its useful information in its direction rather than in fine-grained magnitude, consistent with the mechanism-summary picture in the main text. This panel is reported separately so the main figure can carry the full causal chain (path-gain compressibility → alignment → oracle → global summary).




Figure S7: **Feedback alignment baselines (MNIST).** (A) Grouped comparison: standard backprop (neutral gray), DFA (orange), and FA (purple). Hatched N/A markers indicate that FA is not implemented for the block-structured dendritic architectures because the random feedback matrices are not dimensionally compatible with the tree-structured branch updates. DFA achieves 66.1% on shunting vs. 62.2% additive vs. 51.8% point MLP. (B) Backprop–DFA gap: dendritic architectures (24.9–27.6 pp) show smaller gaps than point MLPs (39.5 pp), suggesting conductance-based architecture is partially compatible with random feedback.




Figure S8: **CIFAR-10 mechanism stress test in the compact direct-I-stream family.** (A) Matched additive vs. shunting ladder with a nonlinear decoder and decoder-aware soma-error mapping. Shunting is competitive under standard training ($49.5 \pm 0.7\%$) and transported-error LocalCA nearly recovers that ceiling ($47.4 \pm 0.6\%$), while naive rank-1 broadcast remains much weaker. (B) Shunting rank bridge on the same family. Random low-rank feedback improves over rank-1 broadcast, but exact transported error remains the strongest signal. This figure is a harder-data diagnostic, not a claim of competitive CIFAR-10 benchmarking.




Figure S9: **CIFAR-10 compact direct-I-stream depth-4 with `somatic_synapses=true`.** (A) Absolute soma-on ladder on the compact direct-I-stream depth-4 family. Path transport stays strongest in both cores and remains near the matched backprop ceilings (dashed lines), while low-rank $K=4$ remains weak. (B) Matched shift from soma-off to soma-on for the conditions with a clean paired baseline. Soma helps additive strongly under per-soma and path transport, improves shunting per-soma, leaves shunting transported error close to its soma-off value, and worsens shunting low-rank $K=4$. Additive low-rank $K=4$ is omitted from panel B because the soma-off mechanism package did not include that exact matched condition.

Condition (soma-on)	Additive	Shunting
LocalCA per-soma (rank-1)	41.6 ± 0.6	35.9 ± 1.2
LocalCA low-rank $K=4$	27.5 ± 3.5	26.6 ± 1.7
LocalCA path transport	45.5 ± 0.6	46.6 ± 1.0
soma-off path transport	42.3 ± 1.2	47.4 ± 0.6
standard BP (ceiling)	46.6 ± 1.5	49.5 ± 0.7

Table S7: **CIFAR-10 compact direct-I-stream depth-4 with `somatic_synapses=true`.** Adding direct somatic synapses and using quantile reactivation init improves the additive transported-error condition by about 3.2 pp and keeps the shunting transported-error condition within 1 pp of its soma-off counterpart. Per-soma (rank-1) becomes much more competitive for additive than for shunting, while low-rank $K=4$ remains weak in both cores. The soma channel therefore helps, but does not remove the need for a strong credit signal.




Figure S10: **Additive + normalization control (MNIST).** (A) Standard backprop: normalization provides a small boost (89.7% $\rightarrow$ 90.9%). (B) Local learning: normalization improves additive from 46.5% to 56.0% (+9.5 pp), partially closing the gap to shunting (61.7%, dashed green). The remaining gap (-5.7 pp) indicates that shunting provides benefits beyond simple voltage normalization.

466 Additive Normalization Control

467 Structured Feedback, Activation, and Supportive Extensions

468 Morphology $\times$ Inhibition Regime Map

469 The main-text morphology figure shows the supportive regime map, while the appendix keeps the
 470 summary tables and architecture details that go with it. We treat it as supportive evidence that
 471 morphology changes the inhibitory operating regime in which shunting is most useful; a fuller
 472 mechanistic account would still require matched theory diagnostics for each cell in the grid.

473 Input-Mode Probe: Direct Inhibitory Stream vs. Explicit Inhibitory Cells

474 The headline experiments use `input_mode=1`, where the transfer layer provides nonnegative exci-
 475 tatory and inhibitory streams from the external input and the excitatory dendrites receive learned
 476 I-to-E conductance banks directly. To test whether the same mechanism can be generated by an
 477 explicit feedforward inhibitory population, we ran a one-feedforward-layer noise-resilience probe
 478 that preserves the relevant dendritic depth ([3, 3] morphology) while removing an unnecessary second
 479 feedforward population. In this clean setting, explicit inhibitory cells reach $94.2 \pm 0.2\%$ under
 480 path-transport LocalCA when their dendrites use the same update policy as excitatory dendrites
 481 (`explicit_inhibitory_update_mode=local_ca`), $93.8 \pm 0.2\%$ when those inhibitory-cell up-
 482 dates are frozen (`freeze`), and $95.1 \pm 0.3\%$ under standard backprop. Direct input-driven inhibition
 483 gives the expected broadcast-fidelity ladder on the same one-layer architecture: per-soma rank-1
 484 reaches $85.2 \pm 0.7\%$, while exact path transport reaches $95.2 \pm 0.0\%$. Thus explicit inhibitory cells
 485 can generate useful path-gain structure once the architecture isolates the dendritic-path question. The
 486 older two-feedforward-layer explicit-I diagnostic was much weaker (about 58–63% under LocalCA
 487 despite a 94.7% backprop ceiling), so we treat it as evidence that deeper explicit $E \rightarrow I \rightarrow E$ graphs
 488 need graph-aware local errors, not as evidence against inhibition-mediated path gains.

489 **Fitted inhibitory path-gain diagnostic.** We also asked whether the direct-I-stream models actually
 490 use inhibitory synapses in the way implied by Prop. 2. We analyzed the five successful fixed-router
 491 shunting soma-on cue-routing LocalCA runs and measured first-layer inhibitory synaptic activation,
 492 branch-level local input resistance, and a pathway-inhibition balance statistic. The sign of the branch
 493 balance is not fixed across random seeds, so the meaningful quantity is sign-invariant: whether the
 494 balance carries context information, not whether branch 1 or branch 2 always encodes a named cue.
 495 Table S9 shows that the pathway-inhibition balance decodes context well after allowing this seed-




Figure S11: **Pathwise inhibition story and one-layer input-mode probe.** (A) In a branched conductance tree, the error path gain α_n is the product of local input resistances and dendritic coupling conductances along the path to the soma. Inhibitory conductance on any compartment along that path lowers local input resistance and attenuates all upstream credit paths. (B) The same branch-level inhibitory conductance can be supplied directly from a nonnegative inhibitory input stream (`input_mode=1`) or through an explicit feedforward inhibitory cell (`input_mode=0`). (C) The clean mechanism probe keeps the dendritic tree depth ([3, 3]) but uses only one feedforward dendritic population; adding a second feedforward E/I layer tests a deeper graph-credit problem rather than the path-gain mechanism itself. (D) Noise-resilience results for the one-layer probe. Direct-I path transport reaches the explicit-I backprop ceiling, and explicit inhibitory cells with path-transport LocalCA also remain near ceiling. This supports the interpretation that explicit inhibitory cells can generate useful path-gain structure when the architecture isolates the dendritic-path question.

Inhibitory input mode	Training / broadcast	Test accuracy
Direct inhibitory stream (<code>input_mode=1</code>)	LocalCA, per-soma rank-1	0.852 ± 0.007
Direct inhibitory stream (<code>input_mode=1</code>)	LocalCA, exact path transport	0.952 ± 0.000
Explicit I cells (<code>input_mode=0</code>)	LocalCA, path transport, I-cell updates on	0.942 ± 0.002
Explicit I cells (<code>input_mode=0</code>)	LocalCA, path transport, I-cell updates frozen	0.938 ± 0.002
Explicit I cells (<code>input_mode=0</code>)	standard backprop	0.951 ± 0.003

Table S8: **One-feedforward-layer input-mode path-gain probe on noise resilience (3 seeds).** All rows use one excitatory dendritic population with [3, 3] morphology and nonnegative inputs. The direct-I rows have no explicit inhibitory neurons; the input stream drives learned branch-level inhibitory conductance banks directly. The explicit-I rows use a matched inhibitory population with [3, 3] morphology. `local_ca` updates explicit inhibitory-cell dendrites with the same policy used for excitatory dendrites, while `freeze` holds those dendrites fixed but still lets excitatory I-to-E synapses learn. Exact path transport closes the direct-I rank-1 gap, and explicit inhibitory cells nearly match both direct-I path transport and the explicit-I backprop ceiling.

496 dependent polarity, and that inhibitory conductance is negatively correlated with local input resistance.
497 This does not by itself prove an optimized interneuron circuit, but it supports the mechanistic link
498 used throughout the paper: learned inhibitory conductance can create input-dependent path-gain
499 differences by modulating branch resistance.

500 Cue-Routing Feedback-Rank Diagnostic

501 Cue routing tests the regime where one shared teaching signal is expected to fail: context determines
502 which noisy cue is reliable, so different pathways should receive different credit. Figure S12 shows
503 that the benchmark is learnable and that moving beyond rank-1 feedback helps, but the current
504 path-structured variant does not yet beat the best unstructured low-rank setting. We therefore interpret
505 this result as a failure-mode and rank-requirement diagnostic, not as a solved structured-feedback
506 method.

Diagnostic	Mean $\pm$ s.d.	Interpretation
$I(\text{context}; \text{pathway-inhibition balance})$	0.685 ± 0.209 bits	Context is visible in the inhibitory balance.
Best-polarity context decoding from inhibitory balance	0.796 ± 0.109	Branch polarity varies by seed, but the balance is informative.
$\text{Corr}(\text{inhibitory conductance, local input resistance})$	-0.424 ± 0.122	More inhibition lowers local resistance, as predicted by shunting.

Table S9: **Fitted direct-I cue-routing diagnostic (5 successful fixed-router shunting soma-on LocalCA runs).** In `input_mode=1`, inhibitory synapse banks receive a nonnegative input stream directly. In trained cue-routing models, the balance of inhibitory activation across routed pathways carries context information and higher inhibitory conductance coincides with lower local input resistance. Because the sign of the pathway balance can flip across seeds, the decoding result is reported with best polarity and should be read as evidence for context-dependent inhibitory path gating, not as a fixed anatomical assignment of one branch to one cue.




Figure S12: **Structured feedback when rank-1 broadcast fails.** (A) Cue-routing task schematic. Context determines which noisy cue is reliable on each trial, so different dendritic pathways should receive different teaching signals. (B) Five-seed comparison of rank-1, random low-rank, and pathway-structured feedback. Moving beyond rank-1 helps, while the best structured repair remains open. (C) Test accuracy vs. router specialization across learned-router conditions. High specialization alone does not guarantee success. (D) Recovered pathway assignments for a representative learned-router run. Cue-A and cue-B features segregate into separate latent pathways even when feedback quality, rather than router discreteness, is the limiting factor.

Random Low-Rank Broadcast Channels

Frozen Activation-Choice Audit

B Implementation Details

Biological Plausibility Assumptions

The theorems and rules above rest on a small set of explicit assumptions. We state them as a checklist so that readers can see exactly what is assumed and where each assumption is used:

A1 (Steady-state voltage). We use the steady-state solution of the passive cable equation (Eq. 1). Temporal dynamics are not modeled; all gradients, path gains, and fidelity measurements refer to the conductance-stage voltage at steady state.

A2 (Tree topology). Each dendritic cell is a rooted tree with the soma as the root. There are no recurrent connections within the dendrite, which makes the path from any compartment to the soma unique and is what allows the closed-form path gain α_n in Theorem 1.

A3 (Nonnegative conductances). Synaptic and dendritic conductance parameters are pushed through a positive transform (`softplus`), so $g_j^{\text{syn}}, g_j^{\text{den}} \geq 0$ at every optimisation step. This is a biophysical constraint and is also what keeps the shunting denominator bounded away from zero.

Setting	Broadcast	Test accuracy
<i>Noise resilience, shunting, rank bridge</i>		
per-soma	rank-1 per-soma	0.662 ± 0.016
path propagation	recursive attenuation proxy	0.762 ± 0.047
low-rank	$K=1$	0.453 ± 0.126
low-rank	$K=2$	0.630 ± 0.042
low-rank	$K=4$	0.764 ± 0.025
low-rank	$K=8$	0.795 ± 0.019
path transport	exact conductance-stage transport	0.847 ± 0.018
<i>Cue routing, learned shunting router, rank/structure sweep</i>		
per-soma	tuned rank-1	0.803 ± 0.125
low-rank	$K=1$	0.742 ± 0.022
low-rank	$K=2$	0.846 ± 0.082
low-rank	$K=4$	0.748 ± 0.085
pathway-vector	tuned structured rank-2	0.815 ± 0.126

Table S10: **Rank bridge and rank-structure comparison.** On shunting noise resilience, both the current path-propagation proxy and higher-rank random low-rank broadcast close a substantial fraction of the gap between rank-1 per-soma and exact path transport, with low-rank continuing to improve up to $K=8$. On cue routing, the learned-router sweep shows that moving beyond rank-1 helps, but the best current unstructured low-rank setting ($K=2$) is still slightly better than the tuned structured pathway-vector variant. We therefore interpret routed credit assignment as an open higher-rank problem rather than as a solved pathway-vector rescue.

523 **A4 (Nonnegative presynaptic drive).** The first synaptic drive x is nonnegative, implemented either
524 by nonnegative inputs or an explicit ReLU transfer stage. Together with A3 this enforces
525 the positive-input condition used for all headline sweeps.

526 **A5 (Pre-reactivation upward transfer).** Theorem 1 is stated for the pre-reactivation compartment
527 voltage. A post-voltage reactivation f (e.g. `param_tanh`) is handled by multiplying the
528 path gain by $f'(V_n)$ along the recursion. The compartment error remains the sole non-local
529 quantity; only the effective path gain acquires local activation-derivative factors.

530 **A6 (Single perisomatic broadcast).** Every synapse receives one non-local scalar or low-rank vector
531 signal delivered from the soma; all other ingredients of the update rule (eligibility traces,
532 driving force, input resistance, covariance modulators) are computable from quantities
533 available at the synapse or compartment.

534 Each synapse therefore has access to: presynaptic activity x_j (local), compartment voltage V_n (local
535 membrane potential), reversal potential E_j (fixed by receptor type), and total input resistance $R_n^{\text{tot}} =$
536 $1/g_n^{\text{tot}}$ (computable from local conductances). The 4F modulator ρ_n requires online estimation of
537 voltage covariance (biologically plausible via slow calcium signals); the 5F factor ϕ_n requires a
538 linear regression proxy (implementable via eligibility traces). The only non-local quantity is the
539 broadcast error e_n , which requires a top-down or neuromodulatory signal from the soma to dendritic
540 compartments. We assume per-neuron resolution (one error per output neuron) for the per-soma
541 broadcast mode.

542 Dendritic Structure in Code

543 We use the morphology notation $[b_1, b_2, \dots, b_D]$ for rooted dendritic trees, where each factor gives
544 the fan-in from one dendritic stage to the next on the path to the soma. For example, $[3, 3]$ means that
545 each soma aggregates 3 proximal branches and each proximal branch aggregates 3 distal branches,
546 for 9 distal leaves per soma; $[3, 3, 3]$ adds a third dendritic stage with 27 leaves per soma. In code,
547 each excitatory unit is instantiated as a `DendriNet`, which is a stack of `DendriticBranchLayers`.
548 Each branch layer contains an excitatory synapse bank, an optional inhibitory synapse bank, a
549 branch-to-parent aggregation map, and an optional post-voltage reactivation. In the main feedfor-
550 ward models studied here, `somatic_synapses=false`, so synaptic inputs terminate on dendritic
551 branches rather than directly on the soma. The headline runs use `input_mode=1`: the transfer layer
552 creates nonnegative excitatory and inhibitory streams from the same external input, and nonzero

Dataset / strategy	Core	N_I	Identity (none)	Frozen param_tanh
MNIST / LocalCA	additive	0	0.780 ± 0.014	0.709 ± 0.037
MNIST / LocalCA	additive	10	0.907 ± 0.003	0.881 ± 0.005
MNIST / LocalCA	shunting	0	0.841 ± 0.007	0.778 ± 0.020
MNIST / LocalCA	shunting	10	0.905 ± 0.009	0.840 ± 0.016
Noise resilience / LocalCA	additive	0	0.590 ± 0.162	0.109 ± 0.006
Noise resilience / LocalCA	additive	10	0.859 ± 0.001	0.772 ± 0.009
Noise resilience / LocalCA	shunting	0	0.411 ± 0.028	0.331 ± 0.020
Noise resilience / LocalCA	shunting	10	0.769 ± 0.004	0.701 ± 0.006
MNIST / backprop	additive	0	0.925 ± 0.001	0.942 ± 0.001
MNIST / backprop	additive	10	0.921 ± 0.001	0.950 ± 0.001
MNIST / backprop	shunting	0	0.963 ± 0.0004	0.950 ± 0.001
MNIST / backprop	shunting	10	0.967 ± 0.001	0.946 ± 0.001
Noise resilience / backprop	additive	0	0.896 ± 0.003	0.106 ± 0.007
Noise resilience / backprop	additive	10	0.893 ± 0.002	0.927 ± 0.002
Noise resilience / backprop	shunting	0	0.898 ± 0.001	0.869 ± 0.002
Noise resilience / backprop	shunting	10	0.926 ± 0.001	0.912 ± 0.001

Table S11: **Frozen activation-shape audit on matched dendritic architectures (5 seeds per condition)**. Identity (none) and a frozen bounded post-voltage reactivation param_tanh lead to markedly different operating regimes under nonnegative first-layer synaptic drive. In this audit, identity is the safer LocalCA choice on both MNIST and the noise-resilience task, while the backprop effect is strongly regime-dependent: frozen param_tanh helps additive most clearly in the inhibited noise-resilience setting ($N_I=10$) but collapses it at $N_I=0$. These runs match additive reactivation initialization to the shunting setting and hold the activation parameters fixed, isolating activation shape from both additive/shunting initialization differences and activation learning itself.

Dataset	Core	N_I	Identity (none)	Frozen param_tanh
MNIST	additive	0	CV 0.280, cosine 0.220	CV 1.122, cosine 0.074
MNIST	additive	10	CV 0.310, cosine 0.212	CV 1.079, cosine 0.094
MNIST	shunting	0	CV 0.393, cosine 0.170	CV 0.770, cosine 0.114
MNIST	shunting	10	CV 0.385, cosine 0.281	CV 1.177, cosine 0.106
Noise resilience	additive	0	CV 0.124, cosine 0.079	CV 0.114, cosine 0.052
Noise resilience	additive	10	CV 0.414, cosine 0.206	CV 0.840, cosine 0.094
Noise resilience	shunting	0	CV 0.255, cosine 0.324	CV 0.344, cosine 0.341
Noise resilience	shunting	10	CV 0.762, cosine 0.140	CV 2.497, cosine 0.079

Table S12: **Frozen activation-shape theory audit on matched LocalCA runs (5 seeds per condition)**. Each entry reports conductance-stage path-gain dispersion (CV) and direct per-soma compartment-error fidelity (cosine between the per-soma broadcast and the exact pre-activation compartment error). The positive-input theory audit largely agrees with the empirical one: freezing param_tanh usually broadens path-gain dispersion and weakens per-soma fidelity, especially in the inhibited settings where the main mechanistic story lives. The one mild exception is low-inhibition shunting on noise resilience, where frozen param_tanh leaves fidelity roughly unchanged while still hurting final accuracy, suggesting that activation choice affects optimization and representation as well as direct credit fidelity.

ie_synapses_per_branch_per_layer attaches learned inhibitory conductance banks directly to excitatory dendritic branches. These models therefore have input-driven branch inhibition but no separate inhibitory neuron population. By contrast, input_mode=0 instantiates explicit feedforward inhibitory cells when inhibitory_layer_sizes is nonempty; these cells can transform excitatory activity before projecting inhibitory conductance back onto excitatory dendrites. In that setting the inhibitory cells are also dendritic modules, so their E-to-I and I-to-I synaptic conductances are trained by the same local rule family rather than by a separate global inhibitory optimizer. We treat that explicit-I setting as an exploratory mechanism probe rather than a headline baseline, because the main claims were measured in the direct-I-stream regime. The additive and shunting cores




Figure S13: **Soma-on extension for LocalCA.** Enabling direct somatic input (`somatic_synapses=true`) improves aggregate mean test accuracy across all four manuscript LocalCA families. Each family is summarized over the completed configurations in matched soma-off and soma-on sweeps. The largest gain appears in morphology scaling, where the family mean rises from 35.8% to 70.7% and the best run rises from 57.0% to 76.4%. Gains in the shunting-regime and error-shaping families are smaller but still substantial. Delta labels show soma-on minus soma-off. Because the main mechanistic analysis was developed in the dendrite-only feedforward regime, we report soma-on as a supportive extension rather than replacing the main operating regime.

Family	Soma-off	Soma-on	Δ mean	Δ best
Phase-1 capacity	0.8784	0.8999	+0.0215	-0.0007
Shunting regime	0.5641	0.6715	+0.1074	+0.0090
Morphology scaling	0.3578	0.7070	+0.3492	+0.1940
Error shaping	0.2798	0.3906	+0.1109	+0.1210

Table S13: **Representative soma-on deltas across the four LocalCA families.** Values compare matched families with and without `somatic_synapses` and report both the change in family-mean test accuracy and the change in best-run test accuracy. Cue-routing soma and CIFAR-10 depth-4 soma are reported separately in Fig. S14, Fig. S9, and Table S7 because those extensions are summarized on different task families.

are architecture-matched at the tree level; they differ in the branch-level voltage integration rule rather than in whether a dendritic tree exists. In all reported dendritic runs, synaptic and dendritic conductance parameters are pushed through positive transforms (`softplus` in the main paper runs), so the conductances themselves remain nonnegative at every optimization step; unconstrained decoder weights are separate readout parameters and are not interpreted as conductances.

Matched soma-on LocalCA sweeps suggest that direct somatic input is a meaningful extension rather than a minor implementation detail. Relative to matched non-somatic sweeps, enabling `somatic_synapses=true` raises the mean test accuracy in all four manuscript families: phase-1 capacity from 0.8784 to 0.8999, shunting-regime sweeps from 0.5641 to 0.6715, morphology-scaling sweeps from 0.3578 to 0.7070, and error-shaping sweeps from 0.2798 to 0.3906. These numbers are family-level aggregates over the completed configurations in each matched soma-off and soma-on sweep, rather than a single 5-seed cell. Because the main mechanistic analysis in this paper was developed in the dendrite-only feedforward regime, we keep the main text anchored to `somatic_synapses=false` and treat soma-on as a supportive extension rather than silently replacing the original operating regime. Figure S13 summarizes the mean and best-accuracy comparisons across the four families.

The soma-on benefit extends beyond the capacity/scaling families to the cue-routing benchmark that stress-tests rank-1 feedback. With dendrite-only pathways, the best learned-routing shunting LocalCA configuration was unstable at 0.81 ± 0.13 ; with `somatic_synapses=true`, fixed-router shunting LocalCA reaches 1.00 ± 0.0 test accuracy across 5 seeds, and learned-router additive LocalCA reaches 0.99 ± 0.003 (Fig. S14). The soma channel provides a high-bandwidth direct input that bypasses the rank-1 bottleneck induced by per-soma broadcast.




Figure S14: **Soma-on rescues cue-routing LocalCA.** The left bars show the previously reported soma-off LocalCA results on the cue-integration benchmark. The right bars show the soma-on extension: fixed-router shunting LocalCA reaches 1.00 test accuracy, and learned-router additive LocalCA with soma reaches 0.99, matching the additive backprop ceiling with soma. The soma channel supplies a direct high-bandwidth input that bypasses the rank-1 bottleneck identified in the main text. Learned-router shunting with soma is omitted because this benchmark uses signed cues, which conflict with the shunting positive-input check in the learned-router pipeline; fixed-router shunting is therefore the clean shunting data point.

584 Post-Voltage Reactivation

585 The conductance stage produces a pre-reactivation compartment voltage V_n , after which each branch
 586 layer may apply a monotone scalar nonlinearity. The implementation supports identity (none), fixed
 587 $\tanh/\text{sigmoid}/\text{relu}$, and several parametric families including `param_tanh`, `param_tanh_only_m`,
 588 and piecewise linear-saturating variants. The main manuscript sweeps use `param_tanh`, a learnable
 589 bounded firing-rate transform of the form $(\tanh(m(V - b)) + 1)/2$, together with an explicitly
 590 configured nonnegative transfer stage so that the first synaptic drive remains nonnegative even
 591 after input corruption or structured task noise. Most headline feedforward sweeps use a linear
 592 decoder, while the CIFAR extension uses a nonlinear decoder and therefore maps output error back to
 593 decoder-input/soma space through the decoder Jacobian before applying LocalCA. Unless explicitly
 594 overridden, additive and shunting cores can start from different reactivation initializations; activation-
 595 fairness ablations therefore match additive initialization to the shunting setting when comparing
 596 alternative reactivation choices directly. The appendix activation audit additionally fixes `param_tanh`
 597 after initialization to isolate activation shape from activation plasticity.

598 LocalCA uses occupancy-quantile initialization together with a calibration pass that floors tiny
 599 quantile widths, clamps extreme fitted slopes, and reverts invalid per-layer fits rather than allowing
 600 pathological intermediate values to propagate. In the non-somatic feedforward publication families,
 601 this calibration leaves the results essentially unchanged relative to the same occupancy-quantile setup
 602 without the additional validity checks: phase-1 capacity changes from 0.8786 to 0.8784 mean test
 603 accuracy, shunting-regime sweeps from 0.5617 to 0.5641, morphology-scaling sweeps from 0.3600
 604 to 0.3578, and error-shaping sweeps from 0.2860 to 0.2798. The calibration therefore improves
 605 numerical safety without changing the qualitative LocalCA story.

606 We also compared two post-initialization policies for the reactivation parameters under quantile
 607 initialization: *learned local* (b, m), where LocalCA updates the gate parameters through the local
 608 rule, and *quantile-maintained* (b, m), where (b, m) are periodically refreshed from the current voltage
 609 distribution instead of being updated by the local rule. This comparison matters because quantile-
 610 maintained gates substantially simplify nonlinear reactivation learning: the rest of the network still
 611 uses LocalCA, but the gate parameters themselves are set by a local distributional rule rather than
 612 a learned plasticity rule. On MNIST classification sweeps, learned local (b, m) remains clearly
 613 better (additive 0.9247 vs. 0.9061 mean test accuracy; shunting 0.9104 vs. 0.8766). On CIFAR-10,
 614 the picture is mixed in a useful way: additive is essentially tied on mean (0.4223 learned-local vs.
 615 0.4215 quantile-maintained) while shunting improves under quantile-maintained gates (0.4028 to




Figure S15: (b, m) update policy under quantile initialization. Each cluster of bars compares the mean test accuracy of learned local (b, m) and quantile-maintained (b, m) under LocalCA for additive and shunting cores, averaged across a matched morphology/init grid $([2, 2]$ and $[3, 3, 3]$; analytical and quantile init variants). Dashed and dotted horizontal lines mark the matched standard backpropagation ceiling for additive and shunting respectively. **Left (MNIST):** Learned local (b, m) is consistently better; quantile-maintained lags by 1.9 pp (additive) and 3.4 pp (shunting) on mean accuracy. **Right (CIFAR-10):** The gap reverses for shunting: quantile-maintained reaches 43.6% mean vs. 40.3% for learned local, while additive is essentially tied. The pattern suggests that quantile-maintained (b, m) prevents over-fitting the reactivation gate on harder inputs, making it a useful alternative in harder visual regimes.

Quantity	Symbol	Convention
Voltage	V	Normalized to $[-1, 1]$
Conductances	$g^{\text{syn}}, g^{\text{den}}$	Nonneg. via softplus
Leak conductance	g^{leak}	Set to 1
Input resistance	R^{tot}	≤ 1

Table S14: Units and normalization.

0.4356 mean test accuracy). These bars aggregate over a matched morphology/init grid rather than a dedicated 5-seed rerun, so we treat them as a supportive policy comparison rather than a headline result. Accordingly, the main manuscript continues to use occupancy-quantile initialization followed by LocalCA updates of (b, m) as the default local-learning setting, while quantile-maintained (b, m) is reported as a supplementary alternative. Figure S15 shows the full MNIST and CIFAR-10 comparison.

Component Ablation

To isolate the contribution of each ingredient in our LocalCA recipe, we ran a per-component ablation on MNIST starting from the manuscript default and removing one component at a time. The default combines quantile init, learned local (b, m) , `somatic_synapses=false`, and `param_tanh` reactivation. We also include `somatic_synapses=true` as a positive extension and matched standard backpropagation as the upper reference. Figure S16 reports test accuracy (5 seeds per cell) for both shunting and additive dendritic cores on clean MNIST with morphology $[3, 3]$.

Units and Parameterization

Decoder Update Modes

W_{dec} maps $V_L \rightarrow \hat{y}$. Modes: **backprop** ($\nabla_W L$ via autograd), **local** ($\Delta W = \eta \langle \delta_0 V_L^T \rangle_B$), **frozen** ($\Delta W = 0$).




Figure S16: **Per-component ablation for LocalCA on MNIST.** Bars show mean test accuracy ($\pm$ s.d. across 5 seeds); coloured bars highlight the manuscript default (blue/green) and the soma-on extension (green). **(A) Shunting:** The full default reaches 90.7%; removing quantile init leaves accuracy unchanged at 90.8% (quantile init is a mild calibration nudge on this clean task), removing learned (b, m) drops by about 1 pp, and removing reactivation entirely drops accuracy to 87.3%; the reactivation transform is the largest single LocalCA ingredient. **(B) Additive:** Quantile init contributes +2.1 pp (90.1 $\rightarrow$ 92.2%), learned (b, m) contributes +1.7 pp, and reactivation contributes +1.1 pp; each ingredient helps on the additive core. **Soma-on** is the largest positive change in both cores (+3 to +3.5 pp over full config), while matched standard backpropagation reaches 97.0% in both cores and sets the upper reference. The fixed-relu reactivation condition did not satisfy the same initialization checks and is omitted.

Category	Implemented modes	Role in this paper
Core models	point MLP; dendritic MLP; dendritic additive; dendritic shunting; pathway-routed dendritic cores	Main comparisons use dendritic additive vs. dendritic shunting; routed cores are used for cue integration.
Training strategies	standard backprop; LocalCA; DFA; FA; transported-broadcast oracle	Main text uses standard and LocalCA; DFA/FA remain appendix baselines; path transport is an oracle upper bound.
Broadcast modes	scalar; per-soma; local mismatch; low-rank; path transport; pathway vector	Main text centers on per-soma, low-rank, and transported-error controls; scalar and local-mismatch are supporting controls, while pathway vector remains an appendix structured-feedback extension.
Recent dendritic extensions	path propagation; router-derived branch roles; pathway-vector feedback; inhibitory homeostasis	These were added to test morphology-aware credit transport and structured branch-specific plasticity beyond the original 3F/4F/5F family.

Table S15: Implemented model families and LocalCA operating modes. Only a subset is used for the main claims; the remaining modes serve as controls, ablations, or structured extensions.

Model and Mode Inventory

Representative Manuscript Architectures

Hyperparameters

Table S17 collects the core training hyperparameters for each headline experiment. Learning rates are applied through parameter groups (top- k , dendritic block-linear, reactivation, decoder) with the values given in the representative config files; where a single LR is reported, every group uses that value.

Setting	Encoder	E layers	Tree	Synapses / branch	Seeds	Notes
Gradient fidelity / path-gain / noise-resilience mechanism	id.+ReLU	[128, 128]	[3, 3]	$N_E=40, N_I \in \{0, 5, 10, 20, 40\}$	5 fidelity, 5 oracle	Main mechanism sweeps in Figs. 2 and 3; reactivation <code>param_tanh</code> .
MNIST / context-gating local competence	id.+ReLU	[128]	[3, 3]	$N_E=40, N_I=20$	5	Best local 5F per-soma runs in Table S4; reactivation <code>param_tanh</code> .
Fashion-MNIST competence	id.+ReLU	[128]	[3, 3]	$N_E=40, N_I=20$	5	Dedicated five-seed standard-vs-local competence sweep; reactivation <code>param_tanh</code> .
Cue-routing PV-LocalCA	router	[64]	[2]	$N_E=10, N_I=4$	5	Learned router with two pathway groups and rank-2 structured feedback; reactivation <code>param_tanh</code> .
CIFAR-10 compact direct-I-stream mechanism extension	id.+ReLU	[20] E, no I cells	[3, 3, 3, 3]	$N_E=25, N_I=25$ direct I-to-E	5	Harder-data extension with input-driven inhibitory conductance, decoder [32, 16], and decoder-aware soma mapping.
Morphology $\times$ inhibition appendix map	id.+ReLU	[128, 128]	[2, 2], [3, 3], [4, 4], [2, 2, 2], [3, 3, 3]	$N_E=40, N_I \in \{0, 5, 10, 20, 40\}$	3	Supportive 3-seed sweep; reactivation <code>param_tanh</code> .

Table S16: **Representative architectures used in the manuscript.** All dendritic rows use explicit branch-level excitatory and inhibitory synapse banks with `somatic_synapses=false`, nonnegative conductances, and a nonnegative first-layer drive enforced by an explicit ReLU transfer stage in the main runs. The tree column gives dendritic morphology per excitatory neuron, and the synapse counts report excitatory and inhibitory synapses per branch.

Effective Broadcast Dimensionality in Headline Architectures

LocalCA Extension Compatibility

Seed Protocol and Evidence Map

The seed depth is not uniform across every sweep, and we therefore separate main evidence from supporting diagnostics. Table S20 pins each figure or table in this paper to its seed count and evidence tier.

Compute Resources

All experiments were run on an internal GPU cluster. Most MNIST, Fashion-MNIST, and synthetic-task runs used a single NVIDIA A100 or H100 GPU and finished in minutes to tens of minutes per seed. The flattened CIFAR-10 runs required longer single-GPU jobs but still did not use distributed or multi-GPU training. Reported headline metrics are aggregated over 5 seeds unless noted otherwise. The remaining 3-seed results are confined to selected supportive sweeps, and the broader exploratory screens used to tune and diagnose the method required additional compute beyond the final reported runs.

Code, Data, and Asset Availability

MNIST, Fashion-MNIST, CIFAR-10, and MICrONS are public datasets or public benchmark assets cited in the paper; we use them under their standard published access conditions and cite their original sources in the bibliography. The present anonymous submission does not include a public code URL in order to preserve double-blind review, but the paper specifies the model family, training modes, key hyperparameters, and representative configurations, and we plan to release code and configuration files after review. The paper does not release a new dataset or a stand-alone pretrained model asset.

Setting	Opt.	LR	Batch	Epochs	W-dec.	Notes
MNIST / Fashion-MNIST / context gating (5F per-soma LocalCA)	Adam	$10^{-3} / 5 \cdot 10^{-4}$ (block / react.)	256	100	0	fixed-epoch, no early stopping; <code>param_tanh</code> reactivation
MNIST / Fashion-MNIST / context gating (BP ceiling)	Adam	$10^{-3} / 5 \cdot 10^{-4}$	256	100	0	matched to LocalCA setup
Gradient fidelity / path-gain / noise resilience	Adam	10^{-3}	256	50	0	5 seeds, hooks enabled for diagnostic capture
Morphology $\times$ inhibition regime map (exploratory)	Adam	10^{-3}	256	50	0	3 seeds
Cue routing (soma-off & soma-on)	Adam	10^{-3}	256	90	0	early stopping with patience 30
CIFAR-10 compact direct-I-stream depth-4 LocalCA	Adam	$10^{-3} / 10^{-4}$ (block / react.)	256	400	0.01	grad-clip 5.0, early stop patience 50, nonlinear decoder
CIFAR-10 compact direct-I-stream depth-4 BP	Adam	10^{-3}	256	400	0.01	matched ceiling
Weight-distribution vs. depth	Adam	10^{-3}	256	100	0	<code>weight_analysis</code> hook captures final-epoch statistics
Component ablation (MNIST)	Adam	10^{-3}	256	100	0	5 seeds, single-layer dendrinet [3, 3]
(b, m) policy comparison (MNIST / CIFAR-10)	Adam	$10^{-3} / 10^{-4}$	256	100 / 400	0 / 0.01	quantile refresh every 5 epochs; EMA $\alpha \in \{0.25, 0.5, 1.0\}$

Table S17: **Training hyperparameters by experiment.** All runs use Adam with default $\beta_1=0.9$, $\beta_2=0.999$, $\varepsilon=10^{-8}$. Reactivation and block-linear parameter groups use a slower LR to keep conductance-level dynamics stable. Full configs are provided under `drafts/dendritic-local-learning/configs/`.

Setting	Hidden width(s)	Output dim	Effective default per-soma field
Gradient fidelity / path-gain / noise resilience	128, 128	10	Scalar / rank-1 at both dendritic layers
MNIST / Fashion-MNIST competence	128	10	Scalar / rank-1 at the dendritic hidden layer
Context gating competence	128	2	Scalar / rank-1 at the dendritic hidden layer
Cue routing	64	2	Scalar / rank-1 by default; higher-rank tests use explicit low-rank or pathway-vector feedback
Compact CIFAR-10 harder-data extension	20	decoder-input dim 20	Vector-valued per-soma after decoder-aware mapping; higher-rank tests use explicit low-rank or path transport

Table S18: **Effective dimensionality of the default “per-soma” broadcast in the headline architectures.** In code, per-soma uses the output error vector only when layer width matches decoder output dimension; otherwise it falls back to a shared scalar. The main feedforward settings in this paper therefore test a genuinely rank-1 broadcast regime by default, which is why the higher-rank low-rank, path-transport, and pathway-vector controls are important.

661 Algorithm

Algorithm 1 Local Credit Assignment

- 1: **Input:** Model, batch (x, y) , config $\mathcal{C}$
- 2: Forward pass; loss L , output error δ^y
- 3: Somatic/core error $\delta_0 = \text{decoder-input Jacobian product } J_{\text{dec}}(h_{\text{core}})^\top \delta^y$ (or $W_{\text{dec}}^\top \delta^y$ for a linear decoder)
- 4: **for** each layer n (reverse) **do**
- 5: $e_n = \text{broadcast}(\delta_0, \mathcal{C})$; optionally gate by pathway roles
- 6: Compute ρ_n, ϕ_n (EMA estimators, if enabled)
- 7: Apply the configured local update (Eq. 10 or 11)
- 8: **end for**
- 9: Clip gradients; optimizer step

Extension	Meaning	Compatible with	Typical use here
Per-soma broadcast	Somatic error vector when widths match, otherwise scalar fallback	3F, 4F, 5F	Default main-text LocalCA setting; in the headline feedforward runs this is effectively rank-1
Low-rank broadcast	Small number of broadcast channels instead of a scalar or full field	3F, 4F, 5F	Intermediate control when rank-1 is too restrictive
Path transport	Recursive tree-transported error using conductance-stage path gains	3F, 4F, 5F	Oracle upper-bound broadcast
Path propagation	Approximate path-gain attenuation applied to broadcast	3F, 4F, 5F	Morphology-aware modifier for deeper trees
Pathway vector	Structured branch/pathway-specific broadcast field	3F, 4F, 5F	Used mainly in PV-LocalCA on routed tasks
Branch-role rules	Scales updates by router- or pathway-derived branch specialization	3F, 4F, 5F	Used in the structured pathway extension
Inhibitory homeostasis	Auxiliary local inhibitory balancing term	3F, 4F, 5F	Optional stabilizer in routed or shunting settings

Table S19: Compatibility of the newer LocalCA extensions with the base 3F/4F/5F family. These extensions mostly modify the error field or branch scaling rather than defining a new “6F” or “7F” rule.

C Theoretical Details

Variant Taxonomy

Random-Broadcast Alignment

Proposition 5 (Supportive random-broadcast alignment). *Let the broadcast matrix B_n have i.i.d. zero-mean entries with $\mathbb{E}[B_n^\top B_n] = \alpha I$. Then the expected cosine between the resulting local gradient and the exact gradient is positive, $\mathbb{E}[\cos \angle(g^{\text{local}}, g^{\text{exact}})] \geq c_n > 0$, by an argument analogous to feedback alignment [9]. The constant c_n depends on how strongly local eligibility factors correlate with the conductance-stage path gain in Eq. (4); shunting improves this correlation by narrowing the spread of intermediate sensitivities.*

We treat this argument as supportive rather than central. The main theoretical object in the paper is still the exact pre-reactivation compartment error $\partial L / \partial V_n$; under identity upward transfer this reduces to $\alpha_n \delta_0$, while with post-voltage activation the corresponding effective path gain additionally includes local $f'_n(V_n)$ factors. The main empirical question is how faithfully different broadcast fields approximate that quantity.

Biological Analogs

D Morphology-Aware Extensions

Path-integrated propagation. Modulate broadcast error by $\pi_n = \pi_{n-1} \cdot R_{n-1}^{\text{tot}} \cdot \bar{g}_{n-1}^{\text{den}}$, approximating depth attenuation from Eq. 4.

Depth modulation. Per-branch scaling $\rho_j = \rho_{\text{base}} / (d_j + \alpha)$, mirroring cable attenuation.

Dendritic normalization. $\Delta g_j^{\text{den}} \leftarrow \Delta g_j^{\text{den}} / (\sum_k g_k^{\text{den}} + \varepsilon)$, analogous to homeostatic scaling [21].

Figure / Table	Sweep	Replication	Tier
Fig. 1	Model, rule, and broadcast definitions	N/A	Definitions
Fig. 2	Gradient-fidelity diagnostic	5 seeds	Headline
Fig. 3	Mechanistic chain + oracle + summary	5 seeds	Headline
Fig. 4	Competence / regime dose-response	5 seeds	Headline
Fig. S8 / Table S6	CIFAR-10 compact direct-I-stream mechanism extension	5 seeds	Supportive
Fig. S12	Cue-routing (soma off)	5 seeds	Supportive
Table S4	Competence gaps (BP ceiling vs. 5F)	5 seeds	Headline
Fig. S13	Soma-on extension across manuscript families	Family aggregates (144–420 cfigs)	Supportive
Table S13	Soma-on delta summary across manuscript families	Family aggregates	Supportive
Fig. S15	(b, m) update-policy comparison	Matched 4-cell grid / bar	Supportive
Fig. S16	Component ablation (MNIST)	5 seeds	Supportive
Fig. S14	Cue-routing soma-on (stable subset)	5 seeds	Supportive
Table S9	Fitted direct-I inhibitory path-gain diagnostic	5 runs	Supportive
Fig. S17	Weight-distribution sensitivity	5 seeds	Supportive
Fig. S18	Weight-distribution vs. depth	5 seeds	Supportive
Fig. S19	Weight-distribution soma-off vs. soma-on	5 seeds	Supportive
Fig. S9 / Table S7	CIFAR-10 depth-4 soma extension	3 seeds	Supportive
Fig. S7	FA/DFA baseline comparison	5 seeds	Supportive
Fig. S6	Broadcast-bandwidth / quantization	5 seeds	Supportive
Fig. S10	Additive + normalization control	5 seeds	Supportive
Fig. S5 / S4	Stress tests; verification	5 seeds	Supportive
Fig. S3	5F sensitivity	3 seeds	Supportive
Table S10	Rank-bridge	5 seeds	Supportive
Fig. 5	Morphology $\times$ inhibition map	3 seeds	Supportive
Fig. S11 / Table S8	One-layer direct-I vs. explicit-I input-mode probe	3 seeds	Supportive
Signed-input info-shunting	Signed-input stress test	1–3 seeds	Exploratory

Table S20: **Evidence map.** Each main-paper and appendix figure or table is pinned to its sweep and replication type. Most main claims come from dedicated 5-seed sweeps; the supporting soma-extension and (b, m) policy appendices instead summarize matched sweep families or matched config grids, and are labeled accordingly. The BP ceilings in Table S4 come from dedicated matched-capacity 5-seed standard-training refreshes.

683 **Pathway-vector feedback.** For tasks with latent pathway structure, the broadcast becomes a role
684 vector inferred from the router. Local pathway activity gates this vector. Upward block transport then
685 passes it to earlier branches, aligning their feedback with downstream descendants.

686 **Router-derived branch roles.** Each branch receives a role profile inferred from router assignments
687 and incoming block weights rather than from a hand-coded apical/basal label. Plasticity is then
688 modulated by branch selectivity and a synapse-specific role-alignment factor, emphasizing pathway-
689 consistent updates without imposing a heuristic branch taxonomy.

Asset	Use in this paper	Access / license note
MNIST	Digit classification and derived nonnegative synthetic tasks	Public academic benchmark credited to the original dataset authors; used through standard public access, with no raw-data redistribution.
Fashion-MNIST	Apparel classification stress test	Public benchmark released with the Fashion-MNIST paper and repository; used through standard public access, with no raw-data redistribution.
CIFAR-10	Flattened harder-data diagnostic	Public research benchmark from the CIFAR dataset collection; used through standard public access, with no raw-data redistribution.
MICrONS	Biological reference statistics in the weight-distribution appendix	Public connectomics resource cited to the MICrONS Consortium; only aggregate comparison statistics are reported here.
Synthetic tasks	Context gating, noise resilience, cue integration	Generated procedurally from public benchmarks or random seeds described in Appendix I; no new third-party asset is introduced.

Table S21: **Existing assets used in the manuscript.** We credit the original sources in the bibliography, use public benchmark assets under their published access conditions, and do not redistribute third-party raw data in the anonymous submission.

Rule	Factors	Cost	Best regime
3F	$x, (E - V), e$	$\mathcal{O}(1)$	Baseline
4F	$3F + \rho$	$\mathcal{O}(1)$	Improved conditioning
5F	$4F + \phi$	$\mathcal{O}(d_n)$	Strongest overall
5F+VH	$5F + \text{local voltage homeostasis}$	$\mathcal{O}(d_n)$	Stabilized LocalCA / warm-up
PV-LocalCA	$3F + \text{structured } e_n + \text{role alignment}$	$\mathcal{O}(r_n)$	Pathway discovery

Table S22: Variant taxonomy. ‘5F+VH’ denotes the same base 5F rule with an additional strictly local voltage-centering auxiliary that can also be scheduled through multi-stage LocalCA warm-up; the codebase also supports this as a shorthand ‘5f_vh’ alias in configuration files.

E HSIC Auxiliary Objectives

Following [17], we use kernel-based HSIC objectives:

$$\mathcal{L}^{\text{self}} = B^{-2} \text{tr}(\mathbf{K}_Z \mathbf{H} \mathbf{K}_Z \mathbf{H}), \quad \mathcal{L}^{\text{target}} = -B^{-2} \text{tr}(\mathbf{K}_Z \mathbf{H} \mathbf{K}_Y \mathbf{H}).$$

Moderate weights (0.01–0.1) help on context gating; negligible on MNIST. Online statistics (ρ_n, ϕ_n) use Welford’s algorithm [20].

F Online Variant with Eligibility Traces

The continuous-time eligibility trace is

$$\tau_e \dot{e}_j^{\text{syn}} = -e_j^{\text{syn}} + x_j(E_j - V_n)R_n^{\text{tot}},$$

with update

$$\Delta g_j^{\text{syn}} \propto \int e_j^{\text{syn}}(t) m_n(t) dt$$

[18, 19].

G Weight Statistics and Biological References

As a secondary analysis, we examine whether the conductance-based update naturally induces characteristic weight statistics. Because synaptic updates scale with input resistance $R_n^{\text{tot}} = 1/g_n^{\text{tot}}$, the volt-

Component	Analog	Interpretation
R_n^{tot}	Input resistance	Sensitivity modulation
$(E_j - V_n)$	Synaptic driving force	Local gradient factor
Shunting	Divisive normalization	$\partial V / \partial g_I \propto -V$
ρ_n	Layer relevance	Output correlation
ϕ_n	Signal propagation	Conditional predictability
Pathway vector	Branch-specific top-down drive	Structured teaching signal
Role alignment	Pathway-selective plasticity	Branch specialization

Table S23: Biological analogs.

Condition	MNIST		Fashion-MNIST	
	Exc σ	Inh σ	Exc σ	Inh σ
BP + Shunting	0.94±0.01	0.87±0.01	0.92±0.01	0.84±0.01
BP + Additive	1.30±0.01	1.22±0.01	1.16±0.01	1.05±0.01
Local + Shunting	1.22±0.01	1.71±0.02	1.13±0.06	1.36±0.06
Local + Additive	1.69±0.16	1.57±0.07	1.43±0.16	1.11±0.12
Song et al. 2005	$\sigma = 0.94$ (rat V1 L5, EPSP amplitude)			
MICrONS E→E	$\sigma = 1.14$ (mouse V1, synapse size, $n=3.9\text{M}$)			
MICrONS I→E	$\sigma = 0.92$ (mouse V1, synapse size, $n=3.5\text{M}$)			

Table S24: **Weight distribution width.** Log-normal σ of excitatory and inhibitory synaptic weights (mean±std across 5 seeds). Biological references are included only as descriptive anchors. With biologically constrained E/I ratios (4:1), shunting self-normalization produces weight heterogeneity in the range spanned by those references, whereas additive integration is broader and less stable.

age equation implies multiplicative weight dynamics, creating a regime analogous to exponentiated-gradient updates. Such multiplicative dynamics suggest log-normal weight distributions in trained networks [38, 39]. We compare the resulting distributions against two biological references: electrophysiological data from Song et al. [38] (rat V1 L5 pyramidal, $\sigma = 0.94$) and the MICrONS mm³ connectome [40] (mouse V1 synapse sizes).

Model weight distributions are log-normal. We fit log-normal distributions to the active (top- K masked) excitatory synaptic weights after training on MNIST and Fashion-MNIST. Table S24 shows the fitted σ (standard deviation of $\log w$) for each condition. Shunting consistently produces narrower distributions than additive integration, and backpropagation produces narrower distributions than local learning. These two factors combine approximately additively: BP+Shunting → narrowest, Local+Additive → broadest.

Shunting is closest to the biological references considered here. BP+Shunting produces $\sigma = 0.94$ on MNIST, very close to the Song et al. reference ($\Delta = 0.008$). Local+Shunting produces $\sigma = 1.13$ – 1.22 , close to MICrONS E→E synapse sizes ($\sigma = 1.14$; $\Delta \leq 0.08$). By contrast, Local+Additive produces $\sigma = 1.43$ – 1.69 , broader than any biological reference considered. This pattern is consistent across datasets (MNIST and Fashion-MNIST), suggesting it reflects structural properties of the learning rule rather than task-specific features.

The match depends on inhibitory conductance. We test sensitivity to the E/I synapse ratio using a sweep over $N_I \in \{0, 2, 5, 10, 20, 30, 40\}$ inhibitory synapses per branch (Appendix Fig. S17). Without inhibition ($N_I=0$), all conditions produce $\sigma > 2.0$, far from biology. With biologically constrained ratios ($N_I=10$ – 20 , corresponding to E/I ratios of 4:1 to 2:1; [42]), shunting networks enter the biological range ($\sigma \approx 0.9$ – 1.2), while the effect of N_I on additive networks is less systematic. The weight distribution shape is also robust to dendritic depth (branch factors [9] through [3,3,3,3]; see Appendix Fig. S17A): BP+Shunting converges toward Song et al. with increasing depth, while Local+Shunting remains near MICrONS E→E across depths.




Figure S17: **Synaptic weight distribution sensitivity to architecture.** (A) Log-normal σ vs. dendritic depth (branch factors [9] to [3,3,3,3]). Both backprop and local shunting remain closer to the biological-width references than their additive counterparts across depth. (B) σ vs. inhibitory synapses per branch (N_I). Without inhibition ($N_I=0$), all conditions are overly broad; with biologically constrained $N_I=10$ –20, shunting enters the biological range. Shaded bands show the sweep over $N_E=20$ to 80. (C) Summary of MNIST and Fashion-MNIST results with biological references. The shunting ordering is consistent across datasets. (D) Excitatory vs. inhibitory weight σ on MNIST with MICrONS E→E and I→E reference bands.

H Weight Distribution Sensitivity Analysis

Side-by-side BP vs. LocalCA across depths. To complement the per-architecture analysis above, we ran a matched BP vs. LocalCA sweep over three branch-factor settings ([2, 2], [3, 3], [3, 3, 3]) under both shunting and additive cores on MNIST (5 seeds per cell; quantile init; learned (b, m) for LocalCA). Figure S18 shows that at shallow and medium depths the local rule and backprop reach broadly similar excitatory weight means (≈ 0.8 – 0.9), while the coefficient of variation (CV) under LocalCA is roughly twice as large as under BP at these depths (e.g. shunting [2, 2]: $CV_{BP} = 0.15$ vs. $CV_{Loc.} = 0.31$; shunting [3, 3]: 0.11 vs. 0.26). At the deepest setting [3, 3, 3] the weight means drop and the CV jumps substantially for both optimizers ($CV \approx 0.66$ – 0.88), and test accuracy drops by ~ 5 pp for BP and ~ 15 – 20 pp for LocalCA. Across the explored depth range, shunting LocalCA stays closer to shunting BP than additive LocalCA does to additive BP on both weight and accuracy axes, consistent with the manuscript claim that the conductance denominator is the key mechanistic ingredient.

Weight distributions under soma-on. To check whether the direct somatic synapse extension (Fig. S13) alters the weight-distribution picture, we ran a matched 5-seed sweep at depth [3, 3] on MNIST with `somatic_synapses=true` across all four (core, strategy) cells; results are summarized in Fig. S19. Two effects emerge. First, shunting + BP becomes *tighter* than in the soma-off case: excitatory-weight CV drops from ≈ 0.11 (soma-off, [3, 3]) to ≈ 0.10 (soma-on), consistent with the soma sink absorbing part of the drive and reducing per-branch variance. Second, shunting + LocalCA goes in the opposite direction: CV grows from ≈ 0.26 (soma-off) to ≈ 0.40 (soma-on), while MNIST test accuracy drops ~ 3 pp (from 96.5% to 93.6%). Additive cores sit between these extremes ($CV \approx 0.23$ – 0.30 , accuracy 95.7–97.0%) and are only weakly affected. The ordering is consistent with




Figure S18: **Synaptic weight statistics vs. dendritic depth (MNIST, 5 seeds/cell).** (A) Excitatory weight mean (error bars = std). At [2, 2] and [3, 3], all four conditions cluster around 0.8–0.9; at [3, 3, 3] the means drop to ≈ 0.5 –0.75 and the cross-seed spread grows, especially for additive LocalCA. (B) Coefficient of variation (CV = std/mean). At shallow/medium depth, LocalCA produces $\sim 2\times$ higher CV than matched BP, but both remain well-behaved (≤ 0.33). At the deepest network all four conditions jump to CV ≈ 0.66 –0.88, with additive LocalCA the broadest. (C) MNIST test accuracy. BP tracks ~ 96 –97% at [2, 2]/[3, 3] and ~ 92 –95% at [3, 3, 3]. LocalCA stays within ~ 5 –6 pp of BP at shallow/medium depth but trails by ~ 15 –20 pp at [3, 3, 3], identifying depth as the remaining open challenge for this local rule. The qualitative ordering (shunting LocalCA tracks shunting BP more closely than additive LocalCA tracks additive BP) reinforces the manuscript claim that the conductance denominator is the key mechanistic ingredient.




Figure S19: **Excitatory-weight CV and MNIST accuracy under soma-off vs. soma-on (depth [3, 3], 5 seeds/cell).** (A) Coefficient of variation of excitatory weights for the four (core, strategy) cells; paired bars show soma-off (from Fig. S18) and soma-on (this sweep). Shunting + BP tightens slightly; shunting + LocalCA broadens; additive cells change little. (B) Matched MNIST test accuracy (sanity panel). BP accuracy is preserved or marginally improved; LocalCA accuracy is preserved for additive but drops ~ 3 pp for shunting, consistent with the CV widening in panel A.

748 the mechanism in the main text: the somatic synapse is an additional BP-visible path that backprop
749 exploits cleanly, but under the local rule it adds broadcast variance that the scalar/per-soma signal
750 cannot sharpen, widening the weight distribution without a matching accuracy gain.

751 **MICrONS connectome analysis.** We extracted synapse size distributions from the MICrONS
752 mm³ condensed connectome (v1181; 9.0M connections, 71.9K neurons; 89% excitatory). Split-
753 ting by pre/post cell type: E→E connections ($n=3.85$ M) show $\sigma_{\text{size}}=1.14$ and CV=1.01; I→E
754 ($n=3.53$ M) show $\sigma=0.92$ and CV=1.03; E→I ($n=1.11$ M) show $\sigma=0.83$; I→I ($n=0.51$ M) show
755 $\sigma=0.85$. Inhibitory connections are more frequently multi-synaptic (I→E: 37.5% multi-synapse;
756 E→E: 11.5%), and inhibitory synapses are on average smaller (median 3532 vs. 4676 for E→E).

757 **Sensitivity to ee_synapses.** Using the E/I grid sweep ($N_E \in \{20, 40, 80\}$ and $N_I \in$
758 $\{0, 2, 5, 10, 20, 30, 40\}$; 168 models), excitatory σ increases modestly with N_E in both architec-
759 tures, but the shunting-versus-additive ordering is preserved at every N_E value. The dominant driver
760 of σ is still N_I : moving from $N_I=0$ to $N_I=10$ reduces shunting σ by roughly 1.0–1.5 units, while
761 the effect on additive is smaller and less systematic.




Figure S20: **Synthetic benchmark schematics.** (A) Context gating: the right half carries the MNIST digit; the left half is filled with low-amplitude uniform noise. (B) Noise resilience: MNIST image corrupted by structured channel noise (fixed 50-D latent projection, $\sigma_{\text{task}} = 1.5$, clipped to $[0, 1]$). (C) Cue integration: a context cue selects which of two noisy cue streams is reliable; dendritic integration routes the reliable cue to the binary readout. (D) Fashion-MNIST: 10-class apparel classification sharing the MNIST input shape.

Sensitivity to depth. From the depth-scaling sweep ($[9]$, $[3,3]$, $[3,3,3]$, $[3,3,3,3]$; 80 models, 5 seeds each), BP+Shunting excitatory σ decreases with depth ($1.06 \rightarrow 0.90$), converging toward Song et al. (0.94). Local+Shunting σ increases slightly ($1.18 \rightarrow 1.33$) but remains in the biological range at shallow depths. BP+Additive shows the strongest depth sensitivity ($1.38 \rightarrow 0.79$), while Local+Additive diverges with depth ($2.01 \rightarrow 2.44$). The morphology-aware modulators (path propagation, depth/centrality weighting) have negligible effect on σ .

Mechanistic interpretation. The shunting conductance $g_n^{\text{tot}} = g_n^{\text{leak}} + \sum g_n^{\text{exc}} + \sum g_n^{\text{inh}}$ appears in the update factor $R_n^{\text{tot}} = 1/g_n^{\text{tot}}$. As inhibitory conductance increases, g_n^{tot} grows and R_n^{tot} shrinks, compressing the multiplicative scale of weight updates. This is analogous to a learning rate that self-adjusts via the total conductance: strong synapses contribute more to g_n^{tot} , reducing their own future update magnitude. This acts as a natural form of weight-dependent regularization. The resulting equilibrium distribution is log-normal, consistent with Loewenstein et al. [41] and related multiplicative spine-dynamics analyses. Additive integration lacks this self-normalizing mechanism, producing broader distributions that fall outside the biological range.

I Synthetic Benchmark Descriptions

Each synthetic task is generated procedurally from a fixed random seed and uses fixed train/val/test splits for reproducibility. The MNIST-derived synthetic tasks use flattened 28×28 inputs; cue integration instead uses a small vector input with two output classes. Output dimensionality therefore varies by task and is stated in the task description when it differs from 10-way digit classification. Figure S20 gives a visual summary of each benchmark.

Context gating. Inputs are contextual figure-ground MNIST examples. The right half of the image carries the original MNIST digit, while the left half is replaced by low-amplitude uniform noise; all pixels therefore remain nonnegative. This task tests whether credit assignment can exploit a simple context-dependent spatial structure without leaving the nonnegative-drive regime of the conductance model. The HSIC auxiliary objective (weight 0.01) is used to decorrelate layer representations, adding roughly 3 pp under local learning.

Noise resilience. Inputs are flattened MNIST images corrupted by structured channel noise: a fixed 50-dimensional latent Gaussian perturbation is projected into input space and added to each example, with $\sigma_{\text{task}} = 1.5$, then clipped to $[0, 1]$. The projection is fixed across training, so the network must filter correlated interference to recover the underlying class signal. Credit assignment must remain coherent under the corrupted signal, making this task particularly sensitive to path-gain dispersion.

Info shunting. Inputs contain two additive streams: a low-frequency signal and a high-frequency distractor drawn with equal energy, together with a separate context channel indicating which stream is relevant on each trial. This benchmark uses signed synthetic inputs, so it violates the nonnegative presynaptic-drive assumption enforced in the main experiments. We therefore retain it only as an exploratory stress test and exclude it from the main-text claims.

Cue integration. Two noisy cue streams (A and B) are presented simultaneously, each carrying partial information about one of 2 classes. A binary one-hot context signal indicates which cue is reliable on each trial (cue A or cue B), and each cue vector is clipped to $[0, 1]$ after noise is added. The fixed-pathway variant duplicates the context into both cue branches; the learned-routing variant requires the router to discover the cue separation from data. This task is used in Sec. A to test structured pathway-vector broadcast while staying inside the nonnegative-input regime.

J Depth Scaling and Noise Robustness

Depth scaling. Varying dendritic depth from 1–4 layers (branch factors $[9]$ to $[3, 3, 3, 3]$): shunting local degrades from 63.5% to 57.4%; additive local degrades more steeply from 54.9% to 29.7%. The shunting advantage grows with depth ($+8.5 \rightarrow +27.7$ pp). Backprop ceilings remain stable at about 90–92%. See Fig. S5A.

Noise robustness. Gaussian noise $\mathcal{N}(0, \sigma^2)$ on broadcast error: shunting is robust to $\sigma \leq 0.1$ (about 62%) while additive drops from 46.5% to chance at $\sigma=1.0$, confirming that shunting credit signals carry useful learning information beyond the broadcast magnitude. See Fig. S5B.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [\[Yes\]](#)

Justification: The abstract and introduction state the paper’s main mechanistic claim, the scope of the conductance-based setting, and the regime-dependent nature of the empirical results; see Sec. 1 and Sec. 4.6.

Guidelines:

- The answer [\[N/A\]](#) means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [\[No\]](#) or [\[N/A\]](#) answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [\[Yes\]](#)

Justification: The discussion explicitly narrows the scope of the claims and discusses limitations involving benchmark strength, broadcast assumptions, depth scaling, and the exploratory stress tests; see Sec. 4.6.

Guidelines:

- The answer [\[N/A\]](#) means that the paper has no limitation while the answer [\[No\]](#) means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.

- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors should reflect on how these assumptions might be violated in practice and what the implications would be.
- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [\[Yes\]](#)

Justification: The voltage model, assumptions, theorem statements, and proof details are given in Sec. 2 and Appendix C; proof sketches and the exact factorization sanity check are cross-referenced in the main text.

Guidelines:

- The answer [\[N/A\]](#) means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [\[Yes\]](#)

Justification: The main paper and appendices specify the datasets, architectures, local-rule family, broadcast modes, representative hyperparameters, and compute regime needed to reproduce the headline results; see Sec. 4 and Appendix B.

Guidelines:

- The answer [\[N/A\]](#) means that the paper does not include experiments.
- If the paper includes experiments, a [\[No\]](#) answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.

- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.
- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [No]

Justification: To preserve double-blind review, the anonymous submission does not include a public repository or anonymized code bundle. The paper instead provides architectural, algorithmic, and configuration details and states that code and configs will be released after review; see Appendix B.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

Question: Does the paper specify all the training and test details (e.g., data splits, hyperparameters, how they were chosen, type of optimizer) necessary to understand the results?

Answer: [Yes]

Justification: The main text states the benchmark families, seed protocol, representative local-rule settings, and major training choices, while the appendices provide implementation details and operating-mode inventories; see Sec. 4 and Appendix B.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The experimental setting should be presented in the core of the paper to a level of detail that is necessary to appreciate the results and make sense of them.
- The full details can be provided either with the code, in appendix, or as supplemental material.

7. Experiment statistical significance

Question: Does the paper report error bars suitably and correctly defined or other appropriate information about the statistical significance of the experiments?

Answer: [Yes]

Justification: The paper reports means and standard deviations across 5 seeds for the headline results and across 3 seeds for selected appendix-only support sweeps, states this explicitly in the text, and shows error bars or seed variability in the relevant tables and figures; see Sec. 4 and Appendix A.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- The authors should answer [Yes] if the results are accompanied by error bars, confidence intervals, or statistical significance tests, at least for the experiments that support the main claims of the paper.
- The factors of variability that the error bars are capturing should be clearly stated (for example, train/test split, initialization, random drawing of some parameter, or overall run with given experimental conditions).
- The method for calculating the error bars should be explained (closed form formula, call to a library function, bootstrap, etc.)
- The assumptions made should be given (e.g., Normally distributed errors).
- It should be clear whether the error bar is the standard deviation or the standard error of the mean.
- It is OK to report 1-sigma error bars, but one should state it. The authors should preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis of Normality of errors is not verified.
- For asymmetric distributions, the authors should be careful not to show in tables or figures symmetric error bars that would yield results that are out of range (e.g., negative error rates).
- If error bars are reported in tables or plots, the authors should explain in the text how they were calculated and reference the corresponding figures or tables in the text.

8. Experiments compute resources

Question: For each experiment, does the paper provide sufficient information on the computer resources (type of compute workers, memory, time of execution) needed to reproduce the experiments?

Answer: [Yes]

Justification: Appendix B describes the internal GPU cluster setting, the use of single A100/H100-class GPUs, rough per-run runtime scales, and the fact that broader exploratory sweeps required additional compute beyond the final reported runs.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.

- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The work uses standard public benchmarks and mechanistic simulations, does not involve human-subjects experimentation or restricted data collection, and we are not aware of any aspect that violates the NeurIPS Code of Ethics.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: The discussion includes a broader-relevance and potential-harms paragraph that distinguishes mechanistic neuroscience relevance from possible misuse through overclaiming biological plausibility or overstating robustness; see Sec. 4.6.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

Question: Does the paper describe safeguards that have been put in place for responsible release of data or models that have a high risk for misuse (e.g., pre-trained language models, image generators, or scraped datasets)?

Answer: [N/A]

Justification: The submission does not release a high-risk generative model, foundation model, or scraped dataset, so the safeguard question is not applicable here.

Guidelines:

- The answer [N/A] means that the paper poses no such risks.
- Released models that have a high risk for misuse or dual-use should be released with necessary safeguards to allow for controlled use of the model, for example by requiring that users adhere to usage guidelines or restrictions to access the model or implementing safety filters.
- Datasets that have been scraped from the Internet could pose safety risks. The authors should describe how they avoided releasing unsafe images.
- We recognize that providing effective safeguards is challenging, and many papers do not require this, but we encourage authors to take this into account and make a best faith effort.

12. Licenses for existing assets

Question: Are the creators or original owners of assets (e.g., code, data, models), used in the paper, properly credited and are the license and terms of use explicitly mentioned and properly respected?

Answer: [Yes]

Justification: The paper credits all benchmark and connectomic assets, does not redistribute third-party raw assets, and includes an asset/access table with license or access terms where available; see Appendix B.

Guidelines:

- The answer [N/A] means that the paper does not use existing assets.
- The authors should cite the original paper that produced the code package or dataset.
- The authors should state which version of the asset is used and, if possible, include a URL.
- The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- For scraped data from a particular source (e.g., website), the copyright and terms of service of that source should be provided.
- If assets are released, the license, copyright information, and terms of use in the package should be provided. For popular datasets, paperswithcode.com/datasets has curated licenses for some datasets. Their licensing guide can help determine the license of a dataset.
- For existing datasets that are re-packaged, both the original license and the license of the derived asset (if it has changed) should be provided.
- If this information is not available online, the authors are encouraged to reach out to the asset's creators.

13. New assets

Question: Are new assets introduced in the paper well documented and is the documentation provided alongside the assets?

Answer: [N/A]

Justification: The paper does not release a new dataset, benchmark, or pretrained model asset in this anonymous submission.

Guidelines:

- The answer [N/A] means that the paper does not release new assets.
- Researchers should communicate the details of the dataset/code/model as part of their submissions via structured templates. This includes details about training, license, limitations, etc.

1106	• The paper should discuss whether and how consent was obtained from people whose asset is used.
1107	
1108	• At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.
1109	
1110	14. Crowdsourcing and research with human subjects
1111	Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?
1112	
1113	Answer: [N/A]
1114	
1115	Justification: The work does not involve crowdsourcing or direct research with human subjects.
1116	
1117	Guidelines:
1118	• The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
1119	
1120	• Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
1121	
1122	
1123	• According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.
1124	
1125	
1126	15. Institutional review board (IRB) approvals or equivalent for research with human subjects
1127	
1128	Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?
1129	
1130	
1131	
1132	Answer: [N/A]
1133	
1134	Justification: The work does not involve crowdsourcing or human-subjects research requiring IRB review.
1135	
1136	Guidelines:
1137	• The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
1138	
1139	• Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
1140	
1141	• We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
1142	
1143	
1144	• For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.
1145	
1146	16. Declaration of LLM usage
1147	Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does <i>not</i> impact the core methodology, scientific rigor, or originality of the research, declaration is not required.
1148	
1149	
1150	
1151	Answer: [N/A]
1152	
1153	Justification: LLMs are not part of the proposed method, theorem, experiments, or analysis pipeline, so no declaration is required for the core scientific contribution.
1154	
1155	Guidelines:
1156	• The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
1157	
1158	• Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.