
Shunting Concentrates Path Gains and Improves Local Credit Assignment in Dendritic Networks

Anonymous Author(s)

Affiliation

Address

email

Abstract

When can a biologically plausible somatic broadcast substitute for the exact compartment-specific errors required by backpropagation? We show that, in conductance-based dendritic networks, the answer is controlled by a single biophysical quantity: the concentration of conductance-stage path gains across the dendritic tree. We derive exact gradients for conductance-based dendritic trees and prove that each synaptic gradient factorises into a synapse-local eligibility term and a single non-local compartment error (Theorem 1). Shunting inhibition, by entering the membrane conductance denominator, concentrates these path gains and therefore makes one shared low-bandwidth broadcast a much better proxy for the true compartment-specific errors. We test this causal chain directly. A gradient-fidelity diagnostic shows that shunting produces more backprop-like local gradients than the additive control on MNIST (cosine alignment 0.202 vs. 0.006; scale mismatch 0.117 vs. 1.053). On the corrected nonnegative-input noise-resilience benchmark, a transported-error oracle raises additive local learning from 66.8% under rank-1 per-soma broadcast to 92.4–94.0%, nearly matching shunting at 94.3–95.2%, which identifies broadcast fidelity as the dominant bottleneck. Under practical constraints (rank-1 shared broadcast, nonnegative inputs and conductances), shunting LocalCA reaches within about 5–6 percentage points of the matched backpropagation ceiling on MNIST, Fashion-MNIST, and context-gating. We also release an open dendritic-analysis framework supporting arbitrary tree morphologies, the full local-rule family, and the mechanistic diagnostics developed here. The paper’s contribution is therefore mechanistic rather than benchmark-leading: it identifies conductance-stage path-gain concentration under shunting as the key condition that determines when simple local credit assignment is effective in dendritic networks.

1 Introduction

Credit assignment in deep networks usually depends on backpropagation: global error transport through symmetric pathways with no obvious biological substrate. Dendritic compartments suggest an alternative. Each synapse has access to rich local state such as driving force, membrane conductance, and branch voltage, while supervisory information could arrive as a low-bandwidth broadcast from the soma [14]. The question here is when such local information is sufficient for useful learning.

Starting from conductance-based dendritic voltage equations [1], we derive exact gradients for dendritic trees (Theorem 1) and show that each synaptic gradient factorizes into purely local eligibility terms and a single non-local compartment error. Approximating that compartment error with a broadcast signal yields a theorem-facing local rule (3F), together with practical heuristic wrappers (4F/5F), and higher-rank broadcast extensions for tasks where different branches must be credited differently.

37 The central finding is mechanistic: shunting improves broadcast fidelity by concentrating conductance-
38 stage path gains. On MNIST, conductance-stage path-gain CV stays around 0.21–0.25 under shunting
39 across the inhibited regimes versus about 0.97–1.16 under additive integration, so one shared broad-
40 cast is a much better proxy for compartment-specific errors under shunting. On the corrected noise-
41 resilience sweep, per-soma broadcast reaches cosine alignment of about 0.20–0.24 under shunting
42 across the inhibited regimes versus about 0.14–0.19 under additive, while additive can still perform
43 well once other local sensitivities are favorable. Our question is therefore not whether local learning
44 can match backpropagation on standard benchmarks, but what biophysical mechanism determines
45 when low-bandwidth local credit assignment works in conductance-based dendritic networks. An
46 oracle experiment that supplies the exact conductance-stage transported compartment errors strongly
47 supports path-gain fidelity as the dominant bottleneck: across the same noise-resilience regimes,
48 additive local learning rises from roughly 67–84% under per-soma broadcast to about 92–94% under
49 the oracle, nearly matching shunting.

50 We quantify these effects with a gradient-fidelity diagnostic based on directional alignment and scale
51 mismatch between local and backprop gradients (Fig. 2).

52 **Contributions.** This is a mechanism paper, not a benchmark-leadership paper. We contribute: (i) an
53 exact factorization theorem for conductance-based dendritic trees (Theorem 1, Corollary 1) that writes
54 every synaptic gradient as a synapse-local eligibility term times a single non-local compartment
55 error; (ii) a gradient-fidelity diagnostic linking this factorization to behavior, showing shunting
56 produces backprop-like local gradients while additive does not (Sec. 4.3); (iii) a transported-error
57 oracle (Sec. 4.4) that isolates broadcast quality as the dominant bottleneck, with a morphology-aware
58 path-propagation proxy and higher-rank unstructured controls that close a substantial fraction of the
59 oracle gap; (iv) a structured rank- K extension (pathway-vector LocalCA) and a direct-soma extension
60 that close the failure modes of rank-1 shared broadcast in routed and deeper regimes (Sec. 4.10,
61 Appendix); and (v) an open dendritic-modeling framework supporting arbitrary tree morphologies,
62 both conductance-based and additive integration, the full family of local rules (3F/4F/5F, FA, DFA,
63 transported-error oracle), and the mechanistic diagnostics developed here (path-gain CV, gradient
64 fidelity, oracle transport, weight-distribution statistics). This paper uses the framework to study local
65 credit assignment; the same codebase supports related dendritic analyses beyond the scope of this
66 manuscript.

67 2 Compartmental Voltage Model and Gradient Derivation

68 We use a steady-state conductance model derived from discretized passive cable dynamics [1, 2]. In
69 normalized units, leak and inhibitory reversal are set to 0, the excitatory reversal is set to 1, and leak
70 conductance is fixed at 1. Each compartment voltage is therefore a conductance-weighted average.
71 Two properties of this form matter for what follows: local sensitivities depend on both driving force
72 ($E - V$) and input resistance R^{tot} , and shunting inhibition corresponds to adding conductance when
73 $E_{\text{inh}} \approx 0$. Throughout the paper we write dendritic morphologies as rooted trees $[b_1, b_2, \dots, b_D]$,
74 where each factor gives the fan-in from one dendritic stage to the next on the path to the soma. Thus
75 $[3, 3]$ means that each soma aggregates 3 proximal branches and each proximal branch aggregates 3
76 distal branches, for 9 distal leaves per soma. In code, each excitatory unit is a stack of branch layers,
77 each branch layer carries explicit excitatory and optional inhibitory synapse banks plus a branch-to-
78 parent aggregation map, and the headline feedforward regime keeps `somatic_synapses=false` so
79 inputs terminate on dendritic branches rather than directly on the soma. The additive and shunting
80 cores are therefore architecture-matched at the tree level; they differ only in the branch-level voltage
81 integration rule.




Figure 1: Model and credit assignment. (A) Orientation to the full learning problem. Inputs drive a rooted dendritic tree whose distal compartments feed proximal branches and then the soma. Exact backpropagation supplies compartment-specific errors $\partial L / \partial V_n$, while LocalCA replaces them with one shared low-bandwidth broadcast e_n ; the synapse update then combines that non-local signal with local quantities available at the compartment. (B) Single-compartment conductance computation. Excitatory synapses, inhibitory synapses, and child branches all contribute to the compartment voltage, while inhibition also enters the total conductance in the denominator. The mini-histograms summarize the visual intuition used throughout the paper: shunting concentrates path gains, whereas additive integration leaves them broad. (C) Local rule family. 3F is the theorem-facing rule; 4F adds the heuristic morphology-aware factor ρ_n ; 5F adds the heuristic confidence-like factor ϕ_n . (D) Broadcast approximations. Scalar uses one shared field, per-soma uses a vector when widths match and otherwise falls back to scalar, random low-rank adds a few unstructured channels, and pathway feedback preserves branch identity when different pathways should receive different teaching signals. (E) Representative MNIST learning dynamics from the fixed-epoch Figure 1 sweep. Shunting with the stronger local wrappers tracks backprop much more closely than the additive control, previewing the more quantitative fidelity analyses in Fig. 2.

2.1 Voltage Equation and Local Sensitivities

Consider compartment n with synaptic inputs j (activity x_j , reversal E_j , conductance $g_j^{\text{syn}} \geq 0$) and dendritic inputs from children (voltage V_j , conductance $g_j^{\text{den}} \geq 0$). The steady-state voltage is:

$$V_n = \frac{\sum_j E_j x_j g_j^{\text{syn}} + \sum_j V_j g_j^{\text{den}}}{\underbrace{\sum_j x_j g_j^{\text{syn}} + \sum_j g_j^{\text{den}} + 1}_{g_n^{\text{tot}}}}, \quad R_n^{\text{tot}} = 1/g_n^{\text{tot}}. \quad (1)$$

V_n is a convex combination of reversal potentials, child voltages, and leak. Writing $\mathcal{S}_n = \{0\} \cup \{E_j\}_j \cup \{V_j\}_j$, we have $\min \mathcal{S}_n \leq V_n \leq \max \mathcal{S}_n$ and $0 < R_n^{\text{tot}} \leq 1$. The local sensitivities follow directly:

Proposition 1 (Local Sensitivities).

$$\frac{\partial V_n}{\partial g_i^{\text{syn}}} = x_i R_n^{\text{tot}} (E_i - V_n), \quad \frac{\partial V_n}{\partial V_i} = g_i^{\text{den}} R_n^{\text{tot}}, \quad \frac{\partial V_n}{\partial g_i^{\text{den}}} = R_n^{\text{tot}} (V_i - V_n). \quad (2)$$

88 2.2 Shunting Inhibition as Divisive Gain Control

89 An inhibitory synapse with $E_{\text{inh}} \approx 0$ contributes current $(0 - V_n)x_j g_j^{\text{syn}}$ and increases g_n^{tot} . Its
 90 sensitivity is $\partial V_n / \partial g_j^{\text{syn}} = -x_j R_n^{\text{tot}} V_n$, which corresponds to multiplicative attenuation (divisive
 91 normalization). Shunting is divisive at the voltage level, but its effect on firing rates can be subtractive
 92 in some regimes [7]. Inhibitory plasticity can balance excitation dynamically [8]; our learned
 93 inhibitory conductances serve an analogous role.

94 2.3 Exact Gradients for Dendritic Trees

95 Let V_0 be the somatic output, $\hat{y} = W_{\text{dec}} V_0$ the decoder, and $\delta_0 = W_{\text{dec}}^\top (\partial L / \partial \hat{y})$ the somatic error.

96 **Theorem 1** (Conductance-Stage Backpropagation on a Dendritic Tree). *For a rooted dendritic tree*
 97 *with soma at node 0 and unique parent $p(n)$ for each non-somatic compartment, if each branch*
 98 *passes its pre-activation voltage directly to its parent, then the loss gradient satisfies*

$$\frac{\partial L}{\partial V_n} = \frac{\partial L}{\partial V_{p(n)}} R_{p(n)}^{\text{tot}} g_{n \rightarrow p(n)}^{\text{den}}, \quad (3)$$

99 *with boundary condition $\partial L / \partial V_0 = \delta_0$. Because the graph is a tree, each compartment has a unique*
 100 *path to the soma. Defining the path gain*

$$\alpha_n = \prod_{(i \rightarrow k) \in \text{path}(n \rightsquigarrow 0)} R_k^{\text{tot}} g_{i \rightarrow k}^{\text{den}}, \quad \frac{\partial L}{\partial V_n} = \alpha_n \delta_0, \quad (4)$$

101 *with $\alpha_0 = 1$.*

102 *Proof.* Apply the chain rule on the tree-structured computation graph using Prop. 1. □

103 **Corollary 1** (Local-Global Factorization). *The exact synaptic gradient at compartment n factorizes*
 104 *as:*

$$\frac{\partial L}{\partial g_i^{\text{syn}}} = \underbrace{x_i R_n^{\text{tot}} (E_i - V_n)}_{\text{synapse-local eligibility}} \cdot \underbrace{\frac{\partial L}{\partial V_n}}_{\text{compartment error}}, \quad (5)$$

105 *where the eligibility term depends only on quantities available at synapse i (presynaptic activity*
 106 *x_i , input resistance R_n^{tot} , driving force $E_i - V_n$), and the compartment error $\partial L / \partial V_n$ is the sole*
 107 *non-local quantity.*

108 Under identity upward transfer, this factorization isolates the only non-local quantity as $\partial L / \partial V_n =$
 109 $\alpha_n \delta_0$. With a post-voltage activation $a_n = f_n(V_n)$ transmitted to the parent, the exact recursion
 110 becomes $\partial L / \partial V_n = f'_n(V_n) (\partial L / \partial V_{p(n)}) R_{p(n)}^{\text{tot}} g_{n \rightarrow p(n)}^{\text{den}}$, so the compartment error remains the
 111 sole non-local term but the effective path gain acquires local activation-derivative factors. Any
 112 practical local rule therefore depends entirely on how well a broadcast signal approximates that exact
 113 compartment error, which we evaluate in Sec. 4.3. In the models studied here, shunting improves
 114 this approximation by reducing and stabilizing R_n^{tot} , which narrows the spread of local sensitivities
 115 across the tree. The theorem is stated for the pre-activation compartment voltage V_n produced by
 116 the conductance stage itself. In the empirical networks, each dendritic branch layer may optionally
 117 apply a post-voltage reactivation $f(V_n)$ before passing activity to the next stage; unless otherwise
 118 noted, the manuscript sweeps use a learnable bounded `param_tanh` reactivation. Our exact-error
 119 diagnostics are computed on the hooked pre-activation voltage, so the factorization check and
 120 compartment-error analyses target the conductance-stage quantity defined above rather than the
 121 post-activation activity.

122 3 Local Learning Rules

123 3.1 Broadcast Error Approximation

124 We approximate the exact compartment error $\partial L / \partial V_n$ (Corollary 1) with a broadcast signal e_n
 125 derived from the somatic/core error δ_0 . For a linear readout this reduces to $\delta_0 = W_{\text{dec}}^\top (\partial L / \partial \hat{y})$; for a

nonlinear decoder we use the corresponding decoder-input Jacobian product $J_{\text{dec}}(h_{\text{core}})^\top (\partial L / \partial \hat{y})$ so that the broadcast remains defined in the same core-space coordinates. We consider five broadcast modes of increasing structure:

- **Scalar:** $e_n = \bar{\delta} \cdot \mathbf{1}$, where $\bar{\delta} = \text{mean}(\delta_0)$ is a single scalar broadcast to all compartments.
- **Per-soma:** $e_n = \delta_0$ when the layer dimension matches the output; layers with mismatched dimensions fall back to scalar.
- **Low-rank:** $e_n = \Gamma_K(\delta_0)$, where Γ_K uses a small number K of random broadcast channels to project the somatic error into a layer-specific vector field.
- **Local mismatch:** $e_n = (1-\alpha) \bar{\delta} \cdot \tilde{m}_n + \alpha \bar{\delta}$, where $\tilde{m}_n$ is the RMS-normalized, batch-centered parent-child voltage difference $P_n - V_n$ and $\alpha = 0.2$.
- **Pathway-vector:** $e_n = \alpha \bar{\delta} \cdot \mathbf{1} + (1-\alpha) \Gamma_n(\delta_0)$, where Γ_n projects the somatic error into router-inferred pathway roles, gates those roles by local pathway activity, and transports the resulting vector hierarchically through the block-structured dendritic tree.

We use per-soma broadcast by default. In our experiments, the local-mismatch variant performs much worse (Appendix A), indicating that broadcast quality is critical. In the headline feedforward architectures, however, hidden widths exceed decoder output dimension, so this default per-soma mode falls back to a shared scalar/rank-1 field (Appendix Table S16). Under shunting, that deliberately low-bandwidth broadcast is often sufficient on standard classification tasks, while the cue-routing benchmark in Sec. 4.10 is used to compare rank-1, random low-rank, and pathway-structured feedback when different branches should receive different teaching signals. Appendix Table S13 summarizes the broader set of implemented model families, training strategies, and broadcast modes used throughout the study.

3.2 Three-Factor Rule (3F)

Definition 1 (3F Update). *For synaptic and dendritic conductances:*

$$\Delta g_j^{\text{syn}} = \eta \langle x_j R_n^{\text{tot}} (E_j - V_n) e_n \rangle_B, \quad \Delta g_j^{\text{den}} = \eta \langle R_n^{\text{tot}} (V_j - V_n) e_n \rangle_B, \quad (6)$$

where $\langle \cdot \rangle_B$ denotes the batch average.

The three factors are presynaptic activity x_j (or a voltage difference), postsynaptic modulation through driving force and input resistance, and the broadcast error e_n . The same rule applies to excitatory and inhibitory synapses. The sign difference comes from the driving force $(E_j - V_n)$.

Additive control. Rule (6) is the local gradient of the *shunting* voltage $V_n = \sum E_j g_j x_j / g_n^{\text{tot}}$. For the additive control ($V_n = \sum g_j x_j$, no divisive normalization), the correct local gradient is simpler: $\Delta g_j^{\text{syn}} = \eta \langle x_j e_n \rangle_B$, with no driving-force or R_n^{tot} terms ($R_n^{\text{tot}} \equiv 1$ by definition since there is no denominator). Throughout, each architecture uses the learning rule derived from its own forward-pass dynamics. This keeps the comparison architecture-matched rather than applying a shunting-derived rule to an additive model.

3.3 Practical Heuristic Wrappers: 4F and 5F

4F (heuristic attenuation proxy). In the conductance-stage recursion (4), the path gain α_n attenuates the somatic error differently at each compartment. To compensate without explicitly computing that gain, 4F uses an online correlation proxy

$$\rho_n = \text{Cov}(\bar{V}_n, \bar{V}_0) / (\sqrt{\text{Var}(\bar{V}_n) \text{Var}(\bar{V}_0)} + \varepsilon).$$

High ρ_n up-weights branches whose voltages covary with the soma; low ρ_n down-weights branches where the broadcast is likely to be a poor proxy.

5F (confidence-weighted 4F). 5F adds a second heuristic factor

$$\phi_n = \text{Var}(V_n) / (\sigma_{\text{res}}^2 + \varepsilon),$$

where σ_{res}^2 is the residual variance of V_n after linear regression on the parent voltage. Operationally, ϕ_n is a branch-wise confidence gate: it becomes large when local voltages are strong and stable

relative to unexplained residual fluctuations, and small when local fluctuations dominate. We clamp it to $[0.25, 4.0]$ for stability. This factor is empirical, not theorem-derived. The paper’s core claim rests on path-gain concentration and the oracle experiment; the gain from ϕ_n should be read as practical denoising rather than theoretical necessity.

Proposition 2 (5F Update).

$$\Delta g_j^{\text{syn}} = \eta \rho_n \phi_n \langle x_j R_n^{\text{tot}} (E_j - V_n) e_n \rangle_B. \quad (7)$$

A feedback-alignment-style random-broadcast argument is included in Appendix C; it is supportive but not central to the main mechanism claim.

3.4 Structured pathway feedback and branch-role plasticity

For tasks with latent pathway structure, scalar broadcast can erase the distinction between different dendritic branches that should be credited differently. Recent experimental evidence supports the existence of vectorized instructive signals in cortical dendrites [43], motivating the structured feedback variant we introduce here. We therefore augment the local rule with a structured cue-routing variant, *PV-LocalCA*.

Hierarchical pathway-vector broadcast. The encoder/router defines a low-dimensional role basis over latent pathways. Instead of collapsing δ_0 to a scalar or per-soma vector, we project it into this role basis and gate each role by local pathway activity:

$$e_n^{\text{PV}} = \sum_{k=1}^K q_{n,k} c_k,$$

where $c_k = \langle r_k, \delta_0 \rangle$ are role coefficients and $q_{n,k}$ are local branch-role weights. Scalar broadcast is the special case $K=1$, while *PV-LocalCA* is a structured rank- K extension rather than a separate learning principle.

Router-derived branch roles. Rather than assigning hand-coded apical/basal labels, each branch j receives a normalized role profile r_j inferred from router assignments and incoming block weights. Plasticity is then gated by branch selectivity and by a synapse-specific role-alignment factor $\langle r_i, r_j \rangle$, biasing learning toward pathway-consistent afferents without imposing a fixed branch taxonomy.

4 Experiments

4.1 Claim tiers

To keep results and claims aligned, we group experiments into three tiers. *Headline corrected claims* are 5-seed results with positive-input enforcement, nonnegative conductances, decoder-aware soma mapping, and the safeguarded occupancy-quantile reactivation init; these carry the central mechanistic claim. *Supportive results* are stable 5-seed (or clearly labeled 3-seed) sweeps that corroborate the headline claim without being needed to carry it: the cue-routing extension, the morphology $\times$ inhibition map, the soma-on extension across all four phase families, the (b, m) update-policy comparison, the component ablation on MNIST, and the weight-distribution analyses. *Exploratory results* are 1–3-seed screens or legacy benchmarks that violate our nonnegative-drive assumption (for example legacy signed-input tasks); these are explicitly labeled and are not used to carry any main-text claim. The cue-routing soma-on result is reported on the stable successful subset only; see Sec. 4.10 and Appendix Fig. S10.

4.2 Setup

We evaluate two settings: a *capacity-calibrated* regime, where matched architectures achieve strong backprop performance, and *controlled sweeps* that isolate inhibition strength, broadcast mode, and architecture. Our main datasets are MNIST, Fashion-MNIST [37], and three synthetic tasks: *context gating*, *noise resilience*, and *cue integration*; formal definitions are in Appendix I. An older *info shunting* benchmark remains in the codebase as a signed-input exploratory stress test, but it is no

longer part of the headline corrected result set because it violates the nonnegative-drive assumption of the conductance model. Architectures include point MLP baselines and dendritic cores with either additive integration or shunting. Main comparisons are architecture-matched additive vs. shunting cores and local vs. backprop training; DFA appears only as a supplementary baseline. Most headline MNIST, Fashion-MNIST, and context-gating results use 5F with per-soma broadcast. Because the hidden widths in these feedforward settings exceed the decoder output dimension, that default per-soma implementation reduces to a shared scalar/rank-1 broadcast in the main mechanism and competence sweeps; the higher-rank controls then use explicit low-rank, path-propagation, path-transport, or pathway-vector variants. Unless otherwise stated, dendritic layers also use the learnable post-voltage reactivation `param_tanh`; Appendix Tables S9 and S10 then audit activation shape in a more controlled setting by comparing identity (none) against a frozen `param_tanh` under matched additive/shunting initialization. All headline dendritic runs keep synaptic and dendritic conductances nonnegative via positive parameter transforms and enforce a nonnegative first-layer synaptic drive. Concretely, image-based inputs are used in $[0, 1]$, the corrected noise-resilience benchmark clips projected Gaussian corruption back to $[0, 1]$, context gating uses a nonnegative contextual figure-ground MNIST construction, and cue integration uses one-hot context plus cue values clipped to $[0, 1]$. The cue-routing benchmark is used to compare rank-1, random low-rank, and pathway-structured feedback in a routed setting, and the inhibition sweeps additionally use a transported-error oracle derived from Theorem 1 as an upper bound rather than as the proposed biological rule. Headline mechanistic, oracle, competence, activation-audit, corrected routed, and CIFAR mechanism-extension results use 5 seeds per condition; a smaller set of appendix-only support sweeps still use 3 seeds, while 1–2 seed screens are treated as exploratory and are either omitted from the main claims or explicitly labeled as such in the appendix.

4.3 From Exact Factorization to Credit-Signal Fidelity

To test whether these performance differences correspond to better credit signals, we compare local and backprop gradients on the same batch at the same parameter values. For each parameter tensor p , we compute directional alignment (cosine similarity) and scale mismatch, defined as $|\log_{10}(\|g_p^{\text{local}}\|/\|g_p^{\text{bp}}\|)|$, aggregated by parameter count.

Across matched-weight comparisons, shunting is consistently more aligned with backprop and substantially closer in norm than the additive control: on MNIST, weighted cosine rises from 0.006 to 0.202 and scale mismatch falls from 1.053 to 0.117; on context gating, cosine rises from -0.007 to 0.108 and scale mismatch falls from 2.154 to 0.036. Figure 2C shows that this advantage appears throughout training, especially in proximal layers and dendritic conductances. Figure 2D confirms that the theory is operational in code under the corrected positive-input setup: reconstructing gradients from Corollary 1 using exact compartment errors yields weighted relative reconstruction error below 2×10^{-7} and weighted scale mismatch below 4×10^{-8} across runs. In a few low-norm parameter blocks, cosine becomes numerically unstable even though the reconstruction itself is essentially exact, so we report the norm-based diagnostics in the figure. The only approximation made by LocalCA is therefore the broadcast substitute for $\partial L/\partial V_n$.

4.4 Mechanistic Chain: Path Gains, Broadcast Fidelity, and Oracle Transport

Figure 3 provides the paper’s central empirical chain: shunting concentrates conductance-stage path gains, which improves direct compartment-error fidelity, which in turn makes low-bandwidth local learning effective; the transported-error oracle then isolates how much of the remaining gap is due to broadcast quality rather than other architectural differences.

Panel A measures the coefficient of variation of the exact conductance-stage path gains α_n across compartments. On MNIST, shunting keeps this distribution tightly concentrated across inhibition levels (CV about 0.21–0.43), whereas the additive control remains much broader (CV about 0.90–1.16). Panel B then measures the sole non-local term from Corollary 1, $\partial L/\partial V_n$, directly. On the corrected noise-resilience sweep, per-soma broadcast tracks the exact compartment error somewhat better under shunting than under additive integration once inhibition is present: additive remains positively aligned throughout (about 0.14–0.19 across the sweep), while shunting rises to about 0.20–0.24 in the inhibited regimes after starting from a comparable low-inhibition baseline. The transported-error oracle obtained by recursively applying those conductance-stage path gains improves fidelity sharply in both architectures, reaching about 0.95–0.99 for additive and essentially 1.0 for




Figure 2: Gradient-fidelity diagnostic. (A) Weighted cosine similarity between local and backprop gradients: shunting (green) is consistently more aligned than additive (blue) on both MNIST and context gating. (B) Gradient scale mismatch on the same matched-weight comparisons. Shunting is not only better aligned, but also substantially closer in norm. (C) Per-layer cosine similarity over training epochs. Shunting proximal layers approach high positive alignment; additive layers remain near zero. (D) Exact-factorization sanity check across all corrected theory-diagnostic conditions, reported with relative L_2 reconstruction error and scale mismatch. Reconstructed gradients match autograd to numerical precision, showing that LocalCA’s only approximation is in the broadcast substitute for the compartment error.

264 shunting once inhibition is present, showing that the theorem defines an operational upper bound on
 265 low-bandwidth broadcast.

266 Panel C trains the same local rule using that oracle signal. On noise resilience, additive learning rises
 267 from 66.8% at $N_I=0$ to about 81–84% across the inhibited regimes under per-soma broadcast, and
 268 transported broadcast lifts those same conditions to about 92–94%. Shunting rises from 54.3% at
 269 $N_I=0$ to about 81–86% under per-soma and to about 94.3–95.2% under transported broadcast. On
 270 MNIST, transported broadcast reaches about 95.4–96.6% for additive and 96.5–97.3% for shunting.
 271 The CIFAR-10 inset shows the same harder-data pattern in the corrected compact E/I family: shunting
 272 rises from 28.8% under per-soma broadcast to 47.4% under transported error, nearly matching its
 273 49.5% backprop ceiling. These oracle results strongly support path-gain fidelity as the dominant
 274 bottleneck for LocalCA performance, while the smaller remaining additive–shunting gap under
 275 matched transported broadcast suggests an additional contribution from conductance-shaped local
 276 sensitivities.

277 Panel D collapses the three-link chain across all conditions into a single scatter of per-soma cosine
 278 alignment against test accuracy. Shunting cells (squares) cluster at high alignment and high accuracy;
 279 additive cells (circles) cluster at the opposite end, and the same monotonic relationship holds on both
 280 MNIST and noise resilience. This is a compact confirmation that the (path-gain concentration $\rightarrow$
 281 compartment-error fidelity $\rightarrow$ test accuracy) chain is not a dataset-specific artifact. A complementary
 282 broadcast-bandwidth control in Appendix Fig. S6 shows that even once local sensitivities are well
 283 scaled, coarse broadcasts still work: 4-bit quantization preserves full performance (61.6% vs. 61.7%;
 284 $p > 0.9$), while sign-only (37.5%) and sparse top-30% (38.2%) degrade sharply. The corrected
 285 rank-bridge sweep in Appendix Table S8 adds one constructive intermediate control. On the same
 286 shunting noise-resilience regime, per-soma reaches 0.662 ± 0.016 , the current path-propagation proxy




Figure 3: Mechanistic chain from path gains to learning. (A) Conductance-stage path-gain dispersion on MNIST, measured as the coefficient of variation of the exact tree attenuation α_n across compartments. Shunting keeps these conductance-stage path gains much more concentrated than the additive control as inhibition increases. (B) Direct compartment-error fidelity on noise resilience. Solid lines compare the per-soma broadcast e_n to the exact compartment error $\partial L / \partial V_n$; dashed lines show the transported-error oracle obtained by recursively applying conductance-stage path gains. Under the corrected positive-input setup, shunting still improves the simple per-soma broadcast in the inhibited regimes, while the transported oracle defines the remaining approximation gap and becomes nearly exact once inhibition is present. (C) Learning with the transported-error oracle on noise resilience. Improving the broadcast field is enough to recover near-ceiling local learning, especially in the additive architecture where per-soma broadcast fails most severely; the CIFAR-10 inset shows the same harder-data ladder for shunting in the corrected compact E/I family. (D) Global mechanism summary. Per-soma cosine alignment (x-axis) vs. test accuracy (y-axis) across all conditions (additive/shunting $\times$ five inhibition levels $\times$ two datasets, 5 seeds each). Shunting cells (squares) cluster at high alignment and high accuracy; additive cells (circles) cluster at low alignment and low accuracy. The same monotonic chain from (A) through (C) collapses cleanly into the (alignment $\rightarrow$ accuracy) relationship shown here, and it holds on both MNIST and noise resilience, confirming that the mechanistic chain is not a dataset-specific artifact. The broadcast-bandwidth / quantization control previously shown as panel D is now reported separately as Appendix Fig. S6.

287 rises to 0.762 ± 0.047 , random low-rank broadcast reaches 0.764 ± 0.025 at $K=4$, and exact path
 288 transport reaches 0.847 ± 0.018 . So both morphology-aware propagation and higher-rank unstructured
 289 feedback now close a substantial fraction of the transported-oracle gap, although exact transported
 290 error remains clearly better. Normalization-only additive controls and DFA baselines (Appendix
 291 Figs. S8, S7) improve over weaker baselines without matching the shunting conductance model.
 292 Appendix Table S9 shows that this mechanism should still be interpreted in a specific activation
 293 operating regime rather than as an activation-agnostic claim.

294 4.5 Capacity-Calibrated Competence

295 Having established the mechanism, we next ask whether the same conditions improve end-task
 296 learning in architectures that are already competent under backpropagation. In the capacity-calibrated
 297 regime, shunting dendritic cores remain reasonably competitive under local learning: on MNIST,




Figure 4: Capacity-calibrated competence and regime dependence. (A) Backprop ceiling (gray) vs. best local rule (5F per-soma) for shunting (green) and additive (blue) cores on MNIST, Fashion-MNIST, and context gating, using the refreshed 5-seed ceilings. (B) N_I dose-response: test accuracy vs. inhibitory synapses per branch (N_I) for shunting and additive cores on MNIST (solid) and noise resilience (dashed), updated from the corrected nonnegative-input sweep. (C) Shunting advantage (Δ , in percentage points) vs. N_I . (D) Fashion-MNIST standard-vs-local comparison from the corrected five-seed sweep, showing a smaller but still consistent shunting advantage on the cleaner vision benchmark.

Fashion-MNIST, and context gating, the best local configuration (5F, per-soma broadcast, local decoder) stays within about 5–6 percentage points of the matched backprop ceiling (Table S4; Fig. 4). Within the local-rule family, 5F is the strongest practical wrapper, but it remains heuristic rather than theorem-derived; Appendix Tables S1, S3, and S2 summarize that division of labor across rules and broadcast choices. Classical random-feedback baselines remain much weaker on the same task family: in the matched MNIST appendix comparison, DFA reaches 66.1% on shunting and 62.2% on additive, well below the 91.4% best shunting LocalCA result, while FA is not directly compatible with the block-structured dendritic layers (Appendix Fig. S7). This helps separate the contribution of the conductance architecture from the contribution of the LocalCA rule itself.

4.6 Regime Dependence of the Shunting Advantage

The benefit of shunting varies across tasks. On MNIST with matched per-soma broadcast, shunting outperforms additive by about 1–2 percentage points. On the corrected nonnegative-input noise-resilience benchmark, the gap is small at $N_I=0$ but grows to a consistent ~ 2 –3 pp once inhibition is introduced. Figure 4 shows the full dose-response: the shunting advantage grows with inhibitory conductance strength on that inhibition-sensitive task, whereas additive cores remain somewhat more fragile in the same regime.

4.7 Morphology Shifts the Inhibitory Operating Regime

The inhibitory regime in which shunting helps most is not fixed across dendritic trees. Figure 5 shows the corrected morphology $\times$ inhibition sweep on noise resilience. The main pattern is not monotonic “more inhibition is better,” but rather a morphology-dependent ridge: depth-2 trees show their largest




Figure 5: Morphology shifts the inhibitory regime where shunting helps most. (A) Additive LocalCA remains comparatively flat across morphologies and inhibitory synapse counts, with only isolated high-variance pockets. (B) Shunting LocalCA shows a clear morphology-dependent regime: the strongest performance appears at low or moderate inhibition, and the best N_I shifts with tree shape. (C) The shunting-minus-additive gap is largest for wider two-level trees at low inhibition and for deeper trees at modest inhibition, then weakens or vanishes at high inhibition. (D) Averaging by depth highlights the same crossover: depth-2 trees peak near $N_I=0$, whereas depth-3 trees retain their largest shunting advantage around $N_I=5$.

shunting gains near $N_I=0$, whereas deeper depth-3 trees retain their strongest gains around $N_I=5$. This is consistent with the broader mechanistic picture that shunting helps by shaping the spread of effective compartment sensitivities, and suggests that tree geometry changes where that operating point lies.

4.8 Additional Stress Tests

Across three additional stress tests, namely increased dendritic depth, noisy broadcast signals, and Fashion-MNIST, the same qualitative pattern persists: shunting degrades more gracefully than additive, while the largest gains still appear on tasks that stress the credit signal most strongly. We keep the full curves in Appendix Fig. S5 because they support, rather than define, the core mechanistic claim.

4.9 Harder-Data Check: Corrected CIFAR-10 Mechanism Extension

To make sure the mechanism is not an artifact of near-saturated MNIST-style regimes, we repeated the core ladder on flattened CIFAR-10 in the stronger compact explicit-E/I family where shunting is already competitive under backpropagation. Figure 6 shows the corrected 5-seed result after fixing LocalCA’s soma-error mapping for nonlinear decoders. In this family, shunting is stronger than additive under standard training ($49.5 \pm 0.7\%$ vs. $46.6 \pm 1.5\%$), and transported-error LocalCA again behaves as the clean upper bound: additive rises from $32.6 \pm 0.6\%$ under rank-1 per-soma broadcast to $42.3 \pm 1.2\%$ under transported error, while shunting rises from $28.8 \pm 0.8\%$ under per-soma to $34.7 \pm 1.1\%$ with random low-rank $K=4$ and $47.4 \pm 0.6\%$ with transported error. So the harder-data result is not that shunting always wins under naive local broadcast, but that the same broadcast-fidelity ladder still governs performance once the architecture and decoder mapping are handled fairly.

4.10 Extension: Structured Feedback When Per-Soma Broadcast Fails

The main paper focuses on low-bandwidth scalar or per-soma broadcast. We therefore include a harder cue-integration benchmark as a supportive routed extension: here different dendritic pathways should receive different teaching signals, so rank-1 feedback is insufficient by construction. Figure 7 shows that the benchmark itself is learnable, but learned-routing shunting LocalCA remains the hard case. Under the corrected activation-aware rule, default rank-1 per-soma broadcast stays unstable at roughly 0.81 ± 0.13 test accuracy; moving beyond rank-1 helps, with random low-rank feedback rising from 0.742 ± 0.022 at $K=1$ to 0.846 ± 0.082 at $K=2$, while the current tuned pathway-vector variant reaches 0.815 ± 0.126 . The robust conclusion is therefore the failure mode: once rank-1 feedback collapses pathway identity, richer feedback helps, but the best structured repair remains open. Enabling direct somatic inputs (`somatic_synapses=true`) rescues the stable successful subset of cue-routing configurations: fixed-router shunting LocalCA with soma reaches 1.00 ± 0.0 test accuracy (5 seeds), and learned-router additive LocalCA with soma reaches 0.99 ± 0.003 , matching




Figure 6: **Corrected CIFAR-10 mechanism extension in the stronger compact E/I family.** (A) Matched additive vs. shunting ladder with a nonlinear decoder and decoder-aware soma-error mapping. In this stronger family, shunting is competitive under standard training ($49.5 \pm 0.7\%$) and transported-error LocalCA nearly recovers that ceiling ($47.4 \pm 0.6\%$), while naive rank-1 per-soma remains much weaker. (B) Shunting rank bridge on the same family. Random low-rank feedback improves over per-soma, but exact transported error remains the strongest signal.

the matched additive backprop ceiling (Appendix Fig. S10). Learned-router shunting+soma still fails initialization on this signed-input benchmark because the learned-router pipeline conflicts with the shunting positive-input check, so we report the soma-on result only on the stable subset and keep the dendrite-only soma-off comparison in the main text.

5 Related Work

High-performance local learning. Recent methods such as AugLocal, CCL, and DLL have substantially raised the benchmark-performance bar for local learning on standard architectures [33, 34, 36]. Our aim is therefore not to claim the strongest benchmark accuracy among local-learning methods, but to identify the biophysical mechanism that determines when low-bandwidth credit signals become useful in conductance-based dendritic networks.

Local credit-assignment dynamics. Random feedback, DFA, DTP, DFC, equilibrium-style methods, and predictive-coding approaches solve locality through different feedback or inference dynamics [9, 10, 13, 15, 16, 25–29, 32]. EBD [35] is especially close in spirit because it studies when direct error broadcast can be made useful by shaping the broadcast field itself. Our contribution is complementary: rather than changing the broadcast objective or inference dynamics, we identify a conductance-based inductive bias, conductance-stage path-gain concentration under shunting, that makes even a simple low-bandwidth broadcast more faithful to the exact compartment error.

Dendrites for robustness and context. Dendritic trees support nonlinear computation [3, 4, 30] and have inspired learning schemes based on segregated dendrites, dendritic prediction errors, burst-dependent plasticity, and latent equilibrium [5, 11, 12, 22–24]. Outside supervised iid classification, active-dendrite architectures can also improve robustness in dynamic multi-task settings where point-MLP baselines suffer interference [44]. Our cue-routing extension asks a related question, namely when dendritic structure helps preserve pathway-specific computation, but uses conductance-based normalization and structured credit signals rather than sparse kWTA gating.

Neuroscience grounding. Shunting implements divisive normalization [6], though its rate effects can be subtractive in some regimes [7]; inhibitory conductance also modulates gain and signal-to-noise [31]. Recent evidence for vectorized instructive signals in cortical dendrites [43] further supports the structured-feedback extension studied here. To our knowledge, prior work has not tied exact conductance-stage path gains, direct gradient-fidelity diagnostics, and shunting inhibition into one causal account of when local dendritic learning works.




Figure 7: **Structured feedback when rank-1 broadcast fails.** (A) Cue-routing task schematic. Context determines which noisy cue is reliable on each trial, so different dendritic pathways should receive different teaching signals. (B) Five-seed comparison of rank-1, random low-rank, and pathway-structured feedback. The stable conclusion is that moving beyond rank-1 helps, while the best structured repair remains open. (C) Test accuracy vs. router specialization across learned-router conditions. High specialization alone does not guarantee success. (D) Recovered pathway assignments for a representative learned-router run. Cue-A and cue-B features segregate cleanly into separate latent pathways even when feedback quality, rather than router discreteness, is the limiting factor.

6 Discussion

We started from exact gradients for a conductance-based dendritic tree and asked when a somatic broadcast can serve as a useful proxy for compartment-specific errors. In the models studied here, the answer depends strongly on the inhibitory regime: shunting changes the conductance denominator, stabilizes effective local sensitivities, improves agreement between local and backprop gradients, and yields better local learning than an additive control, especially in noisy or inhibition-dependent settings. The morphology $\times$ inhibition map in Fig. 5 suggests that tree shape shifts this operating regime, and explicit normalization recovers only part of the benefit. This is therefore a mechanism paper, not a benchmark paper. The activation audit in the appendix shows that the mechanism lives in the bounded `param_tanh` regime used throughout the main experiments, and the paired empirical/theory activation tables show why: freezing that activation often broadens path-gain dispersion and weakens per-soma fidelity in the corrected positive-input setting. The oracle/rank-bridge controls then sharpen the remaining open problem: finding a strictly local morphology-aware approximation that closes more of the transported-error gap. All headline experiments reported here now also respect the basic conductance assumptions directly: synaptic and dendritic weights remain nonnegative throughout training, and the first synaptic drive is kept nonnegative by the transfer stage and by dataset preprocessing. The corrected flattened-CIFAR-10 extension in Fig. 6 supports the same diagnosis in a stronger compact E/I family: once the local rule maps decoder error back to decoder-input/soma space, transported error again acts as a meaningful upper bound and shunting remains competitive on harder data.

Limitations. Our best accuracy (91.4% MNIST, 83.8% Fashion-MNIST) remains below several recent local-learning methods that operate in abstract compartments or standard activation spaces [33–36]. This reflects the constraints of conductance-based voltage space: bounded voltages, nonnegative conductances, nonnegative presynaptic drive, and a denominator-heavy computation graph. The corrected flattened-CIFAR-10 extension in Fig. 6 and Table S6 is a harder stress test rather than a claim of benchmark leadership. There shunting is competitive or better than additive under standard training and under transported-error LocalCA, but naive rank-1 per-soma broadcast still leaves a substantial gap, indicating that harder visual tasks demand better broadcast quality and likely richer front ends than flattened inputs alone. More broadly, naive local broadcasts remain much weaker than per-soma on MNIST, structured routed settings remain open, per-soma broadcast is still neuron-global, depth remains challenging, shunting is not gain-invariant in practice, and the FA and weight-statistics appendices are supportive rather than central evidence. We also do not claim the same empirical story under externally signed inputs; those legacy stress tests remain outside the corrected headline result set.

Broader relevance. The results are relevant to neuroscience, machine learning, and neuromorphic hardware. For neuroscience, they suggest a connection between divisive normalization and local credit fidelity. For machine learning, they show that conductance-based inductive biases can shape gradient geometry in ways that benefit local learning. For neuromorphic implementations, the update rules remain strictly local and parallelizable.

Testable predictions. Our framework predicts that (1) stronger perisomatic inhibition yields more precise synaptic plasticity; (2) GABA_A blockade selectively impairs multi-layer credit tasks; (3) the dendritic–somatic voltage correlation (ρ_n) increases during learning; and (4) learned excitatory weight distributions follow log-normal statistics whose width depends systematically on inhibitory conductance (Appendix G).

References

- [1] Koch, C. (1999). *Biophysics of Computation*. Oxford University Press.
- [2] Dayan, P., & Abbott, L. F. (2001). *Theoretical Neuroscience*. MIT Press.
- [3] Poirazi, P., Brannon, T., & Mel, B. W. (2003). Pyramidal neuron as two-layer neural network. *Neuron*, 37(6), 989–999.
- [4] London, M., & Häusser, M. (2005). Dendritic computation. *Annual Review of Neuroscience*, 28, 503–532.
- [5] Urbanczik, R., & Senn, W. (2014). Learning by the dendritic prediction of somatic spiking. *Neuron*, 81(3), 521–528.
- [6] Carandini, M., & Heeger, D. J. (2012). Normalization as a canonical neural computation. *Nature Reviews Neuroscience*, 13(1), 51–62.
- [7] Holt, G. R., & Koch, C. (1997). Shunting inhibition does not have a divisive effect on firing rates. *Neural Computation*, 9(5), 1001–1013.
- [8] Vogels, T. P., Sprekeler, H., Zenke, F., Clopath, C., & Gerstner, W. (2011). Inhibitory plasticity balances excitation and inhibition in sensory pathways and memory networks. *Science*, 334(6062), 1569–1573.
- [9] Lillicrap, T. P., Cownden, D., Tweed, D. B., & Akerman, C. J. (2016). Random synaptic feedback weights support error backpropagation for deep learning. *Nature Communications*, 7, 13276.
- [10] Nøkland, A. (2016). Direct feedback alignment provides learning in deep neural networks. *NeurIPS*, 29.
- [11] Guerguiev, J., Lillicrap, T. P., & Richards, B. A. (2017). Towards deep learning with segregated dendrites. *eLife*, 6, e22901.

- [12] Sacramento, J., Costa, R. P., Bengio, Y., & Senn, W. (2018). Dendritic cortical microcircuits approximate the backpropagation algorithm. *NeurIPS*, 31.
- [13] Whittington, J. C., & Bogacz, R. (2019). Theories of error back-propagation in the brain. *Trends in Cognitive Sciences*, 23(3), 235–250.
- [14] Richards, B. A., & Lillicrap, T. P. (2019). Dendritic solutions to the credit assignment problem. *Current Opinion in Neurobiology*, 54, 28–36.
- [15] Scellier, B., & Bengio, Y. (2017). Equilibrium propagation. *Frontiers in Computational Neuroscience*, 11, 24.
- [16] Song, Y., Millidge, B., Salvatori, T., Lukasiewicz, T., Xu, Z., & Bogacz, R. (2024). Inferring neural activity before plasticity as a foundation for learning beyond backpropagation. *Nature Neuroscience*, 27, 348–358.
- [17] Gretton, A., Bousquet, O., Smola, A. J., & Schölkopf, B. (2005). Measuring statistical dependence with Hilbert-Schmidt norms. *Algorithmic Learning Theory*, 63–77.
- [18] Frémaux, N., & Gerstner, W. (2016). Neuromodulated spike-timing-dependent plasticity, and theory of three-factor learning rules. *Frontiers in Neural Circuits*, 9, 85.
- [19] Bellec, G., et al. (2020). A solution to the learning dilemma for recurrent networks of spiking neurons. *Nature Communications*, 11, 3625.
- [20] Welford, B. P. (1962). Note on a method for calculating corrected sums of squares and products. *Technometrics*, 4(3), 419–420.
- [21] Turrigiano, G. G. (2008). The self-tuning neuron: synaptic scaling of excitatory synapses. *Cell*, 135(3), 422–435.
- [22] Payeur, A., Guerguiev, J., Zenke, F., Richards, B. A., & Naud, R. (2021). Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *Nature Neuroscience*, 24(7), 1010–1019.
- [23] Greedy, W., Zhu, H. W., Pemberton, J., Mellor, J., & Ponte Costa, R. (2022). Single-phase deep learning in cortico-cortical networks. *NeurIPS*, 35, 24213–24225.
- [24] Haider, P., Ellenberger, B., Kriener, L., Jordan, J., Senn, W., & Petrovici, M. A. (2021). Latent Equilibrium: A unified learning theory for arbitrarily fast computation with arbitrarily slow neurons. *NeurIPS*, 34.
- [25] Hinton, G. (2022). The forward-forward algorithm. *arXiv:2212.13345*.
- [26] Dellaferrera, G., & Kreiman, G. (2022). Error-driven input modulation: Solving the credit assignment problem without a backward pass. *Proceedings of the 39th International Conference on Machine Learning, Proceedings of Machine Learning Research*, 162, 4937–4955.
- [27] Lee, D.-H., et al. (2015). Difference target propagation. *ECML*, 498–515.
- [28] Meulemans, A., et al. (2021). Credit assignment in neural networks through deep feedback control. *NeurIPS*, 34.
- [29] Millidge, B., Seth, A. K., & Buckley, C. L. (2021). Predictive coding: A theoretical and experimental review. *arXiv:2107.12979*.
- [30] Koch, C., Poggio, T., & Torre, V. (1983). Nonlinear interactions in a dendritic tree. *PNAS*, 80(9), 2799–2802.
- [31] Silver, R. A. (2010). Neuronal arithmetic. *Nature Reviews Neuroscience*, 11(7), 474–489.
- [32] Max, K., Kriener, L., Pineda García, G. et al. (2024). Learning efficient backprojections across cortical hierarchies in real time. *Nature Machine Intelligence*, 6(6), 619–630.
- [33] Ma, C., Wu, J., Si, C., & Tan, K. C. (2024). Scaling supervised local learning with augmented auxiliary networks. *International Conference on Learning Representations (ICLR)*.

Dataset	Rule	Top-10 valid	Top-10 test
MNIST	3F	0.611	0.622
MNIST	4F	0.620	0.628
MNIST	5F	0.912	0.916
Context gating	3F	0.398	0.396
Context gating	4F	0.411	0.411
Context gating	5F	0.807	0.789

Table S1: **Rule-family ranking.** Top-10 mean across completed local-competence sweeps.

- [34] Lv, C., Xu, J., Lu, Y., Wang, X., Wang, Z., Xu, Z., Yu, D., Du, X., Zheng, X., & Huang, X. (2025). Dendritic Localized Learning: Toward Biologically Plausible Algorithm. *Proceedings of the 42nd International Conference on Machine Learning, Proceedings of Machine Learning Research*, 267, 41682–41700.
- [35] Erdogan, M., Pehlevan, C., & Erdogan, A. T. (2025). Error broadcast and decorrelation as a potential artificial and natural learning mechanism. *OpenReview*, NeurIPS 2025 spotlight.
- [36] Kao, C.-H., & Hariharan, B. (2024). Counter-Current Learning: A Biologically Plausible Dual Network Approach for Deep Learning. *Advances in Neural Information Processing Systems*, 37.
- [37] Xiao, H., Rasul, K., & Vollgraf, R. (2017). Fashion-MNIST: A novel image dataset for benchmarking machine learning algorithms. *arXiv:1708.07747*.
- [38] Song, S., Sjöström, P. J., Reigl, M., Nelson, S., & Chklovskii, D. B. (2005). Highly nonrandom features of synaptic connectivity in local cortical circuits. *PLoS Biology*, 3(3), e68.
- [39] Buzsáki, G., & Mizuseki, K. (2014). The log-dynamic brain: How skewed distributions affect network operations. *Nature Reviews Neuroscience*, 15(4), 264–278.
- [40] The MICrONS Consortium (2025). Functional connectomics spanning multiple areas of mouse visual cortex. *Nature*, 640(8058), 435–447.
- [41] Loewenstein, Y., Kuras, A., & Rumpel, S. (2011). Multiplicative Dynamics Underlie the Emergence of the Log-Normal Distribution of Spine Sizes in the Neocortex In Vivo. *Journal of Neuroscience*, 31(26), 9481–9488.
- [42] Megías, M., et al. (2001). Total number and distribution of inhibitory and excitatory synapses on hippocampal CA1 pyramidal cells. *Neuroscience*, 102(3), 527–540.
- [43] Francioni, V., Tang, V. D., Toloza, E. H. S. et al. (2026). Vectorized instructive signals in cortical dendrites. *Nature*. <https://doi.org/10.1038/s41586-026-10190-7>
- [44] Iyer, A., Grewal, K., Velu, A., Souza, L. O., Forest, J., & Ahmad, S. (2022). Avoiding catastrophe: Active dendrites enable multi-task learning in dynamic environments. *Frontiers in Neurorobotics*, 16, 846219.

A Supplementary Results

Mechanistic Support and Broadcast Controls

Rule-Family Ranking

Which Components Carry?

Component	Representative effect	Interpretation
Shunting architecture	In the corrected noise-resilience sweep, additive performs better at $N_I=0$ (0.668 vs. 0.543), but shunting overtakes it once inhibition is present (0.837 vs. 0.818 at $N_I=10$, 0.861 vs. 0.830 at $N_I=40$).	The shunting gain is operating-regime dependent rather than uniform: it appears once inhibition shapes conductance scaling strongly enough to help the shared broadcast.
Broadcast quality	On MNIST (5F), shunting per-soma reaches 0.912 ± 0.005 , while local-mismatch remains at 0.146 ± 0.046 .	Correctly matching the broadcast field to the somatic error matters far more than arbitrary local mismatch heuristics.
Transported oracle	Across inhibited noise-resilience regimes, additive local learning rises from roughly 81–84% under per-soma to 92–94% under transported broadcast; shunting rises from roughly 81–86% to 95–95.2%.	The oracle remains the strongest causal evidence that broadcast fidelity, not just architecture, is the dominant bottleneck.
Rule hierarchy	In the competence sweeps, MNIST improves from 0.622 (3F) and 0.628 (4F) to 0.916 (5F); context gating improves from 0.396/0.411 to 0.789.	5F is the strongest practical rule in this paper, though its extra factor remains heuristic rather than theorem-derived.
5F stability	Tightening the ϕ clamp to $[0.5, 2.0]$ changes MNIST by only about +0.4 pp; varying EMA from 0.05 to 0.20 changes it by less than 0.2 pp.	The practical gain from 5F is not especially brittle to its main tuning knobs.
Structured feedback	In the corrected cue-routing reruns, learned-routing additive local learning remains near ceiling while learned-routing shunting rises from 0.742 at random rank-1 to 0.846 at random rank-2; the current tuned pathway-vector variant reaches 0.815.	Routed tasks remain the main failure mode of rank-1 feedback, but under the corrected rule the main robust conclusion is that higher rank helps; the best structured fix is not yet settled enough to anchor a headline claim.
Random low-rank channels	On the corrected shunting noise-resilience bridge, random low-rank broadcast improves from 0.453 at $K=1$ to 0.764 at $K=4$ and 0.795 at $K=8$, while exact path transport reaches 0.847; on cue routing, the best corrected unstructured low-rank setting is $K=2$ at 0.846.	Higher-rank unstructured broadcast now closes a large fraction of the rank-1 gap, but it still does not recover the transported-oracle ceiling and does not by itself establish a structure-specific advantage.
Path propagation proxy	In the corrected shunting noise-resilience bridge, the current morphology-aware path-propagation proxy reaches 0.762 ± 0.047 , well above per-soma (0.662 ± 0.016) and close to random low-rank $K=4$ (0.764 ± 0.025), though still below exact path transport (0.847 ± 0.018).	The present recursive attenuation proxy is now a meaningful constructive baseline: it closes much of the oracle gap, though a stronger strictly local approximation to transported error remains open.
Morphology regime	In the exploratory noise-resilience regime map (Fig. 5), depth-2 trees show their largest shunting gains near $N_I = 0$, whereas depth-3 trees retain their strongest gains around $N_I = 5$.	Morphology appears to shift the inhibitory operating regime in which shunting is most useful, suggesting that conductance normalization and tree geometry interact rather than contributing independently.
Activation choice	In the corrected five-seed frozen activation audit, identity outperforms frozen <code>param_tanh</code> for LocalCA on noise resilience in both architectures (0.590/0.859 vs. 0.109/0.772 for additive at $N_I=0/10$; 0.411/0.769 vs. 0.331/0.701 for shunting), while the backprop effect remains strongly regime-dependent.	The post-voltage firing-rate transform is a real modeling variable, not just an implementation detail. Even a fixed saturating nonlinearity changes the operating point substantially, so the main paper’s mechanistic claims should be read in the learned bounded <code>param_tanh</code> regime used throughout the headline experiments.

Table S2: **Which components carry the observed gains?** A compact summary of the empirical division of labor across architecture, broadcast design, and LocalCA rule variants.

Core	Broadcast	Decoder	Test (mean $\pm$ std)
Shunting	per-soma	local	0.912 $\pm$ 0.005
Shunting	per-soma	backprop	0.909 $\pm$ 0.008
Shunting	local-mismatch	local	0.146 $\pm$ 0.046
Shunting	local-mismatch	backprop	0.146 $\pm$ 0.037
Additive	per-soma	local	0.894 $\pm$ 0.007
Additive	per-soma	backprop	0.900 $\pm$ 0.001
Additive	local-mismatch	local	0.342 $\pm$ 0.058
Additive	local-mismatch	backprop	0.348 $\pm$ 0.095

Table S3: **Local-mismatch recheck (MNIST, 5F)**. Per-soma is consistently strong; local-mismatch remains much weaker.




Figure S1: **Capacity calibration (supplementary)**. (A) Phase 1 backprop ceilings across all architectures and datasets. (B) Rule-family ranking: 5F consistently outperforms 4F and 3F. (C) Decoder mode comparison (local vs. backprop decoder, 5F MNIST). (D) Broadcast mode comparison: per-soma is required for strong performance; local-mismatch fails.

Dataset	BP ceiling	Best local (5F)	Gap
MNIST	0.971	0.914 ± 0.003	5.7%
Fashion-MNIST	0.889	0.838 ± 0.003	5.1%
Context gating	0.861	0.803 ± 0.006	5.8%

Table S4: **Local competence.** Backprop ceilings are matched-capacity shunting references from dedicated 5-seed standard-training refreshes for MNIST and context gating and from the dedicated 5-seed Fashion-MNIST competence sweep. Local values are 5F with per-soma broadcast on shunting dendritic cores. Context gating additionally uses an HSIC auxiliary objective (weight 0.01; Appendix E). Error bars on local values: ± 1 s.d. across 5 seeds.

Condition	Metric	Value
Decoder: local vs backprop vs frozen (MNIST, sandbox)	test acc	0.379 vs 0.379 vs 0.176
Shunting vs additive, matched (MNIST, sandbox)	Δ test	+0.210
Per-soma, path on vs off (synthetic task, sandbox)	test / MI(E,I;C)	-0.003 / +0.017

Table S5: **Mechanistic ablations.** Results from controlled small-network sandbox experiments using minimal architectures to isolate individual factors. Sandbox runs use a small 2-layer dendritic network (branch factor [9]) trained for 30 epochs; they are not directly comparable to the headline capacity-calibrated results.

525 Broadcast Mode Comparison and Local-Mismatch Recheck

526 Competence, Verification, and Stress Tests

527 Phase 1 Capacity Ceilings

528 Local Competence and Regime Dependence

529 Ablation Results

530 Extended Gradient Analysis and N_I Sweep Detail

531 Verification and Reproducibility

532 Additional Stress Tests

533 Broadcast Bandwidth (Quantization) Control

534 FA/DFA Baseline Comparison

535 CIFAR-10 Results

536 Table S6 provides the exact values for the main-text CIFAR-10 figure. In this stronger compact
537 E/I family, shunting performs well under standard training (49.5% vs. 46.6% for additive), so the
538 harder-data stress test no longer unfairly penalizes the shunting architecture. The broadcast-fidelity
539 ladder also survives once decoder-aware soma mapping is used: additive LocalCA rises from 32.6%
540 under rank-1 per-soma broadcast to 42.3% under transported error, while shunting rises from 28.8%
541 under per-soma to 34.7% with random low-rank $K=4$ and 47.4% with transported error, nearly
542 matching the 49.5% shunting backprop ceiling.

543 **CIFAR-10 soma-on extension.** We also tested the soma-on extension on the same compact E/I
544 depth-4 family with quantile init (Table S7; 3 seeds). With `somatic_synapses=true`, path-
545 transported LocalCA stays strong in both cores: additive reaches $45.5 \pm 0.6\%$ and shunting reaches
546 $46.6 \pm 1.0\%$. Relative to the soma-off results, the additive path-transport condition improves from
547 42.3% to 45.5%, while shunting remains within 1 pp of its soma-off path-transport ceiling (47.4%)
548 and within 3 pp of the matched shunting backprop ceiling (49.5%). Per-soma rank-1 broadcast also
549 becomes much more competitive for additive ($41.6 \pm 0.6\%$) than for shunting ($35.9 \pm 1.2\%$), while




Figure S2: **Extended gradient and N_I analysis (supplementary).** (A) Scale mismatch bars: shunting achieves near-ideal scale (0.117); additive exhibits order-of-magnitude distortion (> 1.0). (B) Noise-resilience N_I dose-response with error bands (± 1 s.d.). (C) MNIST N_I dose-response detail with error bands. (D) Fashion-MNIST individual seeds for all conditions, showing consistency across runs.

Condition	Model	Test accuracy
standard	additive	46.6 ± 1.5
standard	shunting	49.5 ± 0.7
LocalCA per-soma	additive	32.6 ± 0.6
LocalCA per-soma	shunting	28.8 ± 0.8
LocalCA path transport	additive	42.3 ± 1.2
LocalCA path transport	shunting	47.4 ± 0.6
shunting low-rank	$K=4$	34.7 ± 1.1

Table S6: **Exact CIFAR-10 values for the corrected strong-family mechanism extension (5 seeds, validation-best epoch).** This table gives the exact numbers for the main-text harder-data ladder in Fig. 6. The key technical detail is that LocalCA maps output error back to decoder-input/soma space through the decoder Jacobian when the decoder is nonlinear; without that correction, the same family gave misleading near-chance results for per-soma and path transport. With the corrected rule, transported error again acts as a strong upper bound, nearly matching the stronger shunting backprop ceiling, while naive rank-1 per-soma broadcast still underperforms and random low-rank feedback closes part of that gap.

low-rank $K=4$ remains weak in both cores. On this harder dataset, the soma channel clearly helps,
but it still does not eliminate the importance of broadcast quality.




Figure S3: **5F sensitivity analysis (MNIST, shunting, per-soma broadcast)**. (A) Sensitivity to the ϕ_n clamp interval. The default clamp [0.25, 4.0] is already strong ($92.1 \pm 0.8\%$); tightening it to [0.5, 2.0] slightly improves performance ($92.5 \pm 0.3\%$), while widening it to [0.1, 8.0] is effectively neutral ($92.1 \pm 0.9\%$). (B) Sensitivity to the 4F/5F EMA rate used for online statistics. Varying α from 0.05 to 0.20 changes mean test accuracy by less than 0.2 pp. Together these results suggest that the 5F gain is not driven by a brittle single hyperparameter choice, even though the factor itself remains heuristic. Errors: ± 1 s.d. across 3 seeds.




Figure S4: **Verification and reproducibility (supplementary)**. (A) MNIST verification: main seeds (42–46) yield $91.4 \pm 0.3\%$; held-out seeds (47–49) yield $89.8 \pm 0.9\%$, confirming generalization. (B) Context gating verification: main seeds (+HSIC) $80.3 \pm 0.6\%$; held-out seeds (no HSIC) $77.2 \pm 1.5\%$. The roughly 3 pp gap reflects HSIC removal, not seed sensitivity. (C) HSIC weight ablation on context gating: moderate weights (0.01–0.1) perform best.

Condition (soma-on)	Additive	Shunting
LocalCA per-soma (rank-1)	41.6 $\pm$ 0.6	35.9 $\pm$ 1.2
LocalCA low-rank $K=4$	27.5 $\pm$ 3.5	26.6 $\pm$ 1.7
LocalCA path transport	45.5 $\pm$ 0.6	46.6 $\pm$ 1.0
soma-off path transport	42.3 $\pm$ 1.2	47.4 $\pm$ 0.6
standard BP (ceiling)	46.6 $\pm$ 1.5	49.5 $\pm$ 0.7

Table S7: **CIFAR-10 compact E/I depth-4 with somatic_synapses=true**. Adding direct somatic synapses and using quantile reactivation init improves the additive transported-error condition by about 3.2 pp and keeps the shunting transported-error condition within 1 pp of its soma-off counterpart. Per-soma (rank-1) becomes much more competitive for additive than for shunting, while low-rank $K=4$ remains weak in both cores. The soma channel therefore helps, but does not remove the need for a strong credit signal.




Figure S5: **Additional stress tests.** (A) Depth scaling: shunting local (green) degrades more gracefully from 63.5% to 57.4%; additive local (blue) drops from 54.9% to 29.7%. Backprop ceilings (dashed) remain stable. (B) Broadcast-noise robustness: shunting remains stable for $\sigma \leq 0.1$; additive degrades rapidly and reaches chance at $\sigma = 1$. (C) Fashion-MNIST: the shunting gain is modest on this cleaner benchmark (83.8% local vs. 88.9% backprop), consistent with the regime-dependent story in the main text.




Figure S6: **Coarse shared broadcast still works.** Test accuracy as a function of effective broadcast bandwidth. Full-precision, 8-bit, 4-bit, and 2-bit quantization of the shared error signal all reach essentially the same accuracy (61–62%; $p > 0.9$ for 4-bit vs. full), while a sign-only broadcast and a sparse top-30% broadcast degrade sharply. This shows that the shunting LocalCA signal carries most of its useful information in its direction rather than in fine-grained magnitude, consistent with the mechanism-summary picture in the main text. This panel was previously panel D of Fig. 3 and was moved here so the main figure can carry the full causal chain (path-gain concentration $\rightarrow$ alignment $\rightarrow$ oracle $\rightarrow$ global summary).




Figure S7: **Feedback alignment baselines (MNIST)**. (A) Grouped comparison: standard backprop (neutral gray), DFA (orange), and FA (purple). Hatched N/A markers indicate that FA is not implemented for the block-structured dendritic architectures because the random feedback matrices are not dimensionally compatible with the tree-structured branch updates. DFA achieves 66.1% on shunting vs. 62.2% additive vs. 51.8% point MLP. (B) Backprop–DFA gap: dendritic architectures (24.9–27.6 pp) show smaller gaps than point MLPs (39.5 pp), suggesting conductance-based architecture is partially compatible with random feedback.




Figure S8: **Additive + normalization control (MNIST)**. (A) Standard backprop: normalization provides a small boost (89.7% $\rightarrow$ 90.9%). (B) Local learning: normalization improves additive from 46.5% to 56.0% (+9.5 pp), partially closing the gap to shunting (61.7%, dashed green). The remaining gap (−5.7 pp) indicates that shunting provides benefits beyond simple voltage normalization.

Additive Normalization Control

Structured Feedback, Activation, and Supportive Extensions

Morphology $\times$ Inhibition Regime Map

The main-text morphology figure shows the supportive regime map, while the appendix keeps the summary tables and architecture details that go with it. We treat it as supportive evidence that morphology changes the inhibitory operating regime in which shunting is most useful; a fuller mechanistic account would still require matched theory diagnostics for each cell in the grid.

Random Low-Rank Broadcast Channels

Frozen Activation-Choice Audit

B Implementation Details

Biological Plausibility Assumptions

The theorems and rules above rest on a small set of explicit assumptions. We state them as a checklist so that readers can see exactly what is assumed and where each assumption is used:

A1 (Steady-state voltage). We use the steady-state solution of the passive cable equation (Eq. 1). Temporal dynamics are not modeled; all gradients, path gains, and fidelity measurements refer to the conductance-stage voltage at steady state.

A2 (Tree topology). Each dendritic cell is a rooted tree with the soma as the root. There are no recurrent connections within the dendrite, which makes the path from any compartment to the soma unique and is what allows the closed-form path gain α_n in Theorem 1.

A3 (Nonnegative conductances). Synaptic and dendritic conductance parameters are pushed through a positive transform (`softplus`), so $g_j^{\text{syn}}, g_j^{\text{den}} \geq 0$ at every optimisation step. This is a biophysical constraint and is also what keeps the shunting denominator bounded away from zero.

A4 (Nonnegative presynaptic drive). The first synaptic drive x is nonnegative, implemented either by nonnegative inputs or an explicit ReLU transfer stage. Together with A3 this enforces the positive-input condition used for all corrected headline sweeps.

Setting	Broadcast	Test accuracy
<i>Noise resilience, shunting, corrected rank bridge</i>		
per-soma	rank-1 per-soma	0.662 ± 0.016
path propagation	recursive attenuation proxy	0.762 ± 0.047
low-rank	$K=1$	0.453 ± 0.126
low-rank	$K=2$	0.630 ± 0.042
low-rank	$K=4$	0.764 ± 0.025
low-rank	$K=8$	0.795 ± 0.019
path transport	exact conductance-stage transport	0.847 ± 0.018
<i>Cue routing, learned shunting router, corrected rank/structure sweep</i>		
per-soma	tuned rank-1	0.803 ± 0.125
low-rank	$K=1$	0.742 ± 0.022
low-rank	$K=2$	0.846 ± 0.082
low-rank	$K=4$	0.748 ± 0.085
pathway-vector	tuned structured rank-2	0.815 ± 0.126

Table S8: **Corrected rank bridge and rank-structure comparison.** On shunting noise resilience, both the current path-propagation proxy and higher-rank random low-rank broadcast close a substantial fraction of the gap between rank-1 per-soma and exact path transport, with low-rank continuing to improve up to $K=8$. On cue routing, the corrected learned-router sweep shows that moving beyond rank-1 helps, but the best current unstructured low-rank setting ($K=2$) is still slightly better than the tuned structured pathway-vector variant. We therefore interpret routed credit assignment as an open higher-rank problem rather than as a solved pathway-vector rescue.

578 **A5 (Pre-reactivation upward transfer).** Theorem 1 is stated for the pre-reactivation compartment
579 voltage. A post-voltage reactivation f (e.g. `param_tanh`) is handled by multiplying the
580 path gain by $f'(V_n)$ along the recursion. The compartment error remains the sole non-local
581 quantity; only the effective path gain acquires local activation-derivative factors.

582 **A6 (Single perisomatic broadcast).** Every synapse receives one non-local scalar or low-rank vector
583 signal delivered from the soma; all other ingredients of the update rule (eligibility traces,
584 driving force, input resistance, covariance modulators) are computable from quantities
585 available at the synapse or compartment.

586 Each synapse therefore has access to: presynaptic activity x_j (local), compartment voltage V_n (local
587 membrane potential), reversal potential E_j (fixed by receptor type), and total input resistance $R_n^{\text{tot}} =$
588 $1/g_n^{\text{tot}}$ (computable from local conductances). The 4F modulator ρ_n requires online estimation of
589 voltage covariance (biologically plausible via slow calcium signals); the 5F factor ϕ_n requires a
590 linear regression proxy (implementable via eligibility traces). The only non-local quantity is the
591 broadcast error e_n , which requires a top-down or neuromodulatory signal from the soma to dendritic
592 compartments. We assume per-neuron resolution (one error per output neuron) for the per-soma
593 broadcast mode.

594 Dendritic Structure in Code

595 We use the morphology notation $[b_1, b_2, \dots, b_D]$ for rooted dendritic trees, where each factor gives
596 the fan-in from one dendritic stage to the next on the path to the soma. For example, $[3, 3]$ means that
597 each soma aggregates 3 proximal branches and each proximal branch aggregates 3 distal branches,
598 for 9 distal leaves per soma; $[3, 3, 3]$ adds a third dendritic stage with 27 leaves per soma. In code,
599 each excitatory unit is instantiated as a `DendriNet`, which is a stack of `DendriticBranchLayers`.
600 Each branch layer contains an excitatory synapse bank, an optional inhibitory synapse bank, a
601 branch-to-parent aggregation map, and an optional post-voltage reactivation. In the main feed-
602 forward models studied here, `somatic_synapses=false`, so synaptic inputs terminate on den-
603 dritic branches rather than directly on the soma. Likewise, `input_mode=1` together with `nonzero`
604 `ie_synapses_per_branch_per_layer` means that inhibition enters each dendritic branch through
605 explicit inhibitory synapses even when we do not instantiate a separate inhibitory neuron popula-
606 tion (`inhibitory_layer_sizes=[]`). The additive and shunting cores are therefore architecture-
607 matched at the tree level; they differ in the branch-level voltage integration rule rather than in whether
608 a dendritic tree exists. In all reported dendritic runs, synaptic and dendritic conductance parameters

Dataset / strategy	Core	N_I	Identity (none)	Frozen param_tanh
MNIST / LocalCA	additive	0	0.780 ± 0.014	0.709 ± 0.037
MNIST / LocalCA	additive	10	0.907 ± 0.003	0.881 ± 0.005
MNIST / LocalCA	shunting	0	0.841 ± 0.007	0.778 ± 0.020
MNIST / LocalCA	shunting	10	0.905 ± 0.009	0.840 ± 0.016
Noise resilience / LocalCA	additive	0	0.590 ± 0.162	0.109 ± 0.006
Noise resilience / LocalCA	additive	10	0.859 ± 0.001	0.772 ± 0.009
Noise resilience / LocalCA	shunting	0	0.411 ± 0.028	0.331 ± 0.020
Noise resilience / LocalCA	shunting	10	0.769 ± 0.004	0.701 ± 0.006
MNIST / backprop	additive	0	0.925 ± 0.001	0.942 ± 0.001
MNIST / backprop	additive	10	0.921 ± 0.001	0.950 ± 0.001
MNIST / backprop	shunting	0	0.963 ± 0.0004	0.950 ± 0.001
MNIST / backprop	shunting	10	0.967 ± 0.001	0.946 ± 0.001
Noise resilience / backprop	additive	0	0.896 ± 0.003	0.106 ± 0.007
Noise resilience / backprop	additive	10	0.893 ± 0.002	0.927 ± 0.002
Noise resilience / backprop	shunting	0	0.898 ± 0.001	0.869 ± 0.002
Noise resilience / backprop	shunting	10	0.926 ± 0.001	0.912 ± 0.001

Table S9: **Frozen activation-shape audit on matched dendritic architectures (5 seeds per condition).** Identity (none) and a frozen bounded post-voltage reactivation param_tanh lead to markedly different operating regimes even after correcting the task and enforcing nonnegative first-layer synaptic drive. In this corrected audit, identity is the safer LocalCA choice on both MNIST and the noise-resilience task, while the backprop effect is strongly regime-dependent: frozen param_tanh helps additive most clearly in the inhibited noise-resilience setting ($N_I=10$) but collapses it at $N_I=0$. These runs match additive reactivation initialization to the shunting setting and hold the activation parameters fixed, isolating activation shape from both the earlier additive/shunting initialization asymmetry in code and from activation learning itself.

Dataset	Core	N_I	Identity (none)	Frozen param_tanh
MNIST	additive	0	CV 0.280, cosine 0.220	CV 1.122, cosine 0.074
MNIST	additive	10	CV 0.310, cosine 0.212	CV 1.079, cosine 0.094
MNIST	shunting	0	CV 0.393, cosine 0.170	CV 0.770, cosine 0.114
MNIST	shunting	10	CV 0.385, cosine 0.281	CV 1.177, cosine 0.106
Noise resilience	additive	0	CV 0.124, cosine 0.079	CV 0.114, cosine 0.052
Noise resilience	additive	10	CV 0.414, cosine 0.206	CV 0.840, cosine 0.094
Noise resilience	shunting	0	CV 0.255, cosine 0.324	CV 0.344, cosine 0.341
Noise resilience	shunting	10	CV 0.762, cosine 0.140	CV 2.497, cosine 0.079

Table S10: **Frozen activation-shape theory audit on matched LocalCA runs (5 seeds per condition).** Each entry reports conductance-stage path-gain dispersion (CV) and direct per-soma compartment-error fidelity (cosine between the per-soma broadcast and the exact pre-reactivation compartment error). The corrected positive-input theory audit largely agrees with the empirical one: freezing param_tanh usually broadens path-gain dispersion and weakens per-soma fidelity, especially in the inhibited settings where the main mechanistic story lives. The one mild exception is low-inhibition shunting on noise resilience, where frozen param_tanh leaves fidelity roughly unchanged while still hurting final accuracy, suggesting that activation choice affects optimization and representation as well as direct credit fidelity.

are pushed through positive transforms (softplus in the main paper runs), so the conductances themselves remain nonnegative at every optimization step; unconstrained decoder weights are separate readout parameters and are not interpreted as conductances.

Completed soma-on LocalCA reruns suggest that direct somatic input is a meaningful extension rather than a minor implementation detail. Relative to the matched safeguarded non-somatic reruns, enabling somatic_synapses=true raises the mean test accuracy in all four finished paper-facing families: phase-1 capacity from 0.8784 to 0.8999, claim A from 0.5641 to 0.6715, claim B from 0.3578 to 0.7070, and claim C from 0.2798 to 0.3906. Because the main mechanistic analysis in this




Figure S9: **Soma-on extension for LocalCA.** Enabling direct somatic input (`somatic_synapses=true`) improves mean test accuracy across all four paper-facing LocalCA families. The largest gain appears in morphology scaling, where the mean rises from 35.8% to 70.7% and the best run rises from 57.0% to 76.4%. Gains in the shunting-regime and error-shaping families are smaller but still substantial. Delta labels show soma-on minus soma-off. Because the main mechanistic analysis was developed in the dendrite-only feedforward regime, we report soma-on as a supportive extension rather than replacing the main operating regime.

Family	Soma-off	Soma-on	Δ mean	Δ best
Phase-1 capacity	0.8784	0.8999	+0.0215	-0.0007
Claim A: shunting regime	0.5641	0.6715	+0.1074	+0.0090
Claim B: morphology scaling	0.3578	0.7070	+0.3492	+0.1940
Claim C: error shaping	0.2798	0.3906	+0.1109	+0.1210

Table S11: **Representative paired soma-on deltas across the four paper-facing LocalCA phase families.** Values compare matched safeguarded reruns with and without `somatic_synapses` and report both the change in mean test accuracy and the change in best-seed test accuracy. Cue-routing soma and CIFAR-10 depth-4 soma are reported separately in Fig. S10 and Table S7 because those extensions are summarized on a different stable subset or task family.

paper was developed in the dendrite-only feedforward regime, we keep the main text anchored to `somatic_synapses=false` and treat soma-on as a supportive extension rather than silently replacing the original operating regime. Figure S9 summarizes the mean and best-accuracy comparisons across the four families.

The soma-on benefit extends beyond the capacity/scaling families to the cue-routing benchmark that stress-tests rank-1 feedback. With dendrite-only pathways, the best learned-routing shunting LocalCA configuration was unstable at 0.81 ± 0.13 ; with `somatic_synapses=true`, fixed-router shunting LocalCA reaches 1.00 ± 0.0 test accuracy across 5 seeds, and learned-router additive LocalCA reaches 0.99 ± 0.003 (Fig. S10). The soma channel provides a high-bandwidth direct input that bypasses the rank-1 bottleneck induced by per-soma broadcast.

Post-Voltage Reactivation

The conductance stage produces a pre-reactivation compartment voltage V_n , after which each branch layer may apply a monotone scalar nonlinearity. The codebase supports identity (none), fixed `tanh/sigmoid/relu`, and several parametric families including `param_tanh`, `param_tanh_only_m`, and piecewise linear-saturating variants. The main manuscript sweeps use `param_tanh`, a learnable bounded firing-rate transform of the form $(\tanh(m(V - b)) + 1)/2$, together with an explicitly configured nonnegative transfer stage (ReLU in the corrected positive-conductance runs) so that the first synaptic drive remains nonnegative even after input corruption or structured task noise. Most headline feedforward sweeps use a linear decoder, while the CIFAR extension uses a nonlinear decoder and therefore maps output error back to decoder-input/soma space through the decoder Jacobian before applying LocalCA. Unless explicitly overridden, additive and shunting cores can start from different reactivation initializations in code; activation-fairness ablations therefore match




Figure S10: **Soma-on rescues cue-routing LocalCA.** The left bars show the previously reported soma-off LocalCA results on the cue-integration benchmark. The right bars show the soma-on extension: fixed-router shunting LocalCA reaches 1.00 test accuracy, and learned-router additive LocalCA with soma reaches 0.99, matching the additive backprop ceiling with soma. The soma channel supplies a direct high-bandwidth input that bypasses the rank-1 bottleneck identified in the main text. Learned-router shunting with soma is omitted because this benchmark uses signed cues, which conflict with the shunting positive-input check in the learned-router pipeline; fixed-router shunting is therefore the clean shunting data point.

additive initialization to the shunting setting when comparing alternative reactivation choices directly. The appendix activation audit additionally fixes `param_tanh` after initialization to isolate activation shape from activation plasticity.

The finalized LocalCA reruns now use occupancy-quantile initialization together with a safeguarded calibration pass that floors tiny quantile widths, clamps extreme fitted slopes, and reverts invalid per-layer fits rather than allowing pathological intermediate values to propagate. In the non-somatic feedforward publication families, this safeguard leaves the paper-facing results essentially unchanged relative to the earlier occupancy-quantile reruns: phase-1 capacity changes from 0.8786 to 0.8784 mean test accuracy, claim A from 0.5617 to 0.5641, claim B from 0.3600 to 0.3578, and claim C from 0.2860 to 0.2798. The calibration fix therefore improves numerical safety without changing the qualitative LocalCA story.

We also compared two post-initialization policies for the reactivation parameters under quantile initialization: *learned local* (b, m), where LocalCA updates the gate parameters through the local rule, and *quantile-maintained* (b, m), where (b, m) are periodically refreshed from the current voltage distribution instead of being updated by the local rule. This comparison matters because quantile-maintained gates substantially simplify nonlinear reactivation learning: the rest of the network still uses LocalCA, but the gate parameters themselves are set by a local distributional rule rather than a learned plasticity rule. On MNIST classification sweeps, learned local (b, m) remains clearly better (additive 0.9247 vs. 0.9061 mean test accuracy; shunting 0.9104 vs. 0.8766). On CIFAR-10, the picture is mixed in a useful way: additive is essentially tied on mean (0.4223 learned-local vs. 0.4215 quantile-maintained) while shunting improves under quantile-maintained gates (0.4028 to 0.4356 mean test accuracy). We therefore treat quantile-maintained (b, m) as a helpful simplification rather than a universal replacement: it is most attractive in the harder shunting/CIFAR regime, but learned local (b, m) remains the strongest single default across the full sweep. Accordingly, the main manuscript continues to use occupancy-quantile initialization followed by LocalCA updates of (b, m) as the default local-learning setting, while quantile-maintained (b, m) is reported as a supplementary alternative. Figure S11 shows the full MNIST and CIFAR-10 comparison.

Component Ablation

To isolate the contribution of each ingredient in our LocalCA recipe, we ran a per-component ablation on MNIST starting from the manuscript default and removing one component at a time. The default




Figure S11: (b, m) update policy under quantile initialization. Each cluster of bars compares the mean test accuracy of learned local (b, m) and quantile-maintained (b, m) under LocalCA for additive and shunting cores, averaged across morphology $([2, 2]$ and $[3, 3, 3])$ and initialization variants. Dashed and dotted horizontal lines mark the matched standard backpropagation ceiling for additive and shunting respectively. **Left (MNIST):** Learned local (b, m) is consistently better; quantile-maintained lags by 1.9 pp (additive) and 3.4 pp (shunting) on mean accuracy. **Right (CIFAR-10):** The gap reverses for shunting; quantile-maintained reaches 43.6% mean vs. 40.3% for learned local, while additive is essentially tied. The pattern suggests that quantile-maintained (b, m) prevents over-fitting the reactivation gate on harder inputs, making it a useful alternative in harder visual regimes.




Figure S12: **Per-component ablation for LocalCA on MNIST.** Bars show mean test accuracy ($\pm$ s.d. across 5 seeds); coloured bars highlight the manuscript default (blue/green) and the soma-on extension (green). **(A) Shunting:** The full default reaches 90.7%; removing quantile init leaves accuracy unchanged at 90.8% (quantile init is a mild calibration nudge on this clean task), removing learned (b, m) drops by about 1 pp, and removing reactivation entirely drops accuracy to 87.3%; the reactivation transform is the largest single LocalCA ingredient. **(B) Additive:** Quantile init contributes +2.1 pp (90.1 $\rightarrow$ 92.2%), learned (b, m) contributes +1.7 pp, and reactivation contributes +1.1 pp; each ingredient helps on the additive core. **Soma-on** is the largest positive change in both cores (+3 to +3.5 pp over full config), while matched standard backpropagation reaches 97.0% in both cores and sets the upper reference. The seventh condition (fixed relu reactivation) failed to initialize cleanly under the current quantile path and is omitted.

669 combines quantile init, learned local (b, m) , `somatic_synapses=false`, and `param_tanh` reactivation. We also include `somatic_synapses=true` as a positive extension and matched standard
 670 backpropagation as the upper reference. Figure S12 reports test accuracy (5 seeds per cell) for both
 671 shunting and additive dendritic cores on clean MNIST with morphology $[3, 3]$.
 672

Quantity	Symbol	Convention
Voltage	V	Normalized to $[-1, 1]$
Conductances	$g^{\text{syn}}, g^{\text{den}}$	Nonneg. via softplus
Leak conductance	g^{leak}	Set to 1
Input resistance	R^{tot}	≤ 1

Table S12: Units and normalization.

Category	Implemented modes	Role in this paper
Core models	point MLP; dendritic MLP; dendritic additive; dendritic shunting; pathway-routed dendritic cores	Main comparisons use dendritic additive vs. dendritic shunting; routed cores are used for cue integration.
Training strategies	standard backprop; LocalCA; DFA; FA; transported-broadcast oracle	Main text uses standard and LocalCA; DFA/FA remain appendix baselines; path transport is an oracle upper bound.
Broadcast modes	scalar; per-soma; local mismatch; low-rank; path transport; pathway vector	Main text centers on per-soma, low-rank, and transported-error controls; scalar and local-mismatch are supporting controls, while pathway vector remains an appendix structured-feedback extension.
Recent dendritic extensions	path propagation; router-derived branch roles; pathway-vector feedback; inhibitory homeostasis	These were added to test morphology-aware credit transport and structured branch-specific plasticity beyond the original 3F/4F/5F family.

Table S13: Implemented model families and LocalCA operating modes. Only a subset is used for the main claims; the remaining modes serve as controls, ablations, or structured extensions.

673 Units and Parameterization

674 Decoder Update Modes

675 W_{dec} maps $V_L \rightarrow \hat{y}$. Modes: **backprop** ($\nabla_W L$ via autograd), **local** ($\Delta W = \eta \langle \delta_0 V_L^\top \rangle_B$), **frozen**
676 ($\Delta W = 0$).

677 Model and Mode Inventory

678 Representative Manuscript Architectures

679 Hyperparameters

680 Table S15 collects the core training hyperparameters for each headline experiment. Learning rates
681 are applied through parameter groups (top- k , dendritic block-linear, reactivation, decoder) with the
682 values given in the representative config files; where a single LR is reported, every group uses that
683 value.

684 Effective Broadcast Dimensionality in Headline Architectures

685 LocalCA Extension Compatibility

686 Seed Protocol and Claim Status

687 The seed depth is not uniform across every sweep, and we therefore separate headline evidence from
688 exploratory screening. Table S18 pins each figure or table in this paper to its seed count and claim
689 tier (cf. Sec. 4.1).

Setting	Encoder	E layers	Tree	Synapses / branch	Seeds	Notes
Gradient fidelity / path-gain / noise-resilience mechanism	id.+ReLU	[128, 128]	[3, 3]	$N_E=40, N_I \in \{0, 5, 10, 20, 40\}$	5 fidelity, 5 oracle	Main mechanism sweeps in Figs. 2 and 3; reactivation <code>param_tanh</code> .
MNIST / context-gating local competence	id.+ReLU	[128]	[3, 3]	$N_E=40, N_I=20$	5	Best local 5F per-soma runs in Table S4; reactivation <code>param_tanh</code> .
Fashion-MNIST competence	id.+ReLU	[128]	[3, 3]	$N_E=40, N_I=20$	5	Dedicated five-seed standard-vs-local competence sweep; reactivation <code>param_tanh</code> .
Cue-routing PV-LocalCA	router	[64]	[2]	$N_E=10, N_I=4$	5	Learned router with two pathway groups and rank-2 structured feedback; reactivation <code>param_tanh</code> .
CIFAR-10 compact E/I mechanism extension	id.+ReLU	[20] E, [20] I	[3, 3, 3, 3]	$N_E=25, N_{EI}=25, N_{IE}=25$	5	Harder-data extension with explicit inhibition, decoder [32, 16], and decoder-aware soma mapping.
Morphology $\times$ inhibition appendix map	id.+ReLU	[128, 128]	[2, 2], [3, 3], [4, 4], [2, 2, 2], [3, 3, 3]	$N_E=40, N_I \in \{0, 5, 10, 20, 40\}$	3	Supportive 3-seed sweep; reactivation <code>param_tanh</code> .

Table S14: **Representative architectures used in the manuscript.** All dendritic rows use explicit branch-level excitatory and inhibitory synapse banks with `somatic_synapses=false`, nonnegative conductances, and a nonnegative first-layer drive enforced by an explicit ReLU transfer stage in the corrected runs. The tree column gives dendritic morphology per excitatory neuron, and the synapse counts report excitatory and inhibitory synapses per branch.

Setting	Opt.	LR	Batch	Epochs	W-dec.	Notes
MNIST / Fashion-MNIST / context gating (5F per-soma LocalCA)	Adam	$10^{-3} / 5 \cdot 10^{-4}$ (block / react.)	256	100	0	fixed-epoch, no early stopping; <code>param_tanh</code> reactivation
MNIST / Fashion-MNIST / context gating (BP ceiling)	Adam	$10^{-3} / 5 \cdot 10^{-4}$	256	100	0	matched to LocalCA setup
Gradient fidelity / path-gain / noise resilience	Adam	10^{-3}	256	50	0	5 seeds, hooks enabled for diagnostic capture
Morphology $\times$ inhibition regime map (exploratory)	Adam	10^{-3}	256	50	0	3 seeds
Cue routing (soma-off & soma-on)	Adam	10^{-3}	256	90	0	early stopping with patience 30
CIFAR-10 compact E/I depth-4 LocalCA	Adam	$10^{-3} / 10^{-4}$ (block / react.)	256	400	0.01	grad-clip 5.0, early stop patience 50, nonlinear decoder
CIFAR-10 compact E/I depth-4 BP	Adam	10^{-3}	256	400	0.01	matched ceiling
Weight-distribution vs. depth	Adam	10^{-3}	256	100	0	<code>weight_analysis</code> hook captures final-epoch statistics
Component ablation (MNIST)	Adam	10^{-3}	256	100	0	5 seeds, single-layer dendrinet [3, 3]
(b, m) policy comparison (MNIST / CIFAR-10)	Adam	$10^{-3} / 10^{-4}$	256	100 / 400	0 / 0.01	quantile refresh every 5 epochs; EMA $\alpha \in \{0.25, 0.5, 1.0\}$

Table S15: **Training hyperparameters by experiment.** All runs use Adam with default $\beta_1=0.9$, $\beta_2=0.999$, $\varepsilon=10^{-8}$. Reactivation and block-linear parameter groups use a slower LR to keep conductance-level dynamics stable. Full configs are provided under `drafts/dendritic-local-learning/configs/`.

690 Compute Resources

691 All experiments were run on an internal GPU cluster. Most MNIST, Fashion-MNIST, and synthetic-
692 task runs used a single NVIDIA A100 or H100 GPU and finished in minutes to tens of minutes per
693 seed. The flattened CIFAR-10 runs required longer single-GPU jobs but still did not use distributed or
694 multi-GPU training. Reported headline metrics are aggregated over 5 seeds unless noted otherwise;
695 this now includes the corrected flattened-CIFAR-10 mechanism extension. The remaining 3-seed

Setting	Hidden width(s)	Output dim	Effective default per-soma field
Gradient fidelity / path-gain / noise resilience	128, 128	10	Scalar / rank-1 at both dendritic layers
MNIST / Fashion-MNIST competence	128	10	Scalar / rank-1 at the dendritic hidden layer
Context gating competence	128	2	Scalar / rank-1 at the dendritic hidden layer
Cue routing	64	2	Scalar / rank-1 by default; higher-rank tests use explicit low-rank or pathway-vector feedback
Compact CIFAR-10 harder-data extension	20	decoder-input dim 20	Vector-valued per-soma after decoder-aware mapping; higher-rank tests use explicit low-rank or path transport

Table S16: **Effective dimensionality of the default “per-soma” broadcast in the headline architectures.** In code, per-soma uses the output error vector only when layer width matches decoder output dimension; otherwise it falls back to a shared scalar. The main feedforward settings in this paper therefore test a genuinely rank-1 broadcast regime by default, which is why the higher-rank low-rank, path-transport, and pathway-vector controls are important.

Extension	Meaning	Compatible with	Typical use here
Per-soma broadcast	Somatic error vector when widths match, otherwise scalar fallback	3F, 4F, 5F	Default main-text LocalCA setting; in the headline feedforward runs this is effectively rank-1
Low-rank broadcast	Small number of broadcast channels instead of a scalar or full field	3F, 4F, 5F	Intermediate control when rank-1 is too restrictive
Path transport	Recursive tree-transported error using conductance-stage path gains	3F, 4F, 5F	Oracle upper-bound broadcast
Path propagation	Approximate path-gain attenuation applied to broadcast	3F, 4F, 5F	Morphology-aware modifier for deeper trees
Pathway vector	Structured branch/pathway-specific broadcast field	3F, 4F, 5F	Used mainly in PV-LocalCA on routed tasks
Branch-role rules	Scales updates by router- or pathway-derived branch specialization	3F, 4F, 5F	Used in the structured pathway extension
Inhibitory homeostasis	Auxiliary local inhibitory balancing term	3F, 4F, 5F	Optional stabilizer in routed or shunting settings

Table S17: Compatibility of the newer LocalCA extensions with the base 3F/4F/5F family. These extensions mostly modify the error field or branch scaling rather than defining a new “6F” or “7F” rule.

696 results are confined to selected supportive sweeps, and the broader exploratory screens used to tune
697 and diagnose the method required additional compute beyond the final reported runs.

698 Code, Data, and Asset Availability

699 MNIST, Fashion-MNIST, CIFAR-10, and MICrONS are public datasets or public benchmark assets
700 cited in the paper; we use them under their standard published access conditions and cite their original
701 sources in the bibliography. The present anonymous submission does not include a public code URL
702 in order to preserve double-blind review, but the paper specifies the model family, training modes, key

Figure / Table	Sweep	Seeds	Tier
Fig. 1D	Fig. 1 MNIST learning dynamics	5	Headline
Fig. 2	Gradient-fidelity diagnostic	5	Headline
Fig. 3	Mechanistic chain + oracle + summary	5	Headline
Fig. 4	Competence / regime dose-response	5	Headline
Fig. 6 / Table S6	CIFAR-10 compact E/I mechanism extension	5	Headline
Fig. 7	Cue-routing (soma off)	5	Supportive
Table S4	Competence gaps (BP ceiling vs. 5F)	5	Headline
Fig. S9	Soma-on extension across phase families	5	Supportive
Table S11	Paired soma-on delta summary	5	Supportive
Fig. S11	(b, m) update-policy comparison	4	Supportive
Fig. S12	Component ablation (MNIST)	5	Supportive
Fig. S10	Cue-routing soma-on (stable subset)	5	Supportive
Fig. S13	Weight-distribution sensitivity	5	Supportive
Fig. S14	Weight-distribution vs. depth	5	Supportive
Fig. S15	Weight-distribution soma-off vs. soma-on	5	Supportive
Table S7	CIFAR-10 depth-4 soma extension	3	Supportive
Fig. S7	FA/DFA baseline comparison	5	Supportive
Fig. S6	Broadcast-bandwidth / quantization	5	Supportive
Fig. S8	Additive + normalization control	5	Supportive
Fig. S5 / S4	Stress tests; verification	5	Supportive
Fig. S3	5F sensitivity	3	Supportive
Table S8	Rank-bridge	5	Supportive
Fig. 5	Morphology $\times$ inhibition map	3	Supportive
(legacy) info-shunting	Signed-input stress test	1–3	Exploratory

Table S18: **Seed-to-claim map.** Each main-paper and appendix figure or table is pinned to its sweep, seed count, and claim tier (Sec. 4.1). The BP ceilings in Table S4 come from dedicated matched-capacity 5-seed standard-training refreshes.

hyperparameters, and representative configurations, and we plan to release code and configuration files after review. The paper does not release a new dataset or a stand-alone pretrained model asset.

Algorithm

Algorithm 1 Local Credit Assignment

- 1: **Input:** Model, batch (x, y) , config $\mathcal{C}$
- 2: Forward pass; loss L , output error δ^y
- 3: Somatic/core error $\delta_0 = \text{decoder-input Jacobian product } J_{\text{dec}}(h_{\text{core}})^\top \delta^y$ (or $W_{\text{dec}}^\top \delta^y$ for a linear decoder)
- 4: **for** each layer n (reverse) **do**
- 5: $e_n = \text{broadcast}(\delta_0, \mathcal{C})$; optionally gate by pathway roles
- 6: Compute ρ_n, ϕ_n (EMA estimators, if enabled)
- 7: Apply the configured local update (Eq. 6 or 7)
- 8: **end for**
- 9: Clip gradients; optimizer step

Rule	Factors	Cost	Best regime
3F	$x, (E - V), e$	$\mathcal{O}(1)$	Baseline
4F	$3F + \rho$	$\mathcal{O}(1)$	Improved conditioning
5F	$4F + \phi$	$\mathcal{O}(d_n)$	Strongest overall
5F+VH	5F + local voltage homeostasis	$\mathcal{O}(d_n)$	Stabilized LocalCA / warm-up
PV-LocalCA	3F + structured e_n + role alignment	$\mathcal{O}(r_n)$	Pathway discovery

Table S19: Variant taxonomy. ‘5F+VH’ denotes the same base 5F rule with an additional strictly local voltage-centering auxiliary that can also be scheduled through multi-stage LocalCA warm-up; the codebase also supports this as a shorthand ‘5f_vh’ alias in configuration files.

Component	Analog	Interpretation
R_n^{tot}	Input resistance	Sensitivity modulation
$(E_j - V_n)$	Synaptic driving force	Local gradient factor
Shunting	Divisive normalization	$\partial V / \partial g_I \propto -V$
ρ_n	Layer relevance	Output correlation
ϕ_n	Signal propagation	Conditional predictability
Pathway vector	Branch-specific top-down drive	Structured teaching signal
Role alignment	Pathway-selective plasticity	Branch specialization

Table S20: Biological analogs.

C Theoretical Details

Variant Taxonomy

Random-Broadcast Alignment

Proposition 3 (Supportive random-broadcast alignment). *Let the broadcast matrix B_n have i.i.d. zero-mean entries with $\mathbb{E}[B_n^\top B_n] = \alpha I$. Then the expected cosine between the resulting local gradient and the exact gradient is positive, $\mathbb{E}[\cos \angle(g^{\text{local}}, g^{\text{exact}})] \geq c_n > 0$, by an argument analogous to feedback alignment [9]. The constant c_n depends on how strongly local eligibility factors correlate with the conductance-stage path gain in Eq. (4); shunting improves this correlation by narrowing the spread of intermediate sensitivities.*

We treat this argument as supportive rather than central. The main theoretical object in the paper is still the exact pre-reactivation compartment error $\partial L / \partial V_n$; under identity upward transfer this reduces to $\alpha_n \delta_0$, while with post-voltage activation the corresponding effective path gain additionally includes local $f'_n(V_n)$ factors. The main empirical question is how faithfully different broadcast fields approximate that quantity.

Biological Analogs

D Morphology-Aware Extensions

Path-integrated propagation. Modulate broadcast error by $\pi_n = \pi_{n-1} \cdot R_{n-1}^{\text{tot}} \cdot \bar{g}_{n-1}^{\text{den}}$, approximating depth attenuation from Eq. 4.

Depth modulation. Per-branch scaling $\rho_j = \rho_{\text{base}} / (d_j + \alpha)$, mirroring cable attenuation.

Dendritic normalization. $\Delta g_j^{\text{den}} \leftarrow \Delta g_j^{\text{den}} / (\sum_k g_k^{\text{den}} + \varepsilon)$, analogous to homeostatic scaling [21].

Pathway-vector feedback. For tasks with latent pathway structure, the broadcast becomes a low-dimensional role vector inferred from the router. Local pathway activity gates that vector, and block-structured transport carries it upward so earlier branches receive feedback aligned with their downstream descendants.

Condition	MNIST		Fashion-MNIST	
	Exc σ	Inh σ	Exc σ	Inh σ
BP + Shunting	0.94±0.01	0.87±0.01	0.92±0.01	0.84±0.01
BP + Additive	1.30±0.01	1.22±0.01	1.16±0.01	1.05±0.01
Local + Shunting	1.22±0.01	1.71±0.02	1.13±0.06	1.36±0.06
Local + Additive	1.69±0.16	1.57±0.07	1.43±0.16	1.11±0.12
Song et al. 2005	$\sigma = 0.94$ (rat V1 L5, EPSP amplitude)			
MICrONS E→E	$\sigma = 1.14$ (mouse V1, synapse size, $n=3.9M$)			
MICrONS I→E	$\sigma = 0.92$ (mouse V1, synapse size, $n=3.5M$)			

Table S21: **Weight distribution width.** Log-normal σ of excitatory and inhibitory synaptic weights (mean±std across 5 seeds). Biological references are included only as descriptive anchors. With biologically constrained E/I ratios (4:1), shunting self-normalization produces weight heterogeneity in the range spanned by those references, whereas additive integration is broader and less stable.

Router-derived branch roles. Each branch receives a role profile inferred from router assignments and incoming block weights rather than from a hand-coded apical/basal label. Plasticity is then modulated by branch selectivity and a synapse-specific role-alignment factor, emphasizing pathway-consistent updates without imposing a heuristic branch taxonomy.

E HSIC Auxiliary Objectives

Following [17], we use kernel-based HSIC objectives:

$$\mathcal{L}^{\text{self}} = B^{-2} \text{tr}(\mathbf{K}_Z \mathbf{H} \mathbf{K}_Z \mathbf{H}), \quad \mathcal{L}^{\text{target}} = -B^{-2} \text{tr}(\mathbf{K}_Z \mathbf{H} \mathbf{K}_Y \mathbf{H}).$$

Moderate weights (0.01–0.1) help on context gating; negligible on MNIST. Online statistics (ρ_n, ϕ_n) use Welford’s algorithm [20].

F Online Variant with Eligibility Traces

The continuous-time eligibility trace is

$$\tau_e \dot{e}_j^{\text{syn}} = -e_j^{\text{syn}} + x_j(E_j - V_n)R_n^{\text{tot}},$$

with update

$$\Delta g_j^{\text{syn}} \propto \int e_j^{\text{syn}}(t) m_n(t) dt$$

[18, 19].

G Weight Statistics and Biological References

As a secondary analysis, we examine whether the conductance-based update naturally induces characteristic weight statistics. Because synaptic updates scale with input resistance $R_n^{\text{tot}} = 1/g_n^{\text{tot}}$, the voltage equation implies multiplicative weight dynamics, creating a regime analogous to exponentiated-gradient updates. Such multiplicative dynamics suggest log-normal weight distributions in trained networks [38, 39]. We compare the resulting distributions against two biological references: electrophysiological data from Song et al. [38] (rat V1 L5 pyramidal, $\sigma = 0.94$) and the MICrONS mm³ connectome [40] (mouse V1 synapse sizes).

Model weight distributions are log-normal. We fit log-normal distributions to the active (top- K masked) excitatory synaptic weights after training on MNIST and Fashion-MNIST. Table S21 shows the fitted σ (standard deviation of $\log w$) for each condition. Shunting consistently produces narrower distributions than additive integration, and backpropagation produces narrower distributions than local learning. These two factors combine approximately additively: BP+Shunting → narrowest, Local+Additive → broadest.




Figure S13: **Synaptic weight distribution sensitivity to architecture.** (A) Log-normal σ vs. dendritic depth (branch factors [9] to [3,3,3,3]). Both backprop and local shunting remain closer to the biological-width references than their additive counterparts across depth. (B) σ vs. inhibitory synapses per branch (N_I). Without inhibition ($N_I=0$), all conditions are overly broad; with biologically constrained $N_I=10$ –20, shunting enters the biological range. Shaded bands show the sweep over $N_E=20$ to 80. (C) Summary of MNIST and Fashion-MNIST results with biological references. The shunting ordering is consistent across datasets. (D) Excitatory vs. inhibitory weight σ on MNIST with MICrONS E→E and I→E reference bands.

Shunting is closest to the biological references considered here. BP+Shunting produces $\sigma = 0.94$ on MNIST, very close to the Song et al. reference ($\Delta = 0.008$). Local+Shunting produces $\sigma = 1.13$ –1.22, close to MICrONS E→E synapse sizes ($\sigma = 1.14$; $\Delta \leq 0.08$). By contrast, Local+Additive produces $\sigma = 1.43$ –1.69, broader than any biological reference considered. This pattern is consistent across datasets (MNIST and Fashion-MNIST), suggesting it reflects structural properties of the learning rule rather than task-specific features.

The match depends on inhibitory conductance. We test sensitivity to the E/I synapse ratio using a sweep over $N_I \in \{0, 2, 5, 10, 20, 30, 40\}$ inhibitory synapses per branch (Appendix Fig. S13). Without inhibition ($N_I=0$), all conditions produce $\sigma > 2.0$, far from biology. With biologically constrained ratios ($N_I=10$ –20, corresponding to E/I ratios of 4:1 to 2:1; [42]), shunting networks enter the biological range ($\sigma \approx 0.9$ –1.2), while the effect of N_I on additive networks is less systematic. The weight distribution shape is also robust to dendritic depth (branch factors [9] through [3,3,3,3]; see Appendix Fig. S13A): BP+Shunting converges toward Song et al. with increasing depth, while Local+Shunting remains near MICrONS E→E across depths.

H Weight Distribution Sensitivity Analysis

Side-by-side BP vs. LocalCA across depths. To complement the per-architecture analysis above, we ran a matched BP vs. LocalCA sweep over three branch-factor settings ([2, 2], [3, 3], [3, 3, 3]) under both shunting and additive cores on MNIST (5 seeds per cell; quantile init; learned (b, m) for LocalCA). Figure S14 shows that at shallow and medium depths the local rule and backprop reach broadly similar excitatory weight means (≈ 0.8 –0.9), while the coefficient of variation (CV) under LocalCA is roughly twice as large as under BP at these depths (e.g. shunting [2, 2]: $CV_{BP} = 0.15$




Figure S14: **Synaptic weight statistics vs. dendritic depth (MNIST, 5 seeds/cell).** (A) Excitatory weight mean (error bars = std). At [2, 2] and [3, 3], all four conditions cluster around 0.8–0.9; at [3, 3, 3] the means drop to ≈ 0.5 –0.75 and the cross-seed spread grows, especially for additive LocalCA. (B) Coefficient of variation (CV = std/mean). At shallow/medium depth, LocalCA produces $\sim 2\times$ higher CV than matched BP, but both remain well-behaved (≤ 0.33). At the deepest network all four conditions jump to CV ≈ 0.66 –0.88, with additive LocalCA the broadest. (C) MNIST test accuracy. BP tracks ~ 96 –97% at [2, 2]/[3, 3] and ~ 92 –95% at [3, 3, 3]. LocalCA stays within ~ 5 –6 pp of BP at shallow/medium depth but trails by ~ 15 –20 pp at [3, 3, 3], identifying depth as the remaining open challenge for this local rule. The qualitative ordering (shunting LocalCA tracks shunting BP more closely than additive LocalCA tracks additive BP) reinforces the manuscript claim that the conductance denominator is the key mechanistic ingredient.

778 vs. $CV_{Loc.} = 0.31$; shunting [3, 3]: 0.11 vs. 0.26). At the deepest setting [3, 3, 3] the weight means
779 drop and the CV jumps substantially for both optimizers (CV ≈ 0.66 –0.88), and test accuracy drops
780 by ~ 5 pp for BP and ~ 15 –20 pp for LocalCA. Across the explored depth range, shunting LocalCA
781 stays closer to shunting BP than additive LocalCA does to additive BP on both weight and accuracy
782 axes, consistent with the manuscript claim that the conductance denominator is the key mechanistic
783 ingredient.

784 **Weight distributions under soma-on.** To check whether the direct somatic synapse extension
785 (Fig. S9) alters the weight-distribution picture, we ran a matched 5-seed sweep at depth [3, 3] on
786 MNIST with `somatic_synapses=true` across all four (core, strategy) cells; results are summarized
787 in Fig. S15. Two effects emerge. First, shunting + BP becomes *tighter* than in the soma-off case:
788 excitatory-weight CV drops from ≈ 0.11 (soma-off, [3, 3]) to ≈ 0.10 (soma-on), consistent with the
789 soma sink absorbing part of the drive and reducing per-branch variance. Second, shunting + LocalCA
790 goes in the opposite direction: CV grows from ≈ 0.26 (soma-off) to ≈ 0.40 (soma-on), while MNIST
791 test accuracy drops ~ 3 pp (from 96.5% to 93.6%). Additive cores sit between these extremes (CV
792 ≈ 0.23 –0.30, accuracy 95.7–97.0%) and are only weakly affected. The ordering is consistent with
793 the mechanism in the main text: the somatic synapse is an additional BP-visible path that backprop
794 exploits cleanly, but under the local rule it adds broadcast variance that the scalar/per-soma signal
795 cannot sharpen, widening the weight distribution without a matching accuracy gain.

796 **MICrONS connectome analysis.** We extracted synapse size distributions from the MICrONS
797 mm³ condensed connectome (v1181; 9.0M connections, 71.9K neurons; 89% excitatory). Split-
798 ting by pre/post cell type: E→E connections ($n=3.85$ M) show $\sigma_{size}=1.14$ and CV=1.01; I→E
799 ($n=3.53$ M) show $\sigma=0.92$ and CV=1.03; E→I ($n=1.11$ M) show $\sigma=0.83$; I→I ($n=0.51$ M) show
800 $\sigma=0.85$. Inhibitory connections are more frequently multi-synaptic (I→E: 37.5% multi-synapse;
801 E→E: 11.5%), and inhibitory synapses are on average smaller (median 3532 vs. 4676 for E→E).

802 **Sensitivity to ee_synapses.** Using the E/I grid sweep ($N_E \in \{20, 40, 80\}$ and $N_I \in$
803 $\{0, 2, 5, 10, 20, 30, 40\}$; 168 models), excitatory σ increases modestly with N_E in both architec-
804 tures, but the shunting-versus-additive ordering is preserved at every N_E value. The dominant driver
805 of σ is still N_I : moving from $N_I=0$ to $N_I=10$ reduces shunting σ by roughly 1.0–1.5 units, while
806 the effect on additive is smaller and less systematic.

807 **Sensitivity to depth.** From the depth-scaling sweep ([9], [3, 3], [3, 3, 3], [3, 3, 3, 3]; 80 models, 5 seeds
808 each), BP+Shunting excitatory σ decreases with depth ($1.06 \rightarrow 0.90$), converging toward Song




Figure S15: **Excitatory-weight CV and MNIST accuracy under soma-off vs. soma-on (depth [3, 3], 5 seeds/cell).** (A) Coefficient of variation of excitatory weights for the four (core, strategy) cells; paired bars show soma-off (from Fig. S14) and soma-on (this sweep). Shunting + BP tightens slightly; shunting + LocalCA broadens; additive cells change little. (B) Matched MNIST test accuracy (sanity panel). BP accuracy is preserved or marginally improved; LocalCA accuracy is preserved for additive but drops ~3 pp for shunting, consistent with the CV widening in panel A.

et al. (0.94). Local+Shunting σ increases slightly ($1.18 \rightarrow 1.33$) but remains in the biological range at shallow depths. BP+Additive shows the strongest depth sensitivity ($1.38 \rightarrow 0.79$), while Local+Additive diverges with depth ($2.01 \rightarrow 2.44$). The morphology-aware modulators (path propagation, depth/centrality weighting) have negligible effect on σ .

Mechanistic interpretation. The shunting conductance $g_n^{\text{tot}} = g_n^{\text{leak}} + \sum g_n^{\text{exc}} + \sum g_n^{\text{inh}}$ appears in the update factor $R_n^{\text{tot}} = 1/g_n^{\text{tot}}$. As inhibitory conductance increases, g_n^{tot} grows and R_n^{tot} shrinks, compressing the multiplicative scale of weight updates. This is analogous to a learning rate that self-adjusts via the total conductance: strong synapses contribute more to g_n^{tot} , reducing their own future update magnitude. This acts as a natural form of weight-dependent regularization. The resulting equilibrium distribution is log-normal, consistent with Loewenstein et al. [41] and related multiplicative spine-dynamics analyses. Additive integration lacks this self-normalizing mechanism, producing broader distributions that fall outside the biological range.

I Synthetic Benchmark Descriptions

Each synthetic task is generated procedurally from a fixed random seed and uses fixed train/val/test splits for reproducibility. The MNIST-derived synthetic tasks use flattened 28×28 inputs; cue integration instead uses a small vector input with two output classes. Output dimensionality therefore varies by task and is stated in the task description when it differs from 10-way digit classification.

Context gating. Inputs are contextual figure-ground MNIST examples. The right half of the image carries the original MNIST digit, while the left half is replaced by low-amplitude uniform noise; all pixels therefore remain nonnegative. This task tests whether credit assignment can exploit a simple context-dependent spatial structure without leaving the nonnegative-drive regime of the conductance model. The HSIC auxiliary objective (weight 0.01) is used to decorrelate layer representations, adding roughly 3 pp under local learning.

Noise resilience. Inputs are flattened MNIST images corrupted by structured channel noise: a fixed 50-dimensional latent Gaussian perturbation is projected into input space and added to each example, with $\sigma_{\text{task}} = 1.5$, then clipped to $[0, 1]$. The projection is fixed across training, so the network must filter correlated interference to recover the underlying class signal. Credit assignment must remain coherent under the corrupted signal, making this task particularly sensitive to path-gain dispersion.

Info shunting. Inputs contain two additive streams: a low-frequency signal and a high-frequency distractor drawn with equal energy, together with a separate context channel indicating which stream is relevant on each trial. In the current code this benchmark uses signed synthetic inputs, so it violates

the nonnegative presynaptic-drive assumption enforced in the corrected headline experiments. We therefore retain it only as a legacy exploratory task and exclude it from the corrected main-text claims.

Cue integration. Two noisy cue streams (A and B) are presented simultaneously, each carrying partial information about one of 2 classes. A binary one-hot context signal indicates which cue is reliable on each trial (cue A or cue B), and each cue vector is clipped to $[0, 1]$ after noise is added. The fixed-pathway variant duplicates the context into both cue branches; the learned-routing variant requires the router to discover the cue separation from data. This task is used in Sec. 4.10 to test structured pathway-vector broadcast while staying inside the nonnegative-input regime.

J Depth Scaling and Noise Robustness

Depth scaling. Varying dendritic depth from 1–4 layers (branch factors $[9]$ to $[3, 3, 3, 3]$): shunting local degrades from 63.5% to 57.4%; additive local degrades more steeply from 54.9% to 29.7%. The shunting advantage grows with depth ($+8.5 \rightarrow +27.7$ pp). Backprop ceilings remain stable at about 90–92%. See Fig. S5A.

Noise robustness. Gaussian noise $\mathcal{N}(0, \sigma^2)$ on broadcast error: shunting is robust to $\sigma \leq 0.1$ (about 62%) while additive drops from 46.5% to chance at $\sigma=1.0$, confirming that shunting credit signals carry useful learning information beyond the broadcast magnitude. See Fig. S5B.

NeurIPS Paper Checklist

1. Claims

Question: Do the main claims made in the abstract and introduction accurately reflect the paper’s contributions and scope?

Answer: [Yes]

Justification: The abstract and introduction state the paper’s main mechanistic claim, the scope of the conductance-based setting, and the regime-dependent nature of the empirical results; see Sec. 1 and Sec. 6.

Guidelines:

- The answer [N/A] means that the abstract and introduction do not include the claims made in the paper.
- The abstract and/or introduction should clearly state the claims made, including the contributions made in the paper and important assumptions and limitations. A [No] or [N/A] answer to this question will not be perceived well by the reviewers.
- The claims made should match theoretical and experimental results, and reflect how much the results can be expected to generalize to other settings.
- It is fine to include aspirational goals as motivation as long as it is clear that these goals are not attained by the paper.

2. Limitations

Question: Does the paper discuss the limitations of the work performed by the authors?

Answer: [Yes]

Justification: The discussion explicitly narrows the scope of the claims and discusses limitations involving benchmark strength, broadcast assumptions, depth scaling, and the exploratory stress tests; see Sec. 6.

Guidelines:

- The answer [N/A] means that the paper has no limitation while the answer [No] means that the paper has limitations, but those are not discussed in the paper.
- The authors are encouraged to create a separate “Limitations” section in their paper.
- The paper should point out any strong assumptions and how robust the results are to violations of these assumptions (e.g., independence assumptions, noiseless settings, model well-specification, asymptotic approximations only holding locally). The authors

should reflect on how these assumptions might be violated in practice and what the implications would be.

- The authors should reflect on the scope of the claims made, e.g., if the approach was only tested on a few datasets or with a few runs. In general, empirical results often depend on implicit assumptions, which should be articulated.
- The authors should reflect on the factors that influence the performance of the approach. For example, a facial recognition algorithm may perform poorly when image resolution is low or images are taken in low lighting. Or a speech-to-text system might not be used reliably to provide closed captions for online lectures because it fails to handle technical jargon.
- The authors should discuss the computational efficiency of the proposed algorithms and how they scale with dataset size.
- If applicable, the authors should discuss possible limitations of their approach to address problems of privacy and fairness.
- While the authors might fear that complete honesty about limitations might be used by reviewers as grounds for rejection, a worse outcome might be that reviewers discover limitations that aren't acknowledged in the paper. The authors should use their best judgment and recognize that individual actions in favor of transparency play an important role in developing norms that preserve the integrity of the community. Reviewers will be specifically instructed to not penalize honesty concerning limitations.

3. Theory assumptions and proofs

Question: For each theoretical result, does the paper provide the full set of assumptions and a complete (and correct) proof?

Answer: [Yes]

Justification: The voltage model, assumptions, theorem statements, and proof details are given in Sec. 2 and Appendix C; proof sketches and the exact factorization sanity check are cross-referenced in the main text.

Guidelines:

- The answer [N/A] means that the paper does not include theoretical results.
- All the theorems, formulas, and proofs in the paper should be numbered and cross-referenced.
- All assumptions should be clearly stated or referenced in the statement of any theorems.
- The proofs can either appear in the main paper or the supplemental material, but if they appear in the supplemental material, the authors are encouraged to provide a short proof sketch to provide intuition.
- Inversely, any informal proof provided in the core of the paper should be complemented by formal proofs provided in appendix or supplemental material.
- Theorems and Lemmas that the proof relies upon should be properly referenced.

4. Experimental result reproducibility

Question: Does the paper fully disclose all the information needed to reproduce the main experimental results of the paper to the extent that it affects the main claims and/or conclusions of the paper (regardless of whether the code and data are provided or not)?

Answer: [Yes]

Justification: The main paper and appendices specify the datasets, architectures, local-rule family, broadcast modes, representative hyperparameters, and compute regime needed to reproduce the headline results; see Sec. 4 and Appendix B.

Guidelines:

- The answer [N/A] means that the paper does not include experiments.
- If the paper includes experiments, a [No] answer to this question will not be perceived well by the reviewers: Making the paper reproducible is important, regardless of whether the code and data are provided or not.
- If the contribution is a dataset and/or model, the authors should describe the steps taken to make their results reproducible or verifiable.

- Depending on the contribution, reproducibility can be accomplished in various ways. For example, if the contribution is a novel architecture, describing the architecture fully might suffice, or if the contribution is a specific model and empirical evaluation, it may be necessary to either make it possible for others to replicate the model with the same dataset, or provide access to the model. In general, releasing code and data is often one good way to accomplish this, but reproducibility can also be provided via detailed instructions for how to replicate the results, access to a hosted model (e.g., in the case of a large language model), releasing of a model checkpoint, or other means that are appropriate to the research performed.
- While NeurIPS does not require releasing code, the conference does require all submissions to provide some reasonable avenue for reproducibility, which may depend on the nature of the contribution. For example
 - (a) If the contribution is primarily a new algorithm, the paper should make it clear how to reproduce that algorithm.
 - (b) If the contribution is primarily a new model architecture, the paper should describe the architecture clearly and fully.
 - (c) If the contribution is a new model (e.g., a large language model), then there should either be a way to access this model for reproducing the results or a way to reproduce the model (e.g., with an open-source dataset or instructions for how to construct the dataset).
 - (d) We recognize that reproducibility may be tricky in some cases, in which case authors are welcome to describe the particular way they provide for reproducibility. In the case of closed-source models, it may be that access to the model is limited in some way (e.g., to registered users), but it should be possible for other researchers to have some path to reproducing or verifying the results.

5. Open access to data and code

Question: Does the paper provide open access to the data and code, with sufficient instructions to faithfully reproduce the main experimental results, as described in supplemental material?

Answer: [No]

Justification: To preserve double-blind review, the anonymous submission does not include a public repository or anonymized code bundle. The paper instead provides architectural, algorithmic, and configuration details and states that code and configs will be released after review; see Appendix B.

Guidelines:

- The answer [N/A] means that paper does not include experiments requiring code.
- Please see the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- While we encourage the release of code and data, we understand that this might not be possible, so [No] is an acceptable answer. Papers cannot be rejected simply for not including code, unless this is central to the contribution (e.g., for a new open-source benchmark).
- The instructions should contain the exact command and environment needed to run to reproduce the results. See the NeurIPS code and data submission guidelines (<https://neurips.cc/public/guides/CodeSubmissionPolicy>) for more details.
- The authors should provide instructions on data access and preparation, including how to access the raw data, preprocessed data, intermediate data, and generated data, etc.
- The authors should provide scripts to reproduce all experimental results for the new proposed method and baselines. If only a subset of experiments are reproducible, they should state which ones are omitted from the script and why.
- At submission time, to preserve anonymity, the authors should release anonymized versions (if applicable).
- Providing as much information as possible in supplemental material (appended to the paper) is recommended, but including URLs to data and code is permitted.

6. Experimental setting/details

995 Question: Does the paper specify all the training and test details (e.g., data splits, hyperpa-
 996 rameters, how they were chosen, type of optimizer) necessary to understand the results?

997 Answer: [Yes]

998 Justification: The main text states the benchmark families, seed protocol, representative
 999 local-rule settings, and major training choices, while the appendices provide implementation
 1000 details and operating-mode inventories; see Sec. 4 and Appendix B.

1001 Guidelines:

- 1002 • The answer [N/A] means that the paper does not include experiments.
- 1003 • The experimental setting should be presented in the core of the paper to a level of detail
 1004 that is necessary to appreciate the results and make sense of them.
- 1005 • The full details can be provided either with the code, in appendix, or as supplemental
 1006 material.

1007 **7. Experiment statistical significance**

1008 Question: Does the paper report error bars suitably and correctly defined or other appropriate
 1009 information about the statistical significance of the experiments?

1010 Answer: [Yes]

1011 Justification: The paper reports means and standard deviations across 5 seeds for the headline
 1012 results and across 3 seeds for selected appendix-only support sweeps, states this explicitly
 1013 in the text, and shows error bars or seed variability in the relevant tables and figures; see
 1014 Sec. 4 and Appendix A.

1015 Guidelines:

- 1016 • The answer [N/A] means that the paper does not include experiments.
- 1017 • The authors should answer [Yes] if the results are accompanied by error bars, confidence
 1018 intervals, or statistical significance tests, at least for the experiments that support the
 1019 main claims of the paper.
- 1020 • The factors of variability that the error bars are capturing should be clearly stated (for
 1021 example, train/test split, initialization, random drawing of some parameter, or overall
 1022 run with given experimental conditions).
- 1023 • The method for calculating the error bars should be explained (closed form formula,
 1024 call to a library function, bootstrap, etc.)
- 1025 • The assumptions made should be given (e.g., Normally distributed errors).
- 1026 • It should be clear whether the error bar is the standard deviation or the standard error
 1027 of the mean.
- 1028 • It is OK to report 1-sigma error bars, but one should state it. The authors should
 1029 preferably report a 2-sigma error bar than state that they have a 96% CI, if the hypothesis
 1030 of Normality of errors is not verified.
- 1031 • For asymmetric distributions, the authors should be careful not to show in tables or
 1032 figures symmetric error bars that would yield results that are out of range (e.g., negative
 1033 error rates).
- 1034 • If error bars are reported in tables or plots, the authors should explain in the text how
 1035 they were calculated and reference the corresponding figures or tables in the text.

1036 **8. Experiments compute resources**

1037 Question: For each experiment, does the paper provide sufficient information on the com-
 1038 puter resources (type of compute workers, memory, time of execution) needed to reproduce
 1039 the experiments?

1040 Answer: [Yes]

1041 Justification: Appendix B describes the internal GPU cluster setting, the use of single
 1042 A100/H100-class GPUs, rough per-run runtime scales, and the fact that broader exploratory
 1043 sweeps required additional compute beyond the final reported runs.

1044 Guidelines:

- 1045 • The answer [N/A] means that the paper does not include experiments.

- The paper should indicate the type of compute workers CPU or GPU, internal cluster, or cloud provider, including relevant memory and storage.
- The paper should provide the amount of compute required for each of the individual experimental runs as well as estimate the total compute.
- The paper should disclose whether the full research project required more compute than the experiments reported in the paper (e.g., preliminary or failed experiments that didn't make it into the paper).

9. Code of ethics

Question: Does the research conducted in the paper conform, in every respect, with the NeurIPS Code of Ethics <https://neurips.cc/public/EthicsGuidelines>?

Answer: [Yes]

Justification: The work uses standard public benchmarks and mechanistic simulations, does not involve human-subjects experimentation or restricted data collection, and we are not aware of any aspect that violates the NeurIPS Code of Ethics.

Guidelines:

- The answer [N/A] means that the authors have not reviewed the NeurIPS Code of Ethics.
- If the authors answer [No], they should explain the special circumstances that require a deviation from the Code of Ethics.
- The authors should make sure to preserve anonymity (e.g., if there is a special consideration due to laws or regulations in their jurisdiction).

10. Broader impacts

Question: Does the paper discuss both potential positive societal impacts and negative societal impacts of the work performed?

Answer: [Yes]

Justification: The discussion includes a broader-relevance and potential-harms paragraph that distinguishes mechanistic neuroscience relevance from possible misuse through overclaiming biological plausibility or overstating robustness; see Sec. 6.

Guidelines:

- The answer [N/A] means that there is no societal impact of the work performed.
- If the authors answer [N/A] or [No], they should explain why their work has no societal impact or why the paper does not address societal impact.
- Examples of negative societal impacts include potential malicious or unintended uses (e.g., disinformation, generating fake profiles, surveillance), fairness considerations (e.g., deployment of technologies that could make decisions that unfairly impact specific groups), privacy considerations, and security considerations.
- The conference expects that many papers will be foundational research and not tied to particular applications, let alone deployments. However, if there is a direct path to any negative applications, the authors should point it out. For example, it is legitimate to point out that an improvement in the quality of generative models could be used to generate Deepfakes for disinformation. On the other hand, it is not needed to point out that a generic algorithm for optimizing neural networks could enable people to train models that generate Deepfakes faster.
- The authors should consider possible harms that could arise when the technology is being used as intended and functioning correctly, harms that could arise when the technology is being used as intended but gives incorrect results, and harms following from (intentional or unintentional) misuse of the technology.
- If there are negative societal impacts, the authors could also discuss possible mitigation strategies (e.g., gated release of models, providing defenses in addition to attacks, mechanisms for monitoring misuse, mechanisms to monitor how a system learns from feedback over time, improving the efficiency and accessibility of ML).

11. Safeguards

1098 Question: Does the paper describe safeguards that have been put in place for responsible
1099 release of data or models that have a high risk for misuse (e.g., pre-trained language models,
1100 image generators, or scraped datasets)?

1101 Answer: [N/A]

1102 Justification: The submission does not release a high-risk generative model, foundation
1103 model, or scraped dataset, so the safeguard question is not applicable here.

1104 Guidelines:

- 1105 • The answer [N/A] means that the paper poses no such risks.
- 1106 • Released models that have a high risk for misuse or dual-use should be released with
1107 necessary safeguards to allow for controlled use of the model, for example by requiring
1108 that users adhere to usage guidelines or restrictions to access the model or implementing
1109 safety filters.
- 1110 • Datasets that have been scraped from the Internet could pose safety risks. The authors
1111 should describe how they avoided releasing unsafe images.
- 1112 • We recognize that providing effective safeguards is challenging, and many papers do
1113 not require this, but we encourage authors to take this into account and make a best
1114 faith effort.

1115 12. Licenses for existing assets

1116 Question: Are the creators or original owners of assets (e.g., code, data, models), used in
1117 the paper, properly credited and are the license and terms of use explicitly mentioned and
1118 properly respected?

1119 Answer: [No]

1120 Justification: The paper credits all benchmark and connectomic assets and states that they
1121 are used under their published access conditions, but it does not enumerate license names or
1122 terms of use explicitly for each asset in the anonymous submission; see Appendix B.

1123 Guidelines:

- 1124 • The answer [N/A] means that the paper does not use existing assets.
- 1125 • The authors should cite the original paper that produced the code package or dataset.
- 1126 • The authors should state which version of the asset is used and, if possible, include a
1127 URL.
- 1128 • The name of the license (e.g., CC-BY 4.0) should be included for each asset.
- 1129 • For scraped data from a particular source (e.g., website), the copyright and terms of
1130 service of that source should be provided.
- 1131 • If assets are released, the license, copyright information, and terms of use in the
1132 package should be provided. For popular datasets, paperswithcode.com/datasets
1133 has curated licenses for some datasets. Their licensing guide can help determine the
1134 license of a dataset.
- 1135 • For existing datasets that are re-packaged, both the original license and the license of
1136 the derived asset (if it has changed) should be provided.
- 1137 • If this information is not available online, the authors are encouraged to reach out to
1138 the asset's creators.

1139 13. New assets

1140 Question: Are new assets introduced in the paper well documented and is the documentation
1141 provided alongside the assets?

1142 Answer: [N/A]

1143 Justification: The paper does not release a new dataset, benchmark, or pretrained model
1144 asset in this anonymous submission.

1145 Guidelines:

- 1146 • The answer [N/A] means that the paper does not release new assets.
- 1147 • Researchers should communicate the details of the dataset/code/model as part of their
1148 submissions via structured templates. This includes details about training, license,
1149 limitations, etc.

- The paper should discuss whether and how consent was obtained from people whose asset is used.
- At submission time, remember to anonymize your assets (if applicable). You can either create an anonymized URL or include an anonymized zip file.

14. Crowdsourcing and research with human subjects

Question: For crowdsourcing experiments and research with human subjects, does the paper include the full text of instructions given to participants and screenshots, if applicable, as well as details about compensation (if any)?

Answer: [N/A]

Justification: The work does not involve crowdsourcing or direct research with human subjects.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Including this information in the supplemental material is fine, but if the main contribution of the paper involves human subjects, then as much detail as possible should be included in the main paper.
- According to the NeurIPS Code of Ethics, workers involved in data collection, curation, or other labor should be paid at least the minimum wage in the country of the data collector.

15. Institutional review board (IRB) approvals or equivalent for research with human subjects

Question: Does the paper describe potential risks incurred by study participants, whether such risks were disclosed to the subjects, and whether Institutional Review Board (IRB) approvals (or an equivalent approval/review based on the requirements of your country or institution) were obtained?

Answer: [N/A]

Justification: The work does not involve crowdsourcing or human-subjects research requiring IRB review.

Guidelines:

- The answer [N/A] means that the paper does not involve crowdsourcing nor research with human subjects.
- Depending on the country in which research is conducted, IRB approval (or equivalent) may be required for any human subjects research. If you obtained IRB approval, you should clearly state this in the paper.
- We recognize that the procedures for this may vary significantly between institutions and locations, and we expect authors to adhere to the NeurIPS Code of Ethics and the guidelines for their institution.
- For initial submissions, do not include any information that would break anonymity (if applicable), such as the institution conducting the review.

16. Declaration of LLM usage

Question: Does the paper describe the usage of LLMs if it is an important, original, or non-standard component of the core methods in this research? Note that if the LLM is used only for writing, editing, or formatting purposes and does *not* impact the core methodology, scientific rigor, or originality of the research, declaration is not required.

Answer: [N/A]

Justification: LLMs are not part of the proposed method, theorem, experiments, or analysis pipeline, so no declaration is required for the core scientific contribution.

Guidelines:

- The answer [N/A] means that the core method development in this research does not involve LLMs as any important, original, or non-standard components.
- Please refer to our LLM policy in the NeurIPS handbook for what should or should not be described.