# Лабораторная работа №11

## Настройка безопасного удалённого доступа по протоколу SSH

**Студент: ТалебуТенке**

**Группа: НФИбд 02–23**

***дисциплина:*** **Администрирование сетевых подсистем (Lab 11)**

# Цель работы

Целью данной работы является приобретение практических навыков по настройке удалённого доступа к серверу с помощью SSH.

```
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@server ~]# passwd root
Changing password for user root.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@server ~]# passwd root
Changing password for user root.
New password:
Retype new password:
passwd: all authentication tokens updated successfully.
[root@server ~]#
```

root@server:~

root@server:~ | root@server:~

```
  Subject: A start job for unit systemd-hostnamed.service has begun execution
  Defined-By: systemd
  Support: https://wiki.rockylinux.org/rocky/support

  A start job for unit systemd-hostnamed.service has begun execution.

  The job identifier is 2680.
Mar 11 16:09:46 server.user.net systemd[1]: Started Hostname Service.
  Subject: A start job for unit systemd-hostnamed.service has finished successf
ully
  Defined-By: systemd
  Support: https://wiki.rockylinux.org/rocky/support

  A start job for unit systemd-hostnamed.service has finished successfully.

  The job identifier is 2680.
Mar 11 16:10:16 server.user.net systemd[1]: systemd-hostnamed.service: Deactivat
ed successfully.
  Subject: Unit succeeded
  Defined-By: systemd
  Support: https://wiki.rockylinux.org/rocky/support

  The unit systemd-hostnamed.service has successfully entered the 'dead' state.
```

Open Save

sshd_config
/etc/ssh

```
31 #RekeyLimit default none
32
33 # Logging
34 #SyslogFacility AUTH
35 #LogLevel INFO
36
37 # Authentication:
38
39 #LoginGraceTime 2m
40 PermitRootLogin no
41 #StrictModes yes
42 #MaxAuthTries 6
43 #MaxSessions 10
44
45 #PubkeyAuthentication yes
46
47 # The default is to check both .ssh/authorized_keys and .ssh/authorized_keys2
48 # but this is overridden so installations will only check .ssh/authorized_keys
49 AuthorizedKeysFile      .ssh/authorized_keys
50
51 #AuthorizedPrincipalsFile none
52
53 #AuthorizedKeysCommand none
54 #AuthorizedKeysCommandUser nobody
55
56 # For this to work you will also need host keys in /etc/ssh/ssh_known_hosts
57 #HostbasedAuthentication no
58 # Change to yes if you don't trust ~/.ssh/known_hosts for
59 # HostbasedAuthentication
60 #IgnoreUserKnownHosts no
61 # Don't read the user's ~/.rhosts and ~/.shosts files
62 #IgnoreRhosts yes
63
64 # To disable tunneled clear text passwords, change to no here!
65 #PasswordAuthentication yes
66 #PermitEmptyPasswords no
67
68 # Change to no to disable s/key passwords
```

Saving file "/etc/ssh/sshd_config"... Plain Text Tab Width: 8 Ln 44, Col 1 INS

```
ssh: Could not resolve hostname server: Name or service not known
[root@client ~]# ssh root@server.root.net
ssh: Could not resolve hostname server.root.net: Name or service not known
[root@client ~]# ssh vagarnt@server.vagarnt.net
ssh: Could not resolve hostname server.vagarnt.net: Name or service not known
[root@client ~]# ssh vagrant@server.vagrant.net
ssh: Could not resolve hostname server.vagrant.net: Name or service not known
[root@client ~]#
```

root@server:~

root@server:~ root@server:~

```
(gedit:6861): dconf-WARNING **: 16:57:30.437: failed to commit changes t
to execute child process “dbus-launch” (No such file or directory)
[root@server ~]# systemctl restart sshd
[root@server ~]# systemctl status -l sshd
● sshd.service - OpenSSH server daemon
   Loaded: loaded (/usr/lib/systemd/system/sshd.service; enabled; pres
   Active: active (running) since Wed 2026-03-11 16:57:35 UTC; 8s ago
     Docs: man:sshd(8)
           man:sshd_config(5)
 Main PID: 6902 (sshd)
    Tasks: 1 (limit: 22435)
   Memory: 1.4M
```

root@server:~

root@server:~ | root@server:~

```
(gedit:6861): dconf-WARNING **: 16:57:30.437: failed to commit changes to dconf: Failed
to execute child process “dbus-launch” (No such file or directory)
[root@server ~]# systemctl restart sshd
[root@server ~]# systemctl status -l sshd
● sshd.service - OpenSSH server daemon
     Loaded: loaded (/usr/lib/systemd/system/sshd.service; enabled; preset: ena>
     Active: active (running) since Wed 2026-03-11 16:57:35 UTC; 8s ago
       Docs: man:sshd(8)
             man:sshd_config(5)
   Main PID: 6902 (sshd)
      Tasks: 1 (limit: 22435)
     Memory: 1.4M
        CPU: 28ms
     CGroup: /system.slice/sshd.service
             └─6902 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Mar 11 16:57:35 server.user.net systemd[1]: Starting OpenSSH server daemon...
Mar 11 16:57:35 server.user.net sshd[6902]: error: Bind to port 2022 on 0.0.0.0>
Mar 11 16:57:35 server.user.net sshd[6902]: error: Bind to port 2022 on :: fail>
Mar 11 16:57:35 server.user.net sshd[6902]: Server listening on 0.0.0.0 port 22.
Mar 11 16:57:35 server.user.net sshd[6902]: Server listening on :: port 22.
Mar 11 16:57:35 server.user.net systemd[1]: Started OpenSSH server daemon.
lines 1-18/18 (END)
```

root@server:~

root@server:~ | root@server:~ | root@server:~

```
to execute child process “dbus-launch” (No such file or directory)

** (gedit:7031): WARNING **: 17:07:31.628: Set document metadata failed: Setting attribu
te metadata::gedit-spell-language not supported

** (gedit:7031): WARNING **: 17:07:31.630: Set document metadata failed: Setting attribu
te metadata::gedit-encoding not supported

** (gedit:7031): WARNING **: 17:11:37.098: Set document metadata failed: Setting attribu
te metadata::gedit-spell-language not supported

** (gedit:7031): WARNING **: 17:11:37.121: Set document metadata failed: Setting attribu
te metadata::gedit-encoding not supported

** (gedit:7031): WARNING **: 17:11:38.732: Set document metadata failed: Setting attribu
te metadata::gedit-position not supported

(gedit:7031): dconf-WARNING **: 17:11:38.761: failed to commit changes to dconf: Failed
to execute child process “dbus-launch” (No such file or directory)
[root@server ~]# ssh -fNL 8080:localhost:80 user@server.user.net
The authenticity of host 'server.user.net (fe80::a00:27ff:fe69:a8d%eth0)' can't be estab
lished.
ED25519 key fingerprint is SHA256:yiD6CwwpAVWgmZ0LNexnVt25Q77Gy5XU7NfNuqLLz68.
This host key is known by the following other names/addresses:
    ~/.ssh/known_hosts:1: server
Are you sure you want to continue connecting (yes/no/[fingerprint])? yes
Warning: Permanently added 'server.user.net' (ED25519) to the list of known hosts.
user@server.user.net's password:
```

```
user@server.user.net's password:
user@server.user.net: Permission denied (publickey,gssapi-keyex,gssapi-with-mic,passwor
).
[root@server ~]# cd /vagrant/provision/server
[root@server server]# mkdir -p /vagrant/provision/server/ssh/etc/ssh
[root@server server]# cp -R /etc/ssh/sshd_config /vagrant/provision/server/ssh/etc/ssh/
[root@server server]# cd /vagrant/provision/server
[root@server server]# touch ssh.sh
[root@server server]# chmod +x ssh.sh
[root@server server]# gedit ssh.sh

(gedit:7114): dconf-WARNING **: 17:17:30.664: failed to commit changes to dconf: Failed
```

Open

ssh.sh
/vagrant/provision/server

Save

```bash
#!/bin/bash
echo "Provisioning script $0"
echo "Copy configuration files"
cp -R /vagrant/provision/server/ssh/etc/* /etc
restorecon -vR /etc
echo "Configure firewall"
firewall-cmd --add-port=2022/tcp
firewall-cmd --add-port=2022/tcp --permanent
echo "Tuning SELinux"
semanage port -a -t ssh_port_t -p tcp 2022
echo "Restart sshd service"
systemctl restart sshd
```

sh Tab Width: 8 Ln 1, Col 1 INS

# Вывод

В ходе выполнения лабораторной работы были приобретены практические навыки по настройке удалённого доступа к серверу с помощью SSH.

Спасибо за внимание!