Лабораторная работа №10

Расширенные настройки SMTP-сервера

Студент: Талебу Франк

Группа: НФИбд 02–23

дисциплина: **Администрирование сетевых подсистем (Lab 10)**

Цель работы

Целью данной работы является приобретение практических навыков по конфигурированию SMTP-сервера в части настройки аутентификации.

Open Save

10-auth.conf
/etc/dovecot/conf.d

```
# value contains series of from -> to characters. For example "#@/@" means
# that '#' and '/' characters are translated to '@'.
#auth_username_translation =

# Username formatting before it's looked up from databases. You can use
# the standard variables here, eg. %Lu would lowercase the username, %n would
# drop away the domain if it was given, or "%n-AT-%d" would change the '@' into
# "-AT-". This translation is done after auth_username_translation changes.
#auth_username_format = %Ln

# If you want to allow master users to log in by specifying the master
# username within the normal username string (ie. not using SASL mechanism's
# support for it), you can specify the separator character here. The format
# is then <username><separator><master username>. UW-IMAP uses "*" as the
# separator, so that could be a good choice.
#auth_master_user_separator =

# Username to use for users logging in with ANONYMOUS SASL mechanism
#auth_anonymous_username = anonymous

# Maximum number of dovecot-auth worker processes. They're used to execute
# blocking passdb and userdb queries (eg. MySQL and PAM). They're
# automatically created and destroyed as needed.
#auth_worker_max_count = 30

# Host name to use in GSSAPI principal names. The default is to use the
# name returned by gethostname(). Use "$ALL" (with quotes) to allow all keytab
# entries.
#auth_gssapi_hostname =

# Kerberos keytab to use for the GSSAPI mechanism. Will use the system
# default (usually /etc/krb5.keytab) if not specified. You may need to change
# the auth service to run as root to be able to read this file.
#auth_krb5_keytab =
```

root@server:~

root@server:/etc/dovecot/conf.d | root@server:~

```
[vagrant@server ~]$ sudo -i
[root@server ~]# MAIL=~/Maildir/ mai
bash: mai: command not found...
[root@server ~]# MAIL=~/Maildir/ mail
s-nail: No mail for root at /root/Maildir/
s-nail: /root/Maildir/: No such entry, file or directory
[root@server ~]#
```

root@server:/etc/dovecot/conf.d

root@server:/etc/dovecot/conf.d | root@server:~

```
** (gedit:3650): WARNING **: 11:30:26.889: Set document metadata failed: Setting attribut
etadata::gedit-encoding not supported

** (gedit:3650): WARNING **: 11:30:29.288: Set document metadata failed: Setting attribut
etadata::gedit-spell-language not supported

** (gedit:3650): WARNING **: 11:30:29.290: Set document metadata failed: Setting attribut
etadata::gedit-encoding not supported

** (gedit:3650): WARNING **: 11:30:30.057: Set document metadata failed: Setting attribut
etadata::gedit-spell-language not supported

** (gedit:3650): WARNING **: 11:30:30.061: Set document metadata failed: Setting attribut
etadata::gedit-encoding not supported

** (gedit:3650): WARNING **: 11:30:30.867: Set document metadata failed: Setting attribut
etadata::gedit-position not supported

(gedit:3650): dconf-WARNING **: 11:30:30.941: failed to commit changes to dconf: Failed t
xecute child process “dbus-launch” (No such file or directory)
[root@server conf.d]# postconf -e 'smtpd_sasl_type = dovecot'
[root@server conf.d]# postconf -e 'smtpd_sasl_path = private/auth'
[root@server conf.d]# postconf -e 'smtpd_recipient_restrictions =
reject_unknown_recipient_domain, permit_mynetworks,
reject_non_fqdn_recipient, reject_unauth_destination,
reject_unverified_recipient, permit'
postconf: fatal: -e, -X, or -# accepts no multi-line input
[root@server conf.d]# postconf -e 'smtpd_recipient_restrictions = reject_unknown_recipien
omain, permit_mynetworks, reject_non_fqdn_recipient, reject_unauth_destination, reject_un
ified_recipient, permit'
[root@server conf.d]# postconf -e 'mynetworks = 127.0.0.0/8'
[root@server conf.d]#
```

Open ▾ | master.cf /etc/postfix | Save | ≡ | ×

```
1 #
2 # Postfix master process configuration file.  For details on the format
3 # of the file, see the master(5) manual page (command: "man 5 master" or
4 # on-line: http://www.postfix.org/master.5.html).
5 #
6 # Do not forget to execute "postfix reload" after editing this file.
7 #
8 # ==========================================================================
9 # service type  private unpriv  chroot  wakeup  maxproc command + args
10 #               (yes)   (yes)   (no)    (never) (100)
11 # ==========================================================================
12 smtp      inet  n       -       n       -       -       smtpd
13 #smtp      inet  n       -       n       -       1       postscreen
14 #smtpd     pass  -       -       n       -       -       smtpd
15 #dnsblog   unix  -       -       n       -       0       dnsblog
16 #tlsproxy  unix  -       -       n       -       0       tlsproxy
17 #submission inet n       -       n       -       -       smtpd
18 #  -o syslog_name=postfix/submission
19 #  -o smtpd_tls_security_level=encrypt
20 #  -o smtpd_sasl_auth_enable=yes
21 #  -o smtpd_tls_auth_only=yes
22 #  -o smtpd_reject_unlisted_recipient=no
23 #  -o smtpd_client_restrictions=$mua_client_restrictions
24 #  -o smtpd_helo_restrictions=$mua_helo_restrictions
25 #  -o smtpd_sender_restrictions=$mua_sender_restrictions
26 #  -o smtpd_recipient_restrictions=
27 #  -o smtpd_relay_restrictions=permit_sasl_authenticated,reject
28 #  -o milter_macro_daemon_name=ORIGINATING
29 #smtps     inet  n       -       n       -       -       smtpd
30 #  -o syslog_name=postfix/smtps
31 #  -o smtpd_tls_wrappermode=yes
32 #  -o smtpd_sasl_auth_enable=yes
33 #  -o smtpd_reject_unlisted_recipient=no
34 #  -o smtpd_client_restrictions=$mua_client_restrictions
35 #  -o smtpd_helo_restrictions=$mua_helo_restrictions
36 #  -o smtpd_sender_restrictions=$mua_sender_restrictions
37 #  -o smtpd_recipient_restrictions=
```

Plain Text ▾ | Tab Width: 8 ▾ | Ln 18, Col 37 | INS

Open ▾ | master.cf /etc/postfix | Save

```
#
# ==========================================================================
#
# Old example of delivery via Cyrus.
#
#old-cyrus unix  -       n       n       -       -       pipe
#  flags=R user=cyrus argv=/usr/lib/cyrus-imapd/deliver -e -m ${extension} ${user}
#
# ==========================================================================
#
# See the Postfix UUCP_README file for configuration details.
#
#uucp      unix  -       n       n       -       -       pipe
#  flags=Fqhu user=uucp argv=uux -r -n -z -a$sender - $nexthop!rmail ($recipient)
#
# ==========================================================================
#
# Other external delivery methods.
#
#ifmail    unix  -       n       n       -       -       pipe
#  flags=F user=ftn argv=/usr/lib/ifmail/ifmail -r $nexthop ($recipient)
#
#bsmtp     unix  -       n       n       -       -       pipe
#  flags=Fq. user=bsmtp argv=/usr/local/sbin/bsmtp -f $sender $nexthop $recipient
#
#scalemail-backend unix -       n       n       -       2       pipe
#  flags=R user=scalemail argv=/usr/lib/scalemail/bin/scalemail-store
#  ${nexthop} ${user} ${extension}
#
#mailman   unix  -       n       n       -       -       pipe
#  flags=FRX user=list argv=/usr/lib/mailman/bin/postfix-to-mailman.py
#  ${nexthop} ${user}
submission inet n - n - - smtpd
-o smtpd_tls_security_level=encrypt
-o smtpd_sasl_auth_enable=yes
-o smtpd_recipient_restrictions=reject_non_fqdn_recipient,reject_unknow ]
n_recipient_domain,permit_sasl_authenticated,reject
```

Plain Text ▾ Tab Width: 8 ▾ Ln 134, Col 32 INS

root@server:~

root@server:/etc/dovecot/conf.d | root@server:~

```
ix mdns memcache minidlna mongodb mosh mountd mqtt mqtt-tls ms-wbt mssql murmur mysql nbd ne
bula netbios-ns netdata-dashboard nfs nfs3 nmea-0183 nrpe ntp nut openvpn ovirt-imageio ovir
t-storageconsole ovirt-vmconsole plex pmcd pmproxy pmwebapi pmwebapis pop3 pop3s postgresql
privoxy prometheus prometheus-node-exporter proxy-dhcp ps2link ps3netsrv ptp pulseaudio pupp
etmaster quassel radius rdp redis redis-sentinel rpc-bind rquotad rsh rsyncd rtsp salt-maste
r samba samba-client samba-dc sane sip sips slp smtp smtp-submission smtps snmp snmptls snmp
tls-trap snmptrap spideroak-lansync spotify-sync squid ssdp ssh ssh-custom steam-streaming s
vdrp svn syncthing syncthing-gui syncthing-relay synergy syslog syslog-tls telnet tentacle t
ftp tile38 tinc tor-socks transmission-client upnp-client vdsm vnc-server warpinator wbem-ht
tp wbem-https wireguard ws-discovery ws-discovery-client ws-discovery-tcp ws-discovery-udp w
sman wsmans xdmcp xmpp-bosh xmpp-client xmpp-local xmpp-server zabbix-agent zabbix-server ze
rotier
[root@server ~]# firewall-cmd --add-service=smtp-submission
success
[root@server ~]# firewall-cmd --add-service=smtp-submission --permanent
success
[root@server ~]# firewall-cmd --reload
success
[root@server ~]# systemctl restart postfix
Job for postfix.service failed because the control process exited with error code.
See "systemctl status postfix.service" and "journalctl -xeu postfix.service" for details.
[root@server ~]# openssl s_client -starttls smtp -crlf -connect server.vagrant.net:587
801B44331D7F0000:error:8000006F:system library:BIO_connect:Connection refused:crypto/bio/bio
_sock2.c:114:calling connect()
801B44331D7F0000:error:10000067:BIO routines:BIO_connect:connect error:crypto/bio/bio_sock2.
c:116:
801B44331D7F0000:error:8000006F:system library:BIO_connect:Connection refused:crypto/bio/bio
_sock2.c:114:calling connect()
801B44331D7F0000:error:10000067:BIO routines:BIO_connect:connect error:crypto/bio/bio_sock2.
c:116:
connect:errno=111
[root@server ~]#
```

Open Save

mail.sh
/vagrant/provision/server

```
18 firewall-cmd --reload
19 echo "Start postfix service"
20 systemctl enable postfix
21 systemctl start postfix
22 echo "Configure postfix"
23 postconf -e 'mydomain = user.net'
24 postconf -e 'myorigin = $mydomain'
25 postconf -e 'inet_protocols = ipv4'
26 postconf -e 'inet_interfaces = all'
27 postconf -e 'mydestination = $myhostname, localhost.$mydomain, localhost,
28 $mydomain'↪
29 #postconf -e 'mynetworks = 127.0.0.0/8, 192.168.0.0/16'
30 echo "Configure postfix for dovecot"
31 postconf -e 'home_mailbox = Maildir/'
32 echo "Configure postfix for auth"
33 postconf -e 'smtpd_sasl_type = dovecot'
34 postconf -e 'smtpd_sasl_path = private/auth'
35 Королькова А. В., Кулябов Д. С. Администрирование сетевых подсистем 81
36 postconf -e 'smtpd_recipient_restrictions = reject_unknown_recipient_domain,
37 permit_mynetworks, reject_non_fqdn_recipient, reject_unauth_destination,
38 reject_unverified_recipient, permit'
39 ↪
40 ↪
41 postconf -e 'mynetworks = 127.0.0.0/8'
42 echo "Configure postfix for SMTP over TLS"
43 cp /etc/pki/dovecot/certs/dovecot.pem /etc/pki/tls/certs
44 cp /etc/pki/dovecot/private/dovecot.pem /etc/pki/tls/private
45 postconf -e 'smtpd_tls_cert_file=/etc/pki/tls/certs/dovecot.pem'
46 postconf -e 'smtpd_tls_key_file=/etc/pki/tls/private/dovecot.pem'
47 postconf -e 'smtpd_tls_session_cache_database =
48 btree:/var/lib/postfix/smtpd_scache'↪
49 postconf -e 'smtpd_tls_security_level = may'
50 postconf -e 'smtp_tls_security_level = may'
51 postfix set-permissions
52 restorecon -vR /etc
53 systemctl stop postfix
54 systemctl start postfix
55 systemctl restart dovecot
```

Вывод

В ходе выполнения лабораторной работы были приобретены практические навыки по конфигурированию SMTP-сервера в части настройки аутентификации.

Спасибо за внимание!