```
        MailImpl mail = new MailImpl();
        mail.sendMail();
        mail.~~send~~log();
    }
}
```

B2

```
interface Shape {
    double getArea();
    double getPerimeter();
    void draw();
}

class Rectangle implements Shape {
    double width;
    double height;
    Rectangle (double w, double h) {
        width = w;
        height = h;
    }
    Public double getArea() {
        return 2 * (width + height);
    }
```

Thành Đạt

```
    Public void draw (){
        System.out.println(" Draw Rectangle ");
    }
}
class circle implements shape {
    double radius;
    circle (double r){
        radius = r;
    }
    public double getArea(){
    return Math.PI * radius * radius;
}
    public double getPerimeter(){
        return 2 * Math.PI * radius;
}
    public void draw(){
        System.out.println("Draw circle");
    }
}
Class main {
    public static void main (String [] args)
{
```

A Thành Đạt

```
Rectangle r = new Rectangle (4,5);
circle c = new circle (3);
System.out.println("Rectangle Area:" +r.get
Area());
system.out.println("Rectangle Perimeter:" +r
.getPerimeter());
System.out.println("circle Area:" + c.get
Area());
system.out.println("circle perimeter:"
c.getPerimeter();
}
}

interface car {
    void accelerate();
    String getcolor();
    double getspeed();
}
class Bmw implements car {
    String color;
    double speed;
```