

THROTTLE/NOZZLE CONTROL
(CONTINUED)

CHARACTERISTICS			
<u>WEIGHT</u> _____ LB <u>9.00</u> X <u>5.75</u> X _____	<u>DIMENSIONS</u> _____	<u>LOCATION</u> X BL <u>13.905</u> Y FS <u>193.350</u> Z WL <u>93.690</u> <u>DEP TO CENTER</u> TRUE DISTANCE <u>34.771</u> IN. TRUE ANGLE <u>65.80</u> DEG.	
<u>ILLUMINATION</u> 1.0 \pm 0.5 f1		<u>LEGEND SIZE</u> 0.13 \pm 0.01 in	
<u>COLOR</u> IPL WHITE			
<u>OPERATION</u> <u>Left</u> HAND		<u>REACH ZONE</u> <u>2</u>	
INDIVIDUAL CONTROLS	TYPE	FORCE	TRAVEL
THROTTLE	Lever	4-30 lb	36 \pm 7° 21.5 \pm .06° 16 \pm 1°
NOZZLE	Lever	4-30 lb	
RUDDER TRIM	3 Pos Toggle Spring Loaded	8 lb max	
MANUAL FUEL	2 Position Lever Lock Toggle	Rel: 3-6 lb OP: 8 lb max	
JPTL	2 Position Toggle Switch	28 \pm 8 oz	
NOTES			

GP78 8008-77