

Pixel To Geometry (PTG)

Chad B. Hovey¹

Sandia Injury Biomechanics Laboratory
Sandia National Laboratories²

2020-04-13

¹Corresponding author: chovey@sandia.gov

²The Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia, LLC, a wholly owned subsidiary of Honeywell International, Inc., for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

Abstract

Classification of pixel values from human CT/MR scans has been successfully undertaken by this laboratory using the U-Net deep learning algorithm. We have also demonstrated successful conversion of pixels to voxels, as a proxy for finite volume or finite element meshes, a process we have called Pixel To Mesh (PTM). This mesh step quickly becomes intractable when the number of voxels grows past the 10s of millions. Essentially, a map of every pixel (voxel) to a single finite volume or finite element creates computational domains of excessively large and equally unnecessary mesh refinement.

In light of this, we investigated an alternative approach, which we call Pixel To Geometry (PTG). This alternative seeks to selectively use the categorized pixel values as a scaffold for construction of analytical geometric descriptions in 2D and 3D. Thereafter, we propose using the analytical geometries directly in simulation, using isogeometric analysis (IGA). The use of IGA completely eliminates any need to complete the mesh step.

Contents

1	Introduction	3
1.1	Overview	3
1.2	Class Segmentation	4
1.3	Instance Segmentation	7
1.4	Motivation by Analogy	8
2	Non-local Methods	9
2.1	Polynomials	9
2.2	Bézier Curves	11
2.2.1	Bézier Line	11
2.2.2	Bézier Quadratic	11
2.2.3	de Casteljau's Algorithm	13
2.2.4	Bézier Cubic	14
2.2.5	Bernstein Polynomials	15
2.3	Bézier Surfaces	17
3	Local Methods	19
3.1	General Splines	19
3.2	Linear Splines	19
3.3	Quadratic Splines	22
3.4	Cubic Splines	22
3.5	B-Splines	23

Chapter 1

Introduction

In the most general sense, this research strives to create autonomous computational methods to

- **See** axial cross-sections of CT/MR scans (computer vision),
- **Classify** what is seen into basic human anatomy categories (recognition, deep learning), and
- **Build** geometric representations of these anatomies into domains (e.g., voxels, meshes, analytical geometry) suitable for computational analysis (e.g., finite element analysis, finite volume analysis).

In a sense, we wish to combine the skills of a radiologist and an engineer into an automated workflow that can be performed by a computer.

The overarching goal of this effort is to push toward highly personalized medicine, wherein the individual's anatomical geometry, derived from an imaging series, is reconstructed into a high-fidelity, three dimensional (3D) geometric model suitable not only for visualization but also for analysis of a personal response to a mechanically deleterious environment, such as blast, blunt, or ballistic exposure. Common examples of these environments include slip-and-fall accidents and automobile collisions. Less frequent, but particularly relevant to the U.S. warfighter, is exposure to blast overpressure from improvised explosive devices (IEDs) and fragmentation.

In the subsequent sections, we present an overview of the topics covered in this manuscript, followed by details of each.

1.1 Overview

To come.

1.2 Class Segmentation




Figure 1.1: Illustration of an image captured into colored pixel values (top) and then color-coded by category, e.g., sky, building, car, road, person, crosswalk (bottom). Reference: [fig/image.pdf](#), [fig/classification.pdf](#), [Heinrich 2016].




Figure 1.2: Pixel to Mesh (PTM) result of class segmentation, bone versus non-bone, from (a) medical scan; (b) ground truth versus (b) machine prediction. Reference: [fig/ptm_scan.pdf](#), [fig/ptm_ground_truth.pdf](#), [fig/ptm_prediction.pdf](#).




Figure 1.3: Results of the U-NET deep learning algorithm applied [Ronneberger 2015] applied to the IRCAD data set [IRCAD 2019]. Reference: fig/ptm_20_torsos.pdf

1.3 Instance Segmentation



Figure 1.4: A photograph (top) used for (middle) class segmentation, e.g., people versus non-people, and for (bottom) instance segmentation, e.g., a unique person. Reference: [fig/people_photo.pdf](#), [fig/people_class_seg.pdf](#), [fig/people_instance_seg.pdf](#), [Heinrich 2016].

1.4 Motivation by Analogy

The concept of converting pixels to a geometric representation, hereinafter referred to as PTG (Pixel To Geometry), can be introduced by consideration of two similar processes, optical character recognition (OCR) and analytic geometry.

OCR is the process of converting pixel values scanned from a piece of paper with printed or handwritten text into a digital encoding of letters and number, e.g.,

A a B b C c ... Z z 0 1 2 3 4 5 6 7 8 9,

where a collection of pixels is composed to map to letters and numbers.

Figure 1.5 illustrates the difference between vector graphics and rasterized graphics. The word “geometry” appearing with font size 48 point (72 points = 1 inch) composed of vector graphics, and the “e” in yellow, with font size 72 point, appearing from left-to-right at half-inch intervals in rasterized graphics at 10 pixels per inch (ppi), 20 ppi, 40 ppi, and 80 ppi. The image was saved in vectorized format at 600 ppi.




Figure 1.5: Illustration of vector graphics versus rasterized graphics, and the concept of pixel resolution. Reference: [fig/geometry.pdf](#)

Chapter 2

Non-local Methods

In the following sections, we introduce non-local methods to create curves from data points. Thereafter, we introduce local methods. Non-local methods mean that any change in a data point (or a control point) affects the *entire* curve. This is generally undesirable. However, non-local methods are simpler than local methods, so they are introduced first. Table 2.1 presents an overview of the four methods to be covered, categorized by interpolation and locality.

Table 2.1: Categorization of methods by interpolation and locality.

		Locality	
		non-local methods	local methods
Interpolation	data points	polynomial	spline
	control points	Bézier, Bernstein	B-spline, NURB

2.1 Polynomials

We discuss polynomials briefly for three main reasons: (1) To be explicit regarding the terminology of **power** versus **order** and be clear on the conventions and notations used in this document, (2) to illustrate the shortcomings of polynomials and thus motivate alternative approaches, and (3) to lay the framework for more sophisticated interpolations that will rely on polynomials in some form.

First, with regard to *power* versus *order*, [Cottrell 2009] noted the following:

Page 18, Note 3: “There is a terminology conflict between the geometry and analysis communities. Geometers will say a cubic polynomial has degree 3 and order 4. In geometry, order equals degree plus one. Analysts will say a cubic polynomial is order three,

and use the term order and degree synonymously. This is the convention we [Cottrell, Hughes, Bazilevs] adhere to.”

Unlike [Cottrell 2009], we adopt the geometry community convention in this document, thus we distinguish between *order* and *power*. We have elected this approach primarily for consistency of this document with historical writings of the geometry community.

Next, we state as *prima facie* a well-known shortcoming of polynomials is their propensity to overfit the data. This characteristic arises because a polynomial of degree p has $p - 1$ changes of direction, from $-f(x)$ to $f(x)$, or vice versa. No further discussion on overfitting is given here, though explications of this topic are widely available.

Finally, there is some basic notation used with polynomials that we need to make clear and concrete. Let $f(x)$ be the function of degree p (equivalently, order $p + 1$) that is a sum of variable x raised to some increasing non-negative integer power, starting from zero, and multiplied by a constant coefficient a , such that

$$f(x) \triangleq a_0x^0 + a_1x^1 + a_2x^2 + a_3x^3 + \cdots + a_px^p = \sum_{i=0}^p a_ix^i. \quad (2.1)$$

The function $f(x)$ is a **polynomial** of **degree** p , the highest non-zero **power**¹ used in the summation. Table 2.2 lists the first five polynomials by order, degree, name, and function. Hereinafter, p will be considered the index of the power of a polynomial. The p -index, a subset of non-negative integers, will start from zero and consecutively increase by one.

Table 2.2: First five orders of a polynomial function.

order	degree	name	function
$\mathcal{O}(1)$	$p = 0$	constant	$f_0(x) = a_0$
$\mathcal{O}(2)$	$p = 1$	linear	$f_1(x) = a_0 + a_1x$
$\mathcal{O}(3)$	$p = 2$	quadratic	$f_2(x) = a_0 + a_1x + a_2x^2$
$\mathcal{O}(4)$	$p = 3$	cubic	$f_3(x) = a_0 + a_1x + a_2x^2 + a_3x^3$
$\mathcal{O}(5)$	$p = 4$	quartic	$f_4(x) = a_0 + a_1x + a_2x^2 + a_3x^3 + a_4x^4$

One final note regarding conventions of indices. We use the first item of a series $\mathbf{s}$ to be $\mathbf{s}[0]$, the second item to be $\mathbf{s}[1]$, and so forth. We prefer the zero-based indices because it is consistent not only with our work in Python, which is zero-based, but also with concepts from initial boundary value problems (IBVPs), which denote initial conditions, the first values, as occurring at t_0 .

¹We suggest the mnemonic of “ p ” as the index used for the “power” in a “polynomial.”

2.2 Bézier Curves

Several of the ideas in this section are due to the excellent references of [Bartels 1995], [Rogers 2000], and [Shiach 2015]. A Bézier curve is a parametric curve defined by control points. A control point $\mathbf{P}_i$ will have two coordinates (x_i, y_i) in 2D and three coordinates (x_i, y_i, z_i) in 3D. The parameter is typically denoted t . The bounds for t are always $0 \leq t \leq 1$.

A Bézier curve of order p requires $p + 1$ control points. For example, a Bézier curve that is a line (order $p = 1$) requires two control points. Affine transformations may be used to modify the control points, e.g., to scale, reflect, rotate, or translate (offset) the control points.

2.2.1 Bézier Line

Let $\mathbf{P}(t; \mathbf{x})$ be **parametric** equation for a line between two points $\mathbf{P}_0 = (x_0, y_0, z_0)$ and $\mathbf{P}_1 = (x_1, y_1, z_1)$, with $\mathbf{x} = (x, y, z)$. Then, let t be the parameter bounded by $0 \leq t \leq 1$. Then the Bézier line between $\mathbf{x}_0$ and $\mathbf{x}_1$ is simply the parameterized linear interpolation $\mathbf{P}_0$ and $\mathbf{P}_1$,

$$\mathbf{P}(t; \mathbf{P}_0, \mathbf{P}_1) \triangleq (1 - t)\mathbf{P}_0 + t\mathbf{P}_1, \quad (2.2)$$

or in explicit coordinate form,

$$\begin{Bmatrix} x(t) \\ y(t) \\ z(t) \end{Bmatrix} = (1 - t) \begin{Bmatrix} x_0 \\ y_0 \\ z_0 \end{Bmatrix} + t \begin{Bmatrix} x_1 \\ y_1 \\ z_1 \end{Bmatrix}. \quad (2.3)$$

2.2.2 Bézier Quadratic

Let $\mathbf{Q}(t; \mathbf{x})$ be the parametric equation for a quadratic between two points $\mathbf{Q}_0$ and $\mathbf{Q}_1$. Let the position of these two points themselves be parameterized by three points $\mathbf{P}_0$, $\mathbf{P}_1$, and $\mathbf{P}_2$, such that

$$\mathbf{Q}_0(t; \mathbf{P}_0, \mathbf{P}_1) = (1 - t)\mathbf{P}_0 + t\mathbf{P}_1, \quad (2.4)$$

$$\mathbf{Q}_1(t; \mathbf{P}_1, \mathbf{P}_2) = (1 - t)\mathbf{P}_1 + t\mathbf{P}_2. \quad (2.5)$$

Thus, the position of $\mathbf{Q}_0$ is on the line between points $\mathbf{P}_0$ and $\mathbf{P}_1$. The position of $\mathbf{Q}_1$ is on the line between points $\mathbf{P}_1$ and $\mathbf{P}_2$. At $t = 0$, $\mathbf{Q}_0$ resides at $\mathbf{P}_0$, $\mathbf{Q}_1$ resides at $\mathbf{P}_1$. At $t = 1$, $\mathbf{Q}_0$ resides at $\mathbf{P}_1$, $\mathbf{Q}_1$ resides at $\mathbf{P}_2$. Finally, let position along the quadratic Bézier curve $\mathbf{Q}(t; \mathbf{x})$ be defined as

$$\mathbf{Q}(t; \mathbf{Q}_0, \mathbf{Q}_1) \triangleq (1 - t)\mathbf{Q}_0 + t\mathbf{Q}_1. \quad (2.6)$$

This curve can be recast in terms of $\mathbf{P}$ points using (2.4) and (2.5), producing

$$\mathbf{Q}(t; \mathbf{P}_0, \mathbf{P}_1, \mathbf{P}_2) = (1 - t)^2\mathbf{P}_0 + 2t(1 - t)\mathbf{P}_1 + t^2\mathbf{P}_2. \quad (2.7)$$

Figure 2.1 illustrates an example quadratic Bézier curve, with control points indicated. The number of control points is three, so the maximum order Bézier that can be constructed is two (order p requires $p + 1$ control points).




Figure 2.1: A Bézier quadratic curve illustrated at $t = 0.5$ with (a) original notation and (b) the de Casteljau's algorithm notation. Reference: `fig/de_casteljau.py`.

Example 1.

Figure 2.2 illustrates the same quadratic Bézier curve, generated at six discrete points in the interval $t \in [0, 1]$. $\square$




Figure 2.2: The Bézier quadratic curve discussed in Figure 2.1, illustrated in sequence with t starting at 0 and ending at 1. Reference: `fig/de_casteljau.py`.

2.2.3 de Casteljau's Algorithm

The foregoing development can be generalized, and is known as **de Casteljau's algorithm**. Let $P_{i,j}$ be control points where

- i denotes the **control point index**, $i = 0, 1, \dots, n$, (total of $n + 1$ control points), and
- j denote the **order** of the curve, $j = 0, 1, \dots, p$.

Thus $P_{i,0}$ denote the base level control points. In the preceding section,

$$P_0 \mapsto P_{0,0}, \quad j = 0, \text{ thus } P_{i,0} \text{ is a point,} \quad (2.8)$$

$$P_1 \mapsto P_{1,0}, \quad (2.9)$$

$$P_2 \mapsto P_{2,0}, \quad (2.10)$$

$$Q_0 \mapsto P_{0,1}, \quad j = 1, \text{ thus } P_{i,1} \text{ is a line,} \quad (2.11)$$

$$Q_1 \mapsto P_{1,1}, \quad \text{and} \quad (2.12)$$

$$Q(t) \mapsto P_{0,2}, \quad j = 2, \text{ thus } P_{0,2} \text{ is a quadratic.} \quad (2.13)$$

Then, **de Casteljau's algorithm** states

$$\mathbf{P}_{i,j} = (1-t)\mathbf{P}_{i,j-1} + t\mathbf{P}_{i+1,j-1}. \quad (2.14)$$

Equation (2.7) would then be rewritten as

$$\mathbf{P}_{0,2}(t) = (1-t)\mathbf{P}_{0,1} + t\mathbf{P}_{1,1}, \quad (2.15)$$

$$= (1-t)[(1-t)\mathbf{P}_{0,0} + t\mathbf{P}_{1,0}] + t[(1-t)\mathbf{P}_{1,0} + t\mathbf{P}_{2,0}], \quad (2.16)$$

$$= (1-t)^2\mathbf{P}_{0,0} + 2t(1-t)\mathbf{P}_{1,0} + t^2\mathbf{P}_{2,0}, \quad (2.17)$$

where only the t parameter is used to describe $\mathbf{P}_{0,2}(\cdot)$ for the sake of brevity. Figure 2.1 illustrates for the Bézier quadratic development, (a) the original notation and (b) the de Casteljau's algorithm notation.

For efficiency during computational implementation, it is common to rewrite the quadratic Bézier $\mathbf{P}_{0,2}$ in matrix form for *any* set of **three control points**. This is somewhat of a return map, undoing the notation adopted to explain de Casteljau's algorithm. With

$$\mathbf{P}_{0,0} \mapsto \mathbf{P}_0, \quad (2.18)$$

$$\mathbf{P}_{1,0} \mapsto \mathbf{P}_1, \quad (2.19)$$

$$\mathbf{P}_{2,0} \mapsto \mathbf{P}_2, \text{ and} \quad (2.20)$$

$$\mathbf{P}_{0,2} \mapsto \mathbf{C}_2, \text{ to denote a curve } C \text{ of order } p = 2, \quad (2.21)$$

the quadratic Bézier $\mathbf{C}_2$ is written in matrix form as

$$\mathbf{C}_2(t) = \begin{Bmatrix} x(t) \\ y(t) \\ z(t) \end{Bmatrix} = \begin{bmatrix} x_{P_0} & x_{P_1} & x_{P_2} \\ y_{P_0} & y_{P_1} & y_{P_2} \\ z_{P_0} & z_{P_1} & z_{P_2} \end{bmatrix} \begin{bmatrix} 1 & -2 & 1 \\ & 2 & 0 \\ \text{sym.} & & 0 \end{bmatrix} \begin{Bmatrix} t^2 \\ t \\ 1 \end{Bmatrix}. \quad (2.22)$$

2.2.4 Bézier Cubic

The cubic Bézier curve $\mathbf{P}_{0,3}(t)$, given four control points $\mathbf{P}_{0,0}$, $\mathbf{P}_{1,0}$, $\mathbf{P}_{2,0}$, and $\mathbf{P}_{3,0}$, is given by

$$\mathbf{P}_{0,3}(t) = (1-t)^3\mathbf{P}_{0,0} + 3t(1-t)^2\mathbf{P}_{1,0} + 3t^2(1-t)\mathbf{P}_{2,0} + t^3\mathbf{P}_{3,0}. \quad (2.23)$$

Again for efficiency, it is common to rewrite the cubic Bézier $\mathbf{P}_{0,3}$ in matrix form for *any* set of **four control points**. With

$$\mathbf{P}_{0,0} \mapsto \mathbf{P}_0, \quad (2.24)$$

$$\mathbf{P}_{1,0} \mapsto \mathbf{P}_1, \quad (2.25)$$

$$\mathbf{P}_{2,0} \mapsto \mathbf{P}_2, \quad (2.26)$$

$$\mathbf{P}_{3,0} \mapsto \mathbf{P}_3, \text{ and} \quad (2.27)$$

$$\mathbf{P}_{0,3} \mapsto \mathbf{C}_3, \text{ to denote a curve } C \text{ of order } p = 3, \quad (2.28)$$

the cubic Bézier $\mathbf{C}_3$ is written in matrix form as

$$\mathbf{C}_3(t) = \begin{Bmatrix} x(t) \\ y(t) \\ z(t) \end{Bmatrix} = \begin{bmatrix} x_{P_0} & x_{P_1} & x_{P_2} & x_{P_3} \\ y_{P_0} & y_{P_1} & y_{P_2} & y_{P_3} \\ z_{P_0} & z_{P_1} & z_{P_2} & z_{P_3} \end{bmatrix} \begin{bmatrix} -1 & 3 & -3 & 1 \\ & -6 & 3 & 0 \\ & & 0 & 0 \\ \text{sym.} & & & 0 \end{bmatrix} \begin{Bmatrix} t^3 \\ t^2 \\ t \\ 1 \end{Bmatrix}. \quad (2.29)$$

2.2.5 Bernstein Polynomials

The general form of a degree p Bézier curve $\mathbf{C}_p(t)$ defined by $p+1$ control points $\mathbf{P}_i$, $i = 0, 1, \dots, p$, is given by

$$\mathbf{C}_p(t) = \sum_{i=0}^p b_{i,p}(t) \mathbf{P}_i, \quad (2.30)$$

where $b_{i,p}(t)$ is a **Bernstein polynomial**, defined as

$$b_{i,p}(t) = \binom{p}{i} t^i (1-t)^{p-i}. \quad (2.31)$$

Here,

$$\binom{p}{i} = \frac{p!}{i! (p-i)!} \quad (2.32)$$

is the **binomial coefficient**. The binomial coefficients are readily attained from **Pascal's triangle**, written up to $p = 4$ in Table 2.3.

Table 2.3: First five orders of binomial coefficients from Pascal's triangle.

degree	binomial coefficient				
$p = 0$	1				
$p = 1$	1		1		
$p = 2$	1		2	1	
$p = 3$	1	3	3	1	
$p = 4$	1	4	6	4	1

Example 2.

The Bernstein polynomials for a cubic ($p = 3$) Bézier curve are

$$b_{0,3}(t) = \binom{3}{0} t^0 (1-t)^{3-0} = (1-t)^3, \quad (2.33)$$

$$b_{1,3}(t) = \binom{3}{1} t^1 (1-t)^{3-1} = 3t(1-t)^2, \quad (2.34)$$

$$b_{2,3}(t) = \binom{3}{2} t^2 (1-t)^{3-2} = 3t^2(1-t), \quad (2.35)$$

$$b_{3,3}(t) = \binom{3}{3} t^3 (1-t)^{3-3} = t^3, \quad (2.36)$$

which match the coefficients in (2.23). These polynomials are shown in Figure 2.3(c). $\square$

Example 3.

The Bernstein polynomials for a quartic ($p = 4$) Bézier curve are

$$b_{0,4}(t) = \binom{4}{0} t^0 (1-t)^{4-0} = (1-t)^4, \quad (2.37)$$

$$b_{1,4}(t) = \binom{4}{1} t^1 (1-t)^{4-1} = 4t(1-t)^3, \quad (2.38)$$

$$b_{2,4}(t) = \binom{4}{2} t^2 (1-t)^{4-2} = 6t^2(1-t)^2, \quad (2.39)$$

$$b_{3,4}(t) = \binom{4}{3} t^3 (1-t)^{4-3} = 4t^3(1-t), \quad (2.40)$$

$$b_{4,4}(t) = \binom{4}{4} t^4 (1-t)^{4-4} = t^4. \quad (2.41)$$

These polynomials are shown in Figure 2.3(d). $\square$

Notice that for any of the Bernstein polynomials, their sum always adds to one,

$$\sum_{i=0}^p b_{i,p}(t) = 1.0. \quad (2.42)$$

This concept is called **partition of unity**.

2.3 Bézier Surfaces

The Bézier curve was parameterized by t . For the Bézier surface, we have two parameters, u and v .




Figure 2.3: Bernstein polynomials for Bézier (a) linear, (b) quadratic, (c) cubic, and (d) quartic curves. Reference: `fig/bernstein.py`.

Chapter 3

Local Methods

Local methods mean that any change in a control point does not necessarily affects the *entire* parameterization. This is generally very desirable, as changes can be focused on a specific region, without disrupting the balance of the parameterization. However, local methods are more complicated than non-local methods, and require definition over intervals, as well be seen below.

3.1 General Splines

Let a collection of $n+1$ points (x_i, y_i) for $i = 0, 1, \dots, n$ approximate the function $y = f(x)$ over the domain $[x_0, x_n]$. In total, there are $n+1$ points and n intervals. Let $S(x)$ be the piecewise continuous spine that threads through each of the points (x_i, y_i) . For $x \in [x_i, x_{i+1}]$ and $i = 0, 1, \dots, n-1$, the spline takes on n interval definitions as follows:

$$S_i(x) \triangleq a_i + b_i(x - x_i) + c_i(x - x_i)^2 + d_i(x - x_i)^3 + \dots + z_i(x - x_i)^p. \quad (3.1)$$

where constant coefficients¹ multiply successive powers² of $(x - x_i)$, summed to an arbitrary polynomial power p . This is referred to as the **interval spline definition** to polynomial order p . Below we consider linear splines ($p = 1$), quadratic splines ($p = 2$), and cubic splines ($p = 3$).

3.2 Linear Splines

For linear splines, the interval spline definition is

$$S_i(x) \triangleq a_i + b_i(x - x_i) \quad \text{for } x \in [x_i, x_{i+1}] \text{ and } i = 0, 1, \dots, n-1. \quad (3.2)$$

For any collection of points (x_i, y_i) , all coefficients a_i and b_i for $i = 0, 1, \dots, n-1$ can be found using the **zeroth derivative continuity constraint**, which creates a spline that connects to each

¹Here the z_i is arbitrary, meant to denote the last coefficient, but not necessarily the twenty-sixth coefficient.

²The powers are non-negative integers.

point at the beginning and end of each interval, thus

$$S_i(x_i) = y_i \quad \text{and} \quad S_i(x_{i+1}) = y_{i+1} \quad \text{for } i = 0, 1, \dots, n-1. \quad (3.3)$$

Here we see there are two constraints per interval i and two unknowns, a_i and b_i , per interval i . The unknowns can be found directly by evaluating the interval spline definition with each of the two constraint equations. In turn, these are, for $i = 0, 1, \dots, n-1$,

$$S_i(x_i) = a_i + b_i(x_i - x_i) \stackrel{\text{set}}{=} y_i \implies a_i = y_i, \text{ and} \quad (3.4)$$

$$S_i(x_{i+1}) = a_i + b_i(x_{i+1} - x_i) \stackrel{\text{set}}{=} y_{i+1} \implies b_i = \frac{y_{i+1} - y_i}{x_{i+1} - x_i}. \quad (3.5)$$

No additional continuity constraints can be created since the linear spline has only C^0 continuity, meaning no derivatives of the function $S_i(x)$ are continuous.

Example 4.

Let $y = f(x) = \sin(\pi x)$ for $x \in [0, 1]$ be approximated by a linear spline and a collection of three points equally spaced on the domain. Note $n + 1 = 3$, thus $n = 2$, indicating three points and two intervals. Table 3.1 summarizes the spline data. Figure 3.1(a) shows the $\sin$ function and the linear spline interpolations. $\square$

Table 3.1: Linear spline approximation of $y = f(x) = \sin(\pi x)$ using three points and two intervals.

i	x_i	y_i	$\Rightarrow$	a_i	b_i	$\Rightarrow$	$S_i(x)$
0	0/2	0		0	2		$2x$
1	1/2	1		1	-2		$1 - 2(x - 1/2)$
2	2/2	0		—	—		—

Example 5.

Repeat the previous example, but now with a collection of five points equally spaced on the domain. Thus $n + 1 = 5$, thus $n = 4$, indicating five points and four intervals. Table 3.2 summarizes the spline data. Figure 3.1(b) shows the sin function and the linear spline interpolations. $\square$

Table 3.2: Linear spline approximation of $y = f(x) = \sin(\pi x)$ using five points and four intervals.

i	x_i	y_i	$\Rightarrow$	a_i	b_i	$\Rightarrow$	$S_i(x)$
0	0/4	0		0	$2\sqrt{2}$		$2\sqrt{2}x$
1	1/4	$\sqrt{2}/2$		$\sqrt{2}/2$	$4 - 2\sqrt{2}$		$\sqrt{2}/2 + (4 - 2\sqrt{2})(x - 1/4)$
2	2/4	1		1	$2\sqrt{2} - 4$		$1 + (2\sqrt{2} - 4)(x - 2/4)$
3	3/4	$\sqrt{2}/2$		$\sqrt{2}/2$	$-2\sqrt{2}$		$\sqrt{2}/2 - 2\sqrt{2}(x - 3/4)$
4	4/4	0		—	—		—

3.3 Quadratic Splines

For quadratic splines, the interval spline definition is

$$S_i(x) \triangleq a_i + b_i(x - x_i) + c_i(x - x_i)^2 \quad \text{for } x \in [x_i, x_{i+1}] \text{ and } i = 0, 1, \dots, n-1. \quad (3.6)$$

3.4 Cubic Splines

Cubic splines are useful because of their inherent smoothness. The cubic spline, its first derivative, and its second derivative are all continuous. Starting with the cubic spline's third derivative, discontinuity arises.

Let a collection of $n + 1$ points (x_i, y_i) for $i = 0, 1, \dots, n$ approximate the function $y = f(x)$ over the domain $[x_0, x_n]$. In total, there are $n + 1$ points and n intervals. Let $S(x)$ be the piecewise continuous spline, cubic in this case, that threads through each of the points (x_i, y_i) . The spline takes on n interval definitions as follows:

$$S_i(x) \triangleq a_i + b_i(x - x_i) + c_i(x - x_i)^2 + d_i(x - x_i)^3 \quad \text{for } x \in [x_i, x_{i+1}] \text{ and } i = 0, 1, \dots, n-1. \quad (3.7)$$

The n foregoing definitions, with the coefficients a_i, b_i, c_i, d_i , give rise to $4n$ (currently unknown) parameters used to define the complete spline $S(x)$. Note that maintain its cubic nature, the spline must have $d_i \neq 0$.

Next we endow the spline with constraints on continuity and differentiability, which allow the $4n$ unknown parameters to be solved. First, function continuity requires that the spline, on a

particular interval, thread through collection of points (x_i, y_i) and the beginning and end of each interval. Thus,

$$S_i(x_i) = y_i \text{ and } S_i(x_{i+1}) = y_{i+1} \quad \text{for } i = 0, 1, \dots, n-1. \quad (3.8)$$

This is the **continuity constraint**, which gives rise to $2n$ conditions³ and creates a spline that is piecewise continuous. Next, consider two **differentiability constraints**, which state that the first and second derivatives at a point x_i are continuous. That is, the first and second derivatives approaching a point x_i from the interval to the left side of the point must match the respective first and second derivatives approaching the point x_i from the interval to the right side of the point:

$$S'_{i-1}(x_i) = S'_i(x_i) \text{ and } S''_{i-1}(x_i) = S''_i(x_i) \quad \text{for } i = 1, 2, \dots, n-1. \quad (3.9)$$

Because they apply only to the interior points (and not the endpoints x_0 and x_n), the differentiability constraints give rise to $2(n-1)$ constraints.⁴

Finally, two more conditions are necessary to completely define the spline $S(x)$. The two conditions are obtained by specifying differentiability conditions on the two spline endpoints x_0 and x_n . Frequently, the first derivative is set to the known value of the function's derivatives at the endpoints,

$$S'_0(x_0) = f'(x_0) \text{ and } S'_{n-1}(x_n) = f'(x_n). \quad (3.10)$$

This is defined as a **clamped spline**. Alternatively, a **natural spline** defines the second derivatives to be zero at the endpoints,

$$S''_0(x_0) = 0 \text{ and } S''_{n-1}(x_n) = 0. \quad (3.11)$$

Finally, a **not-a-knot** spline requires no additional constraints on the endpoint derivatives,⁵ but requires that the *third* derivative be continuous at x_1 and x_{n-1} .

3.5 B-Splines

To come.

³Two conditions per interval times n intervals yields $2n$ conditions.

⁴Two conditions per interior point times $n-1$ interior points yields $2(n-1)$ conditions.

⁵This has no effect on the original continuity constraint on the endpoints, that $S_0(x_0) = y_0$ and $S_{n-1}(x_n) = y_n$.




Figure 3.1: Linear spline example (a) with three points and (b) with five points, see Table 3.2 for individual definitions of $S_i(x)$. Reference: fig/linear_spline.py.

Bibliography

- [Bartels 1995] Bartels RH, Beatty JC, Barsky BA. An introduction to splines for use in computer graphics and geometric modeling. Morgan Kaufmann; 1995 Sep 15.
- [Cottrell 2009] Cottrell JA, Hughes TJ, Bazilevs Y. Isogeometric analysis: toward integration of CAD and FEA. John Wiley & Sons; 2009 Aug 11.
- [Heinrich 2016] Heinrich G. Image segmentation using DIGITS 5, NVIDIA Developer Blog. <https://devblogs.nvidia.com/image-segmentation-using-digits-5>; 2016 Nov 10.
- [IRCAD 2019] IRCAD France. 3D-IRCADB 01 database, 3D CT-scans of 10 women and 10 men. <https://www.ircad.fr/research/3d-ircadb-01/>; accessed 2019 Aug 29.
- [Rogers 2000] Rogers DF. An introduction to NURBS: with historical perspective. Elsevier; 2000 Aug 22.
- [Ronneberger 2015] Ronneberger O, Fischer P, Brox T. U-net: Convolutional networks for biomedical image segmentation. In International Conference on Medical image computing and computer-assisted intervention 2015 Oct 5 (pp. 234-241). Springer, Cham.
- [Shiach 2015] Shiach J. Bézier Curves. Mathematics of Computer Graphics and Virtual Environments. <https://youtu.be/2HvH9cmHbG4>; 2015 Mar 09.
- [Shiach 2015b] Shiach J. B-Splines. Mathematics of Computer Graphics and Virtual Environments. <https://youtu.be/qhQrRCJ-mVg>; 2015 Mar 13.