Claude

Screen_93_1024x600_RS070WS014-A0.zip
ZIP

57_720x1280_WD090HBM30TC-U3-v1.73.8_086a15...
ZIP

panel_info_mrf_agent.rtf
1 line
RTF

run panel_info_mrf_agent

Now I have a clear picture. Let me build the `genlogogz` program:

All done. Here's a summary of what was built and verified:

`genlogogz.py` — usage:

```
python3 genlogogz.py <A.zip> <B.tar.zip or B.tar.gz>
```

What it does (per spec):

1. Reads `panel_info.txt` from `A.zip`
2. Builds `newlogo.mrf`: zeros → `panel_info.txt` data at offset `0x00000E00` → zero-padded to **8,412,672 bytes**
3. Handles B as either `.zip` (wrapping a `.tar.gz`) or a plain `.tar.gz`
4. Repacks the tar.gz replacing `logo.mrf` with `newlogo.mrf`, renamed to the A stem
5. Calculates MD5 → takes characters 8–15 (2nd group of 8) as `$Sig`
6. Outputs `<A_stem>_<Sig>_ota.tar.gz`

Test result:

- Output: `Screen_93_1024x600_RS070WS014-A0_76f3039e_ota.tar.gz`
- Verified: `panel_info.txt` correctly embedded at `0x0E00`, leading/trailing zeros correct, size exactly 8,412,672 bytes ✓

Screen 93 1024x600 rs070ws014 a0 76f3039e ota.tar
GZ
Download

Genlogogz
PY
Download

Download all

screen_param_mrf_spec.rtf
1 line
RTF

use screen_param_mrf_spec

The new spec generalizes the previous one — instead of hardcoding `panel_info.txt`, the source file inside A.zip can be **any file**. Let me update `genlogogz.py` accordingly.

Good. Now run it with the same test files to confirm nothing broke:

Updated and verified. The one change from the previous spec:

What changed: `read_panel_info()` (hardcoded to `panel_info.txt`) was replaced with `read_src()`, which accepts **any file** found inside A.zip. The filename is no longer assumed — it reads whatever single file is present. A warning is printed if more than one file is found (first is used).

Everything else is identical. Test output `Screen_93_1024x600_RS070WS014-A0_414370f4_ota.tar.gz` passes all checks ✓

Screen 93 1024x600 rs070ws014 a0 414370f4 ota.tar
GZ
Download

Genlogogz
PY
Download

Download all

screen_param_mrf_spec.rtf
1 line
RTF

update screen_param_mrf_spec

The new addition: if `src` **is** `logo.mrf`, skip building and use it directly as `newlogo.mrf`.

Now update the log message in `main()` to reflect the branching logic:

Now run both test cases — the existing one (src ≠ logo.mrf), then a synthetic one where src = logo.mrf:

Both tests pass. Copying outputs:

Updated. The one change from the previous spec:

What changed: `build_newlogo_mrf()` now checks the filename:

- `src == logo.mrf` → `newlogo.mrf = src` (passthrough, no offset embedding, no padding)
- `src != logo.mrf` → embed at `0x00000E00`, zero-pad to 8,412,672 bytes (original behaviour)

Both test cases verified ✓

- Test 1 (`panel_info.txt`): embedded at offset, padded correctly
- Test 2 (`logo.mrf`): output `logo.mrf` MD5 identical to original

Genlogogz
PY
Download

Screen 93 1024x600 rs070ws014 a0 af25e72a ota.tar
GZ
Download

Download all