B06 | October 13 execution handoff

TUESDAY 2026-10-13 | 9:00 AM-NOON PDT | 16:00-19:00 UTC

Engineering only. Exact Howard go already supplied. Two separately invoked Oracle-only J1 attempts; no retry, third attempt, guard increase or observer repair. No qualification or measurement credit.

READINESS FROM OCTOBER 12

111,311 asset hashes, request/index/template seals and 14 class bindings passed (103 seconds). Three pinned image digests present in the one authorized Docker listing. C: free **616.65 GiB** (minimum 60). Host RAM **63.39 total / 17.28 free GiB**; VM/container memory readiness is not established.

Resolve before launch: preparation checkout is 4659d591, not required 62eafdaf; no registered exact execution checkout found. Supply an existing clean exact checkout and dedicated engineering authority directory. No listener found on 8768: its running checkout/commit is unavailable. Do not reset preparation files or restart the Tower.

9:00 AM | PREFLIGHT, THEN ONE INVOCATION

Use the accompanying **docs/factory/b06-oct13-attempt.ps1**. It binds the full request, asset root and output root; performs read-only hash/seal/exact-commit checks, shows disk/RAM, and calls the guarded entry point exactly once. Operator supplies the two existing paths:

```
.\docs\factory\b06-oct13-attempt.ps1 `
  -ExecutionCheckout '<clean checkout at 62eafdaf>' `
  -EngineeringAuthority '<existing b06-engineering-authority directory>'
```

The script is a deferred command, not an action performed today. The entry point freshly checks approval/window, free disk, image pins, overlap, source and prior signed evidence before native startup. Missing prerequisites refuse; do not improvise replacements.

Attempt	Mode	Latest start
1	Strict	9:40 AM PDT
2	Diagnostic unmatched return, cap 10	10:50 AM PDT

Per attempt: 3,600s work + 600s cleanup; candidate timeout 1,800s. Hashing and human review consume margin. Latest starts are ceilings; noon is absolute.

BETWEEN ATTEMPTS | SHOW HOWARD AND WAIT FOR REVIEW

Show signed terminal, owner, consumed number/mode, request/plan/source/artifact hashes; first unmatched sequence and lifecycle/class-prepare/application-phase evidence; input-witness counts, heap/guard/dump/output sizes; signed cleanup and actual owned-resource absence. Show remaining time. Stop on uncertain cleanup, identity, evidence or budget. Only after Howard reviews, invoke the same command separately once: the authenticated ledger selects attempt 2. Every failed attempt stays consumed.

PART 6 | REPORT AFTER AUTHENTICATED CLEANUP

Fill **b06-oct13-part6-template.json**: both outcomes/consumption; generation entries, unmatched sequence/count; ordinary/metadata counts and bytes; output/peak heap; guard/dump hashes; lifecycle/phase/input-witness evidence; signed terminal/archive hashes; cleanup. Cite either (a) a precise lifecycle/class-prepare explanation at first unmatched return or (b) the same operation near generation 12,400 in both attempts. Otherwise: **cause not identified; stop repair; Howard selects an alternative.**

EXACT BINDINGS

```
commit  62eafdaf29dce1d40603d38c3a394f150b98f686
request 107c20733d9bc7862461b6e13ba4c180cdf1dad160f51be410c5523587900f35
```