

Nonlinear Analysis of VR Synchronization

Howon Lee

April 30, 2015

1 Abstract

There exists a literature dealing with time series analysis in the nonlinear sciences in the case of synchronization, or the adjustment of rhythms of oscillating objects to coincide with each other due to weak interaction. We attempt many of these methods in analyzing an instance of the phenomenon of interpersonal synchrony in a virtual environment.

2 Introduction

Before defining what we mean by synchronization in this context, we note that there exists a long history of the study of synchronization outside of social science. Synchronization was first reported in physical systems by Huygens in 1665. He saw that two pendulum clocks in the boat that he was testing the clocks in were mysteriously ticking in unison, and found that the cause was a support beam which connected the clocks, which moved imperceptibly and therefore maintained the synchronization.

Centuries later, the physical and biological systems which were later found to synchronize include mechanical rotators, lasers, fireflies emitting synchronous patterns of light, synchronous contraction of heart cells, synchronization of human circadian rhythm to a solar light cycle, and synchronous interaction of human beings.

Now, we should define the terms. Interpersonal synchrony is defined in the social science literature as individuals' temporal coordination during social interaction. In the physical sciences, synchronization is defined as an adjustment of rhythms of oscillating objects due to weak interaction, with generalizations possible for chaotic systems, which depend upon a phase of the chaotic system existing.

Although social synchrony is one of many other synchronies, many of which do not necessarily serve a function of any kind, it is observed that social synchrony serves a function in human social groups. There exists evidence that synchronization acts as a cooperation-inducing mechanism, that it acts to induce rapport, and that it in actuality, independent of its effect on rapport, enhances the ability to pursue joint goals in tandem for those who are synchronized. This suggests immediately that it must be measured in a systematic way, to study phenomena of that kind.

In the beginning of the social synchronization literature, most psychologists did not use the then-developing automated signals processing techniques for the detection and measurement of synchronization, instead using manual methods to detect and rate the presence or absence of synchronization, with trained raters and validated measuring systems. Although these measurements have been validated, they depend upon human raters and therefore are less replicable and less convenient than automated systems.

Given that the signals created by an individual during social interaction have a phase, and social interaction can be construed as a weak interaction between the two individual systems, it should be clear that the definition of interpersonal synchrony given in the social psychological literature is a subset of the definition given in the physics literature. This has often been noted, and has therefore spawned a cross-disciplinary field wherein signals processing techniques are used to measure interpersonal synchrony.

As a specific instance of a domain where signals processing techniques are used, a large problem in synchronization is the definition of the signal itself and its extraction from observations of social interaction. To this end, many methods have been used, including extraction

of coordination of movement features and speech features, movement of single and dyadic body parts, image processing techniques and video tracking techniques.

An important analogy exists between the collection of time series data about the physiology of the body in order to assess synchrony and the collection of time series data about the body in order to assess health. Indeed, there exists a literature on the synchronization properties and the time series analysis of heart rate variability which we have derived much inspiration from.

This project will attempt to use some of the already existing tools for the analysis of time series data on VR time series data, as well as apply some tools which have not previously been used to analyze synchronization in VR time series data of social synchronization in a virtual world.

3 Time Domain Analysis

3.1 Correlation Analysis

Correlation and the cornettos go here. Talk about benefits and detriments of the cornetto stuff

3.2 Mutual Information Analysis

The main limitation of cross-correlational analysis of time series is that it is fundamentally linear. That is, the dependences which the correlation function can capture are linear in nature. It is possible to learn about higher order dependences if correlations of higher moments are used, but this becomes rapidly time-consuming very quickly.

In order to introduce mutual information, we must introduce Shannon information and Shannon entropy.

Shannon information is defined on a measurement drawn from some set (let the set be discrete, $X \in 1...n$, for ease of notation: there exist continuous analogues). Given that

measurement from some set, the Shannon information in bits is defined as:

$$-\log_2 P_X(i)$$

where $P_X(i)$ is the probability that a measurement will find the system in state i . That is, a lower probability answer is more surprising, and therefore more information is found in it.

Shannon entropy, denoted $H(X)$ is defined on a data stream (a measurement stream) X . It is the average amount of information contained in every message received, and so is also measured in bits. An easy intuition about entropy can be gained by noting that a *fair* coin flipping process is the most entropic possible coin flip, because we are most surprised by it. Formally, entropy is:

$$H(X) = - \sum_i P_X(i) \log_2 P_X(i)$$

Information and entropy are also defined on joint probability distributions in an analogous way. The information of a joint probability distribution on variables X and Y is:

$$-\log_2 P_{XY}(i, j)$$

And the entropy, therefore, is:

$$H(X, Y) = - \sum_i \sum_j P_{XY}(i, j) \log_2 P_{XY}(i, j)$$

Now, if we sample two random variables simultaneously, the relationship has a quantity defined upon it which is called the *mutual information*. Because it is defined on the relation, it has an auto-mutual information variant and a cross-mutual information variant, like correlation does. However, mutual information measures something different, which is the *information which one of the random variables gives me about the other random variable*. It

is defined as:

$$I(X, Y) = H(X) + H(Y) - H(X, Y)$$

And one sees that this quantity is symmetric with respect to X and Y .

Mutual information analysis goes here. So does a KS entropy analysis

4 Frequency Domain Analysis

There is more than one way to represent time series data, even given only the data itself and not any underlying function that generates it. The most important alternate representation is the frequency domain representation, which is taken in finite data with the Fourier transform.

The frequency domain represents data in terms of the linear combination of simple sine and cosine waves: the analogy often used is that of a chord being hit on a piano, which can be represented with its time domain signal but can also be represented as the amplitude of the individual notes within the chord, which presents a better decomposition of the sound in and of itself. Likewise, we can attempt to decompose our time domain signals into the frequencies of the sinusoids which make it up.

4.1 Gibbs Phenomenon

An important precondition of much of the Fourier analysis viewpoint,

4.2 Analytic Functions

Why do we need the Hilbert transform? When can we use it? Give the data that shows that we can use it. Give the data that makes us suspect that we can't use it.

4.2.1 γ

What's gamma? Why gamma?

Why use this one over poincare map? Why would it be more durable?

5 Deterministic dual between discrete time series and ordered multigraph

There exists a line of analysis in the complex network literature which aims to convert time series into a network. This is advantageous for analysis of time series because there is a deep and well-developed theory of networks: so far, an important result is that different time series result in networks with distinct topological properties, and that these topological properties relate to the time series in some way in addition to being determined by them.

Upon hearing of the mapping from a time series into a network, it might be wondered at if there exists a mapping from a network back into a time series. There does exist some methods to apply the inverse mapping, but none of these are deterministic, meaning that the network topology constrains the set of time series that the mapping can produce from that network, but does not completely determine it. Therefore, it cannot be said that the mapping from time series to networks or back is properly a *transform*.

A deterministic transformation from time series to networks and from networks to time series can be made, however, if only a special kind of networks called *labelled multigraph* is talked about.

In order to construct the labelled multigraph from a time series,

In order to reconstruct the time series from a labelled multigraph,