

โจทย์ข้อสอบเพิ่มเติมอีก 70 ข้อ พร้อมคำตอบ สำหรับคอร์ส "MongoDB for Beginners":



Multiple Choice Questions

31. Which of the following is NOT a MongoDB shell command?

- ☐ A. show dbs
- ☐ B. use database
- ☐ C. drop database
- ☐ D. create table



32. Which command is used to list all collections in a database?

- ☐ A. show tables
- ☐ B. show collections
- ☐ C. list collections
- ☐ D. db.showCollections()



33. In MongoDB, which operator is used to match values that are greater than a specified value?

- ☐ A. \$lt
- ☐ B. \$gte
- ☐ C. \$gt
- ☐ D. \$lte



34. Which of the following methods is used to remove a collection in MongoDB?

- ☐ A. db.collection.drop()
- ☐ B. db.collection.remove()
- ☐ C. db.collection.delete()
- ☐ D. db.collection.truncate()



35. What is the command to switch to a different database in MongoDB?

- ☐ A. change db
- ☐ B. switch db
- ☐ C. use dbname
- ☐ D. db.switch(dbname)

██████████

36. Which of the following is a valid way to start a MongoDB server?

- ☐ A. mongod --start
- ☐ B. mongod
- ☐ C. mongodb --start
- ☐ D. start mongodb

██████████

37. What is the default storage engine for MongoDB?

- ☐ A. InnoDB
- ☐ B. MyISAM
- ☐ C. WiredTiger
- ☐ D. RocksDB

██████████

38. Which MongoDB feature allows for efficient searching within large text fields?

- ☐ A. Indexing
- ☐ B. Sharding
- ☐ C. Text Search
- ☐ D. Aggregation

██████████

39. What is the purpose of the \$match stage in an aggregation pipeline?

- ☐ A. To project specific fields
- ☐ B. To filter documents
- ☐ C. To group documents
- ☐ D. To sort documents

██████████

40. Which command is used to create a new user in MongoDB?

- ☐ A. db.createUser()
- ☐ B. db.addUser()
- ☐ C. db.newUser()
- ☐ D. db.userCreate()

██████████



True/False Questions

41. MongoDB supports multi-document ACID transactions since version 4.0.

██████████

42. In MongoDB, the find() method retrieves all documents in a collection if no parameters are passed.

██████████

43. MongoDB provides built-in support for SSL encryption.

██████████

44. In MongoDB, you cannot create an index on a nested field.

██████████

45. By default, MongoDB writes operations are not acknowledged by the server.

██████████

46. The mongo shell is an interactive JavaScript interface to MongoDB.

██████████

47. MongoDB does not support complex data types like arrays and embedded documents.

██████████

48. A collection can contain documents with different structures in MongoDB.

██████████

49. In MongoDB, the \$lookup aggregation stage is used to join data from different collections.

██████████

50. The MongoDB Compass is a graphical user interface for MongoDB.



Multiple Choice Questions

61. Which of the following operators is used to combine multiple conditions in MongoDB?

- ☐ A. \$or
- ☐ B. \$and
- ☐ C. \$nor
- ☐ D. All of the above



62. What does the \$regex operator do in MongoDB?

- ☐ A. Performs a case-sensitive match
- ☐ B. Performs a regular expression match
- ☐ C. Matches documents with similar fields
- ☐ D. Performs a case-insensitive match



63. Which command is used to enable sharding on a database?

- ☐ A. sh.enableSharding()
- ☐ B. db.enableSharding()
- ☐ C. admin.enableSharding()
- ☐ D. shard.enable()



64. Which method is used to find the distinct values for a specified field across a single collection?

- ☐ A. db.collection.distinct()
- ☐ B. db.collection.unique()
- ☐ C. db.collection.findDistinct()
- ☐ D. db.collection.findUnique()



65. Which of the following is not a MongoDB data type?

- ☐ A. Date

- ☐ B. Decimal128
- ☐ C. Blob
- ☐ D. BinData

██████████

66. Which operator would you use to match documents where the value of a field is an array that contains all the specified elements?

- ☐ A. \$in
- ☐ B. \$all
- ☐ C. \$elemMatch
- ☐ D. \$arrayElemAt

██████████

67. What is the use of the \$type operator in MongoDB?

- ☐ A. To specify the data type of a field
- ☐ B. To check the type of a field
- ☐ C. To convert the type of a field
- ☐ D. To remove the type of a field

██████████

68. Which command is used to rename a collection in MongoDB?

- ☐ A. db.collection.rename()
- ☐ B. db.collection.renameCollection()
- ☐ C. db.collection.updateCollection()
- ☐ D. db.collection.renameTo()

██████████

69. What is the primary key in MongoDB called?

- ☐ A. id
- ☐ B. _id
- ☐ C. key
- ☐ D. primaryKey

██████████

70. Which aggregation stage is used to group documents by a specified field?

- ☐ A. \$group
- ☐ B. \$match
- ☐ C. \$project
- ☐ D. \$sort

██████████



True/False Questions

71. The `findOne()` method in MongoDB returns the first document that matches the query criteria.

██████████

72. You can have multiple primary nodes in a MongoDB Replica Set.

██████████

73. MongoDB supports geospatial indexes for spatial queries.

██████████

74. The `mongoimport` utility is used to export data from MongoDB.

██████████

75. The capped collection in MongoDB maintains insertion order and prevents deletions.

██████████

76. The `$project` stage in an aggregation pipeline is used to select specific fields to include or exclude.

██████████

77. MongoDB supports both read and write concerns to handle data consistency.

██████████

78. The `$lookup` stage in an aggregation pipeline is used for performing joins with data from different collections.

██████████

79. The `db.collection.stats()` method provides storage statistics for a collection.

██████████

80. MongoDB uses a master-slave replication model.



Multiple Choice Questions

91. Which operator would you use to match documents where the value of a field is within a specified range?

- ☐ A. \$gt
- ☐ B. \$lt
- ☐ C. \$gte and \$lte
- ☐ D. \$eq



92. What does the \$push operator do in MongoDB?

- ☐ A. Adds an element to an array
- ☐ B. Removes an element from an array
- ☐ C. Updates the value of a field
- ☐ D. Deletes a field



93. Which command is used to restore a database from a backup in MongoDB?

- ☐ A. mongodump
- ☐ B. mongorestore
- ☐ C. mongobackup
- ☐ D. mongorebuild



94. What is the purpose of the db.collection.stats() method?

- ☐ A. To retrieve data from a collection
- ☐ B. To provide statistics about a collection
- ☐ C. To update documents in a collection
- ☐ D. To drop a collection



95. Which of the following is a valid method to rename a field in a MongoDB document?

- ☐ A. \$set

- B. \$rename
- C. \$move
- D. \$update



96. What is the default data format used for backup files created by the mongodump utility?

- A. JSON
- B. BSON
- C. CSV
- D. XML



97. Which MongoDB utility is used to perform a data export in JSON or CSV format?

- A. mongoexport
- B. mongodump
- C. mongorestore
- D. mongoimport



98. What is the purpose of the \$elemMatch operator in MongoDB?

- A. To match elements of an array
- B. To match specific fields
- C. To match nested documents
- D. To match string patterns



99. Which command is used to check the status of a Replica Set?

- A. rs.status()
- B. replSetGetStatus()
- C. rs.info()
- D. replSetStatus()



100. Which of the following is a BSON data type? - A. String - B. Integer - C. Date - D. All of the above - [REDACTED]



True/False Questions

101. The `db.collection.replaceOne()` method replaces an entire document in MongoDB. [REDACTED]
102. You cannot specify write concern for individual write operations in MongoDB. - [REDACTED]
103. The mongo shell can be used to interact with a MongoDB instance using JavaScript. [REDACTED]
104. MongoDB's WiredTiger storage engine supports data compression. [REDACTED]
105. You can create a compound index on multiple fields in MongoDB. [REDACTED]
106. The aggregation framework can be used for real-time analytics in MongoDB. [REDACTED]
107. You cannot use the `find()` method to search for documents in a capped collection. [REDACTED]
108. The `$min` and `$max` operators are used in MongoDB for min-max normalization. [REDACTED]
109. MongoDB Atlas is a fully managed database-as-a-service for MongoDB. [REDACTED]
110. You cannot rename a database in MongoDB. [REDACTED]



Short Answer Questions

111. What does the `db.collection.updateMany()` method do? - Answer: It updates all documents that match the specified filter.
112. How do you enable sharding on a collection in MongoDB? - Answer: By using the command `sh.shardCollection()`.
113. What is the oplog in MongoDB used for? - Answer: The oplog is used for replication purposes, recording all operations that modify the data.
114. Explain the purpose of MongoDB's `$geoWithin` operator. - Answer: The `$geoWithin` operator is used to query for geospatial data within a specified shape.