A beautiful thesis with a complex title

Eine wunderschöne Abschlussarbeit mit einem komplexen Titel

To use the RWTH logo on your title page, you need to submit a special form with your thesis!

Masterarbeit

Master's Thesis

presented by / von

Terschanski, Benjamin Leon

MATRICULATION NUMBER

Supervisors / Betreuer:

First Supervisor

Prof. Dr. Julia Kowalski

Aachen, *YOUR SUBMISSION DATE*

Contents

1 Introduction **1**
1.1 REXUS and stuff . . . 1
1.2 State of the Art . . . 1
1.3 Objectives . . . 1
1.4 Outline . . . 1

2 Subproblem: Liquid Infiltration **2**
2.1 Introduction . . . 2
2.2 Problem Description . . . 3
2.3 Validation Problems . . . 3

References **7**

1 Introduction

1.1 REXUS and stuff

1.2 State of the Art

1.3 Objectives

Primary objectives of the MEEGA experiment:

- fluid-mechanical recreation of a plume qualitatively similar to plumes found on enceladus
- characterisation of the created plume

1.4 Outline

2 Subproblem: Liquid Infiltration

The first subproblem deals with water infiltrating the evaporation chamber during rocket ascent. The injection system assembly in the experiment consists of:

- the hydraulic accumulator, consisting of two volumes separated by a diaphragm and occupied by low-pressure nitrogen and water respectively.
- a pivoted armature valve enabling the flow of water from the accumulator into the cross manifold
- the cross manifold to distribute incoming fluid flow
- the check valves which finally allow the fluid to flow into the evaporation chamber.

The hydraulic accumulator is pressurised to 3.4+/-0.05 bar and heated in order to maintain the temperature of the water contained at 328K. During the ascent of the rocket, a pressure relief valve reduces the pressure in the evaporation chamber to 0.03 MPa. Water infiltrates the evaporation chamber shortly before the apogee is reached and the flow is cut off when the internal pressure rises to 0.05 MPa.

The objective of the first task is to model the water injection into the evaporation chamber and extract quantities of interest in order to better estimate the initial conditions for the second task. The multiphase physics models provided by Star-CCM+ are also evaluated and validated against the one-dimensional Stefan problem and the two-dimensional Rayleigh-Taylor instability.

2.1 Introduction

The evaporation chamber, although a three-dimensional object in real life, due to its axial symmetry is modelled as a two-dimensional rectangular domain in Star-CCM+.

As no flow measurements are made in the injection assembly, and the hydraulic accumulator only contains a temperature sensor, it becomes necessary to make assumptions about the flow of the water to the evaporation chamber. The reduction adapter reduces the diameter of the outflow pipe from the accumulator, D, to the diamter of the rest of pipes used in the rest of the injection system, d. This is followed by two threaded connections in the form of brass T-joints leading to the cross manifold. Using the Darcy-Weisbach equation to estimate the head loss through the pipe and estimating the minor head losses in the form of diameter contractions and threaded connections, the total head loss from the accumulator through to the cross manifold can be written as,

$$h_A = (1 - \frac{d^2}{D^2})\frac{v_A}{2} + 2(0.08)\frac{v_A^2}{2} + f_A\frac{L_A}{d}\rho\frac{v_A^2}{2} \tag{1}$$

The water is distributed through the cross manifold into the brass elbows and through to the evaporation chamber. Similar to the above procedure, the head loss from the manifold to the water outlet incorporates the smooth right angled bends in the elbows and the threaded connections. Thus,

$$h_B = 2(0.3)\frac{v_B^2}{2} + 2(0.08)\frac{v_B^2}{2} + f_B\frac{L_B}{d}\rho\frac{v_B^2}{2} \tag{2}$$

As the pipes used in the injection assembly are congruent, the flow is assumed to be distributed uniformly by the cross manifold. The average velocitiey of water in the first part, v_A can thus be related to the outlet velocity, v_B using the average flow rates Q_A and Q_A respectively.

$$v_A = \frac{Q_A}{A_A} = 3\frac{Q_B}{A_A} = 3v_B\frac{A_B}{A_A} \tag{3}$$

The energy balance for the system is thus written as

$$\frac{\Delta P}{\rho g} = \Delta h + \frac{v_B}{2} + h_A + h_B \tag{4}$$

where after using equations and estimating the Darcy friction factor using the Haaland approximation to the Colebrook equation, the velocity, v_B. With a corresponding Reynolds number, $Re =$, the initial assumption of turbulent flow is validated.

With an initial pressure of $0.03MPa$ in the evaporation chamber, it is also necessary to validate if the continuum hypothesis remains valid for the air present in the chamber. The Knudsen number relates the mean free path, λ, to the scale length of the macroscopic flow property gradients and helps determine the validity of the continuum hypothesis. The magnitude of the mean free path can be used to estimate the Knudsen number.

$$\lambda = \frac{\mu}{\rho}\sqrt{\frac{\pi m}{2k_B T}} \tag{5}$$

For dry air, at a pressure and temperature of $0.03MPa$ and 328 respectively, molecular mass $m = 4.815e-26$ kg, and estimating the kinematic viscosity using Sutherland's formula, the mean free path, $\lambda \approx 2.0732e-06m$.

- Constant density assumption valid? Does that break the rayleigh taylor benchmark test?
- CHANGE INLET FLOW TO ACCOUNT FOR CONSTANCY OF NONDIM NUMBERS

2.2 Problem Description

2.3 Validation Problems

2.3.1 Stefan Problem

Phase changes can be regarded as the growth of the domain of one phase accompanied by the reduction of the domain of the other phase. This growth or reduction in domain sizes can be triggered by thermal as well as non-thermal processes [shumon koga] and the representative mathematical dynamic model containing moving boundaries is known as the Stefan system. The associated problem of analysing and finding the solutions to the aforementioned model is known as the Stefan problem. [koga]. The classical Stefan problem is a one dimensional solidification or melting problem citelaterjonas, jonsson. The one-dimensional Stefan problem under semi-infinite geometry, uniform initial temperature, constant boundary temperature, and thermophysical properties constant in each phase is probably the simplest, explicitly solvable problem of phase change [lectures, uni tenessee knoxville lectures], serving as a good benchmark to validate the phase change VOF solver in Star-CCM+. [DOES IT ALSO SERVE AS A GOOD BENCHMARK FOR SIMPLE HEAT CONDUCTION TOO??? BECOZ TWO BIRDS ONE STONE] Assuming that the region in space, $\Omega \subset \mathbb{R}^2$, occupied by the material is the 2D semi-infinite rectangle $\Omega = \{(x,y) \in \mathbb{R}\times\mathbb{R} : x \in [0,\infty),\ y \in [0,\Delta h]\}$, with the solid phase and the liquid phase occupying the regions Ω_s and Ω_l respectively such that $\Omega = \Omega_s \cup \Omega_l$. At any given time, t, the two phases are separated by the interface, $\Gamma(t)$, that marks the change in phase of the material. The boundary of the domain Ω is denoted by $\partial\Omega$. The problem space, $\mathcal{D}$, is the spatial and temporal domain occupied by the material, $\mathcal{D} = \{[t_0, t_f] \times \Omega\}$. With the heat equation governing the temperature field in the liquid region, the Stefan condition at the interface, and the respective boundary conditions, the system of equations defining the one-dimensional Stefan problem can be written as,

$$\begin{cases} \frac{\partial T}{\partial t} - \alpha\frac{\partial^2 T}{\partial x^2} & = 0, \\ \rho h_m \frac{d\Gamma(x(t),t)}{dt} + \kappa\frac{\partial\Gamma(x(t),t)}{\partial x} & = 0, \\ T(x,0) & = T_l, \\ \nabla T(x,t)\cdot\mathbf{n} & = 0, \\ T(x,0) & = T_m \end{cases} \tag{6}$$

- the system of equations is well-posed and has a unique solution. the evolution of the temperature field along with the evolution of the phase change interface is studied. The simulation assumes laminar and unsteady flow and solves for the solution variables implicitly using the SIMPLE scheme. The 2D region is discretised using

an orthogonal quadrilateral mesh of varying sizes in order to study the spatial convergence of the solution. The physical parameters for the simulation are selected according to water ice, as in [boledi et al]. A constant density $\rho = 1000\,\mathrm{kg} \cdot \mathrm{m}^{-3}$, dynamic viscosity $\mu = 8.8871e-4\,\mathrm{Pa} \cdot \mathrm{s}$, latent heat of fusion $100000\,\mathrm{J} \cdot \mathrm{kg}^{-1}$, and specific heat $4200\,\mathrm{J} \cdot \mathrm{kg}^{-1} \cdot \mathrm{K}^{-1}$. Thermal conductivities are defined as 2.33 and 0.620271 for the solid and liquid phases respectively. All four boundaries are assigned a no-slip shear stress specification. The boundary at $x = 0$ is assigned a Dirichlet condition of temperature, $T = 273\,\mathrm{K}$, while the other boundaries are assumed to be adiabatic. The convection and diffusion terms are discretised using the second-order upwind scheme and the least squares method was used to interpolate the values of the gradients from the cell centres onto the face centres. The transient term is discretised using the implicit Euler-method which is first-order accurate. First-order HRIC is used to reconstruct the interface. Since Star-CCM+ sets under- and over-relaxation factors conservatively, the values are left unchanged.

The evolution of the temperature field for the simulation with cell size, $\Delta h = 5e-3$ is shown in Figure [FIG]. A clear propagation of the interface from the left to right is observed with increasing simulation times. The temperature also gradually decreases in the liquid phase from the Dirichlet boundary at $x = 0$ towards the melting temperature, T_m, at the interface after which it stays constant.

- 'This is exactly what one would expect for a velocity that is decreasing in time as is the case for the classical Stefan problem. One can also see that all simulation results converge to the analytical solution for a finer mesh and a smaller time step.'
- [ABOUT CONVERGENCE]
- [ABOUT COMPARISON OF TEMPERATURE W ANALYTICAL SOLUTION]
- [ABOUT COMPARISON OF PCI W ANALYTICAL SOLUTION]

2.3.2 Rayleigh-Taylor Instability

When two superposed fluids with differing densities are accelerated in a direction perpendicular to their interface, the surface is unstable when the heavier fluid is accelerated into the lighter fluid. [ref 15, p192 - Birkhoff, 1954]. The instability arising therefrom is known as the Rayleigh-Taylor (RT) instability. The growth of perturbations at the interface is characterised by opposing pressure and density gradients [Banerjee 2020, Schilling et all 2020, HutchinsonDissertation] and the density difference is represented by the *Atwood number*, $At = (\rho_H - \rho_L)/(\rho_H + \rho_L)$. Although not encountered in its ideal form, the RT instability may occur across various natural and technological processes where it is often modified by the presence of additional processes [mention which processes?]. The principles governing the nonlinear RT instability also govern any motion of one fluid in another of different density [Tryggvason rt instability], thus serving as a good measure to study the infiltration of the evaporation chamber in the first subproblem. The instability has moreover served as a classical benchmark for the evaluation of the behaviour of two phase flows [Goulding et al.] ['WHY' imminent].

We assume that the two immiscible, viscuous, and incompressible fluids occupy the regions,

$$\Omega_i(t) = \{(x,y) \in \mathbb{R} \times \mathbb{R} : (-1)^i (y - h(t,x)) > 0,\ t \geq 0\},\ i = 1,2$$

and are separated by the interface, $\Gamma(t)$ where

$$\Gamma(t) = \{(x,y) \in \mathbb{R} \times \mathbb{R} : y = h(t,x),\ t \geq 0\}$$

Using the navier stokes equations for incompressible fluids, a mixture density and viscosisty, the jump conditions at the interfaces, and the initial boundary conditions, the governing equation for the Rayleigh-Taylor instability can be written as

$$\begin{cases} \rho\frac{\partial(\mathbf{u})}{\partial t} + \rho\nabla\cdot(\mathbf{u}\mathbf{u}) & = -\nabla p + \mu\nabla^2\mathbf{u} + \mathbf{g}\rho, \\ \nabla\cdot\mathbf{u} & = 0, \\ [\![S(u, p + \mathbf{g}\rho)\mathbf{n}]\!] & = \sigma\kappa\mathbf{n} + [\![\rho]\!]\mathbf{g}y \\ [\![u]\!] & = 0 \\ V & = \mathbf{u}\cdot\mathbf{n} \\ u(0) & = u_0, \\ \Gamma(0) & = \Gamma_0 \end{cases} \tag{7}$$

where ρ is the density, $\mathbf{u}$ is the velocity vector, p is the pressure, μ is the dynamic viscosity, and g is the gravitational acceleration. The simulation assumer turbulent and unsteady flow, utilising the SIMPLE implicit scheme. The computational domain is discretised using an orthogonal quadrilateral mesh. The convection and diffusion terms are discretised using the second-order upwind scheme while the least squares method is again used to interpolate the values of the gradients from the cell centres onto the face centres. The VOF solver utilises the first-order HRIC scheme to reconstruct the interface. The transient term is discretised using the first-order accurate implicit Euler-method. The modified K-Omega (SST k-omega) model is used to account for turbulence and surface is treated semi-implicitly. [MENTION INITIAL CONDITIONS] The instability is simulated on a 2D rectangular domain, $[0, L_x] \times [0, 4L_x]$, where L_x is the reference length. The initial interface, located at y_0, represents a single-mode perturbation with amplitude, $A = 0.1L_x$, and wavelength, $\lambda = L_x$.

$$\Gamma_0 = 2L_x + A\cos\left(\frac{2\pi}{L_x}\right)$$

The lower limit of the high Atwood number regime requires the Atwood number to be atleast 0.5 [1]. Gravitational acceleration acts in a downward direction with a magnitude of $g = 1.0$. Periodic boundary conditions are enforced in the horizontal direction and slip wall conditions are applied at the top and bottom boundaries. The physical parameters are selected to make the simulations dynamically similar to the ones studied [2].

According to [3], a reasonable solution to the RT instability with $At \approx 0.75$ can be obtained with a 128×512 mesh. With similar mesh resolutions being used in [2, 4] to study similar RT instabilities, in addition to a mesh convergence study being performed, the domain is discretised using a uniform trimmer mesh with size $\delta_h = 0.0045$. The timestep for the simulations is selected as $\delta t = 2.5 \times 10e-4/\sqrt{At}$ similar to [5, 2]. The following cases are studied:

Case	At	Re	σ	δ_h
1	0.5	300	$1e-5$	0.05
2	0.5	300	$1e-5$	0.007
3	0.5	300	$1e-5$	0.0045
4	0.5	300	$1e-5$	0.0025
5	0.2	1000	$1e-5$	0.0045
6	0.5	1000	$1e-5$	0.0045
5	0.5	3000	$1e-5$	0.0045
6	0.5	3000	$1e-5$	0.0045

In a system of two fluids with a perturbed interface, the heavier fluid penetrates the lighter fluid due to gravitation thereby pushing the lighter fluid upwards. The initial perturbations, generally studied using linear stability

analysis, lead to an exponential growth [andrews and dalziel] and transition into non-lineartiy resulting in the rise and sink of the bubbles of lighter fluid and spikes of the heavier fluid respectively [sharp, bannerjee]. Figure **??** illustrates the parameter definitions and nomenclature of an evolving single-mode [need i define single mode rt?] RT instability interface. The evolution of RT instabilities for Reynolds numbers 300, 1000, and 3000 are depicted in figure **??**. As the solution evolves, the penetration of the spike increases and it eventually rolls up and forms two transient counter-rotating vortices due to shear forces and Kelvin-Helmholtz type instabilities [hamzelhoo], which go on to contribute to turbulent mixing and chaotic flow features [Sharp].

Figure [name figure] depicts the evolution of the interface at different times for varying density ratios as simulated in Star-CCM+. Upto high Reynolds numbers, the interface structure and its temporal evolution agree qualitatively with the results published in [hamzelhoom huang, ding]. [why does it look different at high Re]. Using the bubble and spike heights, defined as the maximum vertical distance of the spike and bubble as measured from the undisturbed initial interface, the results can be quantitatively compared to [hamzelhoo] as shown in Figure **??**. Table **??** summarises the root mean square errors and the maximum errors between the simulated results and [hamzelhoo].

Simulations conducted for Atwood numbers very close to one also qualitatively show a similar progression and evolution of structures as the simulations in [huang]. [What happens at high atwood numbers]

[Write about mesh convergence study. WHY DO RESULTS NOT MATCH?].

References

[1] Maxwell Hutchinson. A DISSERTATION SUBMITTED TO THE FACULTY OF THE DIVISION OF THE PHYSICAL SCIENCES IN CANDIDACY FOR THE DEGREE OF DOCTOR OF PHILOSOPHY.

[2] Arash Hamzehloo, Paul Bartholomew, and Sylvain Laizet. Direct numerical simulations of incompressible Rayleigh-Taylor instabilities at low and medium Atwood numbers. 33(5):054114, 2021.

[3] Shahab Mirjalili, Christopher B. Ivey, and Ali Mani. Comparison between the diffuse interface and volume of fluid methods for simulating two-phase flows. 116:221–238, 2019.

[4] Ziyang Huang, Guang Lin, and Arezoo M. Ardekani. Consistent, essentially conservative and balanced-force Phase-Field method to model incompressible two-phase flows. 406:109192, 2020.

[5] Hang Ding, Peter D.M. Spelt, and Chang Shu. Diffuse interface model for incompressible two-phase flows with large density ratios. 226(2):2078–2095, 2007.

[6] Yixiang Liao and Dirk Lucas. Computational modelling of flash boiling flows: A literature survey. 111:246–265, 2017.

[7] Jan Wilhelm Gärtner. Modeling and simulation of flash evaporation of cryogenic liquid jets, 2024.

[8] Ahmad Mansour and Norbert Müller. A review of flash evaporation phenomena and resulting shock waves. 107:146–168, 2019.

[9] D. Saury, S. Harmand, and M. Siroux. Flash evaporation from a water pool: Influence of the liquid height and of the depressurization rate. 44(10):953–965, 2005.

[10] Yixiang Liao and Dirk Lucas. A review on numerical modelling of flashing flow with application to nuclear safety analysis. 182:116002, 2021.

[11] Yixiang Liao, Dirk Lucas, Eckhard Krepper, and Roland Rzehak. Flashing evaporation under different pressure levels. 265:801–813, 2013.

[12] Osamu Miyatake, Itsuo Tanaka, and Noam Lior. A simple universal equation for bubble growth in pure liquids and binary solutions with a nonvolatile solute. 40(7):1577–1584, 1997.

[13] Quang Dang Le, Riccardo Mereu, Giorgio Besagni, Vincenzo Dossena, and Fabio Inzoli. Computational Fluid Dynamics Modeling of Flashing Flow in Convergent-Divergent Nozzle. 140(10):101102, 2018.

[14] Mamoru Ishii and Takashi Hibiki. *Thermo-Fluid Dynamics of Two-Phase Flow.* Springer New York, 2011.

[15] Gretar Tryggvason, Ruben Scardovelli, and Stéphane Zaleski. *Direct Numerical Simulations of Gas-Liquid Multiphase Flows.* Cambridge Univ. Press, 1. publ edition, 2011.

[16] Volume-Averaged Macroscopic Transport Equations. In E. Blosch, H. Ouyang, J. Liu, S. S. Thakur, and Wei Shyy, editors, *Computational Techniques for Complex Transport Phenomena*, pages 231–259. Cambridge University Press, 1997.

[17] S. Mostafa Ghiaasiaan. *Two-Phase Flow, Boiling and Condensation: In Conventional and Miniature Systems.* Cambridge University Press, 2007.

[18] M Wörner. A Compact Introduction to the Numerical Modeling of Multiphase Flows.

[19] Geoffrey F. Hewitt and George Yadigaroglu. Modelling Strategies and Two-Phase Flow Models. In George Yadigaroglu and Geoffrey F. Hewitt, editors, *Introduction to Multiphase Flow: Basic Concepts, Applications and Modelling*, pages 39–77. Springer International Publishing, 2018.

[20] George Yadigaroglu. Interfacial Instabilities. In George Yadigaroglu and Geoffrey F. Hewitt, editors, *Introduction to Multiphase Flow: Basic Concepts, Applications and Modelling*, pages 79–94. Springer International Publishing, 2018.

[21] David C. Wilcox. *Turbulence Modeling for CFD.* DCW Industries, 3rd ed edition, 2006.

[22] C. Truesdell and K. R. Rajagopal. *An Introduction to the Mechanics of Fluids.* Birkhäuser, 2000.

[23] Michel O. Deville and Thomas B. Gatski. *Mathematical Modeling for Complex Fluids and Flows.* Springer Berlin Heidelberg, 2012.

[24] Ch Hirsch. *Numerical Computation of Internal and External Flows: Fundamentals of Computational Fluid Dynamics.* Elsevier/Butterworth-Heinemann, 2nd ed edition, 2007.