

Name: _____

Date: _____

Unit 1: Safety

Woodworking

Mr. DellaPietro

JOINTER SAFETY

1. Get permission from your instructor before you use the jointer.
2. Check the safety guard over the cutter head. Make sure it swings freely and returns to its position over the cutter head.
3. The fence should be set so that no more of the cutter head is exposed than is necessary.
4. Check to see that the fence is square, and that it's locked in position before you use the jointer.
5. Do not make any adjustments to the outfeed table. (If the outfeed table needs adjustment, check with the instructor.)
6. Before you turn on the jointer, check the infeed table adjustment. That's the adjustment for the depth of the cut. Adjust it for the smallest cut that'll do the job.
7. When edge jointing, never make a cut deeper than $\frac{1}{8}$ inch.
8. When face jointing, when jointing along the flat surface of the face, never make a cut deeper than $\frac{1}{16}$ inch.
9. Never adjust the jointer while it is operating. Always turn it off first. Wait for it to come to a complete stop before you adjust it.
10. Check the dimensions of the stock. The material must be large enough to be used on the jointer safely. (It should be at least 12 inches long, 1 inch wide and $\frac{1}{2}$ inch thick.)
11. The wood must be sound, with no defects such as knots, splits or checks. It must be clean, with no hardware, paint or other finishes on it.
12. The material must be held down firmly against the table and along the fence.
13. Be sure there is a push stick or a push block within reach. Always use a push stick or a push block when jointing flat or narrow material.
14. Use a push block for face jointing.
15. Stand so you are balanced when you make the cut. Don't overreach. Ask someone to "tail-off" for you if the stock is too long to handle safely by yourself.



Name: _____

Unit 1: Safety

Woodworking

Date: _____

Mr. DellaPietro

16. Move your hands so they never apply pressure directly over the cutter head. Pressure should be applied in front of the cutter head and behind it, not directly over it
17. Keep your hands and arms at least 4 inches away from the rotating knives in the cutter head.
18. Complete each pass on the jointer. Don't interrupt a cut or try to back out of it. Backing out of a cut can cause serious kick-back and you could be injured.
19. Don't joint across the end grain of the wood. End grain jointing should be avoided until you have had specific instruction on how to do it safely.
20. The jointer is sometimes used for beveling or for tapering. These operations require special set-ups. Check with the instructor before you use any special set-up.
21. When you are finished using the jointer, turn it off and stay with it until it has come to a complete stop.
22. Don't do anything on the jointer that you are not sure of. Use the jointer only after its correct, safe use has been demonstrated for you and you understand the instructions.
23. You should always use a bench brush to clear away wood chips and always wait until the jointer comes to a complete stop.