

VSC HPC Introduction

ICTS KU Leuven

VSC staff:

Ehsan Moravveji

Mag Selwa

Wouter van Assche

Geert Jan Bex (Uhasselt)

Jan Ooghe

Material

- ❑ Everything is on Github:
<https://hpcleuven.github.io/HPC-intro/>
- ❑ Video Recordings
 - Scan the QR code
 - Recommended videos: ~ 2 hrs
 - Optional videos: ~1 hr



What is High Performance Computing?

- ❑ using supercomputers to solve advanced computation problems
- ❑ Reduce the computation time from days, years, decades, or centuries to minutes, hours, days, or weeks
- ❑ The key is parallelism



In practice, it is more like ...



The concept is simple: **Parallelism** = employing multiple processors for a single problem

Outline

- What is the VSC?
- What is a cluster?
- Genius Cluster
- Storage
- Login nodes & MFA
- Connection Setup
- Software environment
- How to submit jobs?
- Dedicated hardware
- How to choose resources?
- Optional material
 - Linux in brief
 - Conda for Python and R
 - Worker Framework

VLAAMS
SUPERCOMPUTER
CENTRUM



Vlaanderen
is supercomputing



VSC

(Vlaams Supercomputer Centrum)

VSC PARTNERSHIP



Supported by
fwo

 **ASSOCIATIE**
UNIVERSITEIT GENT





 universitaire
associatie
BRUSSEL





ASSOCIATIE
KU LEUVEN



 ASSOCIATIE
UNIVERSITEIT-HOGESCHOLEN
LIMBURG



 **auha** antwerp
university
association




VSC HPC Environments



www.vscentrum.be

Very rich suite of
courses every
academic year

Documentation!
Answers >80% of
your questions



Welcome to VSC documentation x +

vlaams-supercomputing-centrum-vscdocum...

VSC documentation 1.0 documentation » next | index

Next topic
Getting access

This Page
Show Source

Quick search

Go

Welcome to VSC documentation

- Getting access
 - VSC accounts
 - How to request an account?
 - Next steps
 - Additional information
- Access and data transfer
 - Logging in to a cluster
 - Data storage
 - Transferring data
 - GUI applications on the clusters
 - VPN
- Software stack
 - Using the module system
 - Specialized software stacks
- Running jobs
 - Job script
 - Submitting and monitoring a job
 - Job output
 - Troubleshooting
 - Advanced topics
- Software development

v: latest ▾

Search you
keywords here;
e.g. qsub

Support and Services

Basic support

- Helpdesk (hpcinfo@kuleuven.be)
- Monitoring and reporting

Application support

- Installation and porting
- Optimisation and debugging
- Benchmarking
- Workflows and best practices

Training

- Documentation and tutorials
- Scheduled trainings / workshops
- On request workshops
- One-to-one sessions

To manage your
VSC account:
account.vscentrum.be

The screenshot shows a web browser window with the address bar containing account.vscentrum.be/django/. The page features a navigation bar with the following links: View Account, Edit Account, View Groups, New/Join Group, Edit Group, New/Join VO, Reservations, and Log Out. Below the navigation bar, the 'View account' section is active, displaying 'General information' with the following details: Uid: vsc30745, Institute: Leuven / Hasselt, Institute login: u0090231, and Gecos: Ehsan Moravveji. Four orange callout boxes provide additional context: 'Upload SSH Key Request account' points to the 'View Account' link; 'Upload more SSH public keys' points to the 'Edit Account' link; 'Create or request to join a new group' points to the 'New/Join Group' link; and 'Moderate your own groups (add/remove users)' points to the 'Edit Group' link.

View account — VSC

account.vscentrum.be/django/

VLAAMS SUPERCOMPUTER CENTRUM Vlaanderen is supercomputing

View Account Edit Account View Groups New/Join Group Edit Group New/Join VO Reservations Log Out

View account

General information

Uid: vsc30745
Institute: Leuven / Hasselt
Institute login: u0090231
Gecos: Ehsan Moravveji

Upload SSH Key Request account



Upload more SSH public keys

Create or request to join a new group

Moderate your own groups (add/remove users)

Become a VSC user

- ☐ Create a secure (4096 bit) [SSH key pairs](#)
Upload it on the account page: www.account.vscentrum.be
- ☐ You need to [request a VSC account](#)
Normally processed swiftly
- ☐ Request [introductory credits](#) (2M free credits for 6 months)
- ☐ Request [project credits](#) (for supervisors and project leaders)
You need to create a VSC group
Add users to the group to give them access to use credits
Fill out the request form
- ☐ Extra storage requests
Scratch extension: free of charge
Staging fileset: 20 € per TB per year
- ☐ All service costs (compute and storage) are all explained
Go to ICTS service catalogus: <https://icts.kuleuven.be/sc>
Click on [High Performance Computing](#) (NL/EN)



VSC training

- Introductory

Matlab (Supercalculator)
Matlab Programming

Linux

HPC intro

Linux for HPC

Linux scripting

Infosessions:
• Containers
• Notebooks

Make intro

Linux tools

CMake intro

Version control systems

- Intermediate

C++ for scientific computing

Fortran for programmers

C

- Python as a second language
- Python: System programming
- Scientific Python
- Python for Software engineering
- Python for data science
- Python for machine learning

worker/atools

Julia good bad ugly

- Advanced

High Performance Python

- Specialized track

?

MPI

OpenMP

Debugging techniques

Code optimization

To Acknowledge VSC in publications

Why?

- ☐ a contractual obligation for the VSC
- ☐ helps VSC secure funding
- ☐ you will benefit from it in the long run

At KU Leuven

- ☐ add the relevant papers to the virtual collection "High Performance Computing" in Lirias

In het nederlands

De rekeninfrastructuur en dienstverlening gebruikt in dit werk, werd voorzien door het VSC (Vlaams Supercomputer Centrum), gefinancierd door het FWO en de Vlaamse regering – departement EWI.

In English

The computational resources and services used in this work were provided by the VSC (Flemish Supercomputer Center), funded by the Research Foundation - Flanders (FWO) and the Flemish Government – department EWI.




Tier-2 Clusters

What is a Cluster?

A cluster is comprised of **many powerful interconnected compute nodes**

Some Terminology:

	What	Components
Cluster	The primary part of a cluster are its many powerful interconnected compute nodes.	Compute nodes Login nodes Storage space Interconnect Network ...
Node	A single computer connected with other nodes via an interconnect network	CPU, Storage, Memory, ...
CPU	Processing Component of a computer, also called the processor .	Controllers, Cache Memory, Processing Cores
Core	Processing element of the CPU .	Control Unit, Arithimic-Logic Unit, Memory.



Tier-2 Clusters @ KU Leuven



Genius (since 2018)
250 nodes: 8,936 cores



WICE (since 9/2022)
186 nodes; 13,392 cores



wICE (since 9/2022)
186 nodes; 13,392 cores




Watch out with
login scripts !

login-genius.hpc.kuleuven.be

Genius

wICE Overview





Compute nodes

Large memory nodes

GPU nodes

Interactive nodes



Thin nodes

+ 172x Icelake 72c 256 GB

BigMem

+ 5x Icelake 72c 2 TB

GPUs


+ 4x Icelake 72c 512 GB
4x A100 80 GB

+ 5x Icelake 64c 512 GB
1x A100 80 GB

Tier-2 Overview


wICE

Compute nodes



172x IceLake 72c 256 GB

Large memory nodes




5x IceLake 72c 2048 GB

GPU nodes



4x IceLake 72c 512 GB
4 A100 SXM4 80GB

Interactive nodes



5x IceLake 64c 512 GB
1 A100 80GB

**No Dedicated
Login Nodes**

Tier-2 Cluster: wICE

Type of node	CPU type	Inter-connect	# cores	installed mem	local discs	# nodes
Icelake	Xeon 8358	IB HDR-100	72	256 GB	960 GB	172
Icelake large mem	Xeon 8358	IB HDR-100	72	2048 GB	960 GB	5
Icelake GPU	Xeon 8358 4xA100 SXM2 80GB	IB HDR-100	72	512 GB	960 GB	4
Icelake Interactive	Xeon 8358 1xA100 SXM2 80GB	IB HDR-100	64	512 GB	960 GB	5

The background is a vibrant, stylized illustration. On the left, a cityscape features large, grey, arched structures. A digital screen in the center shows a grid with numbers and a large orange arrow pointing upwards. On the right, a close-up of a plant with large blue and red berries is visible. A large, semi-transparent orange rectangle covers the lower-left portion of the image, containing the word 'Storage' in white text.

Storage

Overview of the storage infrastructure

- Your files are owned only by you.
Other VSC users have no permission to read/write/execute your files (POSIX)
- A VSC account has 3 default storages (free of charge)
 - `$VSC_HOME`
 - `$VSC_DATA`
 - `$VSC_SCRATCH`
- You can additionally request `staging` storage
- Different storage volumes have different:
 - mount point
 - size and performance
 - use case
 - backup and maintenance policy
- More info on [ICTS Service Catalog](#) (EN/NL)


Storage

- ❑ [Request form for extra storage](#)
- ❑ [More information](#)
- ❑ **Do not** use `/tmp`
It is only 10 GB and is reserved for the OS and root processes
Your application can crash if using `/tmp`
- ❑ You are automatically logged into your home folder upon login.
Make sure you immediately go to your other storages, e.g.
`$ cd $VSC_DATA`
- ❑ Always check your storage balance using `myquota` command

Example


```
$ myquota
file system $VSC_HOME
    Blocks: 1479M of 3072M
    Files: 12934 of 100k
file system $VSC_DATA
    Blocks: 12G of 75G
    Files: 1043k of 10000k
file system $VSC_SCRATCH
    Blocks: 15M of 1.5T
```

Storage




Storage	home folder
Env. Variable	<code>\$VSC_HOME</code>
Filesystem Type	NFS
Access	Global
Backup	Hourly, daily, weekly (until last month) inside the <code>.snapshot</code> folder.
Default Quota	3 GB
Extension	Not possible
Usage	Only storing SSH keys, config files
Remarks	<ul style="list-style-type: none">- Stay away from using it- Can easily overflow:<ul style="list-style-type: none">+ Your jobs may crash+ Login issues

Storage




Storage	data folder
Env. Variable	<code>\$VSC_DATA</code>
Filesystem Type	NFS
Access	Global
Backup	Hourly, daily, weekly (until last month) inside the <code>.snapshot</code> folder.
Default Quota	75 GB
Extension	On purchase
Usage	Your data, code, software, results
Remarks	<ul style="list-style-type: none"> - Permanent storage for initial/final results - Not optimal for intensive or parallel I/O

Storage




Storage	scratch folder
Env. Variable	<code>\$VSC_SCRATCH</code>
Filesystem Type	Lustre
Access	Global
Backup	delete after 30 days from last access
Default Quota	500 GB
Extension	Free
Usage	Intensive, parallel I/O, temporary files
Remarks	<ul style="list-style-type: none">- Recommended storage for all jobs- Copy scratch files to VSC_DATA or local storage after jobs are done- Deleted files cannot be recovered

Storage



Storage	Node scratch folder
Env. Variable	<code>\$VSC_SCRATCH_NODE</code>
Filesystem Type	Lustre
Access	On compute node, only at runtime
Backup	None
Default Quota	591 GB
Extension	Read about beeOND
Usage	Temporary storage at runtime
Remarks	<ul style="list-style-type: none">- Fastest I/O, attached to the node- Is cleaned after job terminates- Copy the data to your home, scratch, or staging before job ends

Storage




Storage	Staging folder
Path	/staging/leuven/stg_000XX
Filesystem Type	Lustre
Access	On demand, only Tier-2@KUL
Backup	None
Default Quota	None
Extension	On purchase, from 1 TB
Usage	Permanent; share with a group
Remarks	<ul style="list-style-type: none">- Accessible from login/compute nodes- Fast, parallel I/O



Login Nodes & MFA

Accessing a Cluster



Using Login Nodes

- ☐ To develop code
- ☐ To check your storage and credit balance
- ☐ To manage jobs (submit, check status, debug, resubmit, ...)
- ☐ To move data around
 - within VSC: use data, scratch, staging, archive
 - outside VSC: copy/sync from/to your local storage
- ☐ To pre-process or post-process your data/jobs
- ☐ To visualize your data
- ☐ To share files/folders

Tips

Command
\$ top
Show use of
the system

- ☐ Compile your software on compute nodes (via e.g. interactive job)
- ☐ Login nodes are shared resources
- ☒ **Do not** execute heavy-lifting tasks (core, memory)
- ☐ Instead, submit jobs
- ☐ Check \$ `slurmtop` to see how busy the cluster is

Warning

Login Hosts on Different Machines/partitions

- Windows: [PuTTY](#) or [MobaXterm](#) or NX
Linux/Mac: [terminal](#) or NX
- To login, you need an active VSC number and a hostname
`$ ssh -X vscXXXXXX@<hostname>`

Cluster / Partition	<hostname>	Remark(s)
Genius	<code>login.hpc.kuleuven.be</code>	Recommended
	<code>login{1,2}-tier2.hpc.kuleuven.be</code>	No GPU
	<code>login{3,4}-tier2.hpc.kuleuven.be</code>	Nvidia Quadro P6000
wICE		Accessible only via Genius




Login Setup

- ☐ PuTTY
- ☐ Terminal

Activate Your SSH Agent

(Windows only)



- When you install PuTTY, the agent called **Pageant** is automatically installed
- Open Pageant; it hides inside your bottom-right tray
- Click on “Add Key” and brows to your private key(s) folder
- After choosing a key, you are asked for a passphrase
- If successful, agent always remembers your SSH keys and Certificates (Multi-Factor Authentication)



Setup PuTTY in 12 Clicks



(Windows only)

Host Name:
`login.hpc.kuleuven.be`




Setup PuTTY in 12 Clicks

(Windows only)




Setup PuTTY in 12 Clicks

(Windows only)



If PuTTY asks for **password**, exit immediately, and check the path to your private key. Else you will be blocked for 24h.



Connecting via Terminal

(Linux and Mac)

- Use ssh to connect:
`$ ssh vscXXXXXX@<host_name>`
- If key not found:
`$ ssh -I </path/to/keyfile> ...`

If asked for **password**,
please stop connecting
and contact support,
otherwise after a few
attempts you will be
blocked for 24h.

Host Name:
`login.hpc.kuleuven.be`



```
u0140201 — ssh vsc32591@login.hpc.kuleuven.be — 80x25
The default interactive shell is now zsh.
To update your account to use zsh, please run `chsh -s /bin/zsh`.
For more details, please visit https://support.apple.com/kb/HT208050.
[crd-l-m0318:~ ████████$ ssh vsc██████@login.hpc.kuleuven.be
Enter passphrase for key '/Users/██████/.ssh/id_ed25519':
vsc██████
Please open https://firewall.vscentrum.be/PDihC0i5kk9Sks3VN5m to complete logon.
Last login: Fri Oct  7 11:32:48 2022 from 2a02:2c40:0:2410::a1b

Genius

Informatie over deze server (FQDN): tier2-p-login-4.genius.hpc.kuleuven.be
* cluster: genius
* role: login
* hardware: ProLiant DL380 Gen10 (x86_64)
* os: CentOS 7.9.2009
* kernel: 3.10.0-1160.11.1.el7.x86_64
* architecture: skylake
✓ [okt/12 13:31] vsc██████@tier2-p-login-4 ~ $
```


Connecting via Terminal

With SSH Agent (Linux and Mac)

- Check your SSH Agent. Is your SSH key found?
`$ ssh-add -l`
- If your SSH Agent is not running:
`eval $(ssh-agent)`
- If your key is not found, add it to the Agent:
`$ ssh-add </path/to/keyfile>`
- Use ssh to connect:
`$ ssh vscXXXXX@<hostname>`

Host Name:
login.hpc.kuleuven.be



```
u0140201 — ssh vsc32591@login.hpc.kuleuven.be — 80x25
The default interactive shell is now zsh.
To update your account to use zsh, please run `chsh -s /bin/zsh`.
For more details, please visit https://support.apple.com/kb/HT208050.
[crd-l-m0318:~ ████████$ ssh vsc██████@login.hpc.kuleuven.be
Enter passphrase for key '/Users/██████/.ssh/id_ed25519':
vsc██████
Please open https://firewall.vscentrum.be/PDihC0i5kk9Sks3VN5m to complete logon.
Last login: Fri Oct  7 11:32:48 2022 from 2a02:2c40:0:2410::a1b

  Genius

Informatie over deze server (FQDN): tier2-p-login-4.genius.hpc.kuleuven.be
* cluster: genius
* role: login
* hardware: ProLiant DL380 Gen10 (x86_64)
* os: CentOS 7.9.2009
* kernel: 3.10.0-1160.11.1.el7.x86_64
* architecture: skylake

✓ [okt/12 13:31] vsc██████@tier2-p-login-4 ~ $
```



NX


☐ About

☐ Setup

NX – The Graphical Login

NX is:


- ☐ a graphical remote desktop server
- ☐ login to VSC
- ☐ start a virtual Linux instance(s)
- ☐ Client: [NoMachine](#)
- ☐ [Configuration Guide](#)
- ☐ Using OpenSSH key [Convert your key](#)




Advantages of NX

- ☐ Graphical login
- ☐ A session stays alive/active even if you close your client (e.g. laptop)
- ☐ Resume a session, and immediately keep working where you left off
- ☐ More interactive jobs
- ☐ Available apps:
 - Internet browser, terminal, ...
 - Text editor, PDF reader, Image viewer, ...
 - Matlab, RStudio, SAS
- ☐ **Remark:**
 - NX is shared among tens of users
 - Do not compute/test your code there**
 - Instead, submit jobs from NX to compute nodes

NX virtual desktop







- ❑ NX is a graphical login node
- ❑ A new session stays active for long
- ❑ Rich suite of applications; e.g. Terminal, Firefox, text editor, Matlab, RStudio, SAS etc.
- ❑ NX is a shared, login-node.
Please do not compute on NX.
- ❑ NX server is attached to Genius. Jobs submitted from NX will appear in Genius queue

NX: available software

- ☐ **Accesories:** Gedit, Vi IMproved, Emacs (dummy version), Calculator
- ☐ **Graphics:** gThumb (picture viewer), Xpdf Viewer
- ☐ **Internet:** Firefox
- ☐ **HPC: Computation:** Matlab (2018a), RStudio, SAS
- ☐ **Visualisation:** Paraview, VisIt, VMD
- ☐ **Programming:** Meld Diff Viewer (visual diff and merge tool)
- ☐ **System tools:** File Browser, Terminal
- ☐ **Additionally:** Gnuplot (graphing utility), Filezilla (file transfer tool), Evince (PDF, PostScript, TIFF, XPS, DVI Viewer)
- ☐ Software launched though modules from Terminal.

Setup NX in 10 Steps



Setup NX in 10 Steps

NoMachine

New connection

Protocol Host Authentication Proxy Save as

Insert the hostname or IP and port where you want to connect.

Host Port

The port was chosen automatically based on the default for the protocol. If the remote computer was configured to listen on a different port, please insert it above.

Host: nx.hpc.kuleuven.be

Back Continue

3

NoMachine

New connection

Protocol Host Authentication Proxy Save as



Choose which authentication method you want to use.

- ☐ Password
Use password authentication.
- ☒ Private key
Use key-based authentication with a key you provide.
- ☐ Authentication agent
Use key-based authentication with a key provided by a SSH agent.
- ☐ Smart card
Use key-based authentication with a key stored on a PKCS11 smart card.
- ☐ Kerberos
Use Kerberos ticket-based authentication.



Back Continue

4



Setup NX in 10 Steps



Setup NX in 10 Steps




Setup NX in 10 Steps







File Transfer with FileZilla

File transfer





Application	OS
FileZilla	Windows, Linux, Mac
WinSCP	Windows
rsync, scp	Linux, Mac
Globus	Window, Linux, Mac

File transfer



File transfer





For convenience, you'd better bookmark your data and scratch folders!

Instead, go to your \$VSC_DATA folder, e.g. /data/leuven/399/vsc39934

Your local machine (e.g. laptop)

Your VSC storage (e.g. \$VSC_DATA, \$VSC_SCRATCH).
Note: by default you arrive at your own \$VSC_HOME. Copy **nothing** there!



Open OnDemand










- Access wICE via web browser
- <https://ondemand.hpc.kuleuven.be>
- Login via KULeuven MFA
- File browser
- Interactive apps + integrated shell
- Create, start and monitor jobs
- Develop, compile and test your code
- VSCode editor
- Jupyter Lab, RStudio and Tensorboard

Kuleuven OnDemand Apps Files Jobs Clusters Interactive Apps

KU LEUVEN

OnDemand provides an integrated, single access point for all of your HPC resources.

Pinned Apps A featured subset of all available apps

 Active Jobs System Installed App	 Home Directory System Installed App	 Job Composer System Installed App	 Login Server Shell Access System Installed App
 code-server System Installed App	 Interactive Shell System Installed App	 Jupyter Lab System Installed App	 RStudio Server System Installed App
 Tensorboard System Installed App			



Open OnDemand

- E.g. to start a Jupyter Notebook
- Pick a valid Slurm credit account
- Default partition: batch
interactive: Max 8 cores, 1 GPU, 16 hr
- Default resources:
1 core, 1 hour, 3400MB RAM, no GPU
- (At the moment) you cannot use scratch and staging

Interactive Apps

Servers

● Interactive Shell

● Jupyter Lab

● RStudio Server

● Tensorboard

● code-server

Work in progress

● ParaViewWeb -
Work in progress

● cryosparc

Jupyter Lab

This app will launch a Jupyter Lab server on one or more nodes.

Account

lpt2_sysadmin

Partition

interactive

batch([long]) or bigmem or interactive or gpu or dedicated...

Number of hours

3

Number of cores

1

Required memory per core in megabytes

3400

Number of nodes

1

Number of gpu's

0

[type:] Specify the total number of GPUs slices for the job. An optional GPU type specification can be supplied. For example "A100:3" or "3".

Reservation (optional)

Name of an existing reservation in which the job should run

☐ I would like to receive an email when the session starts

Launch



Software Stack

Software: Available Modules

- OS: Linux CentOS 7.x (Genius) and Rocky Linux 8.x (wICE)
- Toolchains (Genius):
 - Intel 2018a (icc, icpc, ifort; Intel MPI; Intel MKL)
 - FOSS 2018a (gcc, g++, gfortran; OpenMPI; ScaLAPACK, OpenBLAS, FFTW)
- wICE: default is 2021a
- Note: **Never mix** FOSS and Intel compilers (gives dependency conflict)

Command	Remark
<code>module av</code>	List all installed modules
<code>module av Python</code>	List all Python-related modules
<code>module use /apps/leuven/icelake/2022b/modules/all</code>	Expose other modules from non-default toolchains, by including them in the search
<code>module spider Python</code>	Get more info
<code>module load Python/3.6.4-intel-2018a</code>	Load a specific module
<code>module list</code>	List all loaded modules and their dependencies
<code>module unload Python/3.6.4-intel-2018a</code>	Unload a module (but dependencies still stay)
<code>module purge</code>	Remove all modules from your work session

Software: Your Specific Needs

- You can always install your desired software in your \$VSC_DATA
Use Intel or FOSS toolchains
- Compile your code on a compute node (with interactive job)
- If you cannot, ask us for help
- Python/R packages for AI and ML must be installed by the users themselves
- Read more about [Python Package Management](#)
- Read more about [R Package Management](#)



Starting to Compute


Resource Glossary

- ❑ **Nodes:** how many compute servers to request?
- ❑ **Cores:** how many cores per node to use?
- ❑ **Memory requirement:** how much memory each core needs?
- ❑ **Partition:** gpu, bigmem, superdome, amd
- ❑ **Walltime:** how long to use resources?
- ❑ **Storage:** how much storage (data, scratch, etc) the job needs?
- ❑ **Credits:** how many compute credits will be consumed?




Serial Application

(1 process on 1 core)




Multi-Core Appl.

(N threads on N cores
from **1 node**)



Distributed Appl.

(many processes on
multiple cores/nodes)




Backfill


Nodes




Job queue




Interactive Job



Batch Job



Interactive Job on wICE



Remark

- Specifying `<project name>` for credits is mandatory, *e.g.*: **`-A lp_hpcinfo`**
- Implicit defaults for an interactive job on wICE are: `-n 1`, `-t 01:00:00`, `--mem-per-cpu=2000M`

Jobs: Slurm submit options

SLURM	Remarks
<code>--nodes=X --ntasks-per-node=Y</code> <code>--ntasks=X*Y</code> <code>--ntasks=X --cpus-per-task=Y</code>	or or (for Hybrid MPI/OpenMP only)
<code>--partition=gpu</code>	Default: "batch" partition
<code>--mem-per-cpu=XG</code>	Default: average memory/core
<code>--time=hh:mm:ss</code>	
<code>-J jobname</code>	
<code>-o <file_template></code>	output
<code>-e <file_template></code>	Default: same as stdout
<code>--mail-type=FAIL,BEGIN,END</code>	
<code>--mail-user=<mailaddress></code>	
<code>--export=ALL, key=value</code>	Additional variables to pass to job
<code>-A account</code>	Mandatory (credits)

Argument Shorthands

Some of the `sbatch`,
`srun` and `salloc`
command line arguments
have shorthands

Shorthand	Full Argument	Meaning
-A	--account	Slurm account name
-a	--array	Job array range
-M	--cluster	Machine or cluster name
-c	--cpus-per-task	Num cores per task (default=1)
-d	--dependency	Job dependency (after, afterok, afterany, ...)
-I	--input	STDIN filename
-e	--error	STDERR filename
-o	--output	STDOUT filename
-G	--gpus	Num GPUs per job
-t	--time	Maximum walltime
-N	--nodes	Minimum num nodes
-n	--ntasks	Maximum num tasks
-p	--partition	Partition name

Jobs: Defaults

If no explicit resources are given your job will start

- ✓ with 1 node 1 core,
- ✓ with walltime of 1hr
- ✓ in batch partition
- ✓ jobs with no cluster given start on Genius cluster (and get job-id ~760)
- ✓ soon the Slurm accounts will be available also on Genius (with the same account name)

Interactive Jobs

- Interactive job: 1 core for 1 hour (default)

```
$ srun -M wice -A lp_hpcinfo --pty /bin/bash -l
```

- Interactive job with X-forwarding

```
$ srun -M wice -A lp_hpcinfo -x11 --pty /bin/bash -l
```

- Request fraction of a node from interactive partition

```
$ srun -M wice -A lp_hpcinfo -N 1 -n 4 -p interactive --pty /bin/bash -l
```

- Request a GPU accelerator

```
$ srun -M wice -A lp_hpcinfo -N1 -n 18 -p gpu -G 1 --pty /bin/bash -l
```

Example: Slurm Job Script

Shebang

```
#!/bin/bash -l
#SBATCH --cluster wice
#SBATCH --account lp_hpcinfo
#SBATCH --nodes 1
#SBATCH --ntasks 4
#SBATCH --mem-per-cpu 4G
#SBATCH --job-name hpc_workflow
#SBATCH --mail-type BEGIN,END,FAIL
#SBATCH --mail-user my.name@kuleuven.be

Module --force purge
module load intel/2021a
module load Python/3.9.5-GCCcore-10.3.0
which python3

cd $VSC_SCRATCH/projects/simulations
cp -r $VSC_DATA/input_data .

python modelling.py

cp -r output_data $VSC_DATA
rm -rf ./input_data ./output_data
```

Resource List

Module load(s)

Move data

Execute commands

Move data

Batch Workload

- Submit the job to the batch server
- Receive a unique JobID
- Error and output files

Job Script

```
#!/bin/bash -l  
...
```

Command Line

```
$ sbatch simulation.slurm
```

JobID

Submitted batch job 60042478 on cluster wice

stderr, stdout

```
$ ls *.out  
slurm-60042478.out
```

Output File

- STDERR and STDOUT are by default redirected to a single file:
- `slurm-<JobID>.out`
- Contains job info, all errors and warnings, and printouts
- Always study it
- Address all warnings and errors (if you can)
- Typical error examples ...

STDOUT + STDERR

```
$ ls slurm-*.out  
slurm-60042478.out
```

Out of Memory

```
slurmstepd: error: Detected 1 oom-kill event(s).  
Some of your processes may have been killed by the  
cgroup out-of-memory handler.
```

Short Walltime

```
slurmstepd: error: *** JOB 60042478 ON s28c11n2  
CANCELLED AT 2023-02-08T10:03:43 DUE TO TIME LIMIT  
***
```

Low Disk Space

```
IOError: [Errno 122] Disk quota exceeded
```

Output File

- Always created
- `slurm-<job_id>.out`
- Contains all standard output and error (instead of screen)
- Always study it
- Standard Output and Error channels can be redirected to other files:
#SBATCH --output ...
#SBATCH --error ...

stdout

```
$ ls slurm-*.out  
slurm-60041238.out
```

Output File

```
SLURM_JOB_ID: 60033947  
SLURM_JOB_USER: vscXXXXX  
SLURM_JOB_ACCOUNT: lp_wice_pilot  
SLURM_JOB_NAME: testjob  
SLURM_CLUSTER_NAME: wice  
SLURM_JOB_PARTITION: batch  
SLURM_NNODES: 1  
SLURM_NODELIST: m28c30n4  
SLURM_JOB_CPUS_PER_NODE: 72  
Date: Tue Jan 10 17:02:04 CET 2023  
Walltime: 00-01:00:00  
=====  
/apps/leuven/icelake/2021a/software/  
intel-compilers/2021.2.0/compile  
r/2021.2.0/linux/bin/intel64/icc  
cp: cannot stat '/apps/leuven/trai  
ning/test': No such file or directo  
ry  
Hello World
```

Resource
Summary

Stdout

Inspecting Jobs

Example

```
$ scontrol show job -M wice 60049330
JobId=60049330 JobName=f70.slurm
  UserId=vsc3...(253...) GroupId=vsc3...(253...)
Account=lp_metacommunity_models QOS=lp_metacommunity_models
JobState=PENDING Reason=QOSGrpBillingMinutes
SubmitTime=2023-02-16T00:24:58 EligibleTime=2023-02-16T00:24:58
Partition=batch NodeList= NumNodes=4-4 NumCPUs=288 NumTasks=288 CPUs/Task=1
TRES=cpu=288,mem=979200M,node=4,billing=733
MinCPUsNode=72 MinMemoryCPU=3400M
WorkDir=/vsc-hard-mounts/leuven-data/3../vsc3.../Odonate_SOM
StdErr=/vsc-hard-mounts/leuven-data/3../vsc3.../Odonate_SOM/slurm-60049330.out
StdIn=/dev/null
StdOut=/vsc-hard-mounts/leuven-data/3../vsc3.../Odonate_SOM/slurm-60049330.out
```

Diagnosis

Why is my job in pending/hold state?

Check out the “Reason” on Slurm docs: https://slurm.schedmd.com/resource_limits.html

Other Partitions on wICE

GPU

```
#SBATCH --partition=gpu
#SBATCH --nodes=1
#SBATCH --ntasks=18
#SBATCH --gpus-per-node=1
```

Big Memory

```
#SBATCH --partition=bigmem
#SBATCH --nodes=1
#SBATCH --tasks-per-node=72
#SBATCH --mem-per-cpu=28000M
```

Managing & Monitoring Jobs

Command	Purpose
<code>sbatch ...</code>	Submit a batch job
<code>srun ...</code>	Submit an interactive job
<code>scancel --cluster=wice <JobID></code>	Cancel a specific pending or running job
<code>scontrol show job --cluster=wice <JobID></code> <code>slurm_jobinfo <JobID></code>	Detailed job info (very useful to diagnose issues)
<code>squeue --cluster=wice -long</code>	Status of all recent jobs
<code>squeue --cluster=wice -start</code>	Give a <i>rough</i> estimate of start time
<code>sinfo --cluster=wice</code>	Info about the state of available partitions and nodes
<code>sacct --cluster=wice --batch --job <JobID></code>	Show minimal info about a queue or partition
<code>slurmtop --cluster=wice</code>	Overview of the cluster

Interactive Partition

- Accessible via command line and Open OnDemand
- To quickly compile, test, debug your (parallel) application
- To pre-/post-process your data and make visualizations
- Short queue time
- 5 dedicated nodes on wICE
- 64 cores per node, 1 GPU (=7 GPU instances), 512 GB memory
- Max resource per user: 8 cores, 1 GPU instance, 16 hour walltime

Interactive Job


```
$ srun -n 1 -p interactive -t 16:00:00 -G 1 --pty bash -l
```

Singularity Containers

- What?
 - + Self-contained OS & software & data
- Why?
 - + fully resolved dependency chains
 - + portable workflow
- How?
 - + You create the image
 - + Run it on Genius
 - + MPI/OpenMP is supported

Slurm Script

```
#!/bin/bash -l
#SBATCH -t 30:00
#SBATCH -N 2
#SBATCH -n 72
#SBATCH -M wice
#SBATCH -A lp_hpcinfo
singularity run Project.simg ./model.exe
```



Credits

Credits card concept:

- **Pre-authorization**: holding the balance as unavailable until the merchant clears the transaction
- Balance to be held as unavailable: based on requested resourced (walltime, nodes)
- **Actual charge** based on what was really used: used walltime (you pay only what you use, e.g. when job crashes)
- See output file

How to check the rates?
Check service catalogue

How to check available credits?

```
$ sam-balance
```

Did the new credits arrive?

```
$ sam-list-allocations
```


Credit Pricing

- You pay as you go!
- For academic projects:
1000k credits = 3.5 EUR
- Credits needed for a job:

$$\text{\#credits (k)} = \text{Walltime (hr)} \times \text{\#nodes} \times \text{Factor}$$

- For shared nodes, you pay a fraction of the costs, based on the ppn specified

Cluster / Partition	Credits/hr
Genius Cascadelake	11.3
Genius Cascadelake 8 GPUs	40
Genius Skylake 4 GPUs	20
Genius Skylake BigMem	12
Genius Skylake	10
Genius / Superdome	10
Genius / AMD nodes	10
wICE / Thinnode	10,99
wICE Bigmem	19
wICE / 1 GPU	11,25
wICE 4GPUs	45
wICE Interactive	-

How to Manage Credits?

Command	Purpose
<code>sam-balance</code>	List active projects and available credits
<code>sam-list-allocations</code>	List the validity dates of different projects/allocations
<code>sam-list-usagerecords</code>	List current charge rates for different nodes
<code>sam-statement -A <account-name></code>	Job statements from an account



Conda Package Management: Python and R

Conda on wice

https://docs.vscentrum.be/en/latest/software/python_package_management.html?highlight=iniconda#install-python-packages-using-conda

- ✓ Good practice would be 2 separate paths of conda installations for each cluster.
- ✓ Beginning of the slurm script matters. Use `#!/bin/bash -l` not `#!/bin/bash` to load the env properly.
- ✓ Universal `.bashrc`


```
case ${VSC_INSTITUTE_CLUSTER} in
    genius)
        export PATH="${VSC_DATA}/miniconda3/bin:${PATH}"
        ;;
    wice)
        export PATH="${VSC_DATA}/miniconda3-wice/bin:${PATH}"
        ;;
esac
```




Worker Framework


Sequential...

- A shell program consists of a sequential list of commands
- -> bash script on HPC cluster will run sequentially




Sequential...

- A shell program consists of a sequential list of commands
- -> bash script on HPC cluster will run sequentially




Parallel Computing

- Serial:
 - one program, on one core
- 'Embarrassingly parallel' problems:
 - lots of runs of one program, with different parameters
- Problems that require 'real' parallel algorithms
 - OpenMP
 - MPI : Message Passing Interface



Talk to us about
worker framework



Lucky
you!

Use case: parameter exploration

temperature	pressure	humidity
293.0	1.0e05	87
...
313.0	1.3e05	75

```
#!/bin/bash -l
#SBATCH --cluster=wise
#!/bin/bash -l
#SBATCH --cluster=wise
#!/bin/bash -l
#SB #SB #!/bin/bash -l
#SB #SB #SBATCH --cluster=wise
#SB #SB #SBATCH --nodes=1
#SB #SB #SBATCH --ntasks-per-node=1
cd #SB #SBATCH --time=10:00
wea #SB #SBATCH -A lp_myproject
...
wea
...
cd $SLURM_SUBMIT_DIR
weather -p 1.0e05 -t 293.0 -h 87
```

job_030.slurm

job_600.slurm

Many single core computations

Solution: worker with -data

temperature	pressure	humidity
293.0	1.0e05	87
...

data.csv

```
#!/bin/bash -l
#SBATCH --cluster=wice
#SBATCH --nodes=2
#SBATCH --ntasks-per-node=72
#SBATCH --time=01:00:00
#SBATCH -A lp_hpcinfo

cd $SLURM_SUBMIT_DIR
weather -p $pressure -t $temperature -h $humidity
```

job.slurm


```
#From wICE interactive session:
$ module --force purge
$ module use /apps/leuven/icelake/2021a/modules/all
$ module load worker/1.6.12-foss-2021a-wice
$ wsub -data data.csv -batch job.slurm
```

Data exploration: steps

- Write PBS script with parameters
- Create Excel sheet with data
 - Convert to CSV format
- Submit with `wsub`
 - `walltime` is time to complete all work items

$$walltime_{\text{job}} \geq \frac{N \cdot walltime_{\text{work item}}}{nodes \cdot ppn}$$

worker processing: informally



How to use worker well?

- Many work items, i.e., $\text{\#work items}/\text{\#proc} \gg 1$
- $\text{time}(\text{work item}) > 1 \text{ minute}$
- Work item is not multithreaded
- Work item is multithreaded
 - will work, but user must be careful to request the right resources
 - Use `-threaded <n>` flag with `wsub`
- There be dragons: licensing!

worker & multithreading

- Some software uses multithreading automatically, e.g.,
 - R
 - Matlab
- Will use as many threads as there are cores, regardless of system load
 - 36 cores/node
 - 36 work items/node

} **36 × 36** threads/node

Oversubscription: ***very inefficient!!!***

Controlling number of threads

- R, most of the time: `OMP_NUM_THREADS=1`
- Matlab
 - Use `maxNumCompThreads(1)` function call
 - Use compiler flag: `mcc -singleCompThread ...`

```
#!/bin/bash -l
#SBATCH -account=lp_myproject
#SBATCH --cluster=wise
#SBATCH --time=1:00:00
#SBATCH --nodes=2
#SBATCH --ntasks-per-node=72

module load R
cd $SLURM_SUBMIT_DIR

export OMP_NUM_THREADS=1
Rscript program $a $b
```

program_pe.slurm

Help on worker

- See documentation
<http://worker.readthedocs.io/>
 - Each command has help, use `-h`
-
- ✓ All resources have to be specified inside slurm script
 - ✓ `wresume` does not work yet. Only `wsub` is so far supported
 - ✓ `-master` flag does not work yet

Submitting worker jobs

From wICE (Interactive) Node

```
$ module av worker
```

```
----- /apps/leuven/icelake/2021a/modules/all -----  
worker/1.6.12-foss-2021a
```

From Genius Login Node

```
$ module use /apps/leuven/skylake/2021a/modules/all
```

```
$ module av worker
```

```
----- /apps/leuven/skylake/2021a/modules/all -----  
  
worker/1.6.12-foss-2021a-slurm      worker/1.6.12-intel-2021a-slurm  
worker/1.6.12-foss-2021a-wice      worker/1.6.12-foss-2021a  
worker/1.6.12-intel-2021a      (D)
```

Submitting worker jobs

- ✔ Let us use one of the worker examples:
https://github.com/gjbex/worker/tree/development_slurm/examples/bash_example

- ✔ alp.slurm

```
#!/bin/bash -l
#SBATCH --nodes=1
#SBATCH --ntasks-per-node 27
#SBATCH --time=00:30:00
#SBATCH -A lpt2_sysadmin
#SBATCH --cluster=wice
cd $SLURM_SUBMIT_DIR
alphabet.sh $letter $counter
```

alpha.csv

```
letter,counter
a,1
b,2
c,3
d,4
e,5
f,6
...
```


Submitting worker jobs

✓ From Genius

```
#!/bin/bash -l
module purge
module use /apps/leuven/skylake/2021a/modules/all
module load worker/1.6.12-foss-2021a-wice
wsub -batch alp.slurm -data alpha.csv
```

```
total number of work items: 26
Submitted batch job 60008899 on cluster wice
```

Submitting worker jobs

- ✔ From interactive job on wICE

```
#!/bin/bash -l
module --force purge
module use /apps/leuven/icelake/2021a/modules/all
module load worker/1.6.12-foss-2021a
wsub -batch alp.slurm -data alpha.csv
```

```
total number of work items: 26
Submitted batch job 60008889 on cluster wice
```

The background is a vibrant, hand-drawn illustration. On the left, a city with tall, arched buildings and a clock tower is visible. A large, semi-circular clock face dominates the center, featuring a green leaf with a black keyhole in its center. To the right of the clock face, a large, ornate necklace with blue and red gemstones is displayed. The entire scene is set against a backdrop of a blue sky with white clouds and green trees.

Demo: Test for yourself

demo/test yourself

- ✓ Request membership to lp_hpcinfo group (account.vscentrum.be)
- ✓ Login with putty
- ✓ Filetransfer with Filezilla
- ✓ Login with NX
- ✓ Check disk quota
- ✓ Check the credits
- ✓ Check/load/list/unload/purge module

demo/test yourself

- ✓ Copy intro training files `/apps/leuven/training/HPC_intro/` to your `$VSC_DATA`
- ✓ Submit `cpujob` to the cluster
- ✓ List all your jobs `squeue -M wice`
- ✓ Check the information about the `cpujob` `slurm_jobinfo -M wice <job_ID>`
- ✓ Modify the `mpi.slurm` script to request 1 node, 72 cores for 30 minutes and get the notification about job start/end by e-mail
- ✓ Check the status of all the jobs

demo - monitoring

- ✓ Submit an interactive job

Run your program on a compute node

Open a new terminal and ssh to a compute node

Check the resources usage (`top`)

- ✓ Submit a batch GPU job

While the job is running get the information about the node `slurm_jobinfo...`

and check usage of resources on the node `ssh, top, nvidia-smi`

demo – conda installation

✓ Install miniconda in your `$VSC_DATA` directory

- `$ wget https://repo.continuum.io/miniconda/Miniconda3-latest-Linux-x86_64.sh`
- `$ bash Miniconda3-latest-Linux-x86_64.sh -b -p $VSC_DATA/miniconda3`

✓ Add a PATH to conda:

- `$ export PATH="$VSC_DATA/miniconda3/bin:${PATH}"`

✓ Check if conda is added to your `$PATH` (`$ which conda`)

Add it to `$PATH` in your `.bashrc`

- `$ echo 'export PATH="$VSC_DATA/miniconda3/bin:${PATH}"' >> .bashrc`

demo – conda usage

- ✓ Create a conda environment including Jupyter

```
$ conda create -n science jupyter numpy scipy
```

- ✓ Activate this environment

```
$ source activate science
```

- ✓ Add matplotlib package to this environment

```
$ conda install matplotlib
```

- ✓ Return to original environment

```
$ conda deactivate
```

demo – worker

- ✓ Copy intro training files (`/apps/leuven/training/worker/`) to your `$VSC_DATA`
- ✓ Go to `exercise1` directory
- ✓ Submit worker job
- ✓ Check the output file

Command	Purpose
\$ sbatch ...	Submit a batch job
\$ srun ...	Submit an interactive job
\$ scancel --cluster=wice <JobID>	Cancel a specific pending or running job
\$ scontrol show job --cluster=wice <JobID> \$ slurm_jobinfo <JobID>	Detailed job info (very useful to diagnose issues)
\$ squeue --cluster=wice --long	Status of all recent jobs
\$ squeue --cluster=wice --start	Give a rough estimate of start time
\$ sinfo --cluster=wice	Info about the state of available partitions and nodes
\$ sacct --cluster=wice --batch --job <JobID>	Show minimal info about a queue or partition (-p)
\$ slurmtop \$ scontrol --cluster=wice show node <hostname>	Overview of the cluster Get detailed information about the status of a node
\$ sam-balance	Overview of all your available credit projects
\$ sam-list-allocations	Detailed overview of your credit allocation history

Questions

Helpdesk:

hpcinfo@kuleuven.be or https://admin.kuleuven.be/icts/HPInfo_form/HPC-info-formulier

VSC web site:

<http://www.vscentrum.be/>

VSC documentation: <https://docs.vscentrum.be/en/latest/>

VSC agenda: training sessions, events

Systems status page:

<http://status.vscentrum.be>

*Stay Connected
to VSC*

Linked  [®]

