

HANDS-ON 3

Task	Hint
Start the Terminal 1. Display all the environment variables that refer to paths Copy .bashrc file from your home directory to \$VSC_HOME/.barhrc-orig	env grep PATH cp \$VSC_HOME/.bashrc \$VSC_HOME/.bashrc-orig
2. Create a directory in your \$VSC_SCRATCH dir that has a name of output of <code>uname -s</code> command Create a file called system in that directory that includes information given by <code>uname -a</code> command Add the following information to that file: VSC_INSTITUTE is \$VSC_INSTITUTE and I am \$USER where \$USER and \$ VSC_INSTITUTE are refer to environment variables Display the file	mkdir \$VSC_SCRATCH/`uname -s` echo `uname -a`> \$VSC_SCRATCH/`uname -s`/system echo "VSC_INSTITUTE is \$VSC_INSTITUTE and I am \$USER" >> \$VSC_SCRATCH/`uname -s`/system cat \$VSC_SCRATCH/`uname -s`/system
3. Define a new directory doc that refers to \$VSC_HOME/Documents and directory downloads that refers to \$VSC_HOME/Downloads Go to downloads dir and then do to doc dir. Go back to your home directory. Print the value of doc variable	export doc=\$VSC_HOME/Documents export downloads=\$VSC_HOME/Downloads cd \$downloads cd \$doc cd echo \$doc
4. Make an alias so that la command refers to ls -la Test ls on your \$VSC_HOME dir Open a new session and check if the command works Add alias to your .bashrc file Open a new session and check if the command works	alias la='ls -la' cd; la

5. Print the value of PS1 Save it to ps.txt file in your home dir Try to experiment and create your own PS1, e.g. PS1="\e[0m \$LOGNAME \e[0m \e[36m\h\e[0m \e[32m\t\e[0m [:\l] -\j-\e[31m\w\e[0m \n\e[36m> \e[0m" or PS1=":\e[0m \$LOGNAME@\e[31m\h\e[0m \W \$" When satisfied add it to your .bashrc file and open a new session to test it	<pre>echo \$PS1 echo \$PS1> \$VSC_HOME/ps.txt unset PROMPT_COMMAND</pre>
6. Get back the original .bashrc file	<pre>cp \$VSC_HOME/.bashrc-orig \$VSC_HOME/.bashrc</pre>