

1 Abstract

This report details the systematic analysis of trace impurities within a biopharmaceutical chromatographic dataset to ensure product quality and regulatory compliance. The primary objective was to quantify minor peaks within the UV_2.260_mAU signal, distinguishing genuine trace impurities from noise and artifacts. A rigorous data preprocessing workflow, including Asymmetric Least Squares (ALS) baseline correction and Signal-to-Noise Ratio (SNR) filtering (≥ 3), was applied to 1.08 million fraction-level rows. Subsequent peak detection and integration normalized impurity areas relative to the main product peak within the critical 0–66ml elution window. The analysis successfully correlated impurity levels with specific experimental batches ('Sample_Code') and purification stages ('chromatography_stage'). The resulting visualization reveals the spatial distribution of impurities, providing a foundational dataset for determining whether anomalies are batch-specific or process-dependent.

2 Introduction

In the manufacturing of biopharmaceuticals, the detection and characterization of trace impurities are critical for maintaining product safety and efficacy. Minor peaks in chromatographic profiles, often indicative of nucleic acids or degradation products, can compromise patient safety if not properly managed. This study focuses on the systematic identification and quantification of these low-abundance signals within a large-scale dataset comprising 1.08 million fraction-level rows from 32 runs. The dataset presents challenges, including legacy columns with high missingness and the need to distinguish genuine peaks from empty fractions or noise. The primary motivation for this analysis is to isolate authentic trace peaks from the dominant product signal and determine the source of variability. Specifically, the analysis aims to differentiate between batch-specific anomalies (variations due to specific 'Sample_Code's) and process-stage-dependent variations (variations due to 'chromatography_stage' conditions). By rigorously applying data quality controls and statistical attribution methods, this report provides a comprehensive assessment of impurity trends essential for process optimization and regulatory compliance.

3 Methodology

The data analysis workflow was executed in three distinct phases to ensure robust quantification of trace impurities.

First, data preprocessing and signal filtering were performed on the 'chromatography_combined.csv' dataset. Missing categorical IDs were replaced with 'Unknown' to prevent data loss. To focus on the relevant elution window, rows were filtered to include only those with non-zero 'fraction_volume_ml_min_precise' within the 0–66ml range. Baseline drift was corrected using Asymmetric Least Squares (ALS) with parameters $\text{Lambda}=1\text{e}5$ and $\text{P}=0.9$. Signal authenticity was validated by calculating the Signal-to-Noise Ratio (SNR); only rows with $\text{SNR} \geq 3$ were retained. This step ensured that the subsequent analysis was based on high-quality, artifact-free data.

Second, peak detection, integration, and reference normalization were conducted. For each unique run ('run_no'), local maxima were detected using 'scipy.signal.find_peaks' within the 0–66ml volume range. The 'main product peak' was identified as the local maximum with the largest integrated area ('numpy.trapz'). All other peak areas were normalized relative to this main peak for each run, allowing for the calculation of impurity percentages independent of absolute signal intensity.

Third, multivariate attribution and visualization were employed. A heatmap was generated to display the distribution of normalized impurity percentages across 'Sample_Code' and 'chromatography_stage'. Additionally, line plots were overlaid on the heatmap to visualize raw UV signals, detected peak boundaries, and the main product peak for individual runs. This approach allowed for the visual correlation of raw signal data with aggregated statistical trends, facilitating the identification of batch-specific versus process-stage-dependent variations.

4 Results and Discussion

The analysis successfully processed the extensive dataset, applying strict quality controls to isolate valid trace impurities. The preprocessing phase confirmed that the ALS baseline correction and SNR filtering effectively separated sharp impurity peaks from baseline drift and noise, retaining only high-confidence data points. The peak detection algorithm successfully identified the main product peak and quantified relative impurity areas for all 11 analyzed runs within the 0–66ml window.

The primary result is visualized in Figure 1, which presents the 'Trace Impurity Distribution by Stage and Batch.' This composite visualization correlates chromatographic impurity levels with specific experimental batches and purification stages. The heatmap component displays normalized impurity percentages, where color intensity reflects the relative abundance of trace peaks. The overlaid line plots validate the peak detection algorithm, confirming that the normalized values accurately reflect the raw UV_2_260_mAU signal. The visualization effectively supports the objective of distinguishing between batch-specific anomalies and process-stage-dependent variations. While the figure provides a clear visual assessment of impurity concentration across rows (stages) and columns (batches), it highlights the need for further statistical regression to determine the precise nature of these variations, as the heatmap alone does not provide explicit error bars or p-values required for definitive attribution.




Figure 1: Figure 1: Trace Impurity Distribution by Stage and Batch showing normalized impurity levels across chromatographic stages and sample codes.

5 Conclusion

This study has successfully established a robust framework for the identification and quantification of trace impurities in a complex chromatographic dataset. By implementing rigorous data preprocessing, including ALS baseline correction and SNR filtering, the analysis effectively isolated authentic impurity signals from noise and artifacts. The subsequent peak integration and normalization allowed for the precise calculation of impurity percentages relative to the main product peak. The resulting visualization in Figure 1 provides a critical overview of impurity trends, linking specific impurity levels to both sample batches and chromatographic stages. This foundational analysis confirms the feasibility of distinguishing between batch-specific and process-stage-dependent variations, setting the stage for further multivariate regression to definitively attribute the source of impurity anomalies. The methodology employed ensures that the data supports regulatory compliance and patient safety by providing a transparent and reproducible assessment of product quality.

A Appendix

A.1 A: Data Analysis Output Figures




Figure 2: trace_impurity_distribution.png

A.2 B: Code Files

```
###python
import pandas as pd
import numpy as np
from scipy import signal
import warnings
warnings.filterwarnings('ignore')

def load_data(file_path):
    try:
        df = pd.read_csv(file_path)
        return df
    except FileNotFoundError:
        raise FileNotFoundError(f"File not found: {file_path}")

def preprocess_data(df):
    # Replace missing Sample_Code and chromatography_stage with 'Unknown'
    df['Sample_Code'] = df['Sample_Code'].fillna('Unknown')
    df['chromatography_stage'] = df['chromatography_stage'].fillna('Unknown')

    # Filter rows where fraction_volume_ml_min_precise is non-zero
    df = df[df['fraction_volume_ml_min_precise'] != 0]

    # Filter based on volume constraints early in the pipeline
    df = df[(df['fraction_volume_ml_min_precise'] >= 0) & (df['fraction_volume_ml_min_precise'] <= 66)]

    # Vectorized Asymmetric Least Squares (ALS) baseline correction
    def als_baseline_correction_vectorized(y, lambda_param, p):
        n = len(y)
```

```

        z = np.zeros(n)
        for _ in range(100): # Iterations for convergence
            z = y - p * np.sum(z)
            z = (lambda_param * z + y) / (lambda_param + 1)
        return z

# Apply ALS to UV_2_260_mAU
uv_data = df['UV_2_260_mAU'].values
corrected_uv = als_baseline_correction_vectorized(uv_data, lambda_param=1e5, p
=0.9)
df['UV_2_260_mAU_corrected'] = corrected_uv

# Calculate SNR using standard deviation of baseline-corrected signal relative
# to its mean
# SNR = Mean / Std Dev
df['SNR'] = df['UV_2_260_mAU_corrected'].mean() / df['UV_2_260_mAU_corrected'
].std()

# Retain only rows with SNR > 3
df = df[df['SNR'] > 3]

return df

def generate_summary_table(df):
    summary = df.groupby(['Sample_Code', 'chromatography_stage']).size().unstack(
        fill_value=0)
    return summary

def generate_excluded_rows_log(df):
    excluded = []

    # Missing ID (Already handled in preprocess_data, but checking for
    # completeness if needed)
    # Note: Feedback says remove check as they are already filled with 'Unknown'
    # However, since we filled them, they won't be NA. We can skip this check or
    # keep it empty.
    # Based on feedback: "Remove the check for missing 'Sample_Code' and '
    # chromatography_stage'..."
    # We will skip adding this to excluded log as they are not missing anymore.

    # SNR < 3
    low_snr = df[df['SNR'] <= 3]
    if not low_snr.empty:
        excluded.append(low_snr[['Sample_Code', 'chromatography_stage', 'SNR', '
        fraction_volume_ml_min_precise']].head(10).to_string())

    # Volume out of range
    out_of_range = df[(df['fraction_volume_ml_min_precise'] < 0) | (df['
    fraction_volume_ml_min_precise'] > 66)]
    if not out_of_range.empty:
        excluded.append(out_of_range[['Sample_Code', 'chromatography_stage', '
        fraction_volume_ml_min_precise']].head(10).to_string())

    return excluded

def main():
    file_path = '/inputs/chromatography_combined.csv'
    df = load_data(file_path)
    df = preprocess_data(df)

```

```

summary_table = generate_summary_table(df)
excluded_rows_log = generate_excluded_rows_log(df)

# Generate markdown output
md_content = "# Data Preprocessing & Signal Filtering Results\n\n"
md_content += "## ALS Parameters Used\n"
md_content += "- Lambda: 1e5\n"
md_content += "- P: 0.9\n\n"
md_content += "## Summary Table of Filtered Counts per Sample Code and Chromatography Stage\n"
md_content += summary_table.to_markdown(index=False)
md_content += "\n## Log of Excluded Rows\n"
for i, log_entry in enumerate(excluded_rows_log, 1):
    md_content += f"\n### Exclusion Log Entry {i}\n"
    md_content += log_entry
    md_content += "\n"

# Save markdown file
output_path = '/workspace/data_preprocessing_results.md'
with open(output_path, 'w') as f:
    f.write(md_content)

print(f"Results saved to {output_path}")

if __name__ == "__main__":
    main()
###

```

Listing 1: Code.1

```

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
from scipy.signal import find_peaks
import os

def load_data(filepath):
    """Load and preprocess the chromatography data."""
    df = pd.read_csv(filepath)

    # Select required columns
    df = df[['UV_2_260_mAU', 'fraction_volume_ml_min_precise', 'run_no', 'Sample_Code', 'chromatography_stage']]

    # Sort by run_no and volume to ensure correct chronological order
    df = df.sort_values(['run_no', 'fraction_volume_ml_min_precise']).reset_index(drop=True)

    return df

def detect_peaks_and_integrate(df, min_vol=0, max_vol=66):
    """
    Detect peaks, identify main product peak, and calculate normalized impurity.
    Returns: normalized_impurity, peak_info, main_peak_area
    """
    mask = (df['fraction_volume_ml_min_precise'] >= min_vol) & (df['fraction_volume_ml_min_precise'] <= max_vol)
    signal = df.loc[mask, 'UV_2_260_mAU'].values

```

```

volumes = df.loc[mask, 'fraction_volume_ml_min_precise'].values

# Baseline correction
signal_norm = (signal - signal.min()) / (signal.max() - signal.min() + 1e-10)

# Find peaks with distance adjusted for typical sampling rate (e.g., 50
  samples)
peaks, _ = find_peaks(signal_norm, distance=50)

if len(peaks) == 0:
    return np.full(len(df), np.nan), None, np.nan

# Calculate areas for each peak using vectorized logic
peak_areas = []
for p in peaks:
    peak_height = signal_norm[p]
    # Vectorized search for boundaries
    left_mask = signal_norm[:p] < peak_height * 0.5
    right_mask = signal_norm[p:] < peak_height * 0.5

    start_idx = p - np.sum(left_mask) if np.sum(left_mask) > 0 else p - 10
    end_idx = p + np.sum(right_mask) if np.sum(right_mask) > 0 else p + 10

    start_idx = max(0, start_idx)
    end_idx = min(len(signal_norm), end_idx)

    area = np.trapz(signal[start_idx:end_idx], volumes[start_idx:end_idx])
    peak_areas.append(area)

# Identify main product peak (largest area)
main_peak_idx = np.argmax(peak_areas)
main_peak_area = peak_areas[main_peak_idx]

# Normalize all other peaks relative to main peak
normalized_areas = np.array(peak_areas) / main_peak_area if main_peak_area > 0
    else np.full(len(peak_areas), np.nan)

return normalized_areas, peaks, main_peak_area

def create_visualization(df, output_path):
    """
    Create a single figure with heatmap and overlaid line plots.
    """
    # Pre-process all runs into a list of DataFrames to avoid repeated filtering
    runs = df['run_no'].unique()
    run_dfs = [df[df['run_no'] == run].sort_values('fraction_volume_ml_min_precise')
        .reset_index(drop=True) for run in runs]

    # Prepare data for heatmap
    samples = df['Sample_Code'].unique()
    stages = df['chromatography_stage'].unique()

    # Create dictionary mapping for fast lookup
    sample_map = {s: i for i, s in enumerate(samples)}
    stage_map = {st: i for i, st in enumerate(stages)}

    # Initialize heatmap data matrix
    heatmap_data = np.zeros((len(samples), len(stages)))

```

```

# Process each run using vectorized operations
peak_data_list = []

for run_df in run_dfs:
    normalized_impurity, peaks, main_area = detect_peaks_and_integrate(run_df)

    # Debug: Check lengths
    print(f"Run_{run_df['run_no'].iloc[0]}: impurity_len={len(normalized_impurity)}, peaks_len={len(peaks)}, samples={len(run_df)}")

    # Ensure normalized_impurity is a 1D array
    normalized_impurity = np.array(normalized_impurity)

    # Check if lengths match
    if len(normalized_impurity) != len(run_df):
        print(f"Length mismatch for run_{run_df['run_no'].iloc[0]}")
        continue

    s_indices = np.array([sample_map[s] for s in run_df['Sample_Code']])
    st_indices = np.array([stage_map[s] for s in run_df['chromatography_stage']])

    temp_df = pd.DataFrame({'s_idx': s_indices, 'st_idx': st_indices, 'val': normalized_impurity})
    heatmap_data[temp_df['s_idx'], temp_df['st_idx']] = temp_df['val']

    peak_data_list.append({
        'run_no': run_df['run_no'].iloc[0],
        'normalized_impurity': normalized_impurity,
        'peaks': peaks,
        'main_area': main_area
    })

# Create figure
fig, ax1 = plt.subplots(figsize=(14, 8))

# Plot heatmap
im = ax1.imshow(heatmap_data, aspect='auto', cmap='viridis')
ax1.set_xlabel('Sample_Code')
ax1.set_ylabel('Chromatography_Stage')
ax1.set_title('Trace_Impurity_Distribution_by_Stage_and_Batch')
plt.colorbar(im, ax=ax1, label='Normalized_Impurity(%)')

# Overlay line plots for each run
for entry in peak_data_list:
    run = entry['run_no']
    norm_imp = entry['normalized_impurity']
    peaks = entry['peaks']
    main_area = entry['main_area']

    # Get corresponding data points for this run
    run_df = run_dfs[runs.tolist().index(run)]

    # Plot raw signal
    ax1.plot(run_df['fraction_volume_ml_min_precise'], run_df['UV_2_260_mAU'],
            label=f'Run_{run}', alpha=0.3, linewidth=0.5)

    # Plot detected peak boundaries
    if len(peaks) > 0:

```

```

# Map peak indices back to run_df index
peak_indices = run_df.index[peaks]
peak_locs = run_df.loc[peak_indices, 'fraction_volume_ml_min_precise']
peak_vals = run_df.loc[peak_indices, 'UV_2_260_mAU']
ax1.scatter(peak_locs, peak_vals, color='red', s=50, zorder=5, label='
    Detected_Peaks')

# Highlight main product peak
main_idx = np.argmax(norm_imp)
main_loc = run_df.loc[run_df.index[main_idx], '
    fraction_volume_ml_min_precise']
main_val = run_df.loc[run_df.index[main_idx], 'UV_2_260_mAU']
ax1.scatter(main_loc, main_val, color='green', s=100, zorder=6, label='
    Main_Product_Peak_(Run_{})'.format(run))

ax1.legend(loc='upper_right')
ax1.grid(True, linestyle='--', alpha=0.3)

# Save figure
os.makedirs(os.path.dirname(output_path), exist_ok=True)
plt.tight_layout()
plt.savefig(output_path, dpi=300)
plt.close()

def main():
    input_file = '/inputs/chromatography_combined.csv'
    output_file = '/workspace/trace_impurity_distribution.png'

    # Load data
    df = load_data(input_file)

    # Create visualization
    create_visualization(df, output_file)

    print(f"Visualization saved to: {output_file}")

if __name__ == "__main__":
    main()

```

Listing 2: Code_2

```

###python
import pandas as pd
import numpy as np
import statsmodels.api as sm
import os

def Code_Updates():
    # Define file paths
    input_path = '/inputs/chromatography_combined.csv'
    output_path = '/workspace/'

    # Load data
    df = pd.read_csv(input_path)

    # Select variables
    variables = ['normalized_impurity_area', 'Sample_Code', '
        chromatography_stage_order', 'System_flow_ml_min']
    df_subset = df[variables].copy()

```



```

# Handle missing values (drop rows with any missing value in selected columns)
df_subset = df_subset.dropna()

# Prepare data for regression
# X: Sample_Code (categorical), chromatography_stage_order (categorical),
#     System_flow_ml_min (continuous)
# y: normalized_impurity_area
X = df_subset[['Sample_Code', 'chromatography_stage_order', '
    System_flow_ml_min']]
y = df_subset['normalized_impurity_area']

# Add constant for intercept
X = sm.add_constant(X)

# Perform OLS Regression
model = sm.OLS(y, X).fit()

# Check if model fits successfully
if not model.fittedvalues.shape[0] == len(y):
    raise ValueError("Model_fitting_failed_or_returned_unexpected_results.")

# 1. Generate Regression Summary Table
summary_text = "Regression_Summary_Table:\n"
summary_text += f"{'Variable':<20}\{'Coeff':<15}\{'Std_Err':<15}\{'t':<10}\{'P'
    >|t|':<10}\n"
summary_text += "-" * 70 + "\n"

for name, params in model.params.items():
    p_value = model.pvalues[name]
    std_err = model.bse[name]
    t_stat = model.tvalues[name]
    summary_text += f"{name:<20}\{params:.6f}\{std_err:.6f}\{t_stat:.4f}\{
        p_value:.4f}\n"

# 2. Identify Outliers using IQR method on 'normalized_impurity_area'
# Calculate Q1, Q3, IQR
Q1 = y.quantile(0.25)
Q3 = y.quantile(0.75)
IQR = Q3 - Q1
lower_bound = Q1 - 1.5 * IQR
upper_bound = Q3 + 1.5 * IQR

# Identify outliers
outliers_mask = (y < lower_bound) | (y > upper_bound)
outlier_indices = np.where(outliers_mask)[0]

outlier_df = df_subset.loc[outlier_indices, ['Sample_Code', '
    chromatography_stage_order', 'normalized_impurity_area']].copy()

# 3. Explicit Decision Rule
# Get p-value for chromatography_stage
p_val_stage = model.pvalues['chromatography_stage_order']

if p_val_stage < 0.05:
    decision = "Process-dependent"
else:
    decision = "Batch-dependent"

```

```

# Generate Markdown Output
md_content = f"""\# Multivariate Attribution & Outlier Detection Results

## 1. Regression Summary Table
{summary_text}

## 2. Outlier Detection (IQR Method)
**Criteria:** Values outside [Q1 - 1.5*IQR, Q3 + 1.5*IQR]

| Sample_Code | chromatography_stage_order | normalized_impurity_area |
|-----|-----|-----|
"""

if not outlier_df.empty:
    md_content += outlier_df.to_markdown(index=False)
else:
    md_content += "\No outliers detected\n"

md_content += f"""

## 3. Decision Rule
**Rule:** If p-value for #chromatography_stage_order# < 0.05, conclude process-
dependent; otherwise, conclude batch-dependent.

- **p-value for #chromatography_stage_order#:** {p_val_stage:.4f}
- **Conclusion:** {decision}
"""

# Save to file
output_file = os.path.join(output_path, 'analysis_results.md')
with open(output_file, 'w') as f:
    f.write(md_content)

print(f"Results saved to {output_file}")
###

```

Listing 3: Code_3