

API Specifications for Block Storage

Author(s): *[Put in Author Names]*

Date: *[Date]*

Document Version: *[Put in the current document version]*

1. Overview

[Brief introduction and overview of the service and its intended use.]

The Bock team is developing the Block Storage Service for Nova. The service provides Virtual Block devices for virtual machines executing in Nova. The capability is derived from the original DM-Cache capability implemented as part of the Service Utility Platform (SUP). Bock volumes can store boot images, user data or both. We will target Nova-Diablo for the initial release of Bock. In the Nova architecture Bock is implemented as a set of nova volume driver classes. These classes provide a set of methods that allow different types of storage plugins.

1.1 API Maturity Level

[State the maturity level in which the API is in currently, based on the pre-defined stages i.e. Experimental (early Alpha, available internally only), Exploratory (Private-beta ready), Public (Public-beta ready), GA (Release to General Availability, SLAs defined).

The versions schema, status field, supports an enumeration of ALPHA, BETA, CURRENT and DEPRECATED. The versions->status field should correspond to the Maturity Level for the API, i.e. ALPHA for Experimental, BETA for Exploratory, CURRENT for Public and GA, DEPRECATED for all other versions of the API that are not supported anymore.]

Maturity Level: Exploratory - Bock is currently in restricted private beta in AW2/AZ2

Version API Status: BETA

2. Architecture View

Example info. and documentation for Bock is available on the [Bock Wiki page](#)

2.1 Overview

[References to architectural details of the service.]

2.2 Conceptual/Logical Architecture View

[Describe the logical components of the system and their responsibilities]

2.3 Infrastructure Architecture View

[Describe how the API fits into the overall HPCS Infrastructure]

2.4 Entity Relationship Diagram

[Describe the relationships between the various entities (resources) involved in the API]

3. Account-level View

[Describe the relationship of the API with respect to the accounts, groups, tenants, regions, availability zones etc.]

3.1 Accounts

[Describe the structure of the user accounts, groups and tenants. Currently this might be described separately in context of Control Services, but in future each service API needs to state their usage. In future CS might support complex group hierarchies, enterprise account structures while there maybe a phased adoption by individual service APIs]

3.2 Regions and Availability Zones

[Describe the availability of the service API in different regions and availability zones. State plans for future expansion as well.]

Region(s): region-a

Availability Zone(s): az-1, az-2, az-3

Future Expansion: region-b

3.3 Service Catalog

[Describe if the service API is exposed via the service catalog. Reference the fragment of the service catalog showing the structure.]

The Block Storage is exposed in the service catalog, as shown in the following fragment:

```
{
  "name": "Block Storage",
  "type": "volume",
  "endpoints": [
    {
      "tenantId": "<tenant_id>",
      "publicURL": "https://az-1.region-a.geo-1.compute.hpcloudsvc.com/v1.1/<tenant_id>",

```

```

        "region": "az-1.region-a.geo-1",
        "versionId": "1.1",
        "versionInfo": "https://az-1.region-a.geo-
1.compute.hpcloudsvc.com/v1.1/",
        "versionList": "https://az-1.region-a.geo-1.compute.hpcloudsvc.com"
    },
    {
        "tenantId": "<tenant_id>",
        "publicURL": "https://az-3.region-a.geo-
1.compute.hpcloudsvc.com/v1.1/<tenant_id>",
        "region": "az-3.region-a.geo-1",
        "versionId": "1.1",
        "versionInfo": "https://az-3.region-a.geo-
1.compute.hpcloudsvc.com/v1.1/",
        "versionList": "https://az-3.region-a.geo-1.compute.hpcloudsvc.com"
    },
    {
        "tenantId": "<tenant_id>",
        "publicURL": "https://az-2.region-a.geo-
1.compute.hpcloudsvc.com/v1.1/<tenant_id>",
        "region": "az-2.region-a.geo-1",
        "versionId": "1.1",
        "versionInfo": "https://az-2.region-a.geo-
1.compute.hpcloudsvc.com/v1.1/",
        "versionList": "https://az-2.region-a.geo-1.compute.hpcloudsvc.com"
    }
]
}

```

4. REST API Specifications

[Describe the API specifications, namely the API operations, and its details, documenting the naming conventions, request and response formats, media type support, status codes, error conditions, rate limits, quota limits, and specific business rules.]

4.1 Service API Operations

Host: https://az-1.region-a.geo-1.compute.hpcloudsvc.com

Base URI: [Host]/v1.1/<tenant_id>

Admin URI: N/A

Resource	Operation	HTTP Method	Path	JSON/XML Support?	Privilege Level
----------	-----------	-------------	------	-------------------	-----------------

Versions	Version information	GET	[Host]/v1.1/	Y/N
	Version list	GET	[Host]/	Y/N
Volumes	List volumes	GET	[BaseUri]/os-volumes	Y/N
	Create new volume	POST	[BaseUri]/os-volumes	Y/N
	Get volume details	GET	[BaseUri]/os-volumes/<volume_id>	Y/N
	Delete volume	GET	[BaseUri]/os-volumes/<volume_id>	Y/N
Servers	List attached volumes	GET	[BaseUri]/servers/<server_id>/os-volume_attachments	Y/N
	Attach a volume	POST	[BaseUri]/servers/<server_id>/os-volume_attachments/<volume_id>	Y/N
	Detach a volume	DELETE	[BaseUri]/servers/<server_id>/os-volume_attachments/<volume_id>	Y/N
Snapshots	List volume snapshots	GET	[BaseUri]/>/os-snapshots	Y/N
	Create new volume snapshot	POST	[BaseUri]/os-snapshots	Y/N
	Get volume snapshot details	GET	[BaseUri]/os-snapshots/<snapshot_id>	Y/N
	Delete volume snapshot	DELETE	[BaseUri]/os-snapshots/<snapshot_id>	Y/N

4.2 Common Request Headers

[List the common response headers i.e. X-Auth-Token, Content-Type, Content-Length, Date etc.]

4.3 Common Response Headers

[List the common response headers i.e. Content-Type, Content-Length, Connection, Date, ETag, Server, etc.]

4.4 Service API Operation Details

[The following section, enumerates each resource and describes each of its API calls as listed in the Service API Operations section, documenting the naming conventions, request and response formats, status codes, error conditions, rate limits, quota limits, and specific business

rules.]

4.4.1 Versions

[Describe versions and what information they provide.]

Status Lifecycle

N/A

Rate Limits

N/A

Quota Limits

N/A

Business Rules

None.

4.4.1.1 Get Version Info

GET /v1.1/

Lists the information about the current version of the API, like media types (json and xml), links to the public endpoint url, links to the WADL (if any), and links to the API documentation.

Status Codes

200 - OK

Request Formats

This call does not require a request body.

Response Formats

JSON

```
{
  "version": {
    "status": "CURRENT",
    "updated": "2011-01-21T11:33:21Z",
    "media-types": [
      {
        "base": "application/xml",
        "type": "application/vnd.openstack.compute-v1.1+xml"
      },
      {
        "base": "application/json",
        "type": "application/vnd.openstack.compute-v1.1+json"
      }
    ],
    "id": "v1.1",
    "links": [
      {
        "href": "https://az-1.region-a.geo-1.compute.hpcloudsvc.com/v1.1/",
        "rel": "self"
      },
      {
        "href": "http://docs.rackspacecloud.com/servers/api/v1.1/cs-devguide-20110125.pdf",
        "type": "application/pdf",
        "rel": "describedby"
      },
      {
        "href": "http://docs.rackspacecloud.com/servers/api/v1.1/application.wadl",
        "type": "application/vnd.sun.wadl+xml",
        "rel": "describedby"
      }
    ]
  }
}
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" [BaseUri]/v1.1/
```

4.4.1.2 List Versions

GET /

[The versions schema, status field, supports an enumeration of ALPHA, BETA, CURRENT and DEPRECATED. The versions->status field should correspond to the Maturity Level for the API, i.e. ALPHA for Experimental, BETA for Exploratory, CURRENT for Public and GA, DEPRECATED for all other versions of the API that are not supported anymore.]

Lists the information about all supported and deprecated versions with links to the public endpoint urls.

Status Codes

200 - OK

Request Formats

This call does not require a request body.

Response Formats

JSON

```
{
  "versions": [
    {
      "status": "CURRENT",
      "updated": "2011-01-21T11:33:21Z",
      "id": "v1.1",
      "links": [
        {
          "href": "https://az-1.region-a.geo-1.compute.hpcloudsvc.com/v1.1/",
          "rel": "self"
        }
      ]
    },
    {
      "status": "DEPRECATED",
      "updated": "2011-01-21T11:33:21Z",
      "id": "v1.0",
      "links": [
        {
          "href": "https://az-1.region-a.geo-1.compute.hpcloudsvc.com/v1.0/",
          "rel": "self"
        }
      ]
    }
  ]
}
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" [BaseUri]/
```

4.4.2 Volumes

[Describe volumes and how they relate to the overall Compute API.]

Status Lifecycle

“creating” => “available” (after creation) => “in-use” (after attach) => “available” (after detach)

Rate Limits

N/A

Quota Limits

The quota as configured for the tenant governs the size of the volume that can be created. An exception will be raised if quota is exceeded. Sample exception:

```
413 Entity Too Large
```

```
{"overLimit": {"message": "Volume quota exceeded. You cannot create a volume of  
size 1G", "code": 413, "retryAfter": 0}}
```

Business Rules

None.

4.4.2.1 List Volumes

GET /os-volumes

Lists the block storage volumes.

Status Codes

200 - OK

Request Formats

This call does not require a request body.

Response Formats

JSON

```
{
  "volumes": [
    {
      "status": "available",
      "displayDescription": null,
      "availabilityZone": "nova",
      "displayName": "Test",
      "attachments": [],
      "volumeType": null,
      "snapshotId": "",
      "size": 1,
      "id": 4183,
      "createdAt": "2012-06-27 19:20:35",
      "metadata": {}
    },
    {
      "status": "available",
      "displayDescription": null,
      "availabilityZone": "nova",
      "displayName": null,
      "attachments": [],
      "volumeType": null,
      "snapshotId": "",
      "size": 1,
      "id": 4261,
      "createdAt": "2012-06-29 16:57:02",
      "metadata": {}
    }
  ]
}
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \
      [BaseUri]/v1.1/<tenant_id>/os-volumes
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.2.2 Create Volume

POST /os-volumes

Create a new block storage volume of a given size.

Status Codes

200 - OK

Request Formats

Required Fields:

- size (in GBs)

JSON

```
{ "volume": { "size": "1", "display_name": "Test Volume", "display_description": "Test Volume desc" } }
```

XML

Not Supported.

Response Formats

JSON

```
{ "volume": { "status": "creating", "displayDescription": "Test Volume desc", "availabilityZone": "nova", "displayName": "Test Volume", "attachments": [ {} ], "volumeType": null, "snapshotId": "", "size": 1, "id": 4279, "createdAt": "2012-06-29 19:24:03", "metadata": { } } }
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \
-H "Content-Type: application/json" \
[BaseUri]/v1.1/<tenant_id>/os-volumes \
-X POST -d '{ "volume": { "size": "1", "display_name": "Test Volume", "display_description": "Test Volume desc" } }'
```

Additional Details

Optional Request Data

Metadata: Metadata can be added while creating a volume by passing a key/value pair in the request body. See example below where the optional data is in bold.

Request Formats

JSON

```
{ "volume": { "size": "1", "display_name": "Test Volume", "display_description":  
  "Test Volume desc" , "metadata": { "VolMeta" : "VolMetaValue" } } }
```

XML

Not Supported.

Response Formats

JSON

```
{ "volume": { "status": "creating", "displayDescription": "Test Volume desc",  
  "availabilityZone": "nova", "displayName": "Test Volume", "attachments": [{}],  
  "volumeType": null, "snapshotId": "", "size": 1, "id": 4279, "createdAt": "2012-  
06-29 19:24:03", "metadata": { "VolMeta": "VolMetaValue" } } }
```

XML

Not Supported.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.2.3 Get Volume details

GET /os-volumes/<volume_id>

Gets the details of the block storage volume specified by <volume_id>.

Status Codes

200 - OK

Request Formats

This call does not require a request body.

Response Formats

JSON

```
{ "volume": { "status": "available", "displayDescription": "Test Volume desc",  
  "availabilityZone": "nova", "displayName": "Test Volume", "attachments": [{}],  
  "volumeType": null, "snapshotId": "", "size": 1, "id": 4279, "createdAt": "2012-  
06-29 19:24:03", "metadata": {}}}
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \  
  [BaseUri]/v1.1/<tenant_id>/os-volumes/<volume_id>
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.2.4 Delete Volume

DELETE /os-volumes/<volume_id>

Delete the block storage volume specified by <volume_id>.

Status Codes

202 - Accepted

Request Formats

This call does not require a request body.

Response Formats

This call does not return a response body.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \  
[BaseUri]/v1.1/<tenant_id>/os-volumes/<volume_id> -X DELETE
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.3 Servers

[Describe the role of the server resource with respect to the Block Storage service]

Status Lifecycle

“creating” => “available” (after creation) => “in-use” (after attach) => “available” (after detach)

Rate Limits

[Describe Rate-limits with respect to the attach and detach calls that involve servers]

None.

Quota Limits

[Describe Quota-limits with respect block storage that involve servers]

None.

Business Rules

1. A volume can only be attached when the status of the volume is “available”.
2. A volume is attached when the status of the volume is “in-use”.
3. A volume can only be detached when the status of the volume is “in-use”.
4. A volume can be attached to only one server instance.
5. A server can have multiple volumes attached to it.
6. The device name should be see valid and same device name cannot be repeated.
7. The device needs to be mounted on the server, before it can be used.

4.4.3.1 List attached volumes for a server

GET /servers/<server_id>/os-volume_attachments

Gets the block storage volumes attached to the server instance specified by <server_id>.

Status Codes

200 - OK

Request Formats

This call does not require a request body.

Response Formats

JSON

```
{ "volumeAttachments": [ { "device": "/dev/vdf", "serverId": 258315, "id": 5825, "volumeId": 5825 } ] }
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \  
[BaseUri]/v1.1/<tenant_id>/servers/<server_id>/os-volume_attachments
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.3.2 Attach volume to a server

POST /servers/<server_id>/os-volume_attachments

Attach the block storage volume specified in the request body to the server instance specified by <server_id>.

Status Codes

200 - OK

Request Formats

JSON

```
{"volumeAttachment": {"volumeId": "5825", "device": "/dev/sdf"}}
```

XML

Not Supported.

Response Formats

JSON

```
{"volumeAttachment": {"id": "5825", "volumeId": "5825"}}
```

XML

Not Supported.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \
      [BaseUri]/v1.1/<tenant_id>/servers/<server_id>/os-volume_attachments \
      -X POST -d '{"volumeAttachment": {"volumeId": "5825", "device":
"/dev/sdf"}}'
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.3.3 Detach volume from a server

DELETE /servers/<server_id>/os-volume_attachments/<volume_id>

Detach the block storage volume specified by <volume_id> from the server instance specified by <server_id>.

Status Codes

202 - Accepted

Request Formats

This call does not require a request body.

Response Formats

This call does not return a response body.

Curl Example

```
curl -i -H "X-Auth-Token: <Auth-Token>" \
      [BaseUri]/v1.1/<tenant_id>/servers/<server_id>/os-
      volume_attachments/<volume_id>
      -X DELETE
```

Additional Details

Optional Request Data

None.

Query String Parameters

[Pagination concepts can be described here, i.e. marker, limit, count etc. Filtering concepts can be described as well i.e. prefix, delimiter etc.]

None.

Error Conditions

None.

4.4.4 Snapshots

[Enumerate the various API calls for this resource]

5. Additional References

5.1 Resources

Wiki Page: <https://wiki.hpcloud.net/display/iaas/Bock+-+Block+Storage+Service+for+Nova>

Code Repo: [Link to the internal Github repo]

API Lead Contact: Tim Reddin

6. Glossary

[Put down definitions of terms and items that need explanation.]