

# Introduction to Computer Programming

## Week 9.1: Matplotlib - Plotting



University of  
BRISTOL

**Matplotlib** is a large and versatile package for visualising data.

It is useful for creating graphs and plots.

We will study a submodule of `matplotlib` called `pyplot`.

`pyplot` is often *renamed* as `plt` on import.

Any functions from `pyplot` can be used by prepending with `plt`

e.g. `plt.plot()`

In [2]: 

```
1 import matplotlib.pyplot as plt
```

To display plots created using Matplotlib in Jupyter Notebook, the following line of code must be run in the notebook *before* generating the plot:

In [3]: 

```
1 %matplotlib inline
```

To display plots when running a `.py` file (e.g. in Spyder), the following line must appear in the programme *after* generating the plot:

In [4]: 

```
1 plt.show()  
2
```

We will also use `numpy` today

In [5]: 

```
1 import numpy as np
```


# Line and Scatter Graphs

A sample data set:  $x$  with corresponding values of  $f$ :

```
In [6]: 1 x = [-1, 3, 4, 8, 10]
        2 f = [-1, -2, 7, 13, 1]
        3
```

Line plot

```
In [7]: 1 plt.plot(x, f)
        2
        3 plt.show()
        4
```




Printing the statement with format [`<matplotlib.lines.Line2D at 0x30990b0>`] appears each time (the numbers on your computer may look different) can be avoided by including a semicolon after the `plot` function.

```
plot(x, y);
```

**Format string:** an *optional* way to define basic formatting

- the colour of the plot (e.g. `r` = red, `k` = black)  
[https://matplotlib.org/2.0.2/api/colors\\_api.html](https://matplotlib.org/2.0.2/api/colors_api.html)  
([https://matplotlib.org/2.0.2/api/colors\\_api.html](https://matplotlib.org/2.0.2/api/colors_api.html))
- the style of the markers (e.g. `o` = points, `*` = stars)  
[https://matplotlib.org/api/markers\\_api.html](https://matplotlib.org/api/markers_api.html)  
([https://matplotlib.org/api/markers\\_api.html](https://matplotlib.org/api/markers_api.html))
- the style of the line (e.g. `--` = dashes, `.` = dots)  
[https://matplotlib.org/devdocs/gallery/lines\\_bars\\_and\\_markers/line\\_styles\\_reference.h](https://matplotlib.org/devdocs/gallery/lines_bars_and_markers/line_styles_reference.html)  
([https://matplotlib.org/devdocs/gallery/lines\\_bars\\_and\\_markers/line\\_styles\\_reference.h](https://matplotlib.org/devdocs/gallery/lines_bars_and_markers/line_styles_reference.h))

```
In [8]: 1 plt.plot(x, f, 'or') # scatter, o markers, red
        2
        3 plt.show()
```




**Example 1:** Use the format string to change the appearance of the plot of  $f$  against  $x$ .

```
In [12]: 1 plt.plot(x, f, '--og')
```


```
2  
3
```

```
Out[12]: [matplotlib.lines.Line2D at 0x7f907548eaf0>]
```



We can add features like axis labels and a title

```
In [44]: 1 plt.plot(x, f, 'k.')  
2  
3 # Axis labels  
4 plt.xlabel('x data')  
5 plt.ylabel('f data')  
6  
7 # title  
8 plt.title('Plot of f against x')  
9  
10 plt.show()
```




## Multiple lines on the same plot

Names can be given to each data series using the `label` named argument when plotting with `plot`.

In [45]:

```

1  x = [-1, 3, 4, 8, 10]
2  f = [-1, -2, 7, 13, 1]
3  y = [6, 2, 4, 5, 6]
4
5  plt.plot(x, f, '-r', label='f'); # argument 'label' is used in
6  plt.plot(x, y, '-g', label='g');
7
8  plt.xlabel('x');
9
10 plt.legend() # must be called to display f
11
12 plt.show()
```



## Bar Charts

Steps to create a bar chart:

1. Create a numpy array with the same number of positions as bars
2. Generate bar chart using `plt.bar`
3. Replace x ticks with bar names


In [19]:

```

1  #sample data
2  groups = ('A', 'B', 'C', 'D', 'E')
3  num_students = (500, 332, 425, 300, 200)
4
```

In [47]:

```
1 # 1. Create a numpy array with the same number of positions as
2 x_pos = np.arange(len(groups))
3
4 # 2. Generate bar chart
5 plt.bar(x_pos, num_students)
6
7 # 3. Replace x ticks with bar names
8 # (Rotate labels 30 degrees)
9 plt.xticks(x_pos, groups, rotation=30)
10
11 # Add axis labels
12 plt.xlabel('year group')
13 plt.ylabel('number of students')
14
15 plt.show()
16
17
```



## Histograms

We can visualise the distribution values using a histogram.

In a histogram, data is sorted into intervals (bins) along one axis.

The number of values that fall within a 'bin' is then displayed on the perpendicular axis.

Example data set of 25 random integers between 0 and 100, generated using `numpy.random.randint`

In [14]:

```
1 import numpy as np
2 z = np.random.randint(low=0, high=100, size=25)
```


We can visualise the frequency distribution of  $x$  by defining bins to hold different ranges of values.

`np.arange()` generates a numpy array of values.

In the example, the edge values of the bins are defined by the array.

```
In [15]: 1 edges = np.arange(0, 101, 10) # start, stop, step
          2 print(edges)
          3
          4 plt.hist(z, bins=edges)
          5
          6 plt.xlabel('value')
          7 plt.ylabel('frequency')
          8
          9 plt.show()
```

[ 0 10 20 30 40 50 60 70 80 90 100]



Bins are defined by their edge values:

If argument `bins` is:

- **an integer:** defines the number of equal-width bins.
- **a sequence:** ( a range ) defines the bin edges.

Bins *include* left-most value, but *exclude* right-most value.

(Except right-most bin: *includes* left-most and right-most value)

e.g. `bins = [1,2,3,4]`


- first bin `[1, 2)`
- second bin `[2, 3)`
- third bin `[3, 4]`

Generating the histogram returns 3 values:

- value of bins
- edges of bins
- graphical data for constructing histogram

```
In [16]: 1 n, edges, patches = plt.hist(z, bins=10);  
         2  
         3 print(n)  
         4
```

```
[1.  1.  4.  2.  5.  3.  4.  1.  1.  3.]
```





## Subplots


Multiple plots can be included in the same figure using `subplot`

`subplot(nrows ncols index)`

```
In [51]: 1 x = [-1, 3, 4, 8, 10]
          2 f = [-1, -2, 7, 13, 1]
```


```
In [52]: 1 plt.subplot(211)      # 2 rows, 1 column, index 1
          2 plt.plot(x, f, 'r')
          3
          4 plt.subplot(212)      # 2 rows, 1 column, index 2
          5 plt.plot(x, f, 'b--')
```

```
Out [52]: [<matplotlib.lines.Line2D at 0x7fee25c30f10>]
```



```
In [53]: 1 plt.subplot(221)      # 2 rows, 2 columns, index 1
          2 plt.plot(x, f, 'r')
          3
          4 plt.subplot(222)      # 2 rows, 2 columns, index 2
          5 plt.plot(x, f, 'b')
          6
          7 plt.subplot(223)      # 2 rows, 2 columns, index 3
          8 plt.plot(x, f, 'r--')
          9
         10 plt.subplot(224)      # 2 rows, 2 columns, index 4
         11 plt.plot(x, f, 'b--')
```

Out [53]: [`matplotlib.lines.Line2D` at `0x7fee232d0710`>]




Alternatively, `subplots(nrows, ncols)` can be used.

This allows you to control change parameters at plot or subplot level.

```
In [54]: 1 fig, ax = plt.subplots(2, 2)
          2
          3 ax[0,0].plot(x, f, 'r')
          4
          5 ax[0,1].plot(x, f, 'b')
          6
          7 ax[1,0].plot(x, f, 'r--')
          8
          9 ax[1,1].plot(x, f, 'b--')
         10
         11 fig.suptitle('Four plots')
```

Out[54]: Text(0.5, 0.98, 'Four plots')



### Example 2:

Display:

- the bar chart of the students in each group
- the histogram of the frequency distribution of  $z$

as two subplots on the same figure.

`subplots_adjust` can be used to adjust the spacing between plots

[https://matplotlib.org/stable/api/as\\_gen/matplotlib.pyplot.subplots\\_adjust.html](https://matplotlib.org/stable/api/as_gen/matplotlib.pyplot.subplots_adjust.html)

([https://matplotlib.org/stable/api/as\\_gen/matplotlib.pyplot.subplots\\_adjust.html](https://matplotlib.org/stable/api/as_gen/matplotlib.pyplot.subplots_adjust.html))

In [ ]:

1

## Saving plots

Plots can be saved in widely used formats (.png, .pdf etc) specified using the file name extension.

In [27]: 

```
1 plt.savefig('img/my_plots.png')
```

<Figure size 432x288 with 0 Axes>

Must appear *before*:

`matplotlib.pyplot.show()`  
i.e. `plt.show()`

## Importing Data with Numpy

`numpy.loadtxt` can be used to import data from delimited text files.  
The user can specify parameters including:

- **delimiter** (default = whitespace)
- **data type** (default = float) :  
If data contains items that cannot be expressed as a float, importing will cause an error unless the data-type is specified.  
Mixed data types can be imported as `string` values.

**Example:** Import data from `sample_data/data.dat`

- **delimiter** : whitespace
- **data type** : float

```
0.000 1.053 2.105 3.158 4.211
74.452 48.348 68.733 59.796 54.123
```

```
In [5]: 1 import numpy as np
2 A = np.loadtxt('sample_data/sample_data.dat')
3
4 print(A)           # stored as numpy array
5
6 print(A[0][1]) # individual elements can be addressed
```

```
[[ 1.053  2.105  3.158  4.211  6.065]
 [48.348 68.733 59.796 54.123 74.452]]
2.105
```

Regions can be selected, for example to exclude headings and select only numerical data.

`skiprows` skips the first `n` lines.

`usecols` specifies which columns to read (numbering starts at 0)

- `usecols = (1, 4, 5)` : extracts the 2nd, 5th and 6th columns.
- `usecols = (3, 4)` : extracts the 4th and 5th columns

```
In [31]: 1 import numpy as np
2 A = np.loadtxt('sample_data/sample_data.dat',
3               skiprows=1,
4               usecols=(2,3,4))
5
6 print(A)           # stored as numpy array
```

```
[59.796 54.123 74.452]
```

### Example 3:

Import height and weight data from `sample_data/sample_student_data.txt` and plot a scatter plot of the data.

How can we change the colour of the markers in the plot?

```
In [ ]: 1
```

```
In [ ]: 1
```

## Summary

- Simple line and scatter plots can be customised using a `formatstring`
- Features such as a figure legend and axis labels can be added after generating the plot.
- Steps to generate a bar chart:
  1. Create a numpy array with the same number of positions as bars
  2. Generate bar chart
  3. Replace x ticks with bar name
- Plots can be saved with `matplotlib.pyplot.savefig`

## Further reading

- Matplotlib has built-in tools for many more types of plot (scatter, box and whisker, 3D surface, animation etc)
- Matplotlib Gallery (<http://matplotlib.org/gallery.html>)  
(<http://matplotlib.org/gallery.html>)
- Github (<http://gree2.github.io/python/2015/04/10/python-matplotlib-plotting-examples-and-exercises>) (<http://gree2.github.io/python/2015/04/10/python-matplotlib-plotting-examples-and-exercises>)