UNIVERSITÉ LIBRE DE BRUXELLES

DÉPARTMENT D'INFORMATIQUE



$\overline{\text{INFO-F403}}$ - Introduction to language theory and compiling

Project Report - Part 2

Author:
Hakim Boulahya

Professor:
Gilles Geeraerts

November 19, 2017

CONTENTS

Contents

| 1 | Gra | mmar | 2 |
|---|-----|---|-----|
| | 1.1 | Unproductive and unreachable symbols (a) | 2 |
| | 1.2 | Priority and associativity of the operators (b) | 2 |
| | | 1.2.1 Arithmetic expressions | 2 |
| | | 1.2.2 Boolean expressions | 3 |
| | 1.3 | Removing left recusion | 4 |
| | 1.4 | Factorisation | 5 |
| | 1.5 | Transformed Grammar | 5 |
| | LL(| · · | 5 |
| | 2.1 | First and Follow | - 5 |

1. GRAMMAR CONTENTS

1 Grammar

1.1 Unproductive and unreachable symbols (a)

In the given grammar, there is no unproductive and/or unreachable symbols.

1.2 Priority and associativity of the operators (b)

Note In this section, P&A refers to priority and associativity of the operators, AE to arithmetic expression and BE to boolean expression.

1.2.1 Arithmetic expressions

Since an arithmetic expression must always be process first before bing compared to another one in a boolean expression, we will consider those two separatly.

First let's consider the P&A of the arithmetic expressions. We have the following P&A:

| - | right |
|------|-------|
| *, / | left |
| +, - | left |

And the following grammar:

```
<ExprArith>
                    \rightarrow [VarName]
<ExprArith>
                    \rightarrow [Number]
<ExprArith>
                    \rightarrow (<ExprArith>)
<ExprArith>
                   \rightarrow - \langle \text{ExprArith} \rangle
<ExprArith>
                    \rightarrow <ExprArith> <Op> <ExprArith>
< Qp >
<Op>
< Op >
                     \rightarrow *
< Op >
                     \rightarrow /
```

As mention in the course page 111, an AE must be a *sum of products*, more specifically in our case a {*sum, substraction*} of {*produts, division*}. We will use the same atom definition in the course, with Number as the constant rule and VarName as the id rule. The minus operator as a right associativity, meaning that it is always linked to the atom next to the operator, so we will set this operator directly as an atom rule.

Same thing goes for the parenthesis. The must be handled without considering the operators outside the parenthesis, so as an atom.

We have the following grammar results:

1. GRAMMAR CONTENTS

```
\rightarrow <ExprArith> <SumSubOp> <ExprProd>
<ExprArith>
<ExprArith>
                   \rightarrow <ExprProd>
<ExprProd>
                   \rightarrow <ExprProd> <ProdOp> <Atom>
<ExprProd>
                   \rightarrow <Atom>
<SumSubOp>
                   \rightarrow +
<SumSubOp>
                  \rightarrow -
                   \rightarrow *
<ProdOp>
<ProdOp>
                   \rightarrow /
                   \rightarrow [VarName]
<Atom>
                  \rightarrow [Number]
<Atom>
<Atom>
                  \rightarrow - <Atom>
<Atom>
                   \rightarrow (<ExprArith>)
```

1.2.2 Boolean expressions

For boolean expressions we have the following P&A:

| not | right |
|-----------------------|------------------------|
| >, <, >=, <=, =, <> / | left |
| and | left |
| or | left |

And the following grammar:

```
<Cond> -> <Cond> <BinOp> <Cond>
<Cond> -> not <SimpleCond>
<Cond> -> <SimpleCond>
<SimpleCond> -> <ExprArith> <Comp> <ExprArith>
<BinOp> -> and
<BinOp> -> or
<Comp> -> =
<Comp> -> =
<Comp> -> >>
<Comp> -> ><
<Comp> -> <</p>
```

Following the same principe as for AE, we have here disjonction of conjonctions of comparaisons. By using the same mechanics as above, we have this grammar:

```
<Cond> -> <Cond> or <ConjCond>
<Cond> -> <ConjCond>

<ConjCond> -> <ConjCond> and <AtomCond>
<ConjCond> -> <AtomCond>

<AtomCond> -> <SimpleCond>
<AtomCond> -> or <SimpleCond>
<AtomCond> -> not <SimpleCond>
```

1. GRAMMAR CONTENTS

```
<SimpleCond> -> <ExprArith> <Comp> <ExprArith>

<Comp> -> =

<Comp> -> >=

<Comp> -> >

<Comp> -> <=

<Comp> -> <<

<Comp> -> <

<Comp> -> <>

<Comp -> <>

<Comp> -> <>

<Comp -> <-

<comp
```

```
<ExprArithPrime> -> <SumSubOp> <ExprProd> <ExprArithPrime>
<ExprArithPrime> -> \epsilon
<ExprProd> -> <Atom> <ExprProdPrime>
<ExprProdPrime> -> <ProdOp> <Atom> <ExprProdPrime>
<ExprProdPrime> -> \epsilon
\langle SumSubOp \rangle - \rangle +
<SumSubOp> -> -
<ProdOp> -> *
<ProdOp> -> /
<Atom> -> [VarName]
<Atom> -> [Number]
<Atom> -> - <Atom>
<Atom> -> (<ExprArith>)
  For the new BE:
<Cond> -> <ConjCond> <CondPrime>
<CondPrime> -> or <ConjCond> <CondPrime>
<CondPrime> -> \epsilon
```

<ConjCond> -> <AtomCond> <ConjCondPrime>

2. LL(1) CONTENTS

```
<ConjCondPrime> -> and <AtomCond> <ConjCondPrime>
<ConjCondPrime> -> \epsilon

<AtomCond> -> <SimpleCond>
<AtomCond> -> not <SimpleCond>
<SimpleCond> -> <ExprArith> <Comp> <ExprArith>
<Comp> -> =
<Comp> -> >=
<Comp> -> >=
<Comp> -> ><
<Comp> -> <=
<Comp> -> <<
<Comp> -> <<
<Comp> -> <<
<Comp> -> <</p>
```

Those are the only rules where left-recusion appears, all the other rules are right-recusion or no recursion at all.

1.4 Factorisation

```
We can only factorize the following set of rules: < InstList>, < If>, < For>. We have the following new rules:
```

```
<InstList> -> <Instruction> <InstListSeq>
<InstListSeq> -> ; <InstList>
<InstListSeq> -> \epsilon

<If> -> if <Cond> then <Code> <IfSeq>
<IfSeq> -> endif
<IfSeq> -> else <Code> endif
<For> -> for [VarName] from <ExprArith> <ForOp> to <ExprArith> do <Code> done
<ForOp> -> by <ExprArith>
<ForOp> -> \epsilon
```

1.5 Transformed Grammar

2 LL(1)

2.1 First and Follow

 $2. \ LL(1)$ CONTENTS

```
<Program>
                                   \rightarrow begin <Code> end
 [2]
       <Code>
                                   \rightarrow < InstList >
 [3]
                                   \rightarrow \epsilon
 [4]
       <InstList>
                                   \rightarrow <Instruction> <InstListSeq>
 [5]
       <InstListSeq>
                                   \rightarrow; <InstList>
 [6]
                                   \rightarrow \epsilon
 [7]
       <Instruction>
                                   \rightarrow <Assign>
 [8]
                                   \rightarrow <If>
 [9]
                                   \rightarrow <While>
[10]
                                   \rightarrow <For>
[11]
                                   \rightarrow <Print>
[12]
                                   \rightarrow <Read>
                                   \rightarrow [VarName] := < ExprArith >
[13]
       <Assign>
       <ExprArith>
                                   \rightarrow <ExprProd> <ExprArithPrime>
[14]
[15]
       <ExprArithPrime>
                                   \rightarrow <SumSubOp> <ExprProd> <ExprArithPrime>
[16]
                                   \rightarrow \epsilon
[17]
       <ExprProd>
                                   \rightarrow <Atom> <ExprProdPrime>
[18]
       <ExprProdPrime>
                                   \rightarrow <ProdOp> <Atom> <ExprProdPrime>
[19]
                                   \rightarrow \epsilon
[20]
       <SumSubOp>
                                   \rightarrow +
[21]
                                   \rightarrow -
[22]
       <ProdOp>
                                   \rightarrow *
[23]
                                   \rightarrow /
[24]
                                   \rightarrow [VarName]
       <Atom>
[25]
                                   \rightarrow [Number]
[26]
                                   \rightarrow - <Atom>
[27]
                                   \rightarrow (<ExprArith>)

ightarrow if <Cond> then <Code> <IfSeq>
[28]
       <If>
[29]
       <IfSeq>
                                   \rightarrow \mathtt{endif}
                                   \rightarrow else <Code> endif
[30]
[31]
       <Cond>
                                   \rightarrow <ConjCond> <CondPrime>
[32]
       <CondPrime>
                                   → or <ConjCond> <CondPrime>
[33]
[34]
       <ConjCond>
                                   \rightarrow <AtomCond> <ConjCondPrime>
[35]
       <ConjCondPrime>
                                   \rightarrow and <AtomCond> <ConjCondPrime>
[36]
[37]
       <AtomCond>
                                   \rightarrow <SimpleCond>
[38]
                                   \rightarrow not <SimpleCond>
[39]
       <SimpleCond>
                                   \rightarrow <ExprArith> <Comp> <ExprArith>
[40]
       <Comp>
                                   \rightarrow =
[41]
                                   \rightarrow >=
[42]
                                   \rightarrow >
[43]
                                   \rightarrow <=
[44]
                                   \rightarrow <
[45]
                                   \rightarrow <>
                                   \rightarrow while <Cond> do <Code> done
[46]
       <While>
                                   \rightarrow for [VarName] from <ExprArith> <ForOp>
[47]
       <For>
                                      to <ExprArith> do <Code> done
[48]
       <ForOp>
                                   \rightarrow by <ExprArith>
                                                                                                            6
[49]
[50]
       <Print>
                                   \rightarrow print([VarName])
[51]
       <Read>
                                   \rightarrow \text{read}([VarName])
```

Figure 1: Transformed Grammar