

ACS and MMAS for the Permutation Flow Shop Problem with Weighted Tardiness

Swarm Intelligence project

June 17, 2019

Hakim BOULAHYA

Département d'Informatique
Université Libre de Bruxelles

ULB

Project: ACO Algorithms for PFSP-WT

- 1. Algorithms and implementation**
- 2. Adding local search routine**
- 3. Results and comparisons**
- 4. Conclusion**

- ▶ Schedule construction by exploiting with probability q_0 :
 - ▶ Exploit. best schedule: $\operatorname{argmax}_{\text{unscheduled}} (\tau_{ij})^\alpha (\eta_{ij})^\beta$
 - ▶ Biased exploration: $p_{ij} = \frac{(\tau_{ij})^\alpha (\eta_{ij})^\beta}{\sum_{\text{unscheduled}} (\tau_{ij})^\alpha (\eta_{ij})^\beta}$
- ▶ Earliest Due Dates (EDD) heuristic for initialization: Sort due dates and $\eta_{ij} = 1/d_i$
- ▶ Global pheromone update applied only by best-iteration ant (using ρ)

ACS

- ▶ Include local pheromone update during ant's solution build (using ξ)
- ▶ τ_0 based on EDD solution

MMAS

- ▶ $q_0 = 0$: only explore
- ▶ Pheromone interval:
 $\tau_{min} \leq \tau_{ij} \leq \tau_{max}$
- ▶ Interval updated at each iteration based on current best solution

Local search performed using exhaustive *insertion-moves*:

- ▶ That is for all permutation (i, j) , remove job from position i and insert it in position j
- ▶ Performs in $O(n^2)$ for a schedule

Two mechanisms implemented:

- ▶ *best-ant*: Only best-iteration ant can perform local search: $O(n^2)$ per iteration
- ▶ *all-ant*: All ant can perform local search = $O(mn^2)$ per iteration

- ▶ Because local search routine appears to have a big impact on solution quality, we compare the results of the following 6 algorithms:
 - ▶ ACS
 - ▶ MMAS
 - ▶ ACS-LS-BEST (ALB)
 - ▶ ACS-LS-ALL (ALA)
 - ▶ MMAS-LS-BEST (MLB)
 - ▶ MMAS-LS-ALL (MLA)
- ▶ Execution of each algorithm on each instance 10 times
- ▶ One execution = 30 seconds time budget


Best configurations parameters returned by `irace` for each algorithm

	ACS	MMAS	ALB	ALA	MLB	MLA
ants	41	28	5	93	34	87
α	2.56	3.88	2.83	3.69	4.41	0.34
β	7.78	6.69	3.28	5.08	9.48	6.76
ρ	0.32	0.53	0.61	0.05	0.41	0.7
ξ	0.46	-	0.38	0.77	-	-
q_0	0.07	-	0.04	0.24	-	-


Observations:

- ▶ When *all-ant* is used, `irace` returns nearly max. of ants
- ▶ q_0 mostly very low, exploration seems to perform better
- ▶ Heuristic desirability has bigger impact than pheromone trails


Instance with 50 jobs




Instance with 100 jobs



Instance with 50 jobs



Instance with 100 jobs



- ▶ Best results provided by the algorithms for all 20 instances
 - ▶ ACS: 0%
 - ▶ MMAS: 0%
 - ▶ ACS-LS-BEST: 40%
 - ▶ ACS-LS-ALL: 0%
 - ▶ MMAS-LS-BEST: 35%
 - ▶ MMAS-LS-ALL: 25%

- ▶ Intuitive observations
 - ▶ *best-ant* local search seems to always performs better
 - ▶ MMAS-LS-BEST seems better for instances with fewer jobs and ACS-LS-BEST for instances with more jobs
- ▶ Improvements
 - ▶ No parameters analysis..
 - ▶ No analysis of MMAS stagnation and parameters reinitialization

Thank you!

ULB