

Facial Keypoints Detection Using Convolutional Neural Network

Qinyao He
CST34
Tsinghua University
2012010548

Xiaocheng Yang
CST34
Tsinghua University
2013XXXXXX

Abstract

In this report we building an neural network for carrying out facial keypoints detection problem. We have tried several ways, but a problem of non convergence still need to be resolved, which till now we have no idea about that.

1. Introduction

This task comes originally from Kaggle¹, a online website holding many data science competitions. It's aim is to determine the location of several certain key points on face, given a photograph contains a human face.

This key points detection can form the building block for many applications. Such as:

- * tracking faces in images and video
- * analysing facial expressions
- * detecting dysmorphic facial signs for medical diagnosis
- * biometrics / face recognition

Detecting facial keypoints is a very challenging problem. Facial features vary greatly from one individual to another, and even for a single individual, there is a large amount of variation due to 3D pose, size, position, viewing angle, and illumination conditions. Computer vision research has come a long way in addressing these difficulties, but there remain many opportunities for improvement.

In this specific competition², we are required to localize 15 facial key points given a images. Each predicted point is specified as (x, y) real-valued pair in the space of pixel indices. The 15 keypoints is:

left_eye_center, right_eye_center, left_eye_inner_corner,
left_eye_outer_corner, right_eye_inner_corner,
right_eye_outer_corner, left_eyebrow_inner_end,

left_eyebrow_outer_end, right_eyebrow_inner_end,
right_eyebrow_outer_end, nose_tip, mouth_left_corner,
mouth_right_corner, mouth_center_top_lip,
mouth_center_bottom_lip

so 30 real value is going to be predicted for each input image.

Kaggle given a training data set of 7049 image with size of $96 * 96$, color is gray scale and represented as an integer from 0 to 255 for each pixel. And each training images is labeled with 30 real value for position of the 15 key points. In some examples, some of the target keypoint positions are missing.

Also, a test set of 1783 images without label is given, for competitors to submit their predicted result to Kaggle for score.

Performance is graded by MSE(mean square error) for those 30 real values. A lower MSE indicate a better prediction.

In our work, we have carried out experiment on several models, include basic multilayer perceptron, convolutional neural network and cascaded convolutional network.

2. Related Work

3. Technical Approach

In this section we demonstrate some technical approach which, based on previous work, can improve performance of the network, accelerate convergence, and reduce overfitting.

3.1. Data Normalization

In the original training data, each pixel is represented by an integer from 0 to 255, and the real-value label range from 0 to 96. This large range of input and target data may force the neuron to saturate, which slow down convergence. Also, the non-error-centered target value make the full connected layer hard to get a ideal output.

In our implementation, gray scale from 0 to 255 are divided by 256, rescaled to range 0 to 1, and target value are rescaled and zero centered to range from -1 to 1. Let train_x,

¹<https://www.kaggle.com/>

²<https://www.kaggle.com/c/facial-keypoints-detection>

$train_y$ stand for the image data and label, the normalize pre-process looks like:

$$train_x = \frac{train_x}{256.0}$$

$$train_y = \frac{train_y - 48.0}{48.0}$$

3.2. ReLU Nonlinearity

When training deep feedforward neural network, gradient diminishing when back propagation often occurs and make it very slow to converge. This issue is common when using sigmoid-like activation function, since they have a so-called saturation regime where gradient almost vanished. According to experiment by Glorot [1], for a feedforward neural net with 4 layers and activate with sigmoid function, the last hidden layer quickly saturate with output value of 0, which slow down the process of learning. and after a hundred of epochs, it escaped, and the followed layer began to saturate.

Glorot hypothesize that this behavior is the result of combination of random initialization and the fact that an output of zero correspond to a saturated sigmoid. Unsupervised pre-training can successfully solve this issue.

While with another kind of activation function, known as ReLU(rectify linear unit), the problem of saturation and gradient diminishing is also solved. ReLU activation act as follow:

$$rectify(x) = \max(x, 0)$$

It can achieve the performance as better as a pre-trained sigmoid network[2] without any unsupervised pre-training. Its behavior is also more plausible at the viewpoint of biological neural science, which claim a neuron to be closed below zero, and behave linearly when input is above zero with in some range, and this range is satisfied most of time.

Also rectifier activation function allow a network to easily obtain sparse representations, which is biologically plausible and have mathematical advantages.

The non-linearity when using rectify comes from path-selection. For different input, different set of neurons are active. This model can be viewed as an *exponential number of linear models that share parameters*[4].

Experiment shows both improvement on learning speed and performance [3, 2].

In our model, both the convolution layer and the full connected layer is activate by ReLU function except for the last layer, which followed by the finally loss layer. Because we want the output result to have both positive and negative value, while ReLU only result in positive and zero.

Also this approach can be used in classification problem with softmax and cross entropy loss. Allow result to be negative increase the difference when doing softmax, which result in better classification result.

3.3. Weight Initialization

3.4. Dropout

4. Network Structure

5. Experiment

6. Conclusion

References

- [1] X. Glorot and Y. Bengio. Understanding the difficulty of training deep feedforward neural networks. In *International conference on artificial intelligence and statistics*, pages 249–256, 2010.
- [2] X. Glorot, A. Bordes, and Y. Bengio. Deep sparse rectifier neural networks. In *International Conference on Artificial Intelligence and Statistics*, pages 315–323, 2011.
- [3] A. Krizhevsky, I. Sutskever, and G. E. Hinton. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*, pages 1097–1105, 2012.
- [4] V. Nair and G. E. Hinton. Rectified linear units improve restricted boltzmann machines. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10)*, pages 807–814, 2010.