

732A90: Computational Statistics

Computer lab6 - Group11

Sofie Jörgensen, Oriol Garrobé Guilera, David Hrabovszki

29 February 2020

Question 1: Genetic algorithm

In this exercise we are going to perform one-dimensional maximization by using a genetic algorithm.

1.

Firstly, we define the function `f()` as

$$f(x) := \frac{x^2}{e^x} - 2 \exp(-(9 \sin x)/(x^2 + x + 1)).$$

2.

Secondly, we define the function `crossover()`, that takes two scalars x and y as inputs, and returns a child as $\frac{x+y}{2}$.

3.

Thirdly, we define the function `mutate()`, that performs the integer division $x^2 \bmod 30$, for a scalar input x .

4.

Further, we will create a function called `genetic()`, with the parameters `maxiter` and `mutprob`. The settings of this `genetic()` function, as well as its output results, are presented in (a)-(e). The code can be found in the Appendix.

(a). The function $f()$ is plotted in the range from 0 to 30 in Figure X, and we can observe that there is a maximum value located around $x = 1.2$.

(b). An initial population for the genetic algorithm is defined as $X = (0, 5, 10, 15, \dots, 30)$.


(c). A vector called `Values` are computed, containing the function values for each population point.

(d). The `genetic()` function performs `maxiter` iterations. For each iteration...


(e).

5.

By using the defined functions from previous tasks (1.1-1.4), we are going to observe the initial population and final population. This is done by running the code with different combinations of `maxiter`= 10, 100 and `mutprob`= 0.1, 0.5, 0.9.



```
## [1] 0 5 10 15 20 25 30
## [1] -2.000000 -2.473573 -2.085654 -1.951947 -1.961344 -2.003663 -2.019194
```



Question 2: EM algorithm

- 1.
 - 2.
 - 3.
 - 4.
-

Appendix

```
knitr::opts_chunk$set(echo = FALSE)
# R version
RNGversion('3.5.1')
#1.1
f <- function(x){
  return(x^2/exp(x) - 2*exp(-1*(9*sin(x)) / (x^2 + x + 1)))
}

#1.2
crossover <- function(x,y){
  return((x+y) / 2)
}

#1.3
mutate <- function(x){
  return(x^2 %% 30)
}

#4
#4
genetic <- function(maxiter, mutprob){
  #a
  plot(x = seq(0,30,0.1), y = f(seq(0,30,0.1)), type = "l", xlab = "x", ylab = "f(x)")
  abline(v=seq(0,30,0.1)[which.max(f(seq(0,30,0.1)))], col="red" )

  #b
  X = seq(0,30,5)

  #c
  Values = f(X)

  #d
  #set seed
  set.seed(1234567890)
  for (i in 1:maxiter) {
    #e
    parents = match(sample(X, 2),X)
```

```

#ii
victim = order(Values)[1]

#iii
kid = round(crossover(parents[1],parents[2]))
p = runif(1)
if (p < mutprob) {
  kid = mutate(kid)
}

#iv
X[victim] = kid
Values = f(X)

#v
max = max(Values)
}

#e
print(X)
print(Values)
plot(x = seq(0,30,0.1), y = f(seq(0,30,0.1)), type = "l", xlab = "x", ylab = "f(x)")
points(x = X, y = Values, col = "red", pch = 19)
}

# Just testing no change, i.e. initial population
genetic(1,0)
# R version
RNGversion('3.5.1')
# Packages

```