1 AURA-X — GitHub and VS Code Quick-Start

This guide helps you save the AURA-X source in **your own private GitHub repository** and run it from VS Code. The published Manus website is already a separate deployment; GitHub stores source code, not a running app, database, or AI service.

1.1 1. What you need

- The supplied `auraxai-source.tar.gz` source archive.
- Git, VS Code, Node.js 22, Corepack/pnpm 10.18.0.
- A MySQL or MariaDB database for a standalone local/deployed copy.
- Authorized server-side Manus AI configuration for roadmap/chat/transcription features. Optional providers can need their own keys.

The archive excludes `.git`, `.env`, database contents, build outputs, and `node_modules`. It contains the migration files and `.env.example`. No production user data or credentials are bundled.

1.2 2. Open the project in VS Code

Extract the archive, open the extracted project folder in VS Code, and open a terminal at that folder (the one containing `package.json`). On macOS/Linux:

```
tar -xzf auraxai-source.tar.gz
cd auraxai
code .
```

On Windows, use **Extract All** for the `.tar.gz`, open the extracted `auraxai` folder in VS Code, and use the integrated PowerShell terminal.

1.3 3. Configure local services safely

Enable Corepack, install the pinned package manager, install dependencies, and make a private local environment file:

```
corepack enable
corepack prepare pnpm@10.18.0 --activate
pnpm install --frozen-lockfile
cp .env.example .env
```

In Windows PowerShell, use `Copy-Item .env.example .env` instead of `cp` if needed.

Edit `.env` locally and provide:

- `DATABASE_URL`: your own MySQL/MariaDB URL.
- `MANUS_PROJECT_ID`, `MANUS_API_URL`, `MANUS_API_KEY`: authorized server-side Manus AI settings, if you want managed AI and voice transcription in this standalone copy.
- `BRAVE_SEARCH_API_KEY`: optional additional web search.
- `ELEVENLABS_API_KEY`: optional hosted, standard (not cloned) TTS. Device speech is the default and does not need this key.

Never paste credentials into source code, a browser-side `VITE_*` variable, GitHub issues, or this PDF. `.env` is excluded by `.gitignore`; commit `.env.example` only.

1.4 4. Migrate and run

Create/select the local database first, then apply versioned migrations and start the dev server:

```
pnpm db:migrate
pnpm check
pnpm test
pnpm dev
```

Open `http://localhost:3000` and create an account from the website. For a production-mode check, stop the dev server and run:

```
pnpm build
pnpm start
```

`/api/health` is the unauthenticated health route. `pnpm db:migrate` applies pending migrations; do not reset or drop the database to update the schema.

1.5 5. Save to your GitHub account

Use a **Private** repository unless you intentionally want the source to be public. After extracting the archive, initialize Git and create the first commit:

```
git init -b main
git add .
git status --short
git commit -m "Prepare AURA-X source"
```

Before committing, confirm that `.env` is not listed in `git status`. Create an empty private repository on GitHub, then connect it and push:

```
git remote add origin https://github.com/YOUR-USERNAME/YOUR-REPOSITORY.git
git push -u origin main
```

Replace the placeholders with your GitHub username and repository name. GitHub authentication may ask you to sign in in your browser or use your configured Git credential manager. Do not put a token in the remote URL.

1.6 6. Deploy the code

AURA-X is a full-stack Node/Express application with a MySQL database. **GitHub Pages cannot run its authenticated API/database.** Deploy the `Dockerfile` to a Node/container host with MySQL, configure the server-only environment variables as protected secrets, run `pnpm db:migrate` once against that deployment database, and set the host health check to `/api/health`. Honor the platform's supplied `PORT` value. Never copy a production database URL into GitHub Actions logs or the repository.

To build with GitHub Actions, store secrets in **Settings → Secrets and variables → Actions**. Use the same lockfile and commands (`pnpm install --frozen-lockfile`, `pnpm check`, `pnpm test`, `pnpm build`) in CI. Keep production secrets out of CI output.

1.7 7. What the source does—and does not—include

- A goal can start today, tomorrow, or on a selected calendar date; durations support up to 730 days.
- Attendance shows every goal date and lets the owner select a past/current date and set Present, Missed, or Clear. Unmarked dates stay unmarked; future check-ins are rejected.
- Auri stays in place unless deliberately dragged or moved with keyboard controls. Mouse/scroll does not reposition the mascot; her chat panel is clamped inside the viewport.
- Voice recording starts only after the user's action and microphone permission. Browser/device speech is the normal voice path; server transcription and AI need the authorized Manus project service. No voice clone is shipped.
- Provider results can be partial when a third-party search service is unavailable. AURA-X shows provider/error states and does not invent links or course credentials.

See the root `README.md` for the full feature set, tests, provider details, and limitations.

2 Glossary

API – **application programming interface**: A defined interface through which the browser requests validated server actions and data.

database – **MySQL/MariaDB database**: The relational store for account-owned AURA-X users, goals, tasks, resources and attendance.

Dockerfile – **container build recipe**: The project's recipe for building and starting its server in compatible container hosts.

.env – **environment file**: A private local file for connection strings and server-side credentials; never commit it.

PWA – **Progressive Web App**: A website that can be installed from a supported browser.

tRPC – **type-safe Remote Procedure Call**: The typed client/server request layer mounted by AURA-X at /api/trpc.

TTS – **text-to-speech**: Speech synthesis that reads Auri's answer aloud with a device or optional authorized hosted voice.