

## Riktig bruk av håndsignaler og radiokommunikasjon

Viktig at anhuker, signalperson og kranfører har felles forståelse for riktig bruk av håndsignaler, og andre uttrykk.



### HÅNDSIGNALER

**NB!** Kranfører og signalperson må bruke avtalte signaler

**Oransje tekst** er kommandoer i **NORSOK R-003N / R-005N**



### RADIOSIGNALER



- Lær deg signalene.
- Plasser deg riktig.
- Påse at lasten er riktig stroppet.
- Gi tydelige og presise signaler med store hånd- / armbevegelser.
- Unngå skjevtrekk.

- Lær deg korrekt bruk av radio.
- Test sambandet før en løfteoperasjon.
- Snakk sakte og tydelig.
- Hold kontinuerlig samband når lasten ikke er synlig for kranfører.
- Unngå unødig bruk av radio.

• Følg produsentens anbefalinger iht. lastens diameter med bruk av snaring/u-loft

# LØFTETABELL FOR FIBERSTROPPER

Tillatt løftekapasitet (WLL) i samsvar med EN 1492-1 og 2 i tonn

Sikkerhetsfaktor = 7

Rev.nr. 1.2023

• Ved snaring reduseres løftekapasitet til 80 % av rett loft WLL

Farge Anb.	Min. Anl. Dia	Rett loft WLL	Snaret Løft		U-loft Vinkel		0-45°		45,1°-60°		0-45°		45,1°-60°											
			Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret										
<b>EN STROPP</b>																								
<b>TO STROPPER</b>																								
Fiolett	20 mm	1,0	0,8	2,0	1,7	1,4	1,1	1,0	0,8	2,1	1,6	1,5	1,2											
Gronn	20 mm	2,0	1,6	4,0	3,4	2,8	2,2	2,0	1,6	4,2	3,3	3,0	2,4											
Gul	30 mm	3,0	2,4	6,0	5,1	4,2	3,3	3,0	2,4	6,3	5,0	4,5	3,6											
Grå	40 mm	4,0	3,2	8,0	6,8	5,6	4,4	4,0	3,2	8,4	6,7	6,0	4,8											
Rød	50 mm	5,0	4,0	10,0	8,5	7,0	5,6	5,0	4,0	10,5	8,4	7,5	6,0											
Brun	60 mm	6,0	4,8	12,0	10,2	8,4	6,7	6,0	4,8	12,6	10,0	9,0	7,2											
Blå	80 mm	8,0	6,4	16,0	13,6	11,2	8,9	8,0	6,4	16,8	13,4	12,0	9,6											
Oransje	80 mm	10,0	8,0	20,0	17,0	14,0	11,2	10,0	8,0	21,0	16,8	15,0	12,0											
Oransje	115 mm	15,0	12,0	30,0	25,5	21,0	16,8	15,0	12,0	31,5	25,2	22,5	18,0											
Oransje	120 mm	20,0	16,0	40,0	34,0	28,0	22,4	20,0	16,0	42,0	33,6	30,0	24,0											
Oransje	125 mm	25,0	20,0	50,0	42,5	35,0	28,0	25,0	20,0	52,5	42,0	37,5	30,0											
Oransje	130 mm	30,0	24,0	60,0	51,0	42,0	33,6	30,0	24,0	63,0	50,4	45,0	36,0											
Oransje	140 mm	40,0	32,0	80,0	68,0	56,0	44,8	40,0	32,0	84,0	67,2	60,0	48,0											
FAKTOR	1	0,8	2	1,7	1,4		1			2,1		1,5												
<b>USYMMETRISK FAKTOR</b>					<b>Bruk løftekapasitet 1 stropp</b>					<b>Bruk løftekapasitet 2 stropper</b>														
Unngå skarpe kanter, friksjon og alkaliske stoffer - WLL for polyesterstropper gjelder for temperaturområde -40°C -100°C																								
Følg alltid produsentens anbefalinger ved løft.																								

# LØFTETABELL KJETTING - GRADE 80

Tillatt arbeidslast (WLL) i tonn i samsvar med EN 818-4

Sikkerhetsfaktor = 4

Rev.nr. 1.2023

- Lastens diameter og anleggsdiameter bør være min. 9 ganger diameter av kjettinglenken

- Ved snaring reduseres løftekapasitet til 80 % av rett løft WLL

Diameter mm	Anb. Min. Anl. Dia.	Rett løft WLL	Snaret Løft	U-loft	U-loft Vinkel	0-45°		45,1°-60°		0-45°		45,1°-60°	
						Direkte WLL	Snaret	Direkte	Snaret	Direkte WLL	Snaret	Direkte	Snaret
<b>EN PART</b>													
7	63 mm	1,5	1,20	3,00	2,55	2,12	1,7	1,5	1,2	3,15	2,52	2,24	1,8
8	72 mm	2,00	1,60	4,00	3,40	2,80	2,24	2,00	1,60	4,25	3,40	3,00	2,40
10	90 mm	3,15	2,52	6,30	5,36	4,25	3,40	3,15	2,52	6,70	5,40	4,75	3,80
13	117 mm	5,30	4,24	10,60	9,00	7,50	6,00	5,30	4,24	11,20	9,00	8,00	6,40
16	144 mm	8,00	6,40	16,00	13,60	11,20	9,00	8,00	6,40	17,00	13,60	11,80	9,44
18	162 mm	10,00	8,00	20,00	17,00	14,00	11,20	10,00	8,00	21,20	17,00	15,00	12,00
19	171 mm	11,20	9,00	22,40	19,04	16,00	12,80	11,20	9,00	23,60	18,90	17,00	13,60
20	180 mm	12,50	10,00	25,00	21,25	17,00	13,60	12,50	10,00	26,50	21,20	19,00	15,20
22	198 mm	15,00	12,00	30,00	25,50	21,20	17,00	15,00	12,00	31,50	25,20	22,40	17,92
23	207 mm	16,00	12,80	32,00	27,20	23,60	18,90	16,00	12,80	35,50	28,40	25,00	20,00
25	225 mm	20,00	16,00	40,00	34,00	28,00	22,40	20,00	16,00	40,00	32,00	30,00	24,00
26	234 mm	21,20	17,00	42,40	36,04	30,00	24,00	21,20	17,00	45,00	36,00	31,50	25,20
28	252 mm	25,00	20,00	50,00	42,50	33,50	26,80	25,00	20,00	52,50	40,00	37,50	30,00
32	288 mm	31,50	25,20	63,00	53,55	45,00	36,00	31,50	25,20	67,00	53,60	47,50	38,00
<b>FAKTOR</b>		1	0,8	2	1,7	1,4		1		2,1		1,5	
<b>USYMMETRISK FAKTOR</b>						<b>Bruk løftekapasitet 1 stropp</b>				<b>Bruk løftekapasitet 2 stropper</b>			
<b>WLL for kjettingredskap gjelder for temperaturområde fra -40°C opp til 200°C - Følg alltid produsentens anbefalinger ved løft</b>													

# LØFTETABELL KJETTING - GRADE 100

Tillatt arbeidslast (WLL) i tonn i samsvar med EN 818-4

Sikkerhetsfaktor = 4

- Lastens diameter og anleggsdiameter bør være min. 9 ganger diameter av kjettinglenken

- Ved snaring reduseres løftekapasitet til 80 % av rett løft WLL

Rev.nr. 1.2023

Diameter mm	Anb. Min. Anl. Dia.	Rett løft WLL	Snaret Loft	U-loft	U-loft Vinkel	0-45°		45,1°-60°		0-45°		45,1°-60°	
						Direkte WLL	Snaret	Direkte	Snaret	Direkte WLL	Snaret	Direkte	Snaret
													
EN PART													
5	45 mm	<b>1,00</b>	0,80	2,00	1,70	<b>1,40</b>	1,12	1,00	0,80	<b>2,00</b>	1,60	1,50	1,20
6	54 mm	<b>1,40</b>	1,12	2,80	2,38	<b>2,00</b>	1,60	1,40	1,12	<b>3,00</b>	2,40	2,12	1,70
7	63 mm	<b>1,90</b>	1,50	3,80	3,23	<b>2,65</b>	2,12	1,90	1,50	<b>4,00</b>	3,20	2,80	2,24
8	72 mm	<b>2,50</b>	2,00	5,00	4,25	<b>3,55</b>	2,80	2,50	2,00	<b>5,30</b>	4,24	3,75	3,00
10	90 mm	<b>4,00</b>	3,15	8,00	6,80	<b>5,60</b>	4,25	4,00	3,15	<b>8,00</b>	6,40	6,00	4,80
13	117 mm	<b>6,70</b>	5,30	13,40	11,40	<b>9,50</b>	7,50	6,70	5,30	<b>14,00</b>	11,20	10,00	8,00
16	144 mm	<b>10,00</b>	8,00	20,00	17,00	<b>14,00</b>	11,20	10,00	8,00	<b>21,20</b>	17,00	15,00	12,00
18	162 mm	<b>12,50</b>	10,00	25,00	21,25	<b>17,50</b>	14,00	12,50	10,00	<b>26,20</b>	21,00	18,70	15,00
19	171 mm	<b>14,00</b>	11,20	28,00	23,80	<b>20,00</b>	16,00	14,00	11,20	<b>30,00</b>	24,00	21,20	17,00
20	180 mm	<b>16,00</b>	12,80	32,00	27,20	<b>21,20</b>	17,90	16,00	12,80	<b>33,60</b>	26,90	24,00	19,20
22	198 mm	<b>19,00</b>	15,00	38,00	32,30	<b>26,50</b>	21,20	19,00	15,00	<b>40,00</b>	32,00	28,00	22,40
23	207 mm	<b>21,00</b>	16,80	42,00	35,70	<b>29,50</b>	23,60	21,00	16,80	<b>44,10</b>	35,20	31,50	25,20
26	234 mm	<b>26,50</b>	21,20	53,00	45,05	<b>37,50</b>	30,00	26,50	21,20	<b>56,00</b>	44,80	40,00	32,00
32	288 mm	<b>40,00</b>	31,50	80,00	68,00	<b>56,00</b>	45,00	40,00	31,50	<b>85,00</b>	68,00	60,00	48,00
<b>FAKTOR</b>		<b>1</b>	0,8	2	1,7	<b>1,4</b>		<b>1</b>		<b>2,1</b>		<b>1,5</b>	
<b>USYMMETRISK FAKTOR</b>						Bruk løftekapasitet 1 stropp				Bruk løftekapasitet 2 stropper			
WLL for kjettingredskap gjelder for temperaturområde fra -40°C opp til 200°C - Følg alltid produsentens anbefalinger ved løft													

# LØFTETABELL FOR STÅLTAUSTROPPER

Med bløte øyer og stålkjerne (IWRC) i samsvar med EN 13414-1

Sikkerhetsfaktor = 5

- Lastens diameter og anleggsdiameter bør være minst 6 x diameter av ståltauet ved snaring og u-løft

- Ved snaring reduseres løftekapasitet til 80 % av rett løft WLL

Rev.nr. 1.2023

Diameter mm	Anb. Min. Anl. Dia.	Rett løft WLL	Snaret Loft		U-løft Vinkel	0-45°		45,1°-60°		0-45°		45,1°-60°	
			Direkte	Snaret		Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret
<b>EN STROPPE</b>													
8	48 mm	<b>0,75</b>	0,6	1,5	1,2	<b>1,0</b>	0,8	0,7	0,6	<b>1,5</b>	1,2	1,1	0,8
10	60 mm	<b>1,1</b>	0,9	2,3	1,9	<b>1,6</b>	1,2	1,1	0,9	<b>2,4</b>	1,9	1,7	1,3
12	72 mm	<b>1,7</b>	1,3	3,4	2,9	<b>2,3</b>	1,8	1,7	1,3	<b>3,5</b>	2,8	2,5	2,0
14	84 mm	<b>2,2</b>	1,8	4,5	3,8	<b>3,1</b>	2,5	2,2	1,8	<b>4,8</b>	3,8	3,4	2,7
16	96 mm	<b>3,0</b>	2,4	6,0	5,1	<b>4,2</b>	3,3	3,0	2,4	<b>6,3</b>	5,0	4,5	3,6
18	108 mm	<b>3,7</b>	2,9	7,4	6,3	<b>5,2</b>	4,1	3,7	2,9	<b>7,8</b>	6,2	5,6	4,5
20	120 mm	<b>4,6</b>	3,6	9,2	7,8	<b>6,5</b>	5,2	4,6	3,6	<b>9,8</b>	7,8	6,9	5,5
22	132 mm	<b>5,6</b>	4,5	11,3	9,6	<b>7,8</b>	6,2	5,6	4,5	<b>11,8</b>	9,4	8,4	6,7
24	144 mm	<b>6,7</b>	5,3	13,4	11,4	<b>9,4</b>	7,5	6,7	5,3	<b>14,0</b>	11,2	10,0	8,0
26	156 mm	<b>7,8</b>	6,2	15,6	13,2	<b>11,0</b>	8,8	7,8	6,2	<b>16,5</b>	13,2	11,5	9,2
28	168 mm	<b>9,0</b>	7,2	18,0	15,3	<b>12,5</b>	10,0	9,0	7,2	<b>19,0</b>	15,2	13,5	10,8
32	192 mm	<b>11,8</b>	9,4	23,6	20,0	<b>16,5</b>	13,2	11,8	9,4	<b>25,0</b>	20,0	17,5	14,0
FAKTOR	1	0,8	2	1,7		<b>1,4</b>		1		<b>2,1</b>		1,5	
<b>USYMMETRISK FAKTOR</b>				<b>Bruk løftekapasitet 1 stropp</b>				<b>Bruk løftekapasitet 2 stropper</b>					
WLL for ståltau med stålkjerne og aluminiumspresslås gjelder for temperaturområde fra -40°C opp til 150°C Følg alltid produsentens anbefalinger ved løft													

# LØFTETABELL FOR STÅLTAUSTROPPER

Med bløte øyer og fiberkjerne (FC) i samsvar med EN 13414-1

Sikkerhetsfaktor = 5

- Lastens diameter og anleggsdiameter bør være minst 6 x diameter av ståltauet ved snaring og u-løft

- Ved snaring reduseres løftekapasitet til 80 % av rett løft WLL

Rev.nr. 1.2023

Diameter mm	Anb. Min. Anl. Dia.	Rett løft WLL		Snaret Løft		U-løft		U-løft Vinkel		0-45°		45,1°-60°		0-45°		45,1°-60°	
		Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret	Direkte	Snaret
<b>EN STROPP</b>																	
8	48 mm	0,7	0,5	1,4	1,1	0,9	0,7	0,7	0,5	1,5	1,2	1,0	0,8	2,2	1,8	1,6	1,2
10	60 mm	1,0	0,8	2,1	1,7	1,5	1,2	1,0	0,8	2,2	1,8	1,5	1,2	3,3	2,6	2,3	1,8
12	72 mm	1,5	1,2	3,0	2,6	2,1	1,7	1,5	1,2	3,3	2,6	2,1	1,7	4,3	3,4	3,1	2,5
14	84 mm	2,1	1,7	4,2	3,6	3,0	2,4	2,1	1,7	4,3	3,4	3,0	2,7	5,6	4,5	4,2	3,3
16	96 mm	2,7	2,1	5,4	4,6	3,8	3,0	2,7	2,1	5,6	4,5	4,3	3,8	7,2	5,7	5,2	4,1
18	108 mm	3,4	2,7	6,8	5,7	4,8	3,8	3,4	2,7	7,2	5,7	5,3	4,8	11,0	8,8	7,8	6,2
20	120 mm	4,3	3,4	8,7	7,4	6,0	4,8	4,3	3,4	9,0	7,2	6,8	5,8	13,5	10,8	9,4	7,5
22	132 mm	5,2	4,1	10,4	8,8	7,2	5,7	5,2	4,1	11,0	8,8	8,3	7,0	15,0	12,0	11,0	8,8
24	144 mm	6,3	5,0	12,6	10,7	8,8	7,0	6,3	5,0	13,5	10,8	10,0	8,7	18,0	14,4	12,5	10,0
26	156 mm	7,2	5,7	14,4	12,2	10,0	8,0	7,2	5,7	15,0	12,0	11,0	9,5	23,5	18,8	16,5	13,2
28	168 mm	8,4	6,7	16,8	14,2	11,8	9,4	8,4	6,7	18,0	14,4	12,5	11,0	21,0	17,5	15,5	12,0
32	192 mm	11,0	8,8	22,0	18,7	15,0	12,0	11,0	8,8	23,5	18,8	16,5	14,0	25,0	21,0	18,5	15,0
FAKTOR		1	0,8	2	1,7	1,4		1		2,1				1,5			
USYMMETRISK FAKTOR						Bruk løftekapasitet 1 stropp						Bruk løftekapasitet 2 stropper					
WLL for ståltau med fiberkjerne gjelder for temperaturområde fra -40°C opp til 100°C Følg alltid produsentens anbefalinger ved løft																	



# LIFTINGTABLE



Emergency numbers in Norway:

Fire

110

Police

112

Ambulance

113

Emergency room 116117

[booking@biks.no](mailto:booking@biks.no) • [biks.no](http://biks.no)

## Correct use of handsignals and radio communication


It's important that slinger, flagman and crane operator has knowledge about hand signals, and other expressions.



### HAND SIGNALS



HOIST



LOWER



DIRECTION



SLEW/SWING



STOP




EMERGENCY STOP




RAISE BOOM



LOWER BOOM



EXTEND BOOM



RETRACT BOOM



USE MAIN BLOCK



USE WHIP LINE

- Learn the signals
- Be placed in the right position.
- Check that the load is hooked correctly
- Give the signals clearly
- Avoid lifting with angle

- Learn the correct use of radio
- Test the radio before lifting
- Speak clear and slow
- Use continuous radio when load is out of sight of the crane driver
- Avoid unnecessary use of the radio

# LIFTING TABLE FOR FIBER SLINGS

Permitted lifting capacity (WLL) in accordance with EN 1492-1 and 2 in tonnes

Safety factor = 7

Rev.nr. 1.2023

- Follow the manufacturer's recommendations according to the diameter of the load when choked/ basket hitch

- With choking, lifting capacity is reduced to 80% of straight lift WLL

Colour	Recom. Min. Bar diameter	Straight WLL	Choked	Basket hitch	Basket hitch angle	0-45°		45,1°-60°		0-45°		45,1°-60°	
						Direct	Choked	Direct	Choked	Direct	Choked	Direct	Choked
ONE LEG													
Violet	20 mm	1,0	0,8	2,0	1,7	1,4	1,1	1,0	0,8	2,1	1,6	1,5	1,2
Green	20 mm	2,0	1,6	4,0	3,4	2,8	2,2	2,0	1,6	4,2	3,3	3,0	2,4
Yellow	30 mm	3,0	2,4	6,0	5,1	4,2	3,3	3,0	2,4	6,3	5,0	4,5	3,6
Grey	40 mm	4,0	3,2	8,0	6,8	5,6	4,4	4,0	3,2	8,4	6,7	6,0	4,8
Red	50 mm	5,0	4,0	10,0	8,5	7,0	5,6	5,0	4,0	10,5	8,4	7,5	6,0
Brown	60 mm	6,0	4,8	12,0	10,2	8,4	6,7	6,0	4,8	12,6	10,0	9,0	7,2
Blue	80 mm	8,0	6,4	16,0	13,6	11,2	8,9	8,0	6,4	16,8	13,4	12,0	9,6
Orange	80 mm	10,0	8,0	20,0	17,0	14,0	11,2	10,0	8,0	21,0	16,8	15,0	12,0
Orange	115 mm	15,0	12,0	30,0	25,5	21,0	16,8	15,0	12,0	31,5	25,2	22,5	18,0
Orange	120 mm	20,0	16,0	40,0	34,0	28,0	22,4	20,0	16,0	42,0	33,6	30,0	24,0
Orange	125 mm	25,0	20,0	50,0	42,5	35,0	28,0	25,0	20,0	52,5	42,0	37,5	30,0
Orange	130 mm	30,0	24,0	60,0	51,0	42,0	33,6	30,0	24,0	63,0	50,4	45,0	36,0
Orange	140 mm	40,0	32,0	80,0	68,0	56,0	44,8	40,0	32,0	84,0	67,2	60,0	48,0
FACTOR	1	0,8	2	1,7	1,4		1			2,1		1,5	
ASYMMETRICAL FACTOR						Use lifting capacity for 1 leg				Use lifting capacity for 2 legs			
Avoid friction, sharp edges and alkaline substances. - WLL for fibre slings of polyester applies for temperatures between -40°-100° Follow the manufacturer's instructions for safe use, control and maintenance													

# LIFTING TABLE CHAIN SLINGS - GRADE 80

Permitted workload (WLL) in tonnes in accordance with EN 818-4

Safety factor = 4

Rev.nr. 1.2023

- The load's diameter and installation diameter should be min. 9 times the diameter of the chain slings.

- With choking, lifting capacity is reduced to 80% of straight lift WLL

Diameter mm	Min. Rec. Bar Dia.	Straight WLL		Choked		Basket hitch		Basket hitch Angle		0-45°		45,1°-60°		0-45°		45,1°-60°	
		Direct	WLL	Chocked	Direct	WLL	Chocked	Angle	Direct	WLL	Chocked	Direct	WLL	Chocked	Direct	WLL	Chocked
<b>ONE LEG</b>		<b>TWO LEGS</b>		<b>THREE AND FOUR LEGS</b>								<b>ASYMMETRICAL FACTOR</b>					
7	63 mm	1,5	1,20	3,00	2,55	2,12	1,7		1,5	1,2	3,15	2,52	2,24	1,8			
8	72 mm	2,00	1,60	4,00	3,40	2,80	2,24		2,00	1,60	4,25	3,40	3,00	2,40			
10	90 mm	3,15	2,52	6,30	5,36	4,25	3,40		3,15	2,52	6,70	5,40	4,75	3,80			
13	117 mm	5,30	4,24	10,60	9,00	7,50	6,00		5,30	4,24	11,20	9,00	8,00	6,40			
16	144 mm	8,00	6,40	16,00	13,60	11,20	9,00		8,00	6,40	17,00	13,60	11,80	9,44			
18	162 mm	10,00	8,00	20,00	17,00	14,00	11,20		10,00	8,00	21,20	17,00	15,00	12,00			
19	171 mm	11,20	9,00	22,40	19,04	16,00	12,80		11,20	9,00	23,60	18,90	17,00	13,60			
20	180 mm	12,50	10,00	25,00	21,25	17,00	13,60		12,50	10,00	26,50	21,20	19,00	15,20			
22	198 mm	15,00	12,00	30,00	25,50	21,20	17,00		15,00	12,00	31,50	25,20	22,40	17,92			
23	207 mm	16,00	12,80	32,00	27,20	23,60	18,90		16,00	12,80	35,50	28,40	25,00	20,00			
25	225 mm	20,00	16,00	40,00	34,00	28,00	22,40		20,00	16,00	40,00	32,00	30,00	24,00			
26	234 mm	21,20	17,00	42,40	36,04	30,00	24,00		21,20	17,00	45,00	36,00	31,50	25,20			
28	252 mm	25,00	20,00	50,00	42,50	33,50	26,80		25,00	20,00	52,50	40,00	37,50	30,00			
32	288 mm	31,50	25,20	63,00	53,55	45,00	36,00		31,50	25,20	67,00	53,60	47,50	38,00			
<b>FACTOR</b>		1	0,8	2	1,7	1,4			1		2,1		1,5				
<b>ASYMMETRICAL FACTOR</b>						Use lifting capacity for 1 leg						Use lifting capacity for 2 legs					
WLL For chain tools applies to temperature range from -40°C up to 200°C - Always follow the manufacturer's recommendations when lifting																	

# LIFTING TABLE CHAIN SLINGS - GRADE 100

Permitted working load (WLL) in tonnes in accordance with EN 818-4

Safety factor = 4

Rev.nr. 1.2023

- The load's diameter and installation diameter should be min. 9 times the diameter of the chain slings.

- With choking, lifting capacity is reduced to 80% of straight lift WLL

Diameter mm	Min. Rec. Bar Dia.	Straight WLL	Choked	Basket hitch	Basket hitch Angle	0-45°		45,1°-60°		0-45°		45,1°-60°	
						Direct WLL	Choked	Direct	Choked	Direct WLL	Choked	Direct	Choked
<b>ONE LEG</b>													
5	45 mm	<b>1,00</b>	0,80	2,00	1,70	<b>1,40</b>	1,12	1,00	0,80	<b>2,00</b>	1,60	1,50	1,20
6	54 mm	<b>1,40</b>	1,12	2,80	2,38	<b>2,00</b>	1,60	1,40	1,12	<b>3,00</b>	2,40	2,12	1,70
7	63 mm	<b>1,90</b>	1,50	3,80	3,23	<b>2,65</b>	2,12	1,90	1,50	<b>4,00</b>	3,20	2,80	2,24
8	72 mm	<b>2,50</b>	2,00	5,00	4,25	<b>3,55</b>	2,80	2,50	2,00	<b>5,30</b>	4,24	3,75	3,00
10	90 mm	<b>4,00</b>	3,15	8,00	6,80	<b>5,60</b>	4,25	4,00	3,15	<b>8,00</b>	6,40	6,00	4,80
13	117 mm	<b>6,70</b>	5,30	13,40	11,40	<b>9,50</b>	7,50	6,70	5,30	<b>14,00</b>	11,20	10,00	8,00
16	144 mm	<b>10,00</b>	8,00	20,00	17,00	<b>14,00</b>	11,20	10,00	8,00	<b>21,20</b>	17,00	15,00	12,00
18	162 mm	<b>12,50</b>	10,00	25,00	21,25	<b>17,50</b>	14,00	12,50	10,00	<b>26,20</b>	21,00	18,70	15,00
19	171 mm	<b>14,00</b>	11,20	28,00	23,80	<b>20,00</b>	16,00	14,00	11,20	<b>30,00</b>	24,00	21,20	17,00
20	180 mm	<b>16,00</b>	12,80	32,00	27,20	<b>21,20</b>	17,90	16,00	12,80	<b>33,60</b>	26,90	24,00	19,20
22	198 mm	<b>19,00</b>	15,00	38,00	32,30	<b>26,50</b>	21,20	19,00	15,00	<b>40,00</b>	32,00	28,00	22,40
23	207 mm	<b>21,00</b>	16,80	42,00	35,70	<b>29,50</b>	23,60	21,00	16,80	<b>44,10</b>	35,20	31,50	25,20
26	234 mm	<b>26,50</b>	21,20	53,00	45,05	<b>37,50</b>	30,00	26,50	21,20	<b>56,00</b>	44,80	40,00	32,00
32	288 mm	<b>40,00</b>	31,50	80,00	68,00	<b>56,00</b>	45,00	40,00	31,50	<b>85,00</b>	68,00	60,00	48,00
<b>FAKTOR</b>		<b>1</b>	0,8	2	1,7	<b>1,4</b>		<b>1</b>		<b>2,1</b>		<b>1,5</b>	
<b>ASYMMETRICAL FACTOR</b>						Use lifting capacity for 1 leg				Use lifting capacity for 2 legs			
WLL For chain tools applies to temperature range from -40°C up to 200°C - Always follow the manufacturer's recommendations when lifting													

# LIFTING TABLE FOR WIRE ROPE SLINGS

Ferrule-secured eye terminations fibre cord(FC) according to EN 13414-1

Safety factor = 5

- The load's diameter and installation diameter should be min. 6 x diameter of the wire rope when choked/ basket hitch

- With choking, lifting capacity is reduced to 80 % of straight lift WLL

Rev.nr. 1.2023

Diameter mm	Min. Rec. Bar Dia.	Straight WLL	Choked	Basket hitch	Basket hitch Angle	0-45°		45,1°-60°		0-45°		45,1°-60°									
						Direct WLL	Choked	Direct	Choked	Direct WLL	Choked	Direct	Choked								
<b>ONE LEG</b>																					
8	48 mm	0,7	0,5	1,4	1,1	0,9	0,7	0,7	0,5	1,5	1,2	1,0	0,8								
10	60 mm	1,0	0,8	2,1	1,7	1,5	1,2	1,0	0,8	2,2	1,8	1,6	1,2								
12	72 mm	1,5	1,2	3,0	2,6	2,1	1,7	1,5	1,2	3,3	2,6	2,3	1,8								
14	84 mm	2,1	1,7	4,2	3,6	3,0	2,4	2,1	1,7	4,3	3,4	3,1	2,5								
16	96 mm	2,7	2,1	5,4	4,6	3,8	3,0	2,7	2,1	5,6	4,5	4,2	3,3								
18	108 mm	3,4	2,7	6,8	5,7	4,8	3,8	3,4	2,7	7,2	5,7	5,2	4,1								
20	120 mm	4,3	3,4	8,7	7,4	6,0	4,8	4,3	3,4	9,0	7,2	6,5	5,2								
22	132 mm	5,2	4,1	10,4	8,8	7,2	5,7	5,2	4,1	11,0	8,8	7,8	6,2								
24	144 mm	6,3	5,0	12,6	10,7	8,8	7,0	6,3	5,0	13,5	10,8	9,4	7,5								
26	156 mm	7,2	5,7	14,4	12,2	10,0	8,0	7,2	5,7	15,0	12,0	11,0	8,8								
28	168 mm	8,4	6,7	16,8	14,2	11,8	9,4	8,4	6,7	18,0	14,4	12,5	10,0								
32	192 mm	11,0	8,8	22,0	18,7	15,0	12,0	11,0	8,8	23,5	18,8	16,5	13,2								
<b>FACTOR</b>		1	0,8	2	1,7	1,4		1		2,1		1,5									
<b>ASYMMETRICAL FACTOR</b>						Use lifting capacity for 1 leg				Use lifting capacity for 2 legs											
WLL for slings with fibre cord applies for temperatures -40°C up to 100°C																					
Always read the manufacturer's instructions for safe use, maintenance and inspection																					

# LIFTING TABLE FOR WIRE ROPE SLINGS

Ferrule-secured eye terminations steel cord (IWRC) according to EN 13414-1

Safety factor = 5

- The load's diameter and installation diameter should be min. 6 x diameter of the wire rope when choked/ basket hitch

- With choking, lifting capacity is reduced to 80 % of straight lift WLL

Rev.nr. 1.2023

Diameter mm	Min. Rec. Bar Dia.	Straight WLL	Choked	Basket hitch	Basket hitch Angrel	0-45°		45,1°-60°		0-45°		45,1°-60°									
						Direct WLL	Choked	Direct	Choked	Direct WLL	Choked	Direct	Choked								
<b>ONE LEG</b>																					
8	48 mm	0,75	0,6	1,5	1,2	1,0	0,8	0,7	0,6	1,5	1,2	1,1	0,8								
10	60 mm	1,1	0,9	2,3	1,9	1,6	1,2	1,1	0,9	2,4	1,9	1,7	1,3								
12	72 mm	1,7	1,3	3,4	2,9	2,3	1,8	1,7	1,3	3,5	2,8	2,5	2,0								
14	84 mm	2,2	1,8	4,5	3,8	3,1	2,5	2,2	1,8	4,8	3,8	3,4	2,7								
16	96 mm	3,0	2,4	6,0	5,1	4,2	3,3	3,0	2,4	6,3	5,0	4,5	3,6								
18	108 mm	3,7	2,9	7,4	6,3	5,2	4,1	3,7	2,9	7,8	6,2	5,6	4,5								
20	120 mm	4,6	3,6	9,2	7,8	6,5	5,2	4,6	3,6	9,8	7,8	6,9	5,5								
22	132 mm	5,6	4,5	11,3	9,6	7,8	6,2	5,6	4,5	11,8	9,4	8,4	6,7								
24	144 mm	6,7	5,3	13,4	11,4	9,4	7,5	6,7	5,3	14,0	11,2	10,0	8,0								
26	156 mm	7,8	6,2	15,6	13,2	11,0	8,8	7,8	6,2	16,5	13,2	11,5	9,2								
28	168 mm	9,0	7,2	18,0	15,3	12,5	10,0	9,0	7,2	19,0	15,2	13,5	10,8								
32	192 mm	11,8	9,4	23,6	20,0	16,5	13,2	11,8	9,4	25,0	20,0	17,5	14,0								
<b>FACTOR</b>		<b>1</b>	<b>0,8</b>	<b>2</b>	<b>1,7</b>	<b>1,4</b>		<b>1</b>		<b>2,1</b>		<b>1,5</b>									
<b>ASYMMETRICAL FACTOR</b>						Use lifting capacity for 1 leg				Use lifting capacity for 2 legs											
WLL for slings with fibre cord applies for temperatures -40°C up to 150°C																					
Always read the manufacturer's instructions for safe use, maintenance and inspection																					

# FARGEKODER FOR SAKKYNDIG KONTROLL AV LØFTEUTSTYR

FARGE	ÅRSTALL	FARGE	ÅRSTALL
RØD	2025	RØD	2029
GUL	2026	GUL	2030
GRØNN	2027	GRØNN	2031
BLÅ	2028	BLÅ	2024

HVIT FARGE PÅFØRT ET REDSKAP BETYR AT DET SKAL REPARERES ELLER  
KASSERES

ALL LØFTEREDSKAP / UTSTYR SKAL HA DOKUMENTASJON PÅ SAKKYNDIG  
KONTROLL I TILLEGG TIL ÅRETS FARGE. SAKKYNDIG KONTROLL SKAL FORETAES  
HVER 12. MÅNED. ELLER OFTERE HVIS MILJØET TILSIER DET. KONTROLLEN  
SKAL FØRES PÅ ET KONTROLLSKJEMA, OG SKAL UTFØRES AV EN VIRKSOMHET  
SOM ER SERTIFISERT FOR DEN SLAGS UTSTYR. KONTROLLEN SKAL UTFØRES AV  
EN KONTROLLØR UTPEKT AV SAKKYNDIG VIRKSOMHET.