

# U6614: Assignment 3: Subway Fare Evasion Microdata

## Sample Solutions

2023-09-19

*Please submit your knitted .pdf file along with the corresponding R markdown (.rmd) via Courseworks by 11:59pm on the due date.*

## 1 Load libraries.

```
#remember to make sure these packaged are installed before trying to load
library(tidyverse)
library(fastDummies)
```

## 2 Load and inspect the two public defender client datasets (BDS & LAS).

- Get a good look at the data, but don't print long, chunky output here; one approach is to call the `str()` function for each dataset but to suppress the included list of attributes by including the option `give.attr = FALSE`.

```
arrests_bds <- read_csv("microdata_BDS_inclass.csv", na = "")
arrests_las <- read_csv("microdata_LAS_inclass.csv", na = "")
```

```
str(arrests_bds, give.attr = FALSE)
```

```
## spc_tbl_ [2,246 x 8] (S3: spec_tbl_df/tbl_df/tbl/data.frame)
## $ client_zip: num [1:2246] 11205 11385 11226 11207 11225 ...
## $ age       : num [1:2246] 25 20 19 17 21 52 59 32 22 19 ...
## $ ethnicity : chr [1:2246] "Hispanic" "Hispanic" "Non-Hispanic" "Non-Hispanic" ...
## $ race      : chr [1:2246] "White" "Black" "Black" "Black" ...
## $ male      : num [1:2246] 1 1 0 1 1 1 1 0 1 ...
## $ loc2      : chr [1:2246] "jefferson st l line station" "myrtle - wyckoff avs station" "winthrop s
## $ st_id     : num [1:2246] 100 119 156 156 156 156 156 156 156 ...
## $ year      : num [1:2246] 2016 2016 2016 2016 2016 ...
```

```
str(arrests_las, give.attr = FALSE)
```

```
## spc_tbl_ [1,965 x 9] (S3: spec_tbl_df/tbl_df/tbl/data.frame)
## $ client_zip : num [1:1965] 11222 10016 11236 11236 NA ...
## $ las_race_key : chr [1:1965] "Black" "Asian or Pacific Islander" "Black" "Black" ...
## $ hispanic_flag: chr [1:1965] "N" "N" "N" "N" ...
## $ age : num [1:1965] 32 47 20 64 23 29 26 52 52 22 ...
## $ year : num [1:1965] 2016 2016 2016 2016 2016 ...
## $ male : num [1:1965] 1 0 1 1 1 1 0 1 1 1 ...
## $ dismissal : num [1:1965] 0 1 0 0 0 0 1 0 0 1 ...
## $ loc2 : chr [1:1965] "kingston - throop avs" "avenue h q subway" "nostrand ave and fulton s" ...
## $ st_id : num [1:1965] 106 28 131 150 131 27 68 44 85 31 ...
```

2a) Give a brief overview of the data. The aim is not be exhaustive, but to paint a picture of they key features of the data with respect to the policy questions you’ll be exploring.

The BDS data includes 2246 observations (client arrest records), and the LAS data includes another 1965 observations. Both datasets include basic demographic information on age, sex, race, ethnicity (coded differently in each dataset), as well as information on the location/subway station where the arrest occurred. The LAS data also includes information on case dismissal rates.

2b) For each dataset, what is the unit of observation and population represented by this “sample”? Do you think this sample does a good job representing the population of interest? Why or why not?

In each raw dataset, the unit of observation is the arrested individual (client). On the surface the representative population is all individuals arrested by the NYPD for subway fare evasion in Brooklyn during 2016 who are represented by public defenders. If nearly all individuals arrested for fare evasion are represented by public defenders, then this sample comes close to the universe of subway fare evasion arrests in Brooklyn in 2016. This is difficult to argue convincingly without additional information, but is supported anecdotally by court observers.

2c) Inspect and describe the coding of race and ethnicity in each dataset.

```
#recode race/ethnicity information from character to factors
arrests_bds <- arrests_bds %>% mutate(race = as.factor(race),
                                     ethnicity = as.factor(ethnicity) )
arrests_las <- arrests_las %>% mutate(race = as.factor(las_race_key),
                                     ethnicity = as.factor(hispanic_flag) )

#compare race coding
summary(arrests_bds$race)
```

```
##           0           Am Indian Asian/Pacific Islander
##          35           1           21
##        Black           Other           Unknown
##        1465           32           2
##        White           NA's
##        533           157
```

```
summary(arrests_las$race)
```

## Asian or Pacific Islander		Black	Hispanic
## 11		1247	21
## Latino		Other	Unknown
## 2		20	10
## White		NA's	
## 426		228	

```
#compare Hispanic/ethnicity coding
summary(arrests_bds$ethnicity)
```

## 0	Hispanic	Non-Hispanic	Other	NA's
## 33	493	1558	5	157

```
summary(arrests_las$ethnicity)
```

## N	Y	NA's
## 1619	189	157

Race information is generally stored in one variable, Hispanic identity in a second variable. To work towards consistent variable names and coding in both datasets, let's first recode the raw race and ethnicity information into two separate columns of data (factors) named `race` and `ethnicity`.

While each dataset refers to similar race and ethnicity categories, there are different category names in each (including some slightly different spellings).

We also note that Hispanic identity factors into both race and Hispanic variables in the Legal Aid Society (LAS) data; in the BDS data, information on Hispanic identity is only included in the ethnicity variable.

Each dataset also contains a different set of values that seem to convey unknown race/ethnicity information, in addition to true missings (e.g. "0" and "Unknown" in addition to blank entries).

## 2d) From the outset, are there any data limitations you think are important to note?

It's unclear what processes are used to code race and ethnicity at each public defender group. How much does the information reflect client self-identification rather than identity assigned by police and entered into arrest reports?

It's also important to emphasize what information this data does **not** include that might be relevant to the question of biased fare evasion enforcement:

- fare evasion that resulted in a summons (ticket + fine) rather than an arrest
- fare evasion enforcement on buses

### 3 Clean BDS race and ethnicity data (insert code chunks that only include code you used to recode and very briefly validate your recoding).

3a) BDS: race data (generate column race\_clean).

```
#identify every combination of race-ethnicity in the raw data
table(arrests_bds$race, arrests_bds$ethnicity, useNA = "always")
```

```
##
##           0 Hispanic Non-Hispanic Other <NA>
## 0           31         1           3      0    0
## Am Indian    0         0           1      0    0
## Asian/Pacific Islander 0         0          21    0    0
## Black        2        104         1358     1    0
## Other        0         20          11     1    0
## Unknown      0         0           0      2    0
## White        0        368          164     1    0
## <NA>         0         0           0      0   157
```

```
#recode as factor in an internally consistent manner (address NAs, specify levels)
arrests_bds.clean <- arrests_bds %>%
  mutate(race_clean = recode(race, "0" = "NA",
                              "Unknown" = "NA",
                              "Am Indian" = "Other" ) ) %>%
  mutate(race_clean = factor(race_clean,
                             levels = c("Black",
                                           "White",
                                           "Asian/Pacific Islander",
                                           "Other"))))

#validation: confirm the recode worked as intended
arrests_bds.clean %>% count(race_clean, sort = TRUE)
```

```
## # A tibble: 5 x 2
##   race_clean      n
##   <fct>         <int>
## 1 Black        1465
## 2 White         533
## 3 <NA>         194
## 4 Other         33
## 5 Asian/Pacific Islander 21
```

```
table(arrests_bds.clean$race, arrests_bds.clean$race_clean, useNA = "always")
```

```
##
##           Black White Asian/Pacific Islander Other <NA>
## 0           0     0           0      0    35
## Am Indian    0     0           0      1     0
## Asian/Pacific Islander 0     0          21    0     0
```

```
## Black 1465 0 0 0 0
## Other 0 0 0 32 0
## Unknown 0 0 0 0 2
## White 0 533 0 0 0
## <NA> 0 0 0 0 157
```

3b) BDS: ethnicity data (generate column ethnicity\_clean).

```
#ok now let's recode to Hispanic, Non-Hispanic, and NA
arrests_bds.clean <- arrests_bds.clean %>%
  mutate(hispanic = recode(ethnicity, "0" = "NA",
                           "Other" = "Non-Hispanic") ) %>%
  mutate(hispanic = factor(hispanic, levels = c("Hispanic", "Non-Hispanic")))

#validation: confirm the recode worked as intended
summary(arrests_bds.clean$hispanic)
```

```
## Hispanic Non-Hispanic NA's
## 493 1563 190
```

```
table(arrests_bds.clean$race_clean, arrests_bds.clean$hispanic, useNA = "always")
```

```
##
## Hispanic Non-Hispanic <NA>
## Black 104 1359 2
## White 368 165 0
## Asian/Pacific Islander 0 21 0
## Other 20 13 0
## <NA> 1 5 188
```

3c) Generate a single race/ethnicity factor variable race\_eth with mutually exclusive categories.

```
#let's investigate a bit
table(arrests_bds.clean$race_clean, arrests_bds.clean$hispanic, useNA = "always")
```

```
##
## Hispanic Non-Hispanic <NA>
## Black 104 1359 2
## White 368 165 0
## Asian/Pacific Islander 0 21 0
## Other 20 13 0
## <NA> 1 5 188
```

```
#generate race_eth column (as a factor) in steps
arrests_bds.clean <- arrests_bds.clean %>%
  mutate(race_clean_char = as.character(race_clean)) %>% #work with characters
  mutate(hispanic_char = as.character(hispanic)) %>% #work with characters
  mutate(race_eth = ifelse(hispanic_char %in% "Hispanic",
```

```

        hispanic_char,
        race_clean_char) ) %>%
mutate(race_eth = as.factor(recode(race_eth,
                                "White" = "Non-Hispanic White",
                                "Black" = "Non-Hispanic Black")) %>%
select(-race_clean_char, -hispanic_char)

#validate results: joint distribution of race_eth and hispanic
table(arrests_bds.clean$race_eth, arrests_bds.clean$hispanic, useNA = "always")

```

```

##
##           Hispanic Non-Hispanic <NA>
## Asian/Pacific Islander      0      21    0
## Hispanic                   493       0    0
## Non-Hispanic Black          0     1359    2
## Non-Hispanic White          0      165    0
## Other                       0       13    0
## <NA>                        0        5  188

```

```

arrests_bds.clean %>% count(race_eth, sort = TRUE)

```

```

## # A tibble: 6 x 2
##   race_eth      n
##   <fct>      <int>
## 1 Non-Hispanic Black    1361
## 2 Hispanic             493
## 3 <NA>                 193
## 4 Non-Hispanic White    165
## 5 Asian/Pacific Islander   21
## 6 Other                 13

```

Note that `race_eth` assigns individuals who identify as both Hispanic and a race other than white as Hispanic. This means, for example, that an individual who identifies as both Black and Hispanic appears as Hispanic in the `race_eth` column.

## 4 Clean LAS race and ethnicity data

4a) Follow your own steps to end up at a comparably coded `race_eth` variable for the LAS data.

*NOTE: you may be able to do everything in a single pipe, depending on your approach, (but you certainly don't have to).*

```
#inspect race/ethnicity coding in LAS data
```

```
table(arrests_las$las_race_key, arrests_las$hispanic_flag, useNA = "always")
```

```
##
##              N      Y <NA>
## Asian or Pacific Islander    11    0    0
## Black                      1201   46    0
## Hispanic                     20    1    0
## Latino                       2    0    0
## Other                        11    9    0
## Unknown                     10    0    0
## White                       294  132    0
## <NA>                         70    1  157
```

```
#generate race_eth column as a factor
```

```
arrests_las.clean <- arrests_las %>%
  mutate(race_eth = recode(las_race_key, "Asian or Pacific Islander" = "Asian/Pacific Islander",
    "Unknown" = "NA",
    "Latino" = "Hispanic",
    "White" = "Non-Hispanic White",
    "Black" = "Non-Hispanic Black")) %>%
  mutate(race_eth = ifelse(hispanic_flag %in% "Y", "Hispanic", race_eth) ) %>%
  mutate(race_eth = factor(race_eth,
    levels = c("Non-Hispanic Black",
      "Hispanic",
      "Non-Hispanic White",
      "Asian/Pacific Islander",
      "Other")))
```

```
#validate
```

```
arrests_las.clean %>% count(race_eth, sort = TRUE)
```

```
## # A tibble: 6 x 2
##   race_eth      n
##   <fct>      <int>
## 1 Non-Hispanic Black    1201
## 2 Non-Hispanic White    294
## 3 <NA>                 237
## 4 Hispanic             211
## 5 Asian/Pacific Islander    11
## 6 Other                 11
```

```
table(arrests_las.clean$race_eth, arrests_las.clean$hispanic_flag, useNA = "always")
```

```
##
##           N      Y <NA>
## Non-Hispanic Black 1201  0   0
## Hispanic           22 189   0
## Non-Hispanic White 294   0   0
## Asian/Pacific Islander 11  0   0
## Other              11  0   0
## <NA>               80   0 157
```

## 5 Combining (appending) the BDS and LAS microdata

5a) Create a column (pd) to identify public defender data source.

```
arrests_bds.clean <- arrests_bds.clean %>% mutate(pd = "bds")
arrests_las.clean <- arrests_las.clean %>% mutate(pd = "las")
```

5b) Append arrests\_bds.clean and arrests\_las.clean using bind\_rows(). Store as new data frame arrests.clean and inspect for consistency/accuracy.

```
arrests.clean <- bind_rows(arrests_las.clean, arrests_bds.clean) %>%
  mutate(pd = as.factor(pd),
         st_id = as.factor(st_id),
         loc2 = as.factor(loc2)) %>% #station/location info is not continuous
  select(pd, race_eth, age, male, dismissal, st_id, loc2)
summary(arrests.clean)
```

```
##      pd      race_eth      age      male
## bds:2246 Non-Hispanic Black :2562 Min.   : 0.00 Min.   :0.0000
## las:1965 Hispanic           : 704 1st Qu.:20.00 1st Qu.:1.0000
##          Non-Hispanic White : 459 Median :26.00 Median :1.0000
##          Asian/Pacific Islander: 32 Mean   :29.18 Mean   :0.8748
##          Other                : 24 3rd Qu.:35.00 3rd Qu.:1.0000
##          NA's                 : 430 Max.   :71.00 Max.   :1.0000
##          NA's                 :317 NA's    :314
##      dismissal      st_id      loc2
## Min.   :0.0000 66      : 223 coney island-stillwell ave      : 223
## 1st Qu.:0.0000 99      : 198 jay st - metrotech              : 198
## Median :1.0000 150     : 143 utica ave and fulton st         : 143
## Mean   :0.5392 70      : 142 utica ave and eastern parkway   : 142
## 3rd Qu.:1.0000 114     : 141 marcy ave j m z line            : 141
## Max.   :1.0000 131     : 141 nostrand ave and fulton st a c station: 141
## NA's    :2529 (Other):3223 (Other)                          :3223
```

5c) What is the total number of subway fare evasion arrest records?

The total number of subway fare evasion arrest records from both BDS and LAS is 4211.



5d) Save `arrests.clean` as an `.RData` file, in a folder for next class called `Lecture4`.

```
save(list = "arrests.clean",  
      file = "arrests.clean.RData")
```

## 6 Descriptive statistics by race/ethnicity

6a) Print the number of arrests for each race/ethnicity category (a frequency table).

```
arrests.clean %>% count(race_eth, sort = TRUE)
```

```
## # A tibble: 6 x 2
##   race_eth      n
##   <fct>      <int>
## 1 Non-Hispanic Black    2562
## 2 Hispanic              704
## 3 Non-Hispanic White    459
## 4 <NA>                 430
## 5 Asian/Pacific Islander  32
## 6 Other                 24
```

6b) Print the proportion of total arrests for each race/ethnicity category. How does excluding NAs change the results?

```
#including NAs
prop.table(table(arrests.clean$race_eth, useNA = "always")) %>%
  round(2) %>%
  as.data.frame() %>%
  arrange(desc(Freq)) %>%
  rename(race_eth = Var1)
```

```
##           race_eth Freq
## 1 Non-Hispanic Black 0.61
## 2           Hispanic 0.17
## 3 Non-Hispanic White 0.11
## 4           <NA> 0.10
## 5 Asian/Pacific Islander 0.01
## 6           Other 0.01
```

```
#excluding NAs
prop.table(table(arrests.clean$race_eth)) %>%
  round(2) %>%
  as.data.frame() %>%
  arrange(desc(Freq)) %>%
  rename(race_eth = Var1)
```

```
##           race_eth Freq
## 1 Non-Hispanic Black 0.68
## 2           Hispanic 0.19
## 3 Non-Hispanic White 0.12
## 4 Asian/Pacific Islander 0.01
## 5           Other 0.01
```

6c) Show the average age, share male, and dismissal rate for each race/ethnicity category. Describe any noteworthy findings.

```
race_eth_stats <- arrests.clean %>%
  group_by(race_eth) %>%
  summarise(n = n(),
            mean_age = mean(age, na.rm = TRUE),
            mean_male = mean(male, na.rm = TRUE),
            mean_dismissal = mean(dismissal, na.rm = TRUE) )
race_eth_stats
```

```
## # A tibble: 6 x 5
##   race_eth          n mean_age mean_male mean_dismissal
##   <fct>          <int>   <dbl>   <dbl>         <dbl>
## 1 Non-Hispanic Black 2562    29.1    0.875         0.514
## 2 Hispanic           704    29.7    0.901         0.538
## 3 Non-Hispanic White  459    29.7    0.898         0.587
## 4 Asian/Pacific Islander  32    28.9    0.938         0.636
## 5 Other              24    28.3    0.833         0.444
## 6 <NA>             430    26.0    0.603         0.75
```

Interestingly, arrested individuals with NA race/ethnicity are 3 to 4 years younger on average, and only 61% male compared to 83 to 94% male for those with race/ethnicity specified in the data.

The dismissal rate is also noticeably higher for API individuals, and lower for NA individuals. However, the sample sizes for these groups are very small by comparison, and the dismissal variable is only included in the LAS data so the samples sizes for that column are even smaller than for the other columns! With such a small number of observations for these groups it is very unlikely that we'd be able to conclude there are true differences in dismissal rates between API and NA individuals and other groups—we could do t-tests to check, more on that next week! Said another way, we can't rule out that the differences we see here are due to sampling variation, and thus should not be emphasizing them as findings at this point.

## 7 Subway-station level analysis

7a) Create dummy variables for each race/ethnicity category and show summary statistics only for these dummy variables.

```
arrests_clean <- dummy_cols(arrests_clean, select_columns = "race_eth")
arrests_clean %>%
  summarise(mean_black = round(mean(`race_eth_Non-Hispanic Black`, na.rm = TRUE), 2),
            mean_hisp = round(mean(race_eth_Hispanic, na.rm = TRUE), 2),
            mean_nhw = round(mean(`race_eth_Non-Hispanic White`, na.rm = TRUE), 2),
            mean_api = round(mean(`race_eth_Asian/Pacific Islander`, na.rm = TRUE), 2),
            mean_oth = round(mean(race_eth_Other, na.rm = TRUE), 2),
            mean_NA = round(mean(race_eth_NA, na.rm = TRUE), 2) )
```

```
## # A tibble: 1 x 6
##   mean_black mean_hisp mean_nhw mean_api mean_oth mean_NA
##   <dbl>      <dbl>    <dbl>    <dbl>    <dbl>    <dbl>
## 1      0.68      0.19      0.12      0.01      0.01      0.1
```

7b) Aggregate to station-level observations and show a table with the top 10 stations by arrest totals, including the following information for each station:

- station name (loc2)
- station id
- total number of arrests at each station
- total number of arrests for each race\_eth category at each station
- sort in descending order by total number of arrests
- remember to only show the top 10 stations
- use kable() in the knitr package for better formatting

```
arrests_stations <- arrests_clean %>%
  group_by(loc2) %>%
  summarise(st_id = first(st_id),
            n = n(),
            n_black = sum(`race_eth_Non-Hispanic Black`, na.rm = TRUE),
            n_hisp = sum(race_eth_Hispanic, na.rm = TRUE),
            n_api = sum(`race_eth_Asian/Pacific Islander`, na.rm = TRUE),
            n_nhw = sum(`race_eth_Non-Hispanic White`, na.rm = TRUE),
            n_oth = sum(race_eth_Other, na.rm = TRUE) ) %>%
  arrange(desc(n))
knitr::kable(head(arrests_stations, n = 10))
```

loc2	st_id	n	n_black	n_hisp	n_api	n_nhw	n_oth
coney island-stillwell ave	66	223	124	48	5	35	1
jay st - metrotech	99	198	112	43	3	29	0
utica ave and fulton st	150	143	112	19	0	7	0
utica ave and eastern parkway	70	142	118	13	0	5	0
marcy ave j m z line	114	141	55	42	3	34	0
nostrand ave and fulton st a c station	131	141	107	20	0	7	1

loc2	st_id	n	n_black	n_hisp	n_api	n_nhw	n_oth
canarsie rockaway pkwy	54	133	109	4	1	11	2
sutter avenue station l line	147	102	79	12	0	6	0
kingston - throop avs	106	90	69	12	0	6	0
nevins st 2 3 4 5 lines	123	86	63	11	0	6	1

**7c) Aggregate to station-level observations (group by loc2), and show a table of stations with at least 50 arrests along with the following information:**

- station name (loc2)
- station arrest total
- share of arrests that are Black and Hispanic (excluding race\_eth = NA from denominator)
- sorted in ascending order above (of) Black and Hispanic arrest share
- remember to only show stations with at least 50 total arrests
- use kable() in the knitr package for better formatting

```
arrests_stations_top <- arrests.clean %>%
  group_by(loc2) %>%
  summarise(st_id = first(st_id),
            n = n(),
            n_black = sum(`race_eth_Non-Hispanic Black`, na.rm = TRUE),
            n_hisp = sum(race_eth_Hispanic, na.rm = TRUE),
            n_bh = sum(`race_eth_Non-Hispanic Black`, race_eth_Hispanic, na.rm = TRUE),
            n_na = sum(race_eth_NA),
            sh_bh = round(n_bh / (n - n_na), 2)) %>%
  select(loc2, n, n_bh, n_na, sh_bh) %>%
  filter(n >= 50) %>%
  arrange(sh_bh)
knitr::kable(arrests_stations_top)
```

loc2	n	n_bh	n_na	sh_bh
marcy ave j m z line	141	97	7	0.72
myrtle av and broadway station	69	53	3	0.80
coney island-stillwell ave	223	172	10	0.81
graham ave l line	54	39	6	0.81
broadway and lorimer st j m station	70	56	2	0.82
clinton - washington avs station	63	48	5	0.83
jay st - metrotech	198	155	11	0.83
hoyt-schermerhorn a c g line	71	55	6	0.85
myrtle - willoughby avs g line	50	39	5	0.87
canarsie rockaway pkwy	133	113	6	0.89
nevins st 2 3 4 5 lines	86	74	5	0.91
hoyt st 2 3	77	70	2	0.93
kingston - throop avs	90	81	3	0.93
nostrand ave and fulton st a c station	141	127	6	0.94
sutter avenue station l line	102	91	5	0.94
utica ave and fulton st	143	131	5	0.95
court st r subway/borough hall 2 subway 3 subway 4 subway 5 subway	59	53	4	0.96
junius st 3 line	75	70	2	0.96
livonia ave l line	75	69	3	0.96

loc2	n	n_bh	n_na	sh_bh
utica ave and eastern parkway	142	131	6	0.96
rockaway ave c line	61	57	3	0.98
sutter av - rutland rd 3 line	68	64	3	0.98
rockaway ave 3 line	61	57	4	1.00

7d) Briefly summarize any noteworthy findings from the table you just generated.

At every single high-arrest subway station, the majority of arrested individuals are Black or Hispanic. This isn't surprising, given that 87 percent of *all* arrested individuals with coded race/ethnicity are Black or Hispanic.

## 8 (OPTIONAL) Visualize the distribution of arrests by race/ethnicity at stations with > 100 arrests.

- Hint: see R code from class, section 8

```
#get data frame with obs for every station-race_eth pairings on arrest counts
arrests_stations_race <- arrests.clean %>%
  group_by(loc2) %>%
  mutate(st_arrests = n()) %>%
  ungroup() %>%
  group_by(loc2, race_eth) %>%
  summarise(arrests = n(), st_arrests = first(st_arrests)) %>%
  arrange(desc(st_arrests)) %>%
  filter(st_arrests > 100)


arrests_stations_race
```

```
## # A tibble: 39 x 4
## # Groups:   loc2 [8]
##   loc2                race_eth      arrests st_arrests
##   <fct>              <fct>         <int>     <int>
## 1 coney island-stillwell ave Non-Hispanic Black      124      223
## 2 coney island-stillwell ave Hispanic              48      223
## 3 coney island-stillwell ave Non-Hispanic White      35      223
## 4 coney island-stillwell ave Asian/Pacific Islander     5      223
## 5 coney island-stillwell ave Other                  1      223
## 6 coney island-stillwell ave <NA>                   10      223
## 7 jay st - metrotech      Non-Hispanic Black     112      198
## 8 jay st - metrotech      Hispanic              43      198
## 9 jay st - metrotech      Non-Hispanic White      29      198
## 10 jay st - metrotech      Asian/Pacific Islander     3      198
## # i 29 more rows
```

```
g <- ggplot(arrests_stations_race,
  aes(x = reorder(loc2, -st_arrests),
    y = arrests, fill = race_eth)) +
```

```
geom_bar(stat = "identity") +
  theme(legend.position = "right",
        axis.title.x=element_blank(),
        axis.text.x = element_text(angle = 90,
                                     vjust = 0.5,
                                     hjust = 1)) +
  scale_fill_discrete(name = "Race/Ethnicity") +
  ggtitle("Distribution of arrests by race/ethnicity",
          subtitle = "At stations with > 100 arrests")
```

g



```
# alternative way, save plot and recall it
# ggsave(g, filename = "g.png")
# knitr::include_graphics("g.png")
```