



ABB LZ96 PowerFactory Relay model description



DgSILENT GmbH
Heinrich-Hertz-Strasse 9
D-72810 Gomaringen
Tel.: +49 7072 9168 - 0
Fax: +49 7072 9168- 88
<http://www.digsilent.de>
e-mail: mail@digsilent.de

ABB LZ96

PowerFactory
Relay model description

Published by
DgSILENT GmbH, Germany

Copyright 2009. All rights reserved. Unauthorised copying or publishing of this or any part of this document is prohibited.

doc.TechRef, Build 511 12 Januar 2021

Table of Contents

1 MODEL GENERAL DESCRIPTION.....	4
2 RELAY NOT SUPPORTED FEATURES.....	5

1 Model general description

The following functionalities are modelled:

- ◆ Starting feature (Starting Impedance: "Starting" block, Release current: "Release current" block)
- ◆ Polarization feature ("Polarizing" block)
- ◆ 4 Trip zone ("Z1", "Z2", "Z3", "Z4" block)
- ◆ 4 Timers ("Z1D", "Z2D", "Z3D", "Z4D" block)

12 different version of the relay model are available, one for each possible combination of rated frequency (50 or 60 Hz), rated input current (1 or 2 or 5 secondary Amperes) and rated input voltage (100-130 secondary volts or 200-260 secondary volts):

- LZ96 50 Hz 1 A 100-130 V
- LZ96 50 Hz 2 A 100-130 V
- LZ96 50 Hz 5 A 100-130 V
- LZ96 50 Hz 1 A 200-260 V
- LZ96 50 Hz 2 A 200-260 V
- LZ96 50 Hz 5 A 200-260 V
- LZ96 60 Hz 1 A 100-130 V
- LZ96 60 Hz 2 A 100-130 V
- LZ96 60 Hz 5 A 100-130 V
- LZ96 60 Hz 1 A 200-260 V
- LZ96 60 Hz 2 A 200-260 V
- LZ96 60 Hz 5 A 200-260 V

The model implementation has been based on the information available in the CH-ES 65-96 E Edition March 1980 document.

2 Relay not supported features

The following features are not supported:

- KE91 starting characteristic
- 3 phase undervoltage unit L91
- Autoreclosing
- Power swing protection
- Synchrocheck relay