

Class imbalance and Metric Learning

Charles Ollion - Olivier Grisel



Classic Deep Learning data setup

- Classification with a single label per sample
- 2-1000 classes ; 1000+ samples per class

Classic Deep Learning data setup

- Classification with a single label per sample
- 2-1000 classes ; 1000+ samples per class

Real life problems

What if I have multiple classes per sample?

Classic Deep Learning data setup

- Classification with a single label per sample
- 2-1000 classes ; 1000+ samples per class

Real life problems

What if I have multiple classes per sample?

What if I have unbalanced or noisy labels?

Classic Deep Learning data setup

- Classification with a single label per sample
- 2-1000 classes ; 1000+ samples per class

Real life problems

What if I have multiple classes per sample?

What if I have unbalanced or noisy labels?

What if I have 1M classes and 10 samples / class?

Outline

Multi-labeling and Sampling strategies

Outline

Multi-labeling and Sampling strategies

Metric Learning and siamese networks

Outline

Multi-labeling and Sampling strategies

Metric Learning and siamese networks

Triplet Loss and advanced techniques

Multi-labeling and Sampling strategies

Dealing with Imbalance

Many real-life datasets are imbalanced, e.g. **anomaly detection**:
(binary classification, most of the data is normal, very few points
are anomalies)

Dealing with Imbalance

Many real-life datasets are imbalanced, e.g. **anomaly detection**:
(binary classification, most of the data is normal, very few points
are anomalies)

The training process may fail if most batches have only a single
class in them

You may use **oversampling**, **importance weighting** of minority
classes / samples, to help the optimization process. In Keras:

Dealing with Imbalance

Many real-life datasets are imbalanced, e.g. **anomaly detection**:
(binary classification, most of the data is normal, very few points
are anomalies)

The training process may fail if most batches have only a single
class in them

You may use **oversampling**, **importance weighting** of minority
classes / samples, to help the optimization process. In Keras:

```
# build your own batches and add weights
model.train_on_batch(self, x, y, class_weight=None, sample_weight=None)
```

Dealing with Imbalance

Many real-life datasets are imbalanced, e.g. **anomaly detection**: (binary classification, most of the data is normal, very few points are anomalies)

The training process may fail if most batches have only a single class in them

You may use **oversampling**, **importance weighting** of minority classes / samples, to help the optimization process. In Keras:

```
# build your own batches and add weights  
model.train_on_batch(self, x, y, class_weight=None, sample_weight=None)
```

Evaluation must be very rigorous (the test set should represent the **true distribution** of data and labels)

Multilabel classification

Build a **binary classifier for each class** but with shared activations on hidden layers. Easily adapted from classic classification:

```
# ...
x = Convolution2D(2048, 3)(x)
x = GlobalAveragePooling2D()(x)
x = Dense(1000, activation="softmax")(x)
```

Multilabel classification

Build a **binary classifier for each class** but with shared activations on hidden layers. Easily adapted from classic classification:

```
# ...
x = Convolution2D(2048, 3)(x)
x = GlobalAveragePooling2D()(x)
x = Dense(1000, activation="sigmoid")(x)
```

Replace softmax with sigmoid (output activation)

Replace categorical_crossentropy with binary_crossentropy
(loss)

Multilabel classification

Build a **binary classifier for each class** but with shared activations on hidden layers. Easily adapted from classic classification:

```
# ...
x = Convolution2D(2048, 3)(x)
x = GlobalAveragePooling2D()(x)
x = Dense(1000, activation="sigmoid")(x)
```

Replace softmax with sigmoid (output activation)

Replace categorical_crossentropy with binary_crossentropy
(loss)

y^{true} is a binary vector corresponding to classes present in the image (many-hot encoding).

Multilabel classification

Build a **binary classifier for each class** but with shared activations on hidden layers. Easily adapted from classic classification:

```
# ...
x = Convolution2D(2048, 3)(x)
x = GlobalAveragePooling2D()(x)
x = Dense(1000, activation="sigmoid")(x)
```

Replace softmax with sigmoid (output activation)

Replace categorical_crossentropy with binary_crossentropy
(loss)

y^{true} is a binary vector corresponding to classes present in the image (many-hot encoding).

Problem : costly to label images exhaustively for ALL possible tags

Weak supervision



the veranda hotel
portixol palma



plane approaching zrh
avo regional jet rj




not as impressive as
embankment that's for sure



student housing by
lungaard tranberg
architects in copenhagen
click here to see where
this photo was taken



article in the local
paper about all the
unusual things found
at otto s home



this was another one with my old digital
camera i like the way it looks for some things
though slow and lower resolution than new
cameras another problem is that it's a bit of
a bummer when it's a point and shoot you're
carrying a bag with some room it's nearly x x
and weighs ounces new one is x x and weighs
ounces i underexposed this one a bit did
exposure compensation to combat overexposure on
that camera looks pretty yummy
gold kodak film like


Weak supervision



the veranda hotel
portixol palma



plane approaching zrh
avro regional jet rj



not as impressive as
embankment that s for sure



student housing by
lungaard tranberg
architects in copenhagen
click here to see where
this photo was taken



article in the local
paper about all the
unusual things found
at otto s home



this was another one with my old digital
camera i like the way it looks for some things
though slow and lower resolution than new
cameras another problem is that it's a bit of
a bummer when you are carrying a bag with some room it's nearly x
and weighs ounces new one is x and weighs
ounces i underexposed this one a bit did
exposure compensation to prevent overexposure on
gold kodak film like

- **Output dimension (vocabulary) is huge: ~100 000**

Joulin, Armand, et al. "Learning visual features from large weakly supervised data." ECCV, 2016


Weak supervision



the veranda hotel
portixol palma



plane approaching zrh
avro regional jet rj



not as impressive as
embankment that's for sure



student housing by
lunggaard tranberg
architects in copenhagen
click here to see where
this photo was taken



article in the local
paper about all the
unusual things found
at otto s home



this was another one with my old digital
camera i like the way it looks for some things
though slow and lower resolution than new
cameras another problem is that it's a bit of
a bummer when you're carrying a bag with some room it's nearly x
and weighs ounces new one is x and weighs
ounces i underexposed this one a bit did
exposure compensation to prevent overexposure on
that camera looks pretty yummy
gold kodak film like

- **Output dimension (vocabulary) is huge: ~100 000**
- After stopword removal, **importance sampling of positive labels**

Joulin, Armand, et al. "Learning visual features from large weakly supervised data." ECCV, 2016

Weak supervision



the veranda hotel
portixol palma



plane approaching zrh
avro regional jet rj



not as impressive as
embankment that's for sure



student housing by
lunggaard tranberg
architects in copenhagen
click here to see where
this photo was taken



article in the local
paper about all the
unusual things found
at otto s home



this was another one with my old digital
camera i like the way it looks for some things
though slow and lower resolution than new
cameras another problem is that it's a bit of
a bummer when you're carrying a bag with some room it's nearly x
and weighs ounces new one is x and weighs
ounces i underexposed this one a bit did
exposure compensation for overexposure on
that camera looks pretty yummy
gold kodak film like

- **Output dimension (vocabulary) is huge: ~100 000**
- After stopword removal, **importance sampling** of positive labels
- Do not compute the full softmax, randomly sample negatives
Joulin, Armand, et al. "Learning visual features from large weakly supervised datasets." ECCV, 2016

Weak supervision



Mahajan, Dhruv, et al. "Exploring the Limits of Weakly Supervised Pretraining." Technical Report, 2018

Weak supervision



- Facebook trained a ResNet on Instagram's hashtags
- Very noisy labels, most don't represent the image content

Mahajan, Dhruv, et al. "Exploring the Limits of Weakly Supervised Pretraining." Technical Report, 2018

Weak supervision



- Facebook trained a ResNet on Instagram's hashtags
- Very noisy labels, most don't represent the image content
- The model fine-tuned on ImageNet reached the best accuracy

Mahajan, Dhruv, et al. "Exploring the Limits of Weakly Supervised Pretraining." Technical Report, 2018

Inference tricks

You may train with a **softmax**, and do multilabel inference with a **sigmoid**

Inference tricks

You may train with a **softmax**, and do multilabel inference with a **sigmoid**

Fine tune the **output bias** parameter on a small by **fully labeled** dataset

Score reflects the posterior of a tag being present in an image,
e.g. $p(\text{dog} \mid \text{image})$

Inference tricks

You may train with a **softmax**, and do multilabel inference with a **sigmoid**

Fine tune the **output bias** parameter on a small by **fully labeled** dataset

Score reflects the posterior of a tag being present in an image,
e.g. $p(\text{dog} \mid \text{image})$

Measure **precision/recall** per class on a fully labeled test set.

Metric Learning & Siamese networks

Few Examples per class

ex: Face Recognition/Verification

Few Examples per class

ex: Face Recognition/Verification



Angela Mascia-Frye (1)



Angela Merkel (5)



Angelica Romero (1)



Angelina Jolie (20)



Angelo Genova (1)



Angelo Reyes (4)



Angie Arzola (1)



Angie Martinez (1)



Anibal Ibarra (3)



Anil Ramsook (1)

- **Recognition:** given a face, classify among K possible persons
- **Verification:** verify that two faces belongs to the same person

Few Examples per class

ex: Face Recognition/Verification



Angela Mascia-Frye (1)



Angela Merkel (5)



Angelica Romero (1)



Angelina Jolie (20)



Angelo Genova (1)



Angelo Reyes (4)



Angie Arzola (1)



Angie Martinez (1)



Anibal Ibarra (3)



Anil Ramsook (1)

- **Recognition:** given a face, classify among K possible persons
- **Verification:** verify that two faces belongs to the same person

Learning a distance function

We want to build $d_\theta(x_1, x_2)$ which indicates degree of difference between images

Learning a distance function

We want to build $d_\theta(x_1, x_2)$ which indicates degree of difference between images

We define a threshold T such that if $d_\theta(x_1, x_2) < T$, we consider x_1 and x_2 to be of the same class (e.g. identity)

Learning a distance function

We want to build $d_\theta(x_1, x_2)$ which indicates degree of difference between images

We define a threshold T such that if $d_\theta(x_1, x_2) < T$, we consider x_1 and x_2 to be of the same class (e.g. identity)

Not a real distance (no guarantee for triangle inequality)

Learning a distance function

We want to build $d_\theta(x_1, x_2)$ which indicates degree of difference between images

We define a threshold T such that if $d_\theta(x_1, x_2) < T$, we consider x_1 and x_2 to be of the same class (e.g. identity)

Not a real distance (no guarantee for triangle inequality)

Mahalanobis distance Metric Learning may be used to build distances, but are limited to linear projections, which won't be enough for fine-grained image analysis

Weinberger, Kilian Q., John Blitzer, and Lawrence K. Saul. "Distance metric learning for large margin nearest neighbor classification." Advances in neural information processing systems. 2006.

Learning a distance function

$$d_{\theta}(x_1, x_2) = \| f_{\theta}(x_1) - f_{\theta}(x_2) \|_2$$

Learning a distance function

$$d_\theta(x_1, x_2) = \| |f_\theta(x_1) - f_\theta(x_2)| \|_2$$

f_θ is typically a CNN which outputs a fixed dense \mathbb{R}^d representation of the image.

f_θ maps image space to an **isometric representation space** where a simple metric (e.g. euclidean distance) represents **semantic distance**.

Learning a distance function

$$d_\theta(x_1, x_2) = \| |f_\theta(x_1) - f_\theta(x_2)| \|_2$$

f_θ is typically a CNN which outputs a fixed dense \mathbb{R}^d representation of the image.

f_θ maps image space to an **isometric representation space** where a simple metric (e.g. euclidean distance) represents **semantic distance**.

For other problems (sound, NLP), different networks may be used (CNN with 1D convolutions, RNNs, ...) which output a fixed dimension vector representing each input element.

Learning a distance function

$$d_\theta(x_1, x_2) = \| |f_\theta(x_1) - f_\theta(x_2)| \|_2$$


f_θ is typically a CNN which outputs a fixed dense \mathbb{R}^d representation of the image.

f_θ maps image space to an **isometric representation space** where a simple metric (e.g. euclidean distance) represents **semantic distance**.

For other problems (sound, NLP), different networks may be used (CNN with 1D convolutions, RNNs, ...) which output a fixed dimension vector representing each input element.


Training f_θ is also called **representation learning**

Siamese networks



Chopra, Sumit, Raia Hadsell, and Yann LeCun. "Learning a similarity metric discriminatively, with application to face verification." CVPR 2005.

Loss function



Contrastive loss: Pushes together same class pairs, and further away different class ones, up to a margin.

$$L_{\text{contrastive}}(Y, D) = \frac{1}{2}(1 - Y)D^2 + \frac{1}{2}Y \max (0, m - D)^2$$

Chopra, Sumit, Raia Hadsell, and Yann LeCun. "Learning a similarity metric discriminatively, with application to face verification." CVPR 2005.

Alternative loss functions

Can derive equivalent contrastive loss for cosine similarity:

$$\cosine(f_\theta(x_1), f_\theta(x_2))$$

Alternative loss functions

Can derive equivalent contrastive loss for cosine similarity:

$$\text{cosine}(f_\theta(x_1), f_\theta(x_2))$$

Alternatively, absolute difference + Binary classification:

$$y = \text{sigmoid}(\mathbf{w} \cdot |f_\theta(x_1) - f_\theta(x_2)| + b)$$

Alternative loss functions

Can derive equivalent contrastive loss for cosine similarity:

$$\text{cosine}(f_\theta(x_1), f_\theta(x_2))$$

Alternatively, absolute difference + Binary classification:

$$y = \text{sigmoid}(\mathbf{w} \cdot |f_\theta(x_1) - f_\theta(x_2)| + b)$$

Also, concat + Binary classification

$$y = \text{sigmoid}(\mathbf{w} \cdot |f_\theta(x_1)| |f_\theta(x_2)| + b)$$

Alternative loss functions

Can derive equivalent contrastive loss for cosine similarity:

$$\text{cosine}(f_\theta(x_1), f_\theta(x_2))$$

Alternatively, absolute difference + Binary classification:

$$y = \text{sigmoid}(\mathbf{w} \cdot |f_\theta(x_1) - f_\theta(x_2)| + b)$$

Also, concat + Binary classification

$$y = \text{sigmoid}(\mathbf{w} \cdot [f_\theta(x_1) | f_\theta(x_2)] + b)$$

Simpler: regression after cosine similarity

Training

- sample positive pairs (x_i, x_j) , with (i, j) of same class
- sample negative pairs (x_i, x_j) , with (i, j) of different classes

Training

- sample positive pairs (x_i, x_j) , with (i, j) of same class
- sample negative pairs (x_i, x_j) , with (i, j) of different classes

Forward pass using both inputs through the two networks (**same parameters, different activations**)

Training

- sample positive pairs (x_i, x_j) , with (i, j) of same class
- sample negative pairs (x_i, x_j) , with (i, j) of different classes

Forward pass using both inputs through the two networks (**same parameters, different activations**)

Backpropagate through the two networks (the weights are updated with the **sum of the two gradients**)

Training

- sample positive pairs (x_i, x_j) , with (i, j) of same class
- sample negative pairs (x_i, x_j) , with (i, j) of different classes

Forward pass using both inputs through the two networks (**same parameters, different activations**)

Backpropagate through the two networks (the weights are updated with the **sum of the two gradients**)

Important to **craft batches carefully** (balance positive and negative, group positives together). Many negatives are *easy* (closer than margin) & don't contribute to the loss.

Dataset Face verification

Labeled Faces in the Wild (LFW)

13,000 pictures, 1680 identities with at least 2 pictures

Dataset Face verification

Labeled Faces in the Wild (LFW)

13,000 pictures, 1680 identities with at least 2 pictures

- results <http://vis-www.cs.umass.edu/lfw/results.html>
- DeepFace: 0.9735 binary classification accuracy

Taigman et. al., 2014. DeepFace closing the gap to human level performance

Dataset Face verification

Labeled Faces in the Wild (LFW)

13,000 pictures, 1680 identities with at least 2 pictures

- results <http://vis-www.cs.umass.edu/lfw/results.html>
- DeepFace: 0.9735 binary classification accuracy

YouTube Faces Database

3,425 videos of 1,595 different people averaging 181 frames per video

Cars196, CUB200, Online Products




16,185 images of 196 classes of cars

Cars196, CUB200, Online Products



16,185 images of 196 classes of cars



120,053 images, 22,634 Online Products (classes) from eBay.com. 5.3 images per class

Triplet Loss

Triplet Loss

A triplet: (x^a, x^+, x^-)

- an anchor image
- a positive image (same person as anchor)
- a negative image (different person as anchor)

We compute f_θ for each of these 3 images

Triplet Loss

A triplet: (x^a, x^+, x^-)

- an anchor image
- a positive image (same person as anchor)
- a negative image (different person as anchor)

We compute f_θ for each of these 3 images

We want that:

$$\| f(x^a) - f(x^-) \|_2 \geq \| f(x^a) - f(x^+) \|_2$$

Triplet Loss

A triplet: (x^a, x^+, x^-)

- an anchor image
- a positive image (same person as anchor)
- a negative image (different person as anchor)

We compute f_θ for each of these 3 images

We want that:

$$\| f(x^a) - f(x^-) \|_2 \geq \| f(x^a) - f(x^+) \|_2$$

$$\| f(x^a) - f(x^-) \|_2 - \| f(x^a) - f(x^+) \|_2 \geq \alpha$$

α margin typically small positive number (0.2, 0.5, ·)

Triplet Loss

A triplet: (x^a, x^+, x^-)

- an anchor image
- a positive image (same person as anchor)
- a negative image (different person as anchor)

We compute f_θ for each of these 3 images

We want that:

$$\| f(x^a) - f(x^-) \|_2 \geq \| f(x^a) - f(x^+) \|_2$$

$$\| f(x^a) - f(x^-) \|_2 - \| f(x^a) - f(x^+) \|_2 \geq \alpha$$

α margin typically small positive number (0.2, 0.5, ·)

Triplet Loss

$$l(x^a, x^+, x^-) =$$

$$\max(||f(x^a) - f(x^+)||_2 - ||f(x^a) - f(x^-)||_2 + \alpha, 0)$$

Triplet Loss

$$l(x^a, x^+, x^-) =$$

$$\max(||f(x^a) - f(x^+)||_2 - ||f(x^a) - f(x^-)||_2 + \alpha, 0)$$

Training

- Sample a minibatch of triplets $\{(x^a, x^+, x^-)_i\}$
- Forward pass on all 3 networks using f_θ
- Compute $\sum_i l((x^a, x^+, x^-)_i)$

Triplet Loss

$$l(x^a, x^+, x^-) =$$

$$\max(\|f(x^a) - f(x^+)\|_2 - \|f(x^a) - f(x^-)\|_2 + \alpha, 0)$$

Training

- Sample a minibatch of triplets $\{(x^a, x^+, x^-)_i\}$
- Forward pass on all 3 networks using f_θ
- Compute $\sum_i l((x^a, x^+, x^-)_i)$
- Compute the gradients through the 3 networks
- update f_θ using the sum of 3 gradients

Hard negative sampling

After a few epochs, If (x^a, x^+, x^-) are chosen randomly, it will be easy to satisfy the inequality.

Hard negative sampling

After a few epochs, If (x^a, x^+, x^-) are chosen randomly, it will be easy to satisfy the inequality.

Gradient in one batch quickly become almost 0 except for **hard cases**. Random sampling is inefficient to find these hard cases

Hard negative sampling

After a few epochs, If (x^a, x^+, x^-) are chosen randomly, it will be easy to satisfy the inequality.

Gradient in one batch quickly become almost 0 except for **hard cases**. Random sampling is inefficient to find these hard cases


- **Hard triplet sampling:** sample x^- such that:

$$\| f(x^a) - f(x^+) \|_2 > \| f(x^a) - f(x^-) \|_2 + \alpha$$

- **Semi Hard triplet sampling:** sample x^- such that:

$$\| f(x^a) - f(x^+) \|_2 > \| f(x^a) - f(x^-) \|_2$$

Hard negative sampling




- **Hard triplet sampling:** sample x^- such that:

$$\| f(x^a) - f(x^+) \|_2 > \| f(x^a) - f(x^-) \|_2 + \alpha$$


- **Semi Hard triplet sampling:** sample x^- such that:

Triplets results



Schroff, Florian, et al. Facenet: A unified embedding for face recognition and clustering, CVPR 2015. = hard negative mining and semi hard



Triplets results





- A threshold is computed on test set (1.2)
- Best model achieves 99.6% verification accuracy on LFW
- Face alignment is critical!

Schroff, Florian, et al. Facenet: A unified embedding for face recognition and clustering, CVPR 2015. = hard negative mining and semi hard

Quadruplet loss





Quadruplet loss





intraclass distance in a high-density region may be larger than the interclass distance in low-density regions

Quadruplet loss




Position-Dependent Deep Metric (PDDM) depends on two points
+ position of mean (red triangle)

Quadruplet loss



Sample a hard quadruplet (i, j) most dissimilar positive sample, and k and l are hard negatives

N-pair loss



- Generalization of triplets to n-uplets
- Samples pair of similar examples, negatives are all other samples in the batch

Sohn, Kihyuk. "Improved Deep Metric Learning with Multi-class N-pair Loss Objective", NIPS 2016

Results


K	CUB-200-2011						CARS196					
	1	2	4	8	16	32	1	2	4	8	16	32
Contrastive [1]	26.4	37.7	49.8	62.3	76.4	85.3	21.7	32.3	46.1	58.9	72.2	83.4
Triplet [27][33]	36.1	48.6	59.3	70.0	80.2	88.4	39.1	50.4	63.3	74.5	84.1	89.8
LiftedStruct [29]	47.2	58.9	70.2	80.2	89.3	93.2	49.0	60.3	72.1	81.5	89.2	92.8
PDDM+Triplet	50.9	62.1	73.2	82.5	91.1	94.4	46.4	58.2	70.3	80.1	88.6	92.6
PDDM+Quadruplet	58.3	69.2	79.0	88.4	93.1	95.7	57.4	68.6	80.1	89.4	92.3	94.9

Metric: Recall @K

Results

K	CUB-200-2011						CARS196					
	1	2	4	8	16	32	1	2	4	8	16	32
Contrastive [1]	26.4	37.7	49.8	62.3	76.4	85.3	21.7	32.3	46.1	58.9	72.2	83.4
Triplet [27][33]	36.1	48.6	59.3	70.0	80.2	88.4	39.1	50.4	63.3	74.5	84.1	89.8
LiftedStruct [29]	47.2	58.9	70.2	80.2	89.3	93.2	49.0	60.3	72.1	81.5	89.2	92.8
PDDM+Triplet	50.9	62.1	73.2	82.5	91.1	94.4	46.4	58.2	70.3	80.1	88.6	92.6
PDDM+Quadruplet	58.3	69.2	79.0	88.4	93.1	95.7	57.4	68.6	80.1	89.4	92.3	94.9

Metric: Recall @K



Getting started

Available open source implementations / pretrained models:

- Openface <https://cmusatyalab.github.io/openface/>
- FaceNet <https://github.com/davidsandberg/facenet>

Commercial recognition systems are trained on a large datasets like 10/100 million images

Getting started

Available open source implementations / pretrained models:

- Openface <https://cmusatyalab.github.io/openface/>
- FaceNet <https://github.com/davidsandberg/facenet>

Commercial recognition systems are trained on a large datasets like 10/100 million images

Deploying Verification models e.g. Iphone FaceID:

Beforehand, precompute representations of your 10 photos

Getting started

Available open source implementations / pretrained models:

- Openface <https://cmusatyalab.github.io/openface/>
- FaceNet <https://github.com/davidsandberg/facenet>

Commercial recognition systems are trained on a large datasets like 10/100 million images



Deploying Verification models e.g. Iphone FacID:

Beforehand, precompute representations of your 10 photos

At test time, compute representation of the photo, then compute similarities with the 10 representations



If a similarity is within a predefined threshold then Unlock!

Self-supervised learning



SimCLR uses a contrastive loss on pairs of heavily augmented images vs independent images in the batch.

Self-supervised learning



SimCLR uses a contrastive loss on pairs of heavily augmented images vs independent images in the batch.

BYOL can even do away with the negative terms with an asymmetric architecture.

Take Aways on classification

- For most cases, use a **classifier with softmax**
- If you have many classes, and/or strong class imbalance use **representation learning**
- both can give useful embeddings for clustering / low shot learning

Take Aways on classification

- For most cases, use a **classifier with softmax**
- If you have many classes, and/or strong class imbalance use **representation learning**
- both can give useful embeddings for clustering / low shot learning
- Use **ImageNet pre-trained features** in most cases
- If you have many many unlabeled images, self-supervised learning can be an alternative
- Very active area of research!

Take Aways on classification

- For most cases, use a **classifier with softmax**
- If you have many classes, and/or strong class imbalance use **representation learning**
- both can give useful embeddings for clustering / low shot learning
- Use **ImageNet pre-trained features** in most cases
- If you have many many unlabeled images, self-supervised learning can be an alternative
- Very active area of research!

Use of **simulations** for generating data esp localisation / segmentation data (GTA V...)

Lab 09: back here in 15 min!