



Chandojñānam

A Sanskrit Meter Identification and Utilization System

Hrishikesh Terdalkar, Arnab Bhattacharya

18th World Sanskrit Conference, 2023

Department of Computer Science and Engineering,
Indian Institute of Technology Kanpur

Introduction

Recite

योऽन्तः प्रविश्य मम वाचमिमां प्रसुप्तां
सञ्जीवयत्यखिलाशक्तिधरः स्वधाम्ना ।
अन्यांश्च हस्तचरणश्रवणत्वगादीन्
प्राणान्नमो भगवते पुरुषाय तुभ्यम् ॥

yo'ntaḥ praviśya mama vācamimāṃ prasuptāṃ
sañjīvayatyakhilāśaktidharaḥ svadhāmnā ।
anyāṃśca hastacaraṇaśravaṇatvagādīn
prāṇānnamo bhagavate puruṣāya tubhyam ॥

What is the chanda in this verse?

Ans: वसन्ततिलका (Vasantatilakā)

Recite

योऽन्तः प्रविश्य मम वाचं प्रसुप्तां

yo'ntaḥ praviśya mama vācaṃ prasuptāṃ

Why does it feel odd?

- Deviation from a known pattern
- How do we know these patterns?
 - Sanskrit Prosody!

Background

- Classification of syllables
 - Pronunciation dependent
 - Laghu (*short*)
 - Letters with short vowels
 - Guru (*long*)
 - Letters with long vowels
 - Laghu letters followed by a joint letter (saṃyogaḥ)
 - Last letter of a pāda (conditional)
- Mātrā: Laghu 1, Guru 2
- Gaṇa: Sequence of three letters ($2^3 = 8$)

Chanda

- Types
 - Akṣaracchanda: Sequences of laghu-guru
 - Samavṛtta, Ardhasamavṛtta and Viṣamavṛtta
 - Mātrācchanda: Counts of mātrā
- Literature: Vṛttaratnākaraḥ, Chandovicitīḥ, Chandomañjarī etc.


Motivation



Enthusiast



Poet



Teacher



Researcher

Why another meter identification tool?

Aim

- Add more user-friendly features.
 - Catch errors in the text and suggest corrections!
-
- Web-based application
 - Python library
 - Three input modes: (1) plain text, (2) images (3) text files
 - Two OCR Engines: (1) Google Drive OCR (2) Tesseract OCR
 - Transliteration support (powered by `indic-transliteration`)
 - Two meter identification modes: (1) line mode (2) verse mode
 - Fuzzy matching support using edit distance comparison
 - Informative scansion display
 - Downloadable results

Feature Comparison

Features		[Mis07]	[MGS13]	[Raj20]	[Nei22]	Chandojñānam
Availability	Web Interface	✓ ¹	✓ ²	✓	✓	✓
	Software Library			✓	✓	✓
Input	Text	✓	✓	✓	✓	✓
	Arbitrary Lines					✓
	Multiple Verses					✓
	Textfile Upload				✓	✓
	Image Upload					✓
Functionality	Meter Identification	✓	✓	✓	✓	✓
	Error Tolerance			✓	✓	✓
	Fuzzy Matching			✓		✓

Table 1: Feature comparison of extant meter identification systems

¹<http://sanskrit.sai.uni-heidelberg.de/Chanda/HTML/> no longer functional.

²<https://sanskritlibrary.org:8080/MeterIdentification/> no longer functional.

System




Figure 1: Workflow of Chandojñānam

वृत्त	पाद	गण	लक्षण	अक्षरसङ्ख्या	मात्रा	यति
शार्दूलविक्रीडित		मसजसततग	गगगललगलगललललगगलगलग	19	30	12,7
शालिनी		मततगग	गगगगलगलगलगग	11	20	4,7
अपरवक्त्र	1	ननरलग	लललललललललललल	11	14	
अपरवक्त्र	2	नजजर	लललललललललललल	12	16	
सौरभ	1	सजसल	लललललललललललल	10	13	
सौरभ	2	नसजग	लललललललललललल	10	13	
सौरभ	3	रनभग	गलगललललललललल	10	14	
सौरभ	4	सजसजग	लललललललललललल	13	18	
अनुष्टुभ्	1	----लग--	----लग--	8		
अनुष्टुभ्	2	----लगल-	----लगल-	8		

Figure 2: Generic Chanda definition format

- Column 'Pāda': index of pāda in the meter
- Uniform treatment of samavṛtta, ardhasamavṛtta and viṣamavṛtta
- Regex pattern (*regular expression*) definition

Metrical Database

- Two types of dictionaries
 - Signature of individual pādas (CHANDA_SINGLE)
 - Signature of consecutive pādas (CHANDA_MULTIPLE).

```
CHANDA_SINGLE = {  
    'LGGLGGLGGLGG': ['Bhujāṅgaprayāta'],  
    '[LG] [LG] [LG] [LG] LG [LG] [LG]': ['Anuṣṭubh (Pāda 1)'],  
    '[LG] [LG] [LG] [LG] LGL [LG]': ['Anuṣṭubh (Pāda 2)']  
}
```

```
CHANDA_MULTIPLE = {  
    'LGGLGGLGGLGGLGGLGGLGGLGG': ['Bhujāṅgaprayāta (Pāda 1-2)'],  
    '[LG] [LG] [LG] [LG] LG [LG] [LG] [LG] [LG] [LG] [LG] LGL [LG]': [  
        'Anuṣṭubh (Pāda 1-2)'  
    ]  
}
```

Input

- Text input
- Textfile input
- Image file input

ध्यायेदाजानुबाहुं धृतशरधनुषं बद्धपद्मासनस्थं
पीतं वासो वसानं नवकमलदलस्पर्धिनेत्रं प्रसन्नम् ।
वामाङ्गारूढ सीतामुखकमलमिलल्लोचनं नीरदाभं
नानालङ्कारदीप्तं दधतमुरुजटामण्डनं रामचन्द्रम् ॥

Upload

Choose image file

Browse

☐ Google OCR ☒ Tesseract OCR

OCR + Identify

Figure 3: Upload a screenshot of a verse for meter identification

Text Processing

- Common text processing pipeline for all input modes
- Transliteration (*powered by* `indic-transliteration`³)
 - Detect scheme
 - Convert to internal scheme (Devanagari)
- Line identification
 - Standard line-end markers: `'\n', '।', '॥', '`
- Syllabification (*powered by* `sanskrit-text`⁴)
 - भारत = भा + र + त
- Laghu-Guru markers
 - Standard rules
 - \exists Chanda where last letter should be laghu (Padānta Laghu)
 - Last letter not forced to be guru

³<https://pypi.org/project/indic-transliteration/>

⁴<https://pypi.org/project/sanskrit-text>

Meter Identification Algorithm

Algorithm 1: Meter Identification

Data: Metrical Database (MD)

Input: *lg-signatures* of every 'line' in the input
($T = \{lg_1, lg_2, \dots, lg_n\}$)

Output: Result set containing exact or fuzzy matches

```
1 forall  $lg \in T$  do
2    $SM_1 = \text{FindDirectMatch}(lg, \text{'CHANDA\_SINGLE'})$ 
3    $SM_2 = \text{FindDirectMatch}(lg, \text{'CHANDA\_MULTIPLE'})$ 
4    $RM = \text{FindRegexMatch}(lg, \text{'CHANDA\_SINGLE'} +$ 
    $\text{'CHANDA\_MULTIPLE'})$ 
5    $DM = SM_1 + SM_2 + RM$ 
6    $FM = \phi$ 
7   if  $DM = \phi$  then
8      $FM = \text{FindFuzzyMatch}(lg)$ 
9   end
10  return  $DM + FM$ 
11 end
```

Direct Matching

Algorithm 2: Direct Matching

Input: *lg-signature*

Output: Result set containing exact matches

```
1 Function FindDirectMatch(lg, 'MD')
2    $M_1 = \text{Query}(\textit{lg}, \text{'MD'})$            // dictionary lookup
3    $M_2 = \phi$ 
4   if  $M_1 = \phi$  then                       // if no match found
5     if the last letter of lg is laghu then
6        $\textit{lg}_1 = \text{replace last letter of lg with guru}$ 
7        $M_2 = \text{Query}(\textit{lg}_1, \text{'MD'})$ 
8     end
9   end
10  return  $M_1 + M_2$ 
```

What?

Finding approximate and close matches if an exact match is not found

Why?

- Digitally available Sanskrit text can be erroneous
 - Manual data entry
 - Post-scanning OCR followed by manual correction
- Types of Errors
 - Characters may be misspelt, e.g., रु (ru) as रू (rū)
 - Characters may be missing, e.g., वर्गै (vargai) as वगै (vagai)
 - Characters may be misidentified, e.g., ऋ (ṛ) as क्र (kra)
 - Characters may get split, e.g., ख (kha) as रव (rava)
- Several such errors can affect the metrical pattern of the text

How?

- **Problem:** Finding the *nearest matching string* for the *lg-signature* of the text
- Compute Levenshtein edit distance of the observed pattern (*powered by python-Levenshtein*⁵)
- Normalize the edit distance by the length of target pattern

$$\text{Similarity} = 1 - \frac{\text{Levenshtein distance}}{\text{length of target match}}$$

- Topmost k matches as the possible fuzzy matches (currently, $k = 10$)
- Suggestions: changes required to transform the input into the target
 - **insert, delete, replace**

⁵<https://pypi.org/project/python-Levenshtein/>

Fuzzy Matching Example – Matching

Input text




Output Scheme: Match Input

नमस्ते सदा वत्सले मातृभूमे
त्वया हिन्दुभूमे सुखं वर्धितोऽहम्।
महामङ्गले पुण्यभूमे त्वदर्धे
पतत्त्वेष कायो नमस्ते नमस्ते॥

☐ Verse Mode ☒ Line Mode

Identify

Results



Akṣarāṇi	न	म	स्ते	स	दा	व	त्स	ले	मा	तृ	भु	मे										
Laghu-Guru	ल	ग	ग	ल	ग	ग	ल	ग	ग	ल	ल	ग										
Gaṇa	य		य		य		य		स													
Counts	12 अक्षराणि, 19 मात्राः																					
Jāti	जगती																					
Chanda	भुजङ्गप्रयात (1 edit)																					

+ Fuzzy

Figure 4: Meter identification with fuzzy matching

Fuzzy Matching Example – Suggestions

Chanda		भुजङ्गप्रयात (1 edit)		- Fuzzy
Fuzzy Matches				
#	Chanda	Gaṇa	Cost	Similarity
1	भुजङ्गप्रयात	यययय	1	91.7%
	[[['न', 'म', 'स्ते'], ['स', 'दा'], ['व', 'त्स', 'ले'], ['मा', 'तृ', 'r(भु)[G]{भू}', 'मे']]]			
2	स्रग्विणी	रररर	2	83.3%
	[[['i(G)', 'd(न)', 'म', 'स्ते'], ['स', 'दा'], ['व', 'त्स', 'ले'], ['मा', 'तृ', 'भु', 'मे']]]			
3	विध्वङ्कमाला	तततगग	2	81.8%
	[[['d(न)', 'म', 'स्ते'], ['स', 'दा'], ['व', 'त्स', 'ले'], ['मा', 'तृ', 'r(भु)[G]{भू}', 'मे']]]			
4	हंसमाला (पाद 1-2)	सरभतगग	3	78.6%
	[[['न', 'i(L)', 'i(L)', 'स्ते'], ['स', 'दा'], ['व', 'त्स', 'ले'], ['मा', 'तृ', 'r(भु)[G]{भू}', 'मे']]]			
5	इन्द्रवंशा	ततजर	3	75.0%
	[[['d(न)', 'म', 'स्ते'], ['स', 'दा'], ['व', 'त्स', 'r(ले)[L]'], ['मा', 'तृ', 'i(G)', 'i(G)', 'मे']]]			

Figure 5: Fuzzy matching suggestions

Identification Modes

- *Line mode*: Treat the input as a set of arbitrary lines
 - Useful for checking meter of a single line or a set of unrelated lines
- *Verse Mode*: Treat the input as a collection of verses
 - Useful for identifying meter of a single or multiple verses
 - Utilizes information from other lines of the verse
 - Re-order results if required

Input text

Output Scheme: Match Input

Input text

Output Scheme: Match Input

माता रामो मम पिता रामचन्द्रः।
स्वामी रामो मल्लखा रामचन्द्रः।
सर्वस्व मे रामचन्द्रो दद्यात्तुर्
नाम्यं जाने नैव जाने न जाने॥

☐ Verse Mode
☒ Line Mode

Identify

माता रामो मम पिता रामचन्द्रः।
स्वामी रामो मल्लखा रामचन्द्रः।
सर्वस्व मे रामचन्द्रो दद्यात्तुर्
नाम्यं जाने नैव जाने न जाने॥

☒ Verse Mode
☐ Line Mode

Identify

Results

1. शालिनी

Hide Scanion

Akṣarāṇi	मा	ता	रा	मो	म	म	पि	ता	रा	म	च	न्द्रः
Laghu-Guru	ग	ग	ग	ग	ल	ल	ल	ग	ग	ल	ग	ग
Gaṇa	म			भ			य			य		
Counts	12 अक्षराणि, 20 मात्राः											
Jāti	जगती											
Chanda	वातोर्मि (1 edit)											

+ Fuzzy

Akṣarāṇi	मा	ता	रा	मो	म	म	पि	ता	रा	म	च	न्द्रः
Laghu-Guru	ग	ग	ग	ग	ल	ल	ल	ग	ग	ल	ग	ग
Gaṇa	म			भ			य			य		
Counts	12 अक्षराणि, 20 मात्राः											
Jāti	जगती											
Chanda	शालिनी (2 edits)											

+ Fuzzy

Figure 6: Meter identification in (a) *Line mode* and (b) *Verse mode*

Chanda	वातोर्मि (1 edit)	+ Fuzzy		
Fuzzy Matches				
#	Chanda	Gaṇa	Cost	Similarity
1	वातोर्मि	मभतगग	1	90.9%
	[[['मा', 'ता'], ['रा', 'मो'], ['म', 'म'], ['द(पि)', 'ता'], ['रा', 'म', 'च', 'न्द्र:']]]			
2	प्रहरिणी	मनजरा	2	84.6%
	[[['मा', 'ता'], ['रा', 'र(मो)(L)'], ['म', 'म'], ['पि', 'ता'], ['(L)', '(L)', 'म', 'च', 'न्द्र:']]]			

Chanda	शालिनी (2 edits)	+ Fuzzy		
Fuzzy Matches				
#	Chanda	Gaṇa	Cost	Similarity
1	शालिनी	मत्तगग	2	81.8%
	[[['मा', 'ता'], ['रा', 'मो'], ['द(म)', 'र(म)(G)'], ['पि', 'ता'], ['रा', 'म', 'च', 'न्द्र:']]]			
2	वातोर्मि	मभतगग	1	90.9%
	[[['मा', 'ता'], ['रा', 'मो'], ['म', 'म'], ['द(पि)', 'ता'], ['रा', 'म', 'च', 'न्द्र:']]]			

Figure 7: Fuzzy matches in (a) *Line mode* and (b) *Verse mode*

Hrshikesh Terdalkar, Arnab Bhattacharya

Chandojñānam (WSC 2023)

18 / 24

- Transliteration-based primitive⁶ multilingual support

Input text

Output Scheme: Devanagari

Input text

Output Scheme: Telugu

सुरंगलि सदा पढो सुजनवाक्य कानी पढो
कलंक मलिषा छटो विषय सर्वदा नावटो
संदर्भिकमाली दटो सुखिता टटने अटो
विषय पढता रटो मन भवच्छरीरी कटो

పిలికిం జెప్పడు: ఈఖ చక్ర యుగముంటేరోలు సంధించడే
పరివారంబును జీర దభ్రవసం బన్నది రాజ్యశాం
తర యుక్తము జక్క నొత్తను పినాచక్రశ్రీ శీ సుదో
పరిచేలాంపలెన్నె పడడు గజ ప్రాణవోగ్గానోచ్చె

☒ Verse Mode
 ☐ Line Mode

Identify

☒ Verse Mode
 ☐ Line Mode

Identify

Results

1. पृथ्वी

Hide Scanlon

Akṣarāṇi	सु	सं	ग	ति	स	दा	घ	डो	सु	ज	न	वा	क्य	का	नी	घ	डो
Laghu-Guru	ल	ग	ल	ल	ल	ग	ल	ग	ल	ल	ग	ल	ग	ग	ल	ग	ग
Gaṇa	ज		स		ज		स		य		ल	ग					
Counts	17 अक्षराणि, 24 मात्राः																
Jāti	अव्ययिः																
Chanda	पृथ्वी																

1. మధ్యపాదీడిత

Hide Scanlon

Akṣarāṇi	సి	రి	కిం	జె	ప్ప	డు	ఖ	చ	క్ర	యు	గ	ముం	జే	దో	య	సం	ధిం	చ	డే
Laghu-Guru	ల	ల	క	క	ల	ల	క	ల	క	ల	ల	క	క	క	ల	క	క	ల	క
Gaṇa	స		భ		ర		స		మ		య		ల	క					
Counts	20 syllables, 30 morae																		
Jāti	కృతి:																		
Chanda	మధ్యపాదీడిత																		

Figure 8: Identification from other Indian languages, (a) Marathi (b) Telugu

⁶Uses the rules and metrical database of Sanskrit prosody

Evaluation for Error Correction

- Single text from different sources can differ in several places
- Three versions of Meghadūta⁷ composed by Kālidāsa
 - Wikisource, sanskritdocuments.org and GRETIL
- Texts with more metrical variety
 - Śāntavilāsa (36 verses) (12 distinct meters)
 - Śrīrāmarakṣāstotra (39 verses) (9 distinct meters)
 - Rājendrakarṇapūra (72 verses) (4 distinct meters)
- Manually tagged meters for each verse from these texts
- Realistic evaluation: Simulate digitization pipeline for all four texts
 - Generate PDF from Wikisource text
 - Run both the OCR systems
 - Obtain the OCR-ed versions of the text
- Total 14 text versions, 1038 verses, exhibiting 17 distinct meters

⁷Also used by [Raj20] for evaluation

Results

		Meghadūta					Śāntavilāsa			Rāmarakṣā			Rājendrakarṇapūra			Total
		SD	GR	WS	GO	TO	WS	GO	TO	WS	GO	TO	WS	GO	TO	
Number of Verses		117	111	123	123	123	36	36	36	39	39	39	72	72	72	1038
Unique Chanda		1	1	1	1	1	12	12	12	9	9	9	4	4	4	17
Erroneous Verses		20	79	2	31	77	13	16	31	1	4	13	12	26	71	396
Correct	[Nei22]	20	79	2	30	66	11	13	14	0	2	9	12	24	36	318 (80.3%)
Meters	[Raj20]	19	79	2	30	75	12	15	24	1	2	9	12	26	58	364 (91.9%)
Identified	Chandojñānam	20	79	2	31	77	13	16	29	1	3	9	12	26	71	389 (98.2%)

Table 2: Error tolerance of meter identification systems. (Versions are WS: Wikisource, GO: Google OCR, TO: Tesseract OCR, SD: sanskritdocuments.org, GR: GRETIL.) Chandojñānam is able to detect correct chanda from erroneous verses 98.2% of the times.

- Successfully detected and corrected two errors from Wikisource version of Meghadūta

Error #1

- Line: कालक्षेपं ककुभसुरभौ पर्वते पर्वते ते (Pāda 3, Śloka 1.23)
- Incorrect word पर्वते (should be पर्वते)
- Likely due to OCR error and an oversight by the curator
- Suggestion: [[['का', 'ल', 'क्षे', 'पं'], ['क', 'कु', 'भ', 'सु', 'र', 'भौ'], ['प', 'र्व', 'ते'], ['प', 'r(र्वे)[L]', 'ते'], ['ते']]]
- System correctly points to the location where a change is required

Error #2

- Line: साभिज्ञानप्रहितकुशलैस्तद्वचोभिर्ममापि (Pāda 3, Śloka 2.53)
- Extra letter (त) present in the sandhi of words कुशलैः and तद्वचोभिः
- Suggestion: [[['सा', 'भि', 'ज्ञा', 'न', 'प्र', 'हि', 'त', 'कु', 'श', 'लै', 'd(स्त)', 'त', 'द्व', 'चो', 'भि', 'र्म', 'मा', 'पि']]]
- Points out correctly that a syllable needs to be deleted
- However, points to an incorrect syllable स्त to be deleted
 - Both स्त and त are laghu letters
 - Deletion of either letter \implies the correct metrical signature
 - Impossible for a meter identification based system

Conclusions

Conclusions and Future Work

- User-friendly meter identification system
- Several input options
- Focus on error detection and correction

Future Work

- Inclusion of Mātrācchandas
- Improvements to meter correction algorithm
- Possible consideration of semantic aspects
- More extensive support for Indian languages that use similar rules of prosody

Links

System: <https://sanskrit.iitk.ac.in/jnanasangraha/chanda/>

Source: <https://github.com/hrishikeshrt/chanda/>

References

References

- [MGS13] Keshav S Melnad, Pawan Goyal, and Peter Scharf.
Meter identification of sanskrit verse.
The Sanskrit Library, USA, 2013.
- [Mis07] Anand Mishra.
Sanskrit metre recognizer, 2007.
- [Nei22] Tyler Neill.
Skrutable: Another step toward effective sanskrit meter identification.
2022.
- [Raj20] Shreevatsa Rajagopalan.
A user-friendly tool for metrical analysis of sanskrit verse.
Computational Sanskrit & Digital Humanities, page 113, 2020.

Thank you!

Questions?