

1. Installation

```
In [5]: import numpy as np
        from numpy import pi

        from qiskit import QuantumCircuit, transpile, assemble, Aer, IBMQ
        from qiskit.providers.ibmq import least_busy
        from qiskit.tools.monitor import job_monitor
        from qiskit.visualization import plot_histogram, plot_bloch_multivector
```

2. Circuit

```
In [6]: qc = QuantumCircuit(3)

        #Qiskit's Least significant bit has the lowest index (0), thus the circuit will be mirrored through the horizontal
        qc.h(2)

        #Next, we want to turn this an extra quarter turn if qubit 1 is in the state |1>

        qc.cp(pi/2, 1, 2)  # CROT from qubit 1 to qubit 2

        #And another eighth turn if the Least significant qubit (0) is |1>

        qc.cp(pi/4, 0, 2)  # CROT from qubit 2 to qubit 0
```

```
Out[6]: <qiskit.circuit.instructionset.InstructionSet at 0x24874a6a7f0>
```


With that qubit taken care of, we can now ignore it and repeat the process, using the same logic for qubits 0 and 1

```
In [7]: qc.h(1)
        qc.cp(pi/2, 0, 1)  # CROT from qubit 0 to qubit 1
        qc.h(0)
```

```
Out[7]: <qiskit.circuit.instructionset.InstructionSet at 0x24820919ac0>
```

Finally we must swap the qubits 0 and 2 to complete the QFT:

```
In [8]: qc.swap(0,2)
         qc.draw()
```



3. General Circuit

QFT

```
In [11]: def qft_rotations(circuit, n):
    if n == 0: # Exit function if circuit is empty
        return circuit
    n -= 1 # Indexes start from 0
    circuit.h(n) # Apply the H-gate to the most significant qubit
    for qubit in range(n):
        # For each less significant qubit, we need to do a
        # smaller-angled controlled rotation:
        circuit.cp(pi/2**(n-qubit), qubit, n)

    # At the end of our function, we call the same function again on
    # the next qubits (we reduced n by one earlier in the function)
    qft_rotations(circuit, n)
```


Swap

```
In [14]: def swap_registers(circuit, n):
          for qubit in range(n//2):
              circuit.swap(qubit, n-qubit-1)
          return circuit
```

General circuit

```
In [15]: def qft(circuit, n):
          """QFT on the first n qubits in circuit"""
          qft_rotations(circuit, n)
          swap_registers(circuit, n)
          return circuit
```

```
In [17]: qc1 = QuantumCircuit(4)
          qft(qc1,4)
          qc1.draw()
```



4. Verifying Circuit (Simulator)


We must first encode a number in the computational basis, here we are selecting '5' which in binary is '101'


```
In [19]: # Create the circuit
          qc = QuantumCircuit(3)


          # Encode the state 5
          qc.x(0)      # since we need '1' at first qubit and at last qubit
```


```
qc.x(2)
qc.draw()
```

Out[19]:



q_0: 

q_1: 


q_2: 

In [31]: *# And let's check the qubit's states using the aer simulator:*

```
sim = Aer.get_backend("aer_simulator")
qc_init = qc.copy()      # making a copy so that we can work on the original one
qc_init.save_statevector()
statevector = sim.run(qc_init).result().get_statevector()
plot_bloch_multivector(statevector)

# we can see the state below as '101'
```

Out[31]:




Finally, let's use our QFT function and view the final state of our qubits:


In [22]:

```
qft(qc,3)
qc.draw()
```





```
In [23]: qc.save_statevector()
statevector = sim.run(qc).result().get_statevector()
plot_bloch_multivector(statevector)
```



We can see out QFT function has worked correctly. Compared the state $|\tilde{0}\rangle = |+++\rangle$, Qubit 0 has been rotated by $\frac{5}{8}$ of a full turn, qubit 1 by $\frac{10}{8}$ full turns (equivalent to $\frac{1}{4}$ of a full turn), and qubit 2 by $\frac{20}{8}$ full turns (equivalent to $\frac{1}{2}$ of a full turn).

5. Real Device

If we want to demonstrate and investigate the QFT working on real hardware, we can instead create the state $|5\rangle$, run the QFT in reverse, and verify the output is the state $|5\rangle$ as expected


Inverse QFT Operation

```
In [24]: def inverse_qft(circuit, n):
        """Does the inverse QFT on the first n qubits in circuit"""
        # First we create a QFT circuit of the correct size:
        qft_circ = qft(QuantumCircuit(n), n)
        # Then we take the inverse of this circuit
        invqft_circ = qft_circ.inverse()
        # And add it to the first n qubits in our existing circuit
        circuit.append(invqft_circ, circuit.qubits[:n])
        return circuit.decompose() # .decompose() allows us to see the individual gates
```

Putting the qubit in the state $|5\rangle$


```
In [25]: nqubits = 3
        number = 5
        qc = QuantumCircuit(nqubits)
        for qubit in range(nqubits):
            qc.h(qubit)
            qc.p(number*pi/4,0)
            qc.p(number*pi/2,1)
            qc.p(number*pi,2)

        qc.draw()
```




```
In [26]: qc_init = qc.copy()
        qc_init.save_statevector()
        sim = Aer.get_backend("aer_simulator")
        statevector = sim.run(qc_init).result().get_statevector()
        plot_bloch_multivector(statevector)
```

Out[26]:



Apply Inverse QFT

```
In [27]: qc = inverse_qft(qc, nqubits)
qc.measure_all()
qc.draw()
```



Real Device

```
In [28]: # Load our saved IBMQ accounts and get the least busy backend device with less than or equal to nqubits
```

```

IBMQ.load_account()
provider = IBMQ.get_provider(hub='ibm-q')
backend = least_busy(provider.backends(filters=lambda x: x.configuration().n_qubits >= nqubits
                                     and not x.configuration().simulator
                                     and x.status().operational==True))

print("least busy backend: ", backend)

```

least busy backend: ibmq_bogota

```

In [29]: shots = 2048
transpiled_qc = transpile(qc, backend, optimization_level=3)
job = backend.run(transpiled_qc, shots=shots)
job_monitor(job)

```


Job Status: job has successfully run

```

In [30]: counts = job.result().get_counts()
plot_histogram(counts)

```

Out[30]:



We (hopefully) see that the highest probability outcome is 101

