# AERIAL BUNCHED CABLE (ABC)

**AERIAL BUNCHED CABLES (ABC) is a very novel concept for over head power distribution.** When compared to the conventional bare conductor over head distribution system, ABC provides higher safety and reliability, low power losses and ultimate system economy by reducing installation, maintenance and operative cost. This system is ideal for rural distribution and attractive for installation in difficult terrains such as hilly areas, forest areas, coastal areas etc. Aerial Bunched Cahles is also considered to be the best choice for power distribution in congested urban areas with narrow lanes and by lanes. in developing urban complex, Aerial Bunched Cables is also considered to be the best choice for power distribution in congested urban areas with narrow lanes and by lanes. In developing urban complex, Aerial Bunched Cables is a better choice because of flexibility for rerouting as demanded by changes in urban development plan.



**REF SPECIFICATION : IS-14255, IS 8130 | IEC 60502 Part 1**

| Phase Conductor (Aluminium) | | | Street Lighting Conductor (Aluminium) | | | Messenger Conductor (Aluminium Alloy) | | |
|---|---|---|---|---|---|---|---|---|
| Nominal Area | Max Conductor D.C. Resistance at 20 $^0$C | Nominal Thickness of Insulation | Noinal Area | Conductor D.C. Resistance at 20$^0$C | Nominal Thickness of Insulation | Nominal Area | Conductor D.C. Resistance at 20$^0$C | Minimum Breaking Load |
| Sq. mm | Ω/Km | mm | Sq. mm | Ω/Km | mm | Sq. mm | Ω/Km | kN |
| 16 | 1.910 | 1.20 | 16 | 1.910 | 1.20 | 25 | 1.380 | 7.00 |
| 25 | 1.200 | 1.20 | 16 | 1.910 | 1.20 | 25 | 1.380 | 7.00 |
| 35 | 0.868 | 1.20 | 16 | 1.910 | 1.20 | 25 | 1.380 | 7.00 |
| 50 | 0.641 | 1.50 | 16 | 1.910 | 1.20 | 35 | 0.986 | 9.80 |
| 70 | 0.443 | 1.50 | 16 | 1.910 | 1.20 | 50 | 0.689 | 14.00 |
| 95 | 0.320 | 1.50 | 16 | 1.910 | 1.20 | 70 | 0.492 | 19.70 |

