ALL ALUMINIUM CONDUCTORS (AAC)

AS PER CANADIAN SPECIFICATION CAN/CSA - C61089 W11

Code Word	Stranding & Wire dia no./mm	Approx Overall Diameter mm	Sectional Area sq. mm	Approx. Weight Kg/Km	Approx. Calculated Breaking load Kn	Calculated Resistance at 20°c (Max.) ohm/Km
ROSE	7/1.96	5.89	21.16	58	4.07	1.351
LILY	7/2.20	6.61	26.65	73	5.05	1.072
IRIS	7/2.47	7.42	33.61	92	6.23	0.8497
PANSY	7/2.78	8.33	42.39	116	7.6	0.6739
POPPY	7/3.12	9.36	53.48	146	9.22	5.5341
ASTER	7/3.50	10.51	67.47	184	11.62	0.4236
PHLOX	7/3.93	11.8	85.03	232	14.07	0.336
OXLIP	7/4.42	13 25	107.23	293	17.75	0.2664
DALSY	7/4.96	14.9	135.16	369	22.36	0.2113
VALERIAN	19/2.91	14.57	126.71	348	22.26	0.2274
LAUREL	19/3.01	15.05	135.16	371	23.78	0.2129
PEONY	19/3.19	15.97	152	417	26.15	0.189
TULIP	19/3.38	16.11	170.45	467	29.3.8	0.1638
DAFFODIL	19/3.45	17.24	177.35	488	30.56	0.1624
CANNA	19/3.67	36.16	201.41	554	34.04	0.1427
GOLDTUFT	19/3.91	19.55	228	626	37.72	0.1263
COSMOS	19/4.02	20.12	241.68	664	40.07	0.1166
ZINNIA	19/4.12	20.6	251.35	695	41.91	0.1137
DAHLIA	19/4.35	21.73	282	774	46.69	5.1018
MEADOWSWEET	37/3.23	22.63	304	838	52.43	0.0948
ORCHID	37/3.33	23.11	372.26	688	55.57	0.0896
HEUCHERA	17/3.32	23.56	329.35	906	56.79	0.0876
VERBENA	37/3.49	24.45	354.77	978	61.16	8.0814
VIOLET	37/3.53	24:74	362.58	1000	62.34	0.0797
PETUNIA	37/3.62	48341	380	1048	64.2	0.0758
ARBIJRIS	37/3.72	26.06	402.84	1112	68.02	0.0715
ANEMONE	37/3.90	27.33	443.1	1222	73.32	0.0653
COCKSOMB	37/3.96	27.73	456.06	1257	75.48	0.0633
MAGNOLIA	37/4.06	28.55	483.42	1333	80	4.0597
HAMMED	37/4.18	29.23	506.71	1396	83.87	0.0568
BLUEBELL	37/4.24	29.72	523.68	1415	86.48	0.0551
MARIGOLD	61/3.43	30.89	563.93	1559	97.22	0.0512
HAWTHORN	61/3.55	31.95	604.26	1670	104.13	0.0479
NA.C15505	61/3.67	33.02	645.37	1781	108.79	0.045
COLUMBINE	61/3.78	34.01	684.84	1893	115.71	0.0423
CARNATION	61/389	35.03	725.1	2004	119.92	0.04
GLADIOLUS	61/4.00	35.99	765.35	2116	126.59	0.0377
COREOPSIE	61/4.10	36.91	205.68	2226	133.26	0.0358

ALUMINIUM CONDUCTORS STEEL REINFORCED (ACSR)

AS PER IS-398-II: 1996 & IS-398-V: 1992

Code Word	Nominal Aluminium Area sq. mm	Stranding & Wire Dia no./mm Alum.	Steel	Sectional Area (Aluminium) sq. mm	Total Sectional sq. mm	Approx. Overall mm	Approx. Weight Kg/Km Total Alum.	Steel		Calculated at 20°c (Max.) ohm/Km	Approx. Calculated Breaking Load Kn
MOLE	10	6/1.50	1/1.50	10.6	12.37	4.5	43	29	14	2.78	3.97
SPL. CONDUCTOR	18	6/1.96	1/1.96	18.1	21.12	5.88	73	50	23	1.618	6.74
SQUIRREL	20	6/2.11	1/2.11	20.98	24.48	6.33	85	58	27	1.394	7.61
WEASEL	30	6/2.59	1/2.59	31.61	36.88	7.77	128	87	41	0.9289	11.12
RABBIT	50	6/3.35	1/3.35	52.88	61.7	10.05	214	145	69	0.5524	18.25
RACCOON	80	6/4.09	1/4.09	78.83	91.97	12.27	319	217	102	0.3712	26.91
DOG	100	6/4.72	7/1.57	105	118 50	14.15	394	288	106	0.2792	32.41
WOLF	150	30/2.59	7/2.59	158.1	194.9	18.13	726	438	288	0.1871	67.34
PANTHER	200	30/3.00	7/3.00	212.1	261.5	21	974	587	387	0.1391	89.67
KUNDAH	400	42/3.50	7/1.96	404.1	425.2	26.88	1281	1120	161	0.07312	88.79
ZEBRA	420	54/3.18	713.18	428.9	484.5	28.62	1621	1187	434	0.06868	130.32
MOOSE	520	54/3.53	7/3.53	528.5	597	31.77	2004	1465	539	0.05595	159.6
MARKULLA	560	42/4.13	7/2.30	562.7	591.7	31.68	1781	1559	228	0.05231	120.16
BERSIMIS	690	42/4.57	7/2.54	688.9	724.4	35.04	2187	1907	280	0.04242	146.87

ALUMINIUM CONDUCTORS STEEL REINFORCED (ACSR)

AS PER BRITISH SPECIFICATION BS-215-II-1970

acsr code World	conductor) size sq. mm	stranding & wire dia no./mm		calculated sectional area sq mm		overall diameter mm	approx Weight kg/km			ultimate strength Kg	calculated resistance at 20°c (Max.) ohm/Km
		alum	steel	alum	acsr	acsr	acsr	alum	steel		
GOPHER	25	6/2.36	1/2.36	26.24	30.62	7.08	106	72	34	980	1.093
WEASELL	30	6/2.59	1/2.59	31.61	36.58	7.77	128	87	41	1170	0.9077
FOX	35	6/2.79	1/2.79	36.48	42.8	8.37	146	101	47	1340	0.7822
FERRET	40	6/3.00	1/3.00	42 41	49.43	9	172	117	55	1550	0.6766
RABBIT	50	6/3.35	1/3.35	52.88	61.7	10.05	214	145	69	1870	0.5426
MINK	60	6/3.66	1/3.66	63.17	72.64	10.98	255	173	82	2220	0.4546
HORSE	70	12/2.79	7/2.79	73.37	116.2	13.95	538	203	335	6240	0.3936
DOG	100	6/4.72	7/1.57	105	118.5	14.15	394	288	106	3330	0.2733
COYOTE	130	2672.54	7/1.91	131.7	151.8	15.89	521	364	157	4730	0.2191
WOLF	150	30/2.59	7/2.59	158.1	194.9	18.13	726	437	289	7060	0.1828
LYNX	175	30/2.79	7/2.79	183.4	226 20	19.53	642	507	335	8140	0.1576
PANTHER	200	30/3.00	7/3.00	212.1	261.5	21	974	586	388	9430	0.1363
JAGUAR	200	18/3.86	7/3.86	210.6	222.3	19.3	671	580	91	4750	0.1367
GOAT	320	30/3.71	7/3.71	324.3	400	25.97	1489	896	593	13850	0.08912
BISON	380	54/3.00	7/3.00	381.7	431.2	27	1443	1055	886	12330	0.07574
ZEBRA	400	54/3.18	7/3.18	428.9	484.5	28.62	1622	1186	436	13450	0.0674
DEER	425	30/4.27	7/4.27	429.6	529.8	29.89	1973	1187	786	16210	0.06727
MOOSE	525	54/3.53	7/3.53	528.5	597	31.71	1998	1461	537	16420	0.0547

AS PER GERMAN SPECIFICATION DIN 48.204/1974

Nominal Size sq. mm	Stranding & Wire Dia no./mm		Approx. Overall Diameter mm	Sectional Area sq. mm		Total Sectional Area sq. mm	Approx. Weight Kg/Km			Approx. Calculated Breaking Load Kn	Calculated Resistance at 20°c (Max) ohm/Km
	Alum	Steel		Alu.	Steel		ACSR	Alum	Steel		
16/2.5	6/1.80	1/1.80	5.4	15.3	2.55	17.85	42	20	62	5.83	1.875
25/4.0	6/2.25	1/2.25	6.8	23.8	4	27.8	65	32	97	9.02	1.206
35/6.0	6/2.70	1/2.70	8.1	34 30	5.7	40	94	46	140	!2_41	0.8365
44/32	14/2.0	7/2.40	8.2	44	31.7	75.7	122	250	372	44 i4	0.657
50/8	6/3.20	1/3.20	9.6	48.3	5	56 30	137	64	196	16.77	0.5941
50/30	12/2.3	7/2.33	11.65	51.2	29.8	8 l .00	141	237	378	42_96	0.5642
70/12	26/1.5	7/1.44	11.7	69.9	11.4	81.3	193	91	284	16.29	0.113
95/15	26/2.5	7/1.67	13.6	94.4	15.3	109 70	260	123	383	35.07	0.3058
95/55	12/3.0	7/3.20	16	96.5	56.3	152.8	266	446	712	77.84	0.2992
105/75	14/3.0	19/2.5	17.5	105.7	75.5	181.5	292	599	891	106 38	0.2735
120/20	26/2.4	7/1.90	15.5	121.6	19.8	141.4	336	158	494	4.78	0.2741
120/70	12/3.0	7/3.60	18	122	71.3	193.3	337	564	901	98.1	0.2367
125/30	30/2.3	7/2.33	16.1	127.9	29.8	157.7	353	138	511	56.5	0.2259
150/25	26/20	7/2.10	17.1	148.9	24.2	171.1	411	194	605	54.2	0.1939
170/40	30/2.0	7/2.70	18.9	71.8	40.1	211.9	475	319	794	75.29	0.1682
185/30	26/3.0	7/2.33	19	183 80	29.5	213.6	507	239	146	64.94	0.15/1
210/35	26/3.0	7/2.49	20.3	209.1	14.1	243.2	577	273	850	73.47	0.138
210/50	30/3.0	7/3.00	21	212.1	49.5	261.6	587	94	981	92.11	1.1362
230/30	24/3.0	7/2.33	21	230.9	29.8	260.7	638	239	877	7.16	0.1249
240/40	26/3.5	7/2.68	21.9	243	39.5	282.5	671	316	987	84.7	0.1188
265/35	24/3.4	7/2.49	22.4	263.7	31.1	797.8	728	274	1007	81.47	0.1094
300/50	26/3.6	7/3.00	24.5	304.3	49.5	353.8	840	396	1236	104.96	0.09486
305/40	54/2.8	7/2.68	24.1	304.6	39.5	344.1	843	317	1160	97.51	0.0949
340/30	48/3.0	7/2.33	25	339.3	29.6	369.1	938	242	1180	91.13	0.08508
380/50	54/3.0	7/3.00	27	382	49.5	431.5	1056	397	1453	120.7	0.07568
385/35	48/3.0	7/2.49	26.7	386	34.1	420.1	1067	277	1344	102.8	0.07479
435/55	54/3.0	7/3.20	28.8	434.3	56.3	490.6	1203	450	1653	133.8	0.06686
450/40	48/3.5	7/2.68	28.7	448.7	39.5	489.2	1241	320	1561	118.45	0.06434
490/65	54/3.0	7/3.40	30.6	490.3	63.6	553.9	1356	510	1866	150.19	0.05896
495/35	45/3.4	7/2.49	29.9	494.1	34.1	528.2	1369	2.77	1646	119.5	0.05846
510/45	48/3.8	7/2.87	30.7	510.2	45.3	555.5	1413	365	1778	134	0.05661
550/70	4/3.0	7/3.60	32.4	550	71.3	621.3	1520	572	2092	167.35	0.05256
560/50	48/3.6	7/3.00	32.2	561.7	49.5	611.2	1553	401	1954	146.12	0.0514
570/40	45/4.2	7/2.68	32.2	571.2	39.5	610.7	1571	317	1888	133.61	0.05057
650/45	45/4.0	7/2.87	34	653.5	45.3	698.8	1806	365	2171	152.54	0.0442
680/85	54/4.0	19/2.0	36	678.6	86	764.6	1868	702	2570	202.33	0.04259
1045/45	72/4.0	7/2.87	43	1045.6	45.3	1090.9	2893	358	3251	213.46	0.02765

ALUMINIUM CONDUCTORS STEEL REINFORCED (ACSR)

AS PER CANADIAN SPECIFICATION CAN/CSA - C61089 - 11

Code Name	Stranding & Wire Dia no./mm		Approx Overall Diameter mm	Sectional Area sq. mm		Total Sectional Area sq. mm	Approx Weight Kg/Km			Approx. Calculated Breaking Load Kn	Calculated Resistance at 20°c (Max.) ohm/Km
	Alum.	Steel		Alu.	Steel		Alu.	Steel	ACSR (TOTAL)		
WREN	6/1.33	1/1.33	3.99	8.39	1.42	9.81	23	11	34	3.33	3.4280
WRABLER	6/1.50	1/1.50	4.50	10.59	1.77	12.36	29	14	43	4.16	2.7200
TURKEY	6/1.68	1/1.68	5.04	13.29	2.19	15.48	37	17	54	5.19	2.1570
THRUSH	6/1.89	1/1.89	5.67	16.77	2.77	19.54	46	22	68	6.47	1.7711
SWAN	6/2.12	1/2.12	6.36	21.16	3.55	24.71	58	27	85	8.14	1.3570
SWALLOW	6/2.38	1/2.38	7.14	26.65	4.45	31.09	73	35	108	10.05	1.0760
SPARROW	6/2.67	1/2.67	8.01	33.61	5.61	39.22	92	44	136	12.44	0.8532
ROBIN	6/3.00	1/3.00	9.00	42.39	7.10	49.49	116	55	171	15.54	0.6766
RAVEN	6/3.37	1/3.37	10.11	53.48	8.90	62.38	146	69	215	18.90	0.5362
QUALL	6/3.78	1/3.78	11.34	67.42	11.23	78.65	185	88	273	23.50	0.4255
PIGEON	6/4.25	1/4.25	12.75	85.03	14.19	99.22	233	110	343	29.60	0.3375
PENGUIN	6/4.77	1/4.77	14.31	107.23	17.87	125.10	294	139	433	37.47	0.2677
OWL	6/5.36	7/1.79	16.09	135.16	17.55	152.71	371	137	508	42.10	0.2123
WAXWING	18/3.9	1/3.09	15.45	135.16	7.48	142.54	372	58	430	31.20	0.2130
PARTRIDGE	26/2.57	7/2.00	16.28	135.16	22.00	157.16	374	171	545	50.03	0.2136
PHOEBE	18/3.28	1/3.28	16.40	152.00	8.45	160.45	418	65	483	35.10	0.1895
OSTRICH	26/2.73	7/2.12	17.28	152.00	24.71	176.71	420	193	613	56.71	0.1900
PIPER	30/2.54	7/2.54	17.78	152.00	35.48	187.48	420	277	697	68.67	0.1900
MERLIN	18/3.47	1/3.47	17.35	170.45	9.48	179.93	469	74	54	39.40	0.1686
LINNET	26/2.89	7/2.25	18.31	170.45	27.81	198.26	470	217	687	62.30	0.1694
IBIS	26/3.14	7/2.44	19.85	201.42	32.77	234.19	557	256	813	72.00	0.1434
LARK	30/2.92	7/2.92	20.44	201.42	46.97	248.39	557	366	923	88.87	0.1434
PELICAN	18/4.14	1/4.14	20.70	241.68	13.42	255.10	665	104	769	54.78	0.1191
HAWK	26/3.44	7/2.67	21.77	241.68	39.42	281.10	667	308	975	86.52	0.1195
HEN	30/3.20	7/3.20	22.40	241.68	56.39	298.07	688	440	1128	103.88	0.1195
HERON	30/3.28	7/3.28	22.96	253.35	59.10	312.45	701	461	1162	108.79	0.1142
SAPSUCHER	22/4.04	7/2.24	22.85	282.00	27.68	309.68	777	216	993	79.11	0.1024
DOVE	26/3.72	7/2.89	23.55	282.00	45.94	327.94	778	359	1137	99.91	0.1024
EAGLE	30/3.46	7/3.46	24.22	282.00	65.81	347.81	780	513	1293	121.25	0.1027
DUCK	54/2.69	7/2.69	24.21	306.58	39.81	346.39	848	311	1159	100.11	0.0945
GROSBBEAK	26/3.97	7/3.09	25.15	322.26	52.45	374.71	890	409	1299	111.24	0.0896
EGRET	30/3.70	19/2.2	25.90	322.26	41.74	364.00	891	326	1217	105.26	0.0899
GOOSE	54/2.76	7/2.76	24.84	322.26	41.74	364.00	891	326	1217	105.26	0.0899
GULL	54/2.82	7/2.82	25.38	337.74	43.81	381.55	935	342	277	109.23	0.0856
STARLING	26/4.1	7/3.28	26.68	362.58	59.03	421.61	1002	460	1462	125.02	0.0796
REDWING	30/3.92	19/2.35	27.43	362.58	82.58	445.16	1002	646	1648	153.96	0.0796
CROW	54/2.92	7/2.92	26.28	362.58	46.97	409.55	1003	366	1369	117.22	0.0798
DRAKE	26/4.4	7/3.45	28.11	402.84	65.61	468.45	1112	512	1624	139.05	0.0715
MALLARD	30/4.14	19/2.48	28.96	402.84	91.87	494.71	1113	719	1832	171.08	0.0719
CONDOR	54/3.08	7/3.08	27.72	402.84	52.19	455.03	1113	408	1521	127.03	0.0719
CRANE	54/3.23	7/3.23	29.07	443.10	57.48	500.58	1226	448	1674	139.69	0.0653
CANARY	54/3.28	7/3.28	29.52	456.06	59.10	515.16	1262	462	1724	143.71	0.0633
CARDINAL	54/3.38	7/3.38	30.42	483.42	62.65	546.07	1338	488	1826	152.39	0.0597
CURLEW	54/3.51	7/3.51	31.59	523.68	67.87	591.55	1448	530	1978	165.29	0.0551
FINCH	54/3.65	19/2.19	32.85	563.93	71.55	636.48	1561	560	2121	176.88	0.0512
GRACKEE	54/3.77	19/2.27	33.97	604.26	76.58	680.84	1671	600	2271	191.78	0.0479
PHEASANT	54/3.90	19/2.34	35.10	644.51	81.68	726.19	1783	538	2421	199.33	0.0449
MARTIN	54/4.02	19/2.41	36.17	684.84	86.71	771.55	1894	679	2573	211.79	0.0432
PLOVER	54/4.14	19/2.48	37.24	725.10	91.87	816.97	2006	719	2725	224.25	0.0400
PARROT	54/4.25	19/2.55	38.25	765.35	96.84	862.19	2118	759	2877	237.15	0.0377
FALCON	54/4.36	19/2.62	39.26	805.68	102.13	907.81	2229	799	3028	249.61	0.0358

AS PER AMERICAN SPECIFICATIONS ASTM B - 232 - 1992

ACSR Code Word	Conductor Size (MCM/Awg)	Stranding & Wire Dia no./mm		Calculated Sectional Area sq.mm		Overall Diameter mm ACSR	Approx. Weight. Kg/Km			Ultimate Strength Kg	Calculated Resistance at 20°c (Max.) ohm/Km
		Alum.	Steel	Alum.	ACSR		ACSR	Alum.	Steel		
SPARROW	(2)	6/2.67	1/2.67	33.61	39.22	8.01	136	92	44	1295	0.853
SWALLOW	(3)	6/2.38	1 /2.38	26.65	31.1	7.14	108	73	35	1040	1.076
RAVEN	(1/0)	6/3.37	1/3.37	53.48	62.38	10.11	216	147	69	1990	0.5364
PENGUIN	(4/0)	6/4.77	1/4.77	107.23	125.1	14.31	433	294	139	3800	0.2676
MERLIN	336400	18/3.47	1/3.47	170.45	179.9	17.36	544	470	74	3930	0.1692
IBIS	397500	26/3.14	7/2.44	201.4	234	19.88	814	558	256	7380	0.1438
PELICAN	477000	18/4.14	1/4.14	241.68	255.1	20.7	771	666	105	5350	0.1193
HAWK	477000	26/3.43	7/2.67	241.7	280.8	21.78	976	669.2	307	8880	0.1194
GROSBEAK	636000	26/3.97	7/3.08	322.26	374.78	25.15	1303	893	409.8	11500	0.08989
DRAKE	795000	26/ 4.44	7/3.45	402.8	466.84	28.11	1628	1110	512	14300	0.07192
COOT	795000	36/3.77	1/3.77	402.8	414	26.42	1197	1110	87	7610	0.07134
MALLARD	795000	30/4.14	19/2.48	402.84	494.71	28.96	1839	1119	719	17450	0.07208
RAIL	954000	45/3.70	7/2.47	483.42	516.84	29.61	1600	1339	260	12020	0.05994
CARDINAL	954000	54/3.38	7/3.38	483.42	546.07	30.42	1829	1339	490	15500	0.05994
CURLEW	1033500	54/3.52	7/3.52	523.68	591.55	31.68	1981	1451	530	16700	0.05531
FALCON	1590000	54/4.36	19/2.62	805.8	908.12	39.26	3042	2243	799	25000	0.03612