

Connect and Disconnect Event Functions

Function	Purpose
<code>bind(event, data, handler)</code>	Connect a function to an event <code>\$('#navbar a').bind('click', fcnDoSomething);</code>
<code>unbind(event, handler)</code>	Disconnect a function to an event <code>\$('#navbar a').unbind('click', fcnDoSomething);</code>

Parameters

bind()/unbind() Parameter	Purpose
event	Defines the event to bind to the element result set. Possible values are: <ul style="list-style-type: none">• blur• focus• focusin<ul style="list-style-type: none">◦ includes parents/children; if the <a> in <a> has focus, then the <a>, , and all have focus• focusout<ul style="list-style-type: none">◦ includes parents/children; if the <a> in <a> is blurred, then the <a>, , and all are blurred• load• resize• scroll• unload• click<ul style="list-style-type: none">◦ pressed and released• dblclick• mousedown<ul style="list-style-type: none">◦ pressed only• mouseup<ul style="list-style-type: none">◦ released only• mousemove• mouseover• mouseout• change• select• submit• keydown• keypress• keyup• error
data	Optional. Defines a piece of data to be passed to the handler
handler	The function that handles the event

Helper Functions

Function	Purpose
<code>click(fcn)</code>	Shortcut for defining a click function handler <code>\$('#navbar a').click(fcnDoSomething);</code>
<code>hover(fcnOver, fcnOut)</code>	Shortcut for defining a mouseover and mouseout <code>\$('#navbar a').hover(overFunction, outFunction);</code>

Also useful is...

Function	Purpose
<code>preventDefault()</code>	Prevents browser from executing the default action
<code>one(event, data, handler)</code>	Just like <code>bind()</code> , but only fires once