Hypothesizing the 64 Meta–State System: A Generative Grammar

Ryan Rook

July 15, 2025

Abstract

We introduce a comprehensive *64 Meta–State System* for modeling the dynamic interplay of cognitive function pairings in the TRPI framework. Each meta–state is a unique combination of **Ego** and **Superego** pairings (e.g. `SeFi-SiTe`) and each pairing obeys three rules: (i) one introverted *and* one extraverted function per pairing; (ii) each pairing mixes a perceiving and a judging function of opposite attitudes; (iii) pairings are localised to a single cerebral hemisphere. Crossing the eight Ego and eight Superego options yields a neurocognitively plausible matrix of $8 \times 8 = 64$ discrete states, each corresponding to a distinct pattern of lateralised prefrontal activity. We present the full matrix, outline testable neuroscientific predictions, and illustrate applications for two prototypical types (ENTP and ESFP), thereby offering a generative grammar for future research in personality neuroscience.

Prefrontal Cortex Organisation of TRPI Pairs

Contemporary network neuroscience indicates that cognitive functions emerge as distributed yet regionally biased patterns within the prefrontal cortex (PFC). In line with classic work [2, 3], we adopt the following lateralised map (right = abstract/contextual; left = concrete/sequential):

Recent fMRI evidence with *information-restricted neural language models* demonstrates that left-hemisphere regions favour short-context processing while right-hemisphere hubs favour long contexts [**?**]. The context length itself aligns with Extraversion and Introversion: short context supports rapid, surface-level connections and immediate responsiveness (Extraversion), while long context enables integrative, deep connections and sustained internal processing (Introversion). This preference directly supports the lateralization of Sensing and Intuition: Sensing (S), rooted in the left hemisphere, is adapted for short-context, detail-focused processing, while Intuition (N),rooted the right hemisphere, is specialized for long-context, pattern-oriented integration.

Accordingly, we map *short context → Ne/Se and Te/Fe* and *long context → Ni/Si and Ti/Fi* within TRPI.

- **Right dlPFC** (`NeTi`): *Enables abstract, improvisational reasoning and idea generation.* This region orchestrates the rapid exploration of novel concepts, flexible hypothesis testing, and "out-of-the-box" problem-solving. Supports working memory for complex, hypothetical scenarios—underpinning divergent thinking, intellectual play, and the ability to adapt logic on the fly.
- **Left dlPFC** (`SeTi`): *Specializes in concrete, analytic action and real-time adjustment.* Mediates logical reasoning applied to sensory input, focusing on immediate, practical details and systematic implementation. Supports focused attention, detail-oriented planning, and rapid response in action-heavy tasks.
- **Right dmPFC** (`NiFe`): *Supports empathic pattern recognition and social intuition.* Enables the reading of subtle social signals, pattern-based understanding of others' intentions, and complex perspective-taking—driving intuition about social meaning and group dynamics.
- **Left dmPFC** (`SiFe`): *Embodies tradition-based social awareness and moral grounding.* Anchors social cognition in established roles, norms, and collective memory. Promotes empathy based on shared experience, history, and the maintenance of social harmony through convention.
- **Right vmPFC** (`NeFi`): *Orchestrates imaginative valuation and affective meaning-making.* Integrates emotional salience with future possibilities, helping to appraise the personal significance of imagined outcomes. Essential for creativity infused with personal values, empathy for hypothetical scenarios, and authentic emotional self-expression.
- **Left vmPFC** (`SeFi`): *Processes immediate, sensory-driven valuation and emotional response.* Assigns personal relevance and feeling to direct, concrete experiences. Governs authentic gut-reactions, instant likes/dislikes, and the affective tone of lived events.

- **Right vlPFC** (`NiTe`): *Implements externally-driven logical control based on internal models and foresight.* Executes structured decisions by translating intuitive trajectories into actionable frameworks. Supports logical planning under uncertainty, especially in unfamiliar or novel situations.

- **Left vlPFC** (`SiTe`): *Applies rule-based reasoning grounded in routine and precedent.* Enforces procedural logic and consistent task execution based on stored experience. Optimized for reliability, schedule adherence, and operational precision in familiar contexts.

Context Networks and Core Subcortical Structures in TRPI Meta-States

The TRPI meta-state system relies on a coordinated interplay between large-scale cortical networks—the **Default Mode Network (DMN)** and the **Task-Positive Network (TPN)**—and three core subcortical structures: the **thalamus**, **hypothalamus**, and **hippocampus**. Each component plays a distinct role in mediating the flow, context, and salience of information that underpins Sensing/Intuition (S/N) and the dynamic states of TRPI.

Cortical Context Networks

- **Default Mode Network (DMN):** A distributed network (dmPFC, PCC, precuneus, lateral parietal cortex, medial temporal lobe) active during rest, introspection, autobiographical memory, and narrative construction. The DMN is the substrate for long-context, internally-directed cognition, supporting meta-states rooted in Intuition (Ni) and Sensing (Si), as well as the construction of personal and social meaning (Fe).

- **Task-Positive Network (TPN):** Also known as the frontoparietal or executive control network (dlPFC, inferior parietal lobule, dorsal ACC, posterior parietal cortex). The TPN is maximally active during focused attention, immediate task execution, and rapid environmental response. It provides the substrate for short-context, externally-oriented cognition, supporting meta-states grounded in Sensing (Se) and intuition (Ne), rapid Judging (Ti), and action-oriented Extraversion.

These networks are anticorrelated: increased activity in one corresponds to decreased activity in the other, reflecting the brain's dynamic alternation between internally and externally focused meta-states.

Core Subcortical Substrate

- **Thalamus:** The universal relay for sensory input and arousal; selects which sensory data reaches consciousness and which network (DMN/TPN) becomes dominant. Lateralized processing in the thalamus supports the Sensing/Intuition divide.

- **Hypothalamus:** Regulates motivational and affective salience, homeostasis, and survival responses (Fight, Flight, Freeze, Fawn). The hypothalamus influences meta-state switching based on internal and external cues, modulating both DMN and TPN engagement.

- **Hippocampus:** Binds contextual and temporal information into memory and supplies it to the prefrontal cortex. The left hippocampus supports sequential, explicit memory (Si/Se), while the right hippocampus specializes in associative, spatial, and narrative memory (Ni/Ne). Its interaction with both DMN and TPN underpins context-dependent cognition and dynamic states.

Integrated Model Summary

> *The DMN and TPN form the dynamic cortical context axis for the TRPI meta-state system, while the thalamus, hypothalamus, and hippocampus provide the essential subcortical substrate that gates, motivates, and contextualizes all experience. Together, these networks and structures scaffold the emergence and regulation of Sensing/Intuition and the fluid transitions between meta-states.*

Context-Length Modulation and Dynamic Adaptation

Recent work in network neuroscience demonstrates that the *length of contextual processing* is a fundamental variable in brain organization [5]. Left-hemisphere prefrontal regions and the Task-Positive Network (TPN) favour **short-context** (extraverted, immediate, objective) processing, supporting Sensing (`Se`), Intuition (`Ne`), and reflective Judging (`Ti`, `Fi`) operations. By contrast, right-hemisphere hubs and the Default Mode Network (DMN) support **long-context** (introverted, sustained, subjective) integration—the core of Intuition (`Ni`), Sensing (`Si`), and rapid Judging (`Te`, `Fe`) [2, 3].

Core Principle: *The TRPI meta-state model proposes that personality is organized around the capacity to dynamically modulate context length.* Individuals flexibly shift between short-context (present, environment-focused) and long-context (extended, narrative or internal) processing as demanded by situation or adaptation. This dynamic is not arbitrary but follows lawful transitions governed by the interplay of functional pairings and lateralized brain organization.

Functional Modification Rules

Transitions between meta-states occur via compensatory shifts that adjust context length, formalized as:

$$\texttt{Se} < \texttt{Ti/Fi} = \texttt{Si}$$
$$\texttt{Si} < \texttt{Te/Fe} = \texttt{Se}$$
$$\texttt{Ni} < \texttt{Te/Fe} = \texttt{Se}$$
$$\texttt{Ne} < \texttt{Ti/Fi} = \texttt{Si}$$

Here, "$<$" denotes modification of the active function by the compensatory mode, resulting in a context shift (e.g., from short to long, or vice versa). This captures Jung's principle that the unconscious compensates the conscious attitude by reversing its direction [1].

Significance: This model accounts not only for stable type differences but for *dynamic adaptation and psychological resilience*. The ability to flexibly expand or contract one's context window—modifying between objective immediacy and subjective depth—is proposed as a core feature of cognitive health and growth within the TRPI framework. Empirically, these shifts align with transitions in DMN and TPN engagement, lateralized prefrontal activity, and the gating role of the thalamus, hypothalamus, and hippocampus (see Tables 1 and 2).

Jungian Foundations

> "For all the types met with in practice, the rule holds good that besides the conscious, primary function there is a relatively conscious, auxiliary function which is in every respect different from the nature of the primary function."
> *C. G. Jung, CW6 §669*

> "No individual is simply introverted or extraverted, but he is so in one of his functions."
> *CW6 §707*

> "This absolute sovereignty always belongs, empirically, to one function alone, and can belong only to one function, because the equally independent intervention of another function would necessarily produce a different orientation."
> *CW6 §667*

> "Apart from the qualities I have mentioned, the undeveloped functions possess the further peculiarity that, when the conscious attitude is introverted, they are extraverted and *vice versa*."
> *CW6 §908*

These passages ground our pairing rules in Jung's original text: the auxiliary must differ in both kind and attitude, attitude is defined *per function*, and the unconscious compensates by reversing that attitude.

Formal Rules of the Meta–State System

1. **Composition.** A meta–state is denoted `[Ego]-[Superego]` (or the reverse when Superego dominates); e.g. `SeFi-SiTe`.
2. **Attitude Balance.** Each pairing contains exactly one extraverted and one introverted function—no double-introvert or double-extravert combinations.
3. **Perceiving–Judging Mix.** Within every pairing, one function belongs to the perceiving axis (`S/N`) and one to the judging axis (`T/F`).
4. **Hemispheric Locality.** All functions in a pairing are lateralised to the *same* hemisphere; cross-hemisphere mixtures are invalid.

Crossing the eight valid Ego options with the eight valid Superego options yields 64 meta–states.

Meta–State Matrix

Table 1 enumerates all valid combinations. Rows correspond to *Ego* (dynamic focus) pairings, columns to *Superego* (regulatory backdrop) pairings.

Illustrative Meta–States

ENTP (`NeTi/SiFe`). When debating a novel idea, an ENTP likely occupies the `NeTi-SiFe` meta–state: right dlPFC–driven divergent reasoning (`NeTi`) synchronised with left dmPFC social calibration (`SiFe`).

ESFP (`SeFi/NiTe`). During improvisational performance, the ESFP engages `SeFi-NiTe`: left vmPFC promotes affective reward tracking (`SeFi`) alongside right vlPFC strategic foresight (`NiTe`).

Neuroscientific Predictions

1. **Meta–State Connectivity.** Each cell should correspond to a reproducible functional-connectivity fingerprint coupling contralateral PFC hubs.
2. **Behavioural Signatures.** Tasks emphasising novelty versus routine should selectively recruit the predicted Ego–Superego combination.

Conclusion

The 64 Meta–State System furnishes a generative grammar for personality neuroscience, translating Jungian dynamics into a network-based ontology. Future work should employ multimodal imaging and longitudinal designs to examine the stability, developmental trajectory, and clinical relevance of these states.

References

[1] C. G. Jung, *Psychological Types*. Princeton University Press, 1971 (Original work published 1921).

[2] Miller, E. K., & Cohen, J. D. (2001). An integrative theory of prefrontal cortex function. *Annual Review of Neuroscience*, 24, 167–202.

[3] Stuss, D. T., & Knight, R. T. (Eds.). (2013). *Principles of Frontal Lobe Function* (2nd ed.). Oxford University Press.

[4] Nardi, D. (2012). *Neuroscience of Personality*. Radiance House.

[5] Pasquiou, A., Lakretz, Y., Thirion, B., & Pallier, C. (2023). Information-restricted neural language models reveal different brain regions' sensitivity to semantics, syntax, and context. *Neurobiology of Language, 4*(4), 611–636. `https://doi.org/10.1162/nol_a_00125`

Table 1: Complete 64 Meta–State Matrix. Each cell is labelled `<Ego>-<Superego>`.

	TeSi	**SiTe**	**TeNi**	**NiTe**	**FeSi**	**SiFe**	**FeNi**	**NiFe**
SeTi	SeTi–TeSi	SeTi–SiTe	SeTi–TeNi	SeTi–NiTe	SeTi–FeSi	SeTi–SiFe	SeTi–FeNi	SeTi–NiFe
TiSe	TiSe–TeSi	TiSe–SiTe	TiSe–TeNi	TiSe–NiTe	TiSe–FeSi	TiSe–SiFe	TiSe–FeNi	TiSe–NiFe
SeFi	SeFi–TeSi	SeFi–SiTe	SeFi–TeNi	SeFi–NiTe	SeFi–FeSi	SeFi–SiFe	SeFi–FeNi	SeFi–NiFe
FiSe	FiSe–TeSi	FiSe–SiTe	FiSe–TeNi	FiSe–NiTe	FiSe–FeSi	FiSe–SiFe	FiSe–FeNi	FiSe–NiFe
NeTi	NeTi–TeSi	NeTi–SiTe	NeTi–TeNi	NeTi–NiTe	NeTi–FeSi	NeTi–SiFe	NeTi–FeNi	NeTi–NiFe
TiNe	TiNe–TeSi	TiNe–SiTe	TiNe–TeNi	TiNe–NiTe	TiNe–FeSi	TiNe–SiFe	TiNe–FeNi	TiNe–NiFe
NeFi	NeFi–TeSi	NeFi–SiTe	NeFi–TeNi	NeFi–NiTe	NeFi–FeSi	NeFi–SiFe	NeFi–FeNi	NeFi–NiFe
FiNe	FiNe–TeSi	FiNe–SiTe	FiNe–TeNi	FiNe–NiTe	FiNe–FeSi	FiNe–SiFe	FiNe–FeNi	FiNe–NiFe

Component	**Core Function**	**Context Type**	**Typological Mapping**
DMN	Introspection, narrative, memory	Long-context	Ni, Si, Fe
TPN	Attention, action, execution	Short-context	Se, Ne, Ti
Thalamus	Sensory relay, context switching	Both	S/N (all)
Hypothalamus	Motivation, arousal, salience	Both	4F modulation
Hippocampus	Episodic and narrative memory	Both	Si/Se (left), Ni/Ne (right)

Table 2: Integrated roles of context networks and subcortical substrate in the TRPI meta-state system.