

ELECTRONICS									
Item No.	Part Name	Quantity	Unit Cost (CAD)	Replacement Link	Manufacturer Product Listing	Wire Length	Connector type	Manufacturing Notes	
1	SSH1106 1.3 in OLED	1	3.53	link	link	120mm	4 wires soldered -> 4 pins JST XH female	Ensure header configuration according to schematic	
2	Dual 18650 Battery Shield	1	3.84	link	link	100mm	2 wires soldered -> 2 pins JST XH female	Ensure +/- header according to schematic, Cable to be soldered to 5v pinout on mod	
3	EVE 18650 Lithium Ion Cell 3.7V 5000mah	2	5.56	link	link	N/A	N/A	N/A	
4	USB C Male to Female	1	3.53	link	link	75mm	USBC Male -> USBC Female	Ensure cable length, 90 degree male connector would be preferred	
5	ESP32-Wroom-32 CP1202 30 Pin Dev Board	1	3.53	link	link	N/A	USB C INPUT female	Ensure USB C input	
6	Passive buzzer module (Piezoelectric, 3 pin)	1	0.4	link	link	50mm	3 wire female dupont -> 3 wire JST XH	Ensure header configuration according to schematic	
8	2750646 - PUSH SWITCH MOM 1P1T NO THF	2	0.32	link	link	100mm	2 wires soldered -> 2 pin JST XH female	Header configuration does not matter	
8	Cherry MX Blue Mechanical Switch	4	0.9028	link	link and link	110mm	2 wires soldered -> 2 pin JST XH female	Header configuration does not matter	
9	LED Matrix 8x8 Flexible	1	2.47	link	link	70mm and 30mm	solder->3 pin JST XH female	Ensure JST XH header (NOT JST SM)	
10	PCB	1	2	link	link	N/A	ALL JST XH	Has its own manufacturing files which must be sent to manufacturer	
HARDWARE - (washers and nuts just buy in bulk, all are m3) (per unit)									
Size	Type	Size	Quantity	Driver					
M3	Countersunk Bolt screw	15mm	4	Hex					
		20mm	3	Hex					
		10mm	2	Hex					
		5mm	4	Phillips					
Hardware Cost ~ 1.5 CAD									
3D printing cost ~ 7 CAD									
Shipping ~ 5 CAD									
UNIT PRICE = 39.58 CAD per unit									