NMix

Parametrisation

The N-Mixture distribution is a Poisson mixture of the Binomials, as

$$\text{Prob}(y) = \sum_{n=y}^{\infty} \binom{n}{y} p^n (1-p)^{n-y} \times \frac{\lambda^n}{n!} \exp(-\lambda)$$

for responses $y = 0, 1, 2, \ldots, n$, where n is Poisson number of trials, and p is probability of success. Replicated reponses $y_1, y_2, \ldots, y_r$, are iid from the Binomial with the same p, conditioned on the same n from the Poisson,

$$\text{Prob}(y_1, \ldots, y_r) = \sum_{n=\max\{y_1,\ldots,y_r\}}^{\infty} \left\{ \prod_{i=1}^{r} \binom{n}{y_i} p^n (1-p)^{n-y_i} \right\} \times \frac{\lambda^n}{n!} \exp(-\lambda)$$

Link-function

The probability p is linked to the linear predictor by

$$p(\eta) = \frac{\exp(\eta)}{1 + \exp(\eta)}$$

for the default logit link, while λ depends on fixed covariates

$$\log(\lambda) = \sum_{j=1}^{m} \beta_j x_j$$

with one vector of covariates for each observation. m can be maximum 15 and minimum 1.

Hyperparameters

The parameters $\theta_1 = \beta_1, \theta_2 = \beta_2, \ldots, \theta_m = \beta_m$.

Hyperparameter spesification and default values

doc `Binomial-Poisson mixture`

hyper

theta1

hyperid `101101`
name `beta1`
short.name `beta1`
output.name `beta[1] for NMix observations`
output.name.intern `beta[1] for NMix observations`
initial `2.30258509299405`
fixed `FALSE`
prior `normal`
param `0 0.5`
to.theta `function(x) x`
from.theta `function(x) x`

theta2

hyperid `101102`
name `beta2`
short.name `beta2`
output.name `beta[2] for NMix observations`
output.name.intern `beta[2] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta3

hyperid `101103`
name `beta3`
short.name `beta3`
output.name `beta[3] for NMix observations`
output.name.intern `beta[3] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta4

hyperid `101104`
name `beta4`
short.name `beta4`
output.name `beta[4] for NMix observations`
output.name.intern `beta[4] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta5

hyperid `101105`
name `beta5`
short.name `beta5`
output.name `beta[5] for NMix observations`
output.name.intern `beta[5] for NMix observations`
initial `0`
fixed `FALSE`

prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta6
hyperid 101106
name beta6
short.name beta6
output.name beta[6] for NMix observations
output.name.intern beta[6] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta7
hyperid 101107
name beta7
short.name beta7
output.name beta[7] for NMix observations
output.name.intern beta[7] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta8
hyperid 101108
name beta8
short.name beta8
output.name beta[8] for NMix observations
output.name.intern beta[8] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta9
hyperid 101109
name beta9
short.name beta9

output.name `beta[9] for NMix observations`
output.name.intern `beta[9] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta10

hyperid `101110`
name `beta10`
short.name `beta10`
output.name `beta[10] for NMix observations`
output.name.intern `beta[10] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta11

hyperid `101111`
name `beta11`
short.name `beta11`
output.name `beta[11] for NMix observations`
output.name.intern `beta[11] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta12

hyperid `101112`
name `beta12`
short.name `beta12`
output.name `beta[12] for NMix observations`
output.name.intern `beta[12] for NMix observations`
initial `0`
fixed `FALSE`
prior `normal`
param `0 1`
to.theta `function(x) x`
from.theta `function(x) x`

theta13

hyperid 101113
name beta13
short.name beta13
output.name beta[13] for NMix observations
output.name.intern beta[13] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta14

hyperid 101114
name beta14
short.name beta14
output.name beta[14] for NMix observations
output.name.intern beta[14] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

theta15

hyperid 101115
name beta15
short.name beta15
output.name beta[15] for NMix observations
output.name.intern beta[15] for NMix observations
initial 0
fixed FALSE
prior normal
param 0 1
to.theta function(x) x
from.theta function(x) x

survival FALSE

discrete TRUE

link default logit loga probit

pdf nmix

Specification

- `family="nmix"`
- Required arguments: the response Y and covariates X as `inla.mdata(Y, X [, additional.covariates])`

The response is a matrix where each row are replicates, where responses that are `NA`'s are ignored. The covariates is one or many vectors, matrices or data.frames. Each row of the covariates $(x_{i1}, x_{i2}, \ldots, x_{im})$ defines the covariates used for the i'th response(s) (the i'th row of `Y`). Note that $\beta_{m+1}, \ldots, \beta_{15}$ are fixed to zero.

Example

In the following example we estimate the parameters in a simulated example with replications.

```
nrep.max = 5
n = 50
y = matrix(NA, n, nrep.max)
x = c()
xx = c()
intercept = 1

for(i in 1:n) {
    local.x = runif(1) - 0.5
    lambda = exp(2 + local.x)
    N = rpois(1, lambda)
    local.xx = runif(1) - 0.5
    eta = intercept + local.xx
    p = exp(eta)/(exp(eta) + 1)
    ## sample the number of replications
    nr = sample(1:nrep.max, 1)
    ## and sample these. note that 'y' is initialized with NA's,
    ## so if nr < nrep.max, then
    ## y[i,(nr+1):nrep.max]  would be NA.
    y[i, 1:nr]= rbinom(nr, size = N, prob = p)
    x = c(x, local.x)
    xx = c(xx, local.xx)
}

Y = inla.mdata(y, 1, x)
r = inla(Y ~ 1 + xx,
         data = list(Y=Y, xx=xx),
         family = "nmix",
         control.fixed = list(prec.intercept=1,  prec=1))
```

Notes