Cricket Shot Recognition: Comparing Gradient Features and a Frozen CNN

Hrushikesh Roop Avvari (230249) Voora Rakesh (231174)
Gokavarapu Manikanta Sri Akshith (230418)
Lokesh Kumar Moond (230606) Bollu Sharath chandra (230303)
Indian Institute of Technology Kanpur
EE604, October 2026

Abstract

We study a small, practical task: classify one cricket image as drive, leg glance/flick, pull or sweep. We compare a hand-crafted histogram of oriented gradients (HOG) with frozen MobileNetV2 features followed by a linear classifier. Our implemented extension combines global and fixed regional CNN features with their absolute difference, and exposes disagreement between separate view classifiers. On an unchanged test set of 945 images in 70 visual groups, HOG obtains 35.3% accuracy and 34.5% macro F1; the global CNN obtains 63.0% and 62.9%. Contrast obtains 65.5% and 64.9%, only three additional correct predictions over concatenation. Group-based uncertainty does not establish a clear advantage. A duplicate audit substantially reduces the optimistic preliminary result, and temperature scaling worsens test calibration. We report these limitations alongside a local demo and reproducible predictions. The study is exploratory because grouping was revised after earlier evaluation.

1. Introduction

A collection of labeled cricket images can help retrieve examples of batting shots. Our task takes one image containing a shot and returns one of four supplied labels. It assumes that someone has already chosen the image. It does not locate the batter, identify a contact frame or grade batting technique.

Visual differences can be subtle. The bat may be blurred, a frame may show preparation rather than contact, and camera angle or background may dominate. We ask two focused questions. How does a gradient descriptor compare with pretrained CNN features on the same images? Does comparing a global view with a fixed central region provide evidence beyond simply concatenating them?

Our foundation is feature extraction followed by classification. HOG supplies an explicit descriptor; a frozen pretrained network supplies a learned one. The course-level extension is a two-view absolute-difference feature and a visible agreement diagnostic. We implement and ablate this design, but do not claim its components or combination are unprecedented. The small gain leaves algorithmic novelty a weakness. Auditing modified copies is useful evaluation work, rather than a new recognition algorithm.

2. Related work and positioning

HOG accumulates gradient orientations into normalized spatial blocks [3]. Our documented variant uses this idea for whole-image classification; it does not reproduce the original pedestrian detector. MobileNetV2 is an established efficient CNN [9]. We select public ImageNet ONNX weights [8] and freeze them. This follows the pretrained-feature-extractor plus classifier approach in Lecture 15; the architecture itself need not have been taught by name.

Cricket recognition already has datasets and model studies, including KUCricShot [6] and Kang's preprint [7]. We did not import those models, and their scores use different data and protocols. They are prior work, not numerical baselines for this experiment. Temperature scaling [5] and selective classification [4] are established. Our threshold heuristic provides no guaranteed risk bound.

3. Data and evaluation

We use version 2 of Aneesh's *Cricket Shots Dataset* on Kaggle [2]. Its 4,724 files have four upstream labels. Drive and leg glance/flick each combine related stroke types. We retain these labels and do not claim original collection or annotation. The downloaded metadata reports an unknown license. Provenance and checksums are recorded; source-control defaults exclude raw images and examples.

Decoded RGB hashes remove one excess exact copy. A visual audit connects qualifying near copies, including rotated and mirrored versions, then keeps each connected

Label	Train	Val.	Test
Drive	734	244	245
Glance/flick	672	224	224
Pull	756	252	252
Sweep	672	224	224
Total	2834	944	945

Table 1. Retained image counts; all visual groups remain in one split.

group in one split. It leaves 4,723 representatives in 363 visual groups. The initial hash-only contrast accuracy was 96.3%. Visual review found missed transformed pictures, so grouping was strengthened and the comparison rerun. The corrected result is 65.5%. Both predictions and both grouping records remain available. This history makes the final study exploratory; the new HOG comparison uses the corrected split unchanged.

Training has 2,834 images in 221 groups, validation 944 in 72 groups, and test 945 in 70 groups. These are fixed stratified group folds with seed 604: fold 0 is test, fold 1 validation, and the others training. This is one holdout, not five-fold cross-validation. The source has no verified match or player identities. Visual groups are not necessarily independent photographs or matches. Appendix A.1 gives detailed audit criteria.

4. Proposed method

4.1. Common geometry

We apply EXIF orientation, convert to RGB and bound the image to a 1,024-pixel box. The CNN uses the image extent and a central crop with $x \in [0.15W, 0.85W]$, $y \in [0.05H, 0.95H]$. Each view is fitted to 224 by 224 while preserving aspect ratio and cropping the center. Even the global branch loses peripheral pixels at this step. The crop can miss an off-center batter.

4.2. HOG baseline

HOG uses the identical global geometry, converted to 8-bit luminance and scaled to $[0, 1]$. Central differences give g_x, g_y, magnitude $m = \sqrt{g_x^2 + g_y^2}$ and unsigned angle $\theta = \operatorname{atan2}(g_y, g_x) \bmod 180°$. Boundary derivatives are zero. Each 16 by 16 cell accumulates *magnitudes*, not pixel counts, into nine bins centered at $0, 20, \ldots, 160°$. A pixel splits its vote linearly between adjacent orientation bins, wrapping at $180°$. Votes do not interpolate across cell boundaries.

A 2 by 2 cell block has 36 values and moves one cell per step. Each block is divided by $\sqrt{\sum_i h_i^2 + 10^{-10}}$. The 14 by 14 cells yield 13 by 13 blocks: $13 \cdot 13 \cdot 36 = 6,084$ concatenated values. Final per-image L2 normalization gives the classifier input. There is no learned scaling, PCA or feature selection. These fixed settings are not claimed to be optimal HOG settings. The lecture's signed-angle example and our unsigned bins are distinct variants of the same principle.

4.3. Frozen CNN and contrast

The CNN uses ImageNet RGB mean $(0.485, 0.456, 0.406)$ and standard deviation $(0.229, 0.224, 0.225)$. We remove the ImageNet classifier and retain the pooled 1,280-value output. No CNN parameters are updated on cricket images. For separately normalized global and regional vectors u, v, compare u, v, $\mathrm{Norm}([u; v])$, and

$$z = \mathrm{Norm}([u; v; |u - v|]) \in \mathbb{R}^{3840}. \tag{1}$$

Absolute difference gives a linear classifier a nonlinear relationship between the views. A signed difference would already be expressible by a linear map of concatenation. This motivates the construction without proving it improves recognition. Coordinates have no claimed physical interpretation, and the crop vector is not a local keypoint descriptor.

All five representations use class-balanced, L2-regularized multinomial logistic regression. Logits are $a = Wz + b$ and scores are $p_c = \exp(a_c/T)/\sum_j \exp(a_j/T)$. Training minimizes weighted multiclass cross-entropy with regularization. Contrast stores a 4×3840 matrix and four biases: 15,364 parameters. These cricket parameters are learned; the CNN and HOG extraction rules stay fixed.

5. Experiments

5.1. Controlled comparison

Every head uses the corrected manifest and $C \in \{0.1, 1, 10, 100\}$. Validation macro F1 selects C, with smaller values winning ties. HOG's configuration and selection are saved before test scoring. No new split, seed, feature setting or threshold was searched for a better test result. We retain the original CNN heads and predictions. HOG is an exploratory extension after prior results on this archive were known.

The original validation set also selected CNN temperatures and the review threshold. This reuse can overfit validation. We disclose it and preserve the choices; separate calibration data is future work. HOG uses $T = 1$ and does not alter the review gate.

HOG selects $C = 0.1$ and reaches 49.4% validation macro F1, falling to 34.5% on test. Its 35.3% accuracy is below all four CNN configurations. This supports pretrained features *for this configuration and split*. It does not isolate color, pretraining or architecture effects, or establish universal HOG inferiority.




Figure 1. Two feature approaches on the same split. Only the linear cricket classifiers learn from training images. CNN ablations share a frozen encoder. The fixed crop is a regional view, not a detected or segmented batter.




Figure 2. A selected test image traced through luminance, gradient magnitude and magnitude-weighted cell bins. This explains HOG; it is not a localization result or a representative performance sample.

Feature	Dim.	C	Acc.	F1
HOG	6084	0.1	35.3	34.5
CNN global	1280	10	63.0	62.9
CNN crop	1280	10	62.4	61.7
Concat.	2560	10	65.2	64.6
Contrast	3840	10	65.5	64.9

Table 2. All-test accuracy and macro F1 in percent. Same images, labels, groups, split and regularization grid; HOG has no ImageNet pretraining.

Contrast gets 619/945 correct, versus 616/945 for concatenation: only +0.32 accuracy points. A paired group-bootstrap interval is -1.46 to +2.38 points, spanning zero. Concatenation has the highest validation macro F1. We retain the pre-existing contrast deployment, but do not present a substantial or reliable advantage.

Intervals resample the 70 visual groups with replacement in 2,000 draws, seed 17, retaining each drawn group's images. Identical draws give paired comparisons. Statistics remain image-weighted within each resample. These conditional percentile intervals omit training and split variability and cannot repair unknown match correlation or missed copies. They do not treat 945 images as independent original photographs.

Feature	Acc. 95%	F1 95%
HOG	25.9–48.1	24.9–44.6
CNN global	49.5–74.2	44.6–72.0
CNN crop	45.3–76.7	42.1–72.3
Concat.	48.9–77.9	43.7–74.9
Contrast	49.9–77.6	45.8–74.2

Table 3. Conditional visual-group bootstrap intervals, in percent, from saved individual predictions.

5.2. Errors and model scores

Glance/flick recall is 45.5% on 224 examples, while pull recall is 78.2% on 252. HOG predicts pull for 110 of 224 sweep images. Similar stances, fixed spatial cells and camera layout are plausible limitations, not verified causes for every error.

Temperature scaling retains the top label but worsens test ECE from 0.043 to 0.094 and NLL from 0.859 to 0.898 (ten equal-width ECE bins). It did not demonstrate improved calibration. A softmax score is relative to the supported labels, not a guarantee that an arbitrary image is correct or belongs to these classes.

The unchanged secondary review rule requires score at least 0.70 and agreement of global, crop and contrast heads. It accepts 557/945 images, with 433 correct: 58.9% coverage and 77.7% accepted accuracy. The 90% validation target is not a test result or guarantee. Correlated heads can agree on a wrong label. Appendix A.2 retains the detailed diagnostics.




Figure 3. Contrast confusion counts on all test images. Rows are dataset labels; color is within-class fraction. Review does not remove errors from this matrix.




Figure 4. Dataset label: sweep; prediction: pull (99.7% score). This error was selected after evaluation and retained in the demo, alongside successes and disagreement.

5.3. Implementation and demonstration

Training uses scikit-learn; inference uses CPU ONNX Runtime and numeric NPZ/JSON heads. Shared functions implement training and demo preprocessing. The image page shows both actual inputs, four scores, review reasons and a HOG comparison. Uploads use temporary storage; inference needs no cloud service or API key after installation. JSON export identifies temperature-scaled softmax scores. Selected examples include a correct result, a confident error and disagreement.

Warm CNN plus HOG inference takes 23 ms median and 52 ms at the 95th percentile over 50 fixed test images on the recorded host. This includes separate image decodes, but excludes initialization, HTTP transport and preview encoding. Preserved older CNN-only timings describe a different operation.

6. Limitations and conclusion

The project implements the course's feature-extractor/classifier structure and tests a small two-view extension. HOG gives an explicit gradient baseline; pretrained features work better on this fixed benchmark. Contrast adds only three correct test predictions over concatenation, with uncertainty spanning no gain. Novelty remains modest; we make no state-of-the-art or first-in-literature claim.

The duplicate-audit effect is an evaluation warning, not proof of independent groups. Unknown match identities, unverified upstream labels, validation reuse and exploratory development limit generalization claims. An independently labeled test collection with known match/player identities would answer a more useful question than searching this split for a higher score. The weak video study remains in Appendix A.3.

References

[1] amittalmale. CRICKET_SHOTS, version 1. Kaggle dataset, 2025. Accessed 17 October 2026.

[2] Aneesh. Cricket shots dataset, version 2. Kaggle dataset, 2022. Accessed 17 October 2026; uploader identifier aneesh10.

[3] Navneet Dalal and Bill Triggs. Histograms of oriented gradients for human detection. In *CVPR*, pages 886–893, 2005.

[4] Yonatan Geifman and Ran El-Yaniv. Selective classification for deep neural networks. In *NeurIPS*, 2017.

[5] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. On calibration of modern neural networks. In *ICML*, pages 1321–1330, 2017.

[6] Sk. Wasiqul Hoque, Md Ahsan Habib, Atanu Shome, and Sadman Sakib. KUCricShot: A dataset for developing detection model of cricket shots. In *ICCIT*, 2023. Dataset description checked against the authors' repository.

[7] Sungwoo Kang. Modern deep learning approaches for cricket shot classification: A comprehensive baseline study. arXiv:2510.09187, preprint, 2025.

[8] ONNX Model Zoo contributors. MobileNetV2 pretrained onnx models. Accessed 17 October 2026.

[9] Mark Sandler, Andrew Howard, Menglong Zhu, Andrey Zhmoginov, and Liang-Chieh Chen. MobileNetV2: Inverted residuals and linear bottlenecks. In *CVPR*, pages 4510–4520, 2018.

[10] Limin Wang, Yuanjun Xiong, Zhe Wang, Yu Qiao, Dahua Lin, Xiaoou Tang, and Luc Van Gool. Temporal segment networks: Towards good practices for deep action recognition. In *ECCV*, 2016.

A. Supplementary evidence

A.1. Visual-copy audit

The initial audit uses decoded RGB hashes, 64-bit perceptual hash Hamming distance at most six, and 16 by 16 RGB thumbnail mean absolute difference at most 18. Exact copies collapse; conflicting-label components are quarantined. The stronger audit adds quarter-turn/mirror hashes (same bit cutoff, aligned thumbnail difference at most 24), then proposes the nearest 15 frozen-feature neighbors within cosine distance 0.20.

ORB binary descriptors and a RANSAC homography verify proposed geometric links. Requirements are a 0.72 match-ratio cutoff, at least 16 filtered matches, 12 inliers, 65% inlier fraction and 8% convex-hull coverage in both images. This adds 948 transform and 1,797 geometric edges. There are no final conflicting components. All linked copies and initial hash components stay in one split. These checks reduce leakage but can still miss related photographs or join visually similar ones. Full criteria and preserved edges are in the commented audit script and data directory.

A.2. Secondary diagnostics

Scores	NLL	ECE	Brier
Unscaled	0.859	0.043	0.470
Scaled	0.898	0.094	0.482

Table 4. Unchanged contrast scores on test; lower is better. Scaling worsens NLL and ECE.

The original temperature is approximately 0.802. Validation is reused for regularization, temperature and review selection. The review search chooses the lowest threshold from 0.50 to 0.95 in steps of 0.05 attaining 90% validation accuracy with at least 20 accepted images and 20% coverage, with 0.80 fallback. Its chosen 0.70 threshold stays unchanged. At that threshold confidence alone covers 62.2% with 77.6% accepted accuracy; adding agreement covers 58.9% with 77.7%. This modest difference is descriptive, not a guaranteed improvement.

Head	Clean	Dark	Blur	Mirror
CNN global	63.0	62.8	48.0	62.9
Contrast	65.5	67.1	49.7	65.2

Table 5. Preserved descriptive stress-test accuracy in percent; no retraining or parameter choice.

Dark multiplies source brightness by 0.6; blur uses Gaussian radius two at source resolution; mirror reflects horizontally while retaining the four broad labels. Both CNN views are recomputed. These conditions do not represent a new match or camera, and blur severity varies with source resolution. Original predictions, stress evidence and CNN-only timings remain under `results/images/`; preliminary hash-only evidence remains under `results/images_initial_hash/`.

A.3. Exploratory video pilot

The separate Kaggle CRICKET_SHOTS archive [1] contains 562 clips in eight labels and 25 normalized source-title groups. Its test set has 116 clips from five groups. Nine uniformly sampled frames feed the frozen encoder. Three ordered phase means, late-minus-early difference and temporal standard deviation form 6,400 features. This sparse temporal summary is motivated by segment-based representations [10], without reproducing TSN training.

The full-frame pilot obtains 18.1% accuracy. A fixed upper-center crop, introduced after pilot test feedback, reaches 30.2% accuracy and 21.3% macro F1. The training-majority baseline also reaches 30.2% accuracy (5.8% macro F1). Equal majority accuracy is not a successful general video recognizer. Defence has only three test clips; validation has one unorthodox clip. The reused holdout makes this exploratory. Original and revised predictions remain available; different data and labels prevent a direct image-versus-video comparison.

A.4. Code, data and repositories

The complete report appends every current custom executable source and configuration, with a SHA-256 inventory. Public libraries, pretrained weights and the unmodified CVPR style are not original code. The project includes dependency files, manifests, numeric heads, saved predictions, tests and reproduction commands. The separate course mapping and viva guide explain lecture references, advanced audit tools and one measured image trace.

Project repository: `https://github.com/hrushikeshroop/cricket-shot-recognition-ee604`.

Data: Cricket Shots Dataset v2 and CRICKET_SHOTS v1. Pretrained weights: ONNX Model Zoo. Libraries: scikit-learn, ONNX Runtime, OpenCV, Flask, and NumPy. Complete dependency links and attribution accompany `docs/sources.md`. Our NumPy HOG follows the cited method and supplied lectures; no external cricket classifier code was imported.